

error 16:56:26.408220 +0200 Console Detected missing constraints for <private>. It cannot be placed because there are not enough constraints to fully define the size and origin. Add the missing constraints, or set translatesAutoresizingMaskIntoConstraints=YES and constraints will be generated for you. If this view is laid out manually on macOS 10.12 and later, you may choose to not call [super layout] from your override. Set a breakpoint on DETECTED_MISSING_CONSTRAINTS to debug. This error will only be logged once.

default 16:56:26.430970 +0200 Console [0x7f981010d600] Created session
default 16:56:26.431133 +0200 Console [0x7f981010d600] Decoding: C0
0x002A0027 0x0006354A 0x11111100 0x00000000 766

default 16:56:26.431149 +0200 Console [0x7f981010d600] Options: 42x39
[FFFFFFFF,FFFFFFFF] 0001D060

default 16:56:26.431183 +0200 Console [0x7f981010d600] Decoding
completed without errors

default 16:56:26.431295 +0200 Console [0x7f981010d600] Releasing
session

default 16:56:26.460290 +0200 com.apple.WebKit.Networking
0x110c5c400 - NetworkResourceLoader::didFinishLoading: (pageID = 7,
frameID = 1, resourceID = 15)

default 16:56:26.460491 +0200 com.apple.WebKit.WebContent
0x11264d150 - WebResourceLoader::didFinishResourceLoad: (pageID = 7,
frameID = 1, resourceID = 15)

default 16:56:26.515344 +0200 opendirectoryd initiating reconnect of module
connection

default 16:56:26.515493 +0200 opendirectoryd queuing request to connection
- '<private>'

default 16:56:26.515687 +0200 opendirectoryd queuing request to connection
- '<private>'

default 16:56:26.516051 +0200 opendirectoryd cache miss with id type: 1

default 16:56:26.517021 +0200 opendirectoryd queuing request to connection
- '<private>'

default 16:56:26.517105 +0200 opendirectoryd queuing request to connection
- '<private>'

default 16:56:26.517493 +0200 opendirectoryd cache miss with id type: 1

default 16:56:26.518951 +0200 opendirectoryd queuing request to connection
- '<private>'

default 16:56:26.519042 +0200 opendirectoryd queuing request to connection
- '<private>'

default 16:56:26.519414 +0200 opendirectoryd cache miss with id type: 1

default 16:56:26.585424 +0200 eospreflightagent IORegistry entry
'IODeviceTree:/efi/platform' does not contain the key 'apple-coprocessor-version'

default 16:56:26.585526 +0200 eospreflightagent Skipped opportunistic
preflight: Current hardware has no embedded device (r = 1, k = 0,
EmbeddedOSInstall- (built Mar 3 2017 02:31:22))

default 16:56:26.595733 +0200 gamed TIC TCP Conn Event
[1:0x7ffb39f262c0]: 1 Err(0)

default 16:56:26.595733 +0200 SafariDAVClient TIC TCP Conn Event
[1:0x7f88aec176d0]: 1 Err(0)

default 16:56:26.595770 +0200 gamed TIC TCP Conn Connected

```

[1:0x7ffb39f262c0]: Err(0)
default 16:56:26.595770 +0200 SafariDAVClient TIC TCP Conn
Connected [1:0x7f88aec176d0]: Err(0)
default 16:56:26.595856 +0200 gamed TIC Enabling TLS
[1:0x7ffb39f262c0]
default 16:56:26.595847 +0200 SafariDAVClient TIC Enabling TLS
[1:0x7f88aec176d0]
default 16:56:26.615236 +0200 syncdefaultsd TIC TLS Event
[6:0x7fe9f301d800]: 2, Pending(0)
default 16:56:26.622116 +0200 syncdefaultsd TIC TLS Event
[6:0x7fe9f301d800]: 11, Pending(0)
default 16:56:26.622410 +0200 syncdefaultsd TIC TLS Event
[6:0x7fe9f301d800]: 12, Pending(0)
default 16:56:26.622442 +0200 syncdefaultsd TIC TLS Event
[6:0x7fe9f301d800]: 14, Pending(0)
default 16:56:26.633083 +0200 syncdefaultsd CFNetwork-AOSKit: Reaching
out to AOSKit for X-mobile me token
default 16:56:26.635613 +0200 trustd cert[2]: AnchorTrusted =(leaf)[force]>
0
default 16:56:26.636083 +0200 syncdefaultsd TIC TLS Trust Result
[6:0x7fe9f301d800]: 0
default 16:56:26.636523 +0200 com.apple.iCloudHelper MacOS error:
-67050
default 16:56:26.637768 +0200 syncdefaultsd CFNetwork-AOSKit: Applied X-
mobile me auth to request
default 16:56:26.643816 +0200 apsd TIC TCP Conn Event [3:0x7ff10fc3b760]:
1 Err(0)
default 16:56:26.643832 +0200 apsd TIC TCP Conn Connected
[3:0x7ff10fc3b760]: Err(0)
default 16:56:26.672410 +0200 com.apple.WebKit.WebContent
0x7f951fea71b0 -
PerformanceMonitor::measurePostBackgroundingMemoryUsage: Process was using
50302976 bytes of memory after becoming non visible.
default 16:56:26.672412 +0200 com.apple.WebKit.WebContent
0x7fc5f7079f30 -
PerformanceMonitor::measurePostBackgroundingMemoryUsage: Process was using
55599104 bytes of memory after becoming non visible.
default 16:56:26.672419 +0200 com.apple.WebKit.WebContent
0x7f93cd73ab00 -
PerformanceMonitor::measurePostBackgroundingMemoryUsage: Process was using
75313152 bytes of memory after becoming non visible.
default 16:56:26.680456 +0200 com.apple.WebKit.WebContent
0x7fcf3b719160 -
PerformanceMonitor::measurePostBackgroundingMemoryUsage: Process was using
62345216 bytes of memory after becoming non visible.
default 16:56:26.714465 +0200 com.apple.WebKit.WebContent
0x7f93cf822a00 - WebProcess::destroyRenderingResources() took 0.13ms
default 16:56:26.770298 +0200 com.apple.WebKit.WebContent
0x10fdf5000 - WebLoaderStrategy::scheduleLoad: Resource has been queued
for scheduling with the NetworkProcess (frame = 0x10fd61000, priority = 2, pageID =

```

7, frameID = 1, resourceID = 29, WebResourceLoader = 0x113a5a700)
default 16:56:26.770420 +0200 com.apple.WebKit.Networking
0x110ca9400 - NetworkResourceLoader::start: Retrieving resource from cache
(pageID = 7, frameID = 1, resourceID = 29, isMainResource = 0, isSynchronous = 0)
default 16:56:26.770461 +0200 com.apple.WebKit.Networking
0x110ca9400 - NetworkResourceLoader::startNetworkLoad: (pageID = 7,
frameID = 1, resourceID = 29, isMainResource = 0, isSynchronous = 0)
default 16:56:26.770842 +0200 gamed TIC TLS Event [1:0x7ffb39f262c0]:
2, Pending(0)
default 16:56:26.771136 +0200 gamed TIC TLS Event [1:0x7ffb39f262c0]:
11, Pending(0)
default 16:56:26.771611 +0200 gamed TIC TLS Event [1:0x7ffb39f262c0]:
12, Pending(0)
default 16:56:26.771633 +0200 gamed TIC TLS Event [1:0x7ffb39f262c0]:
14, Pending(0)
default 16:56:26.785976 +0200 gamed TIC TLS Trust Result
[1:0x7ffb39f262c0]: 0
default 16:56:26.791305 +0200 SafariDAVClient TIC TLS Event
[1:0x7f88aec176d0]: 2, Pending(0)
default 16:56:26.791380 +0200 SafariDAVClient TIC TLS Event
[1:0x7f88aec176d0]: 11, Pending(0)
default 16:56:26.791963 +0200 SafariDAVClient TIC TLS Event
[1:0x7f88aec176d0]: 12, Pending(0)
default 16:56:26.791986 +0200 SafariDAVClient TIC TLS Event
[1:0x7f88aec176d0]: 14, Pending(0)
default 16:56:26.801800 +0200 SafariDAVClient CFNetwork-AOSKit:
Reaching out to AOSKit for X-mobile me token
default 16:56:26.801955 +0200 SafariDAVClient CFNetwork-AOSKit:
Applied X-mobile me auth to request
default 16:56:26.804298 +0200 SafariDAVClient TIC TLS Trust Result
[1:0x7f88aec176d0]: 0
default 16:56:26.805810 +0200 apsd <APSCOnfiguration: 0x7ff10fe3a9f0>:
validating config signature for host init-s01st.push.apple.com
default 16:56:26.807430 +0200 apsd Bag signature verification succeeded
default 16:56:26.807643 +0200 apsd Calling configuration completion blocks
<APSCOnfiguration: 0x7ff10fe3a9f0> expiration date 2017-05-26 15:25:30 +0000
error: (null)
default 16:56:26.807713 +0200 apsd APSTCPStream <APSTCPStream:
0x7ff10fe0d3b0> got config <APSCOnfiguration: 0x7ff10fe3a9f0>
default 16:56:26.807758 +0200 apsd <APSOOutgoingMessageQueue:
0x7ff10fe26d20> setNumberOfCriticalMessageFlushesBeforeDisconnecting:
changing from 3 to 3 (got number 3)
default 16:56:26.807785 +0200 apsd <APSOOutgoingMessageQueue:
0x7ff10fe26d20> setCriticalMessageKeepAliveTimerDuration: changing from
10.000000 to 10.000000 (got number 10)
default 16:56:26.807808 +0200 apsd <APSOOutgoingMessageQueue:
0x7ff10fe26d20> setCriticalMessageTimeout: changing from 10.000000 to
10.000000 (got number 10)
default 16:56:26.807853 +0200 apsd <APSTCPStream: 0x7ff10fe0d3b0> env
isLoadBalanced, using server count 10 and hostname

```

courier.sandbox.push.apple.com
default 16:56:26.807894 +0200 apsd <APSTCPStream: 0x7ff10fe0d3b0>:
Connecting to server 5-courier.sandbox.push.apple.com and port 5223
default 16:56:26.808013 +0200 apsd Stream client bypassing proxies on TCP
Conn [4:0x7ff10fe3e7b0]
default 16:56:26.808037 +0200 apsd TCP Conn 0x7ff10fe3e7b0 started
default 16:56:26.808107 +0200 apsd <APSCourier: 0x7ff10fe24350>:
Connecting to courier 5-courier.sandbox.push.apple.com with stream:
<APSTCPStreamMaster: 0x7ff10fe30730>
default 16:56:27.077734 +0200 mobileassetd 0x7f87d1253c10 Main Listener:
XPC_TYPE_CONNECTION <connection: 0x7f87d1253c10> { name =
com.apple.mobileassetd (peer), listener = false, pid = 393, euid = 501, egid = 20,
asid = 100008 }
default 16:56:27.077812 +0200 mobileassetd 0x7f87d10033b0 Client
connection: XPC_TYPE_DICTIONARY <dictionary: 0x7f87d10033b0> { count = 5,
transaction: 1, voucher = 0x7f87d1008260, contents =
    "AssetType" => <string: 0x7f87d1003460> { length = 26, contents =
"com.apple.MobileAsset.WiFi" }
    "Local Cache Only" => <bool: 0x7ffdd7a6aa8>: true
    "Timeout" => <double: 0x7f87d1000120>: 15.000000
    "_IPC_TYPE" => <uint64: 0x7f87d1000810>: 13
    "ClientName" => <string: 0x7f87d1005940> { length = 9, contents =
"WiFiProxy" }
}
default 16:56:27.077910 +0200 mobileassetd HANDLER - assetQuery
[com.apple.MobileAsset.WiFi]: (local=1) [(null)]
default 16:56:27.078003 +0200 mobileassetd [MobileAssetError:29] No asset
metadata available to search
default 16:56:27.078040 +0200 mobileassetd No cached asset metadata for
type com.apple.MobileAsset.WiFi
default 16:56:27.078698 +0200 WiFiProxy 0x7ff67e10db40 Copy matching
assets reply: XPC_TYPE_DICTIONARY <dictionary: 0x7ff67e10db40> { count = 1,
transaction: 0, voucher = 0x0, contents =
    "Result" => <int64: 0x7ff67e106ee0>: 29
}
default 16:56:27.078844 +0200 mobileassetd 0x7f87cf4284f0 Main Listener:
XPC_TYPE_CONNECTION <connection: 0x7f87cf4284f0> { name =
com.apple.mobileassetd (peer), listener = false, pid = 393, euid = 501, egid = 20,
asid = 100008 }
default 16:56:27.078908 +0200 mobileassetd 0x7f87cf4264d0 Client
connection: XPC_TYPE_DICTIONARY <dictionary: 0x7f87cf4264d0> { count = 4,
transaction: 1, voucher = 0x7f87cf423210, contents =
    "AssetType" => <string: 0x7f87cf426580> { length = 26, contents =
"com.apple.MobileAsset.WiFi" }
    "DaemonConfigKeys" => <array: 0x7f87cf423690> { count = 1, capacity = 2,
contents =
        0: <string: 0x7f87cf400970> { length = 9, contents = "ServerURL" }
    }
    "_IPC_TYPE" => <uint64: 0x7f87cf4009a0>: 24
    "ClientName" => <string: 0x7f87cf4263a0> { length = 9, contents =

```

```

"WiFiProxy" }
}
default 16:56:27.079013 +0200 WiFiProxy 0x7ff67cd0b790 Daemon
configuration query reply: XPC_TYPE_DICTIONARY <dictionary: 0x7ff67cd0b790>
{ count = 2, transaction: 0, voucher = 0x0, contents =
    "Dictionary" => <dictionary: 0x7ff67cd1d830> { count = 1, transaction: 0,
voucher = 0x0, contents =
    "ServerURL" => <dictionary: 0x7ff67cd0dbf0> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "com.apple.CFURL.magic" => <uuid: 0x7ff67cd05c30>
C3853DCC-9776-4114-B6C1-FD9F51944A6D
        "com.apple.CFURL.string" => <string: 0x7ff67cd03d80> { length =
36, contents = "https://mesu.apple.com/assets/macos/" }
        "com.apple.CFURL.base" => <null: 0x7ffdd7a6f80>: null-object
    }
}
}
"Result" => <int64: 0x7ff67cd04300>: 0
}
default 16:56:27.079127 +0200 WiFiProxy [MobileAssetError:29] Unable to
copy asset information from https://mesu.apple.com/assets/macos/ for asset type
com.apple.MobileAsset.WiFi
default 16:56:27.079130 +0200 mobileassetd 0x7ffdd7a6ca0 Client
connection: XPC_TYPE_ERROR Connection invalid <error: 0x7ffdd7a6ca0> { count
= 1, transaction: 0, voucher = 0x0, contents =
    "XPCErrorDescription" => <string: 0x7ffdd7a6f18> { length = 18, contents =
"Connection invalid" }
}
default 16:56:27.079171 +0200 mobileassetd Client connection invalid
(Connection invalid); terminating connection
default 16:56:27.079215 +0200 mobileassetd 0x7ffdd7a6ca0 Client
connection: XPC_TYPE_ERROR Connection invalid <error: 0x7ffdd7a6ca0> { count
= 1, transaction: 0, voucher = 0x0, contents =
    "XPCErrorDescription" => <string: 0x7ffdd7a6f18> { length = 18, contents =
"Connection invalid" }
}
default 16:56:27.079245 +0200 mobileassetd Client connection invalid
(Connection invalid); terminating connection
default 16:56:27.081368 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default 16:56:27.081527 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 20, EGID: 20
default 16:56:27.081755 +0200 opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default 16:56:27.091304 +0200 opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default 16:56:27.093486 +0200 WiFiVelocityAgent STARTUP! (v49)
default 16:56:27.099311 +0200 WiFiVelocityAgent IORegistry entry
'IODeviceTree:/efi/platform' does not contain the key 'apple-coprocessor-version'
default 16:56:27.100162 +0200 com.apple.WebKit.Networking
0x110ca9400 - NetworkResourceLoader::didReceiveResponse: (pageID = 7,

```

```

frameID = 1, resourceID = 29, httpStatusCode = 200, length = 65536)
default 16:56:27.100198 +0200 com.apple.WebKit.Networking
    0x110ca9400 - NetworkResourceLoader::didReceiveResponse: Should not
wait for message from WebContent process before continuing resource load (pageID
= 7, frameID = 1, resourceID = 29)
default 16:56:27.100275 +0200 com.apple.WebKit.Networking
    0x110ca9400 - NetworkResourceLoader::didReceiveBuffer: Started receiving
data (pageID = 7, frameID = 1, resourceID = 29)
default 16:56:27.100322 +0200 com.apple.WebKit.WebContent
    0x113a5a700 - WebResourceLoader::didReceiveResponse: (pageID = 7,
frameID = 1, resourceID = 29, status = 200)
default 16:56:27.100413 +0200 com.apple.WebKit.WebContent
    0x113a5a700 - WebResourceLoader::didReceiveData: Started receiving data
(pageID = 7, frameID = 1, resourceID = 29)
default 16:56:27.100851 +0200 WiFiVelocityAgent Created new peerID with
idString [35g3cuqy52g9q], displayNameAndPID [Craig's iMac,4036CBDE].
default 16:56:27.102310 +0200 secd WiFiVelocityAgen[463] copy_matching
Error Domain=NSOSStatusErrorDomain Code=-50 "query missing class
name" (paramErr: error in user parameter list) UserInfo={NSDescription=query
missing class name}
default 16:56:27.103360 +0200 opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default 16:56:27.104180 +0200 WiFiVelocityAgent 0x7faa9d80f340 opened /
var/folders/j8/bbhn9g892k14cv1xw2hp2fy80000gn/C//mds/mdsObject.db: 4636
bytes
default 16:56:27.104419 +0200 WiFiVelocityAgent 0x7faa9d814880
opened /var/folders/j8/bbhn9g892k14cv1xw2hp2fy80000gn/C//mds/mdsDirectory.db:
50744 bytes
default 16:56:27.106014 +0200 WiFiVelocityAgent 0x7faa9d809430
opened /var/folders/j8/bbhn9g892k14cv1xw2hp2fy80000gn/C//mds/mdsDirectory.db:
50744 bytes
default 16:56:27.107050 +0200 WiFiVelocityAgent 0x7faa9d832d30
opened /Users/craigdenham/Library/Keychains/login.keychain-db: 218248 bytes
default 16:56:27.113933 +0200 trustd database version is: 0x00000109 :
1 : (null)
default 16:56:27.116077 +0200 WiFiVelocityAgent could not enable test
hierarchy: ApplePinningAllowTestCertsAppleIDAuthority not true
default 16:56:27.116308 +0200 securityd keychain reference in server mode
default 16:56:27.129952 +0200 wifivelocityd STARTUP! (v49)
default 16:56:27.139283 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default 16:56:27.150976 +0200 trustd cert[2]: AnchorTrusted =(leaf)[force]>
0
default 16:56:27.151794 +0200 authd MacOS error: -67050
default 16:56:27.222981 +0200 pkd No plugins found to match query
<private>
default 16:56:27.223931 +0200 pkd No plugins found to match query
<private>
default 16:56:27.224796 +0200 pkd No plugins found to match query
<private>

```

default 16:56:27.326586 +0200 com.apple.WebKit.WebContent
0x1075f5000 - WebLoaderStrategy::scheduleLoad: Resource has been queued for scheduling with the NetworkProcess (frame = 0x10755b000, priority = 1, pageID = 1, frameID = 1, resourceID = 43, WebResourceLoader = 0x1074b7d20)

default 16:56:27.326684 +0200 com.apple.WebKit.Networking
0x110c5c000 - NetworkResourceLoader::start: Retrieving resource from cache (pageID = 1, frameID = 1, resourceID = 43, isMainResource = 0, isSynchronous = 0)

default 16:56:27.326718 +0200 com.apple.WebKit.Networking
0x110c5c000 - NetworkResourceLoader::startNetworkLoad: (pageID = 1, frameID = 1, resourceID = 43, isMainResource = 0, isSynchronous = 0)

default 16:56:27.420189 +0200 com.apple.WebKit.Networking
TIC TCP Conn Event [46:0x7fa644d56600]: 2 Err(0)

default 16:56:27.420218 +0200 com.apple.WebKit.Networking
TIC TCP Conn Cancel [46:0x7fa644d56600]

default 16:56:27.420244 +0200 com.apple.WebKit.Networking
TIC TCP Conn Destroyed [46:0x7fa644d56600]

default 16:56:27.422125 +0200 gamed TIC TLS Event [1:0x7ffb39f262c0]: 20, Pending(0)

default 16:56:27.422326 +0200 gamed TIC TCP Conn Event [1:0x7ffb39f262c0]: 8 Err(0)

default 16:56:27.422341 +0200 gamed TIC TLS Handshake Complete [1:0x7ffb39f262c0]

default 16:56:27.423188 +0200 com.apple.WebKit.Networking
0x110cce400 - NetworkResourceLoader::didFinishLoading: (pageID = 7, frameID = 1, resourceID = 28)

default 16:56:27.423360 +0200 com.apple.WebKit.WebContent
0x114e47c08 - WebResourceLoader::didFinishResourceLoad: (pageID = 7, frameID = 1, resourceID = 28)

default 16:56:27.423922 +0200 com.apple.WebKit.WebContent
0x10fdf5000 - WebLoaderStrategy::scheduleLoad: Resource has been queued for scheduling with the NetworkProcess (frame = 0x10fd61000, priority = 2, pageID = 7, frameID = 1, resourceID = 30, WebResourceLoader = 0x113a5ae38)

default 16:56:27.423972 +0200 com.apple.WebKit.Networking
0x110c5c400 - NetworkResourceLoader::start: Retrieving resource from cache (pageID = 7, frameID = 1, resourceID = 30, isMainResource = 0, isSynchronous = 0)

default 16:56:27.424004 +0200 com.apple.WebKit.Networking
0x110c5c400 - NetworkResourceLoader::startNetworkLoad: (pageID = 7, frameID = 1, resourceID = 30, isMainResource = 0, isSynchronous = 0)

default 16:56:27.518196 +0200 accountsd "Idle-exit-preventing transaction ended!"

default 16:56:27.518255 +0200 accountsd "Idle-exit-preventing transaction ended!"

default 16:56:27.518275 +0200 accountsd "Idle-exit-preventing transaction ended!"

default 16:56:27.518301 +0200 accountsd "Idle-exit-preventing transaction ended!"

default 16:56:27.518327 +0200 accountsd "Idle-exit-preventing transaction ended!"

default 16:56:27.518393 +0200 accountsd "Idle-exit-preventing transaction ended!"

```

default      16:56:27.518422 +0200  accountsd "Idle-exit-preventing transaction
ended!"
default      16:56:27.518451 +0200  accountsd "Idle-exit-preventing transaction
ended!"
default      16:56:27.518488 +0200  accountsd "Idle-exit-preventing transaction
ended!"
default      16:56:27.556681 +0200  opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default      16:56:27.556736 +0200  opendirectoryd queuing request to connection
- '<private>'
default      16:56:27.574406 +0200  syncdefaultsd  TIC TLS Event
[6:0x7fe9f301d800]: 20, Pending(0)
default      16:56:27.574610 +0200  syncdefaultsd  TIC TCP Conn Event
[6:0x7fe9f301d800]: 8 Err(0)
default      16:56:27.574625 +0200  syncdefaultsd  TIC TLS Handshake Complete
[6:0x7fe9f301d800]
default      16:56:27.574773 +0200  syncdefaultsd  CFNetwork-AOSKit: Reaching
out to AOSKit for X-mobile me token
default      16:56:27.574820 +0200  syncdefaultsd  CFNetwork-AOSKit: Applied X-
mobile me auth to request
default      16:56:27.588702 +0200  SafariDAVClient  TIC TLS Event
[1:0x7f88aec176d0]: 20, Pending(0)
default      16:56:27.589099 +0200  SafariDAVClient  TIC TCP Conn Event
[1:0x7f88aec176d0]: 8 Err(0)
default      16:56:27.589137 +0200  SafariDAVClient  TIC TLS Handshake
Complete [1:0x7f88aec176d0]
default      16:56:27.589296 +0200  SafariDAVClient  CFNetwork-AOSKit:
Reaching out to AOSKit for X-mobile me token
default      16:56:27.589414 +0200  SafariDAVClient  CFNetwork-AOSKit:
Applied X-mobile me auth to request
default      16:56:27.668820 +0200  com.apple.WebKit.WebContent
0x7fcb9b108dc0 -
PerformanceMonitor::measurePostBackgroundingMemoryUsage: Process was using
54476800 bytes of memory after becoming non visible.
default      16:56:27.735549 +0200  com.apple.WebKit.Networking
0x110ca9400 - NetworkResourceLoader::didFinishLoading: (pageID = 7,
frameID = 1, resourceID = 29)
default      16:56:27.735744 +0200  com.apple.WebKit.WebContent
0x113a5a700 - WebResourceLoader::didFinishResourceLoad: (pageID = 7,
frameID = 1, resourceID = 29)
default      16:56:27.738004 +0200  com.apple.WebKit.Networking
0x110c5c000 - NetworkResourceLoader::didReceiveResponse: (pageID = 1,
frameID = 1, resourceID = 43, httpStatusCode = 204, length = -1)
default      16:56:27.738041 +0200  com.apple.WebKit.Networking
0x110c5c000 - NetworkResourceLoader::didReceiveResponse: Should not wait
for message from WebContent process before continuing resource load (pageID = 1,
frameID = 1, resourceID = 43)
default      16:56:27.738112 +0200  com.apple.WebKit.Networking
0x110c5c000 - NetworkResourceLoader::didFinishLoading: (pageID = 1,
frameID = 1, resourceID = 43)

```



```

default    16:56:27.738128 +0200    com.apple.WebKit.WebContent
           0x1074b7d20 - WebResourceLoader::didReceiveResponse: (pageID = 1,
frameID = 1, resourceID = 43, status = 204)
default    16:56:27.738182 +0200    com.apple.WebKit.WebContent
           0x1074b7d20 - WebResourceLoader::didFinishResourceLoad: (pageID = 1,
frameID = 1, resourceID = 43)
default    16:56:27.738895 +0200    gamed      GKDataRequestManager:
endTransaction:
default    16:56:27.740681 +0200    com.apple.WebKit.WebContent
           0x7fac3c218f00 -
PerformanceMonitor::measurePostBackgroundingMemoryUsage: Process was using
22388736 bytes of memory after becoming non visible.
default    16:56:27.746893 +0200    gamed      GKClientProxy: clientForBundleID:
default    16:56:27.746969 +0200    gamed      GKClientProxy:
updateIfRecentlyInstalled
default    16:56:27.747112 +0200    gamed      GKDataRequestManager:
beginTransaction:
default    16:56:27.748243 +0200    com.apple.WebKit.Networking
           0x110c5c400 - NetworkResourceLoader::didReceiveResponse: (pageID = 7,
frameID = 1, resourceID = 30, httpStatusCode = 200, length = 103776)
default    16:56:27.748280 +0200    com.apple.WebKit.Networking
           0x110c5c400 - NetworkResourceLoader::didReceiveResponse: Should not wait
for message from WebContent process before continuing resource load (pageID = 7,
frameID = 1, resourceID = 30)
default    16:56:27.748349 +0200    com.apple.WebKit.Networking
           0x110c5c400 - NetworkResourceLoader::didReceiveBuffer: Started receiving
data (pageID = 7, frameID = 1, resourceID = 30)
default    16:56:27.748401 +0200    com.apple.WebKit.WebContent
           0x113a5ae38 - WebResourceLoader::didReceiveResponse: (pageID = 7,
frameID = 1, resourceID = 30, status = 200)
default    16:56:27.748483 +0200    com.apple.WebKit.WebContent
           0x113a5ae38 - WebResourceLoader::didReceiveData: Started receiving data
(pageID = 7, frameID = 1, resourceID = 30)
default    16:56:27.748862 +0200    opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default    16:56:27.748929 +0200    opendirectoryd queuing request to connection
- '<private>'
default    16:56:27.749038 +0200    opendirectoryd queuing request to connection
- '<private>'
default    16:56:27.755685 +0200    gamed      TIC TCP Conn Start
[2:0x7ffb39e22790]
default    16:56:27.758733 +0200    apsd TCP Conn 0x7ff10fe3e7b0 event 1. err: 0
default    16:56:27.758749 +0200    apsd TCP Conn 0x7ff10fe3e7b0 complete. fd:
18, err: 0
default    16:56:27.758847 +0200    apsd TCP Conn 0x7ff10fe3e7b0 starting SSL
negotiation
default    16:56:27.765662 +0200    accountsd "Idle-exit-preventing transaction
ended!"
default    16:56:27.765839 +0200    NotificationCenter calling plugin beginUsing:
default    16:56:27.766070 +0200    pkd allowing host 426 <private> to use plug-in

```

```

<private>(<private>) uuid=BF109B75-83EB-4781-AF89-818E5FD4F3DF at
<private>
default 16:56:27.768516 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default 16:56:27.768693 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 20, EGID: 20
default 16:56:27.768931 +0200 opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default 16:56:27.778146 +0200 opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default 16:56:27.780371 +0200 trustd cert[2]: AnchorTrusted =(leaf)[force]>
0
default 16:56:27.782743 +0200 opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default 16:56:27.783399 +0200 opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default 16:56:27.791530 +0200 trustd cert[2]: AnchorTrusted =(leaf)[force]>
0
default 16:56:27.799306 +0200 trustd cert[2]: AnchorTrusted =(leaf)[force]>
0
default 16:56:27.800069 +0200 com.apple.WebKit.WebContent
0x10fdf5000 - WebLoaderStrategy::scheduleLoad: Resource has been queued
for scheduling with the NetworkProcess (frame = 0x10fd61000, priority = 2, pageID =
7, frameID = 1, resourceID = 31, WebResourceLoader = 0x113bbe348)
default 16:56:27.800138 +0200 com.apple.WebKit.Networking
0x110c5cc00 - NetworkResourceLoader::start: Retrieving resource from cache
(pageID = 7, frameID = 1, resourceID = 31, isMainResource = 0, isSynchronous = 0)
default 16:56:27.800183 +0200 com.apple.WebKit.Networking
0x110c5cc00 - NetworkResourceLoader::startNetworkLoad: (pageID = 7,
frameID = 1, resourceID = 31, isMainResource = 0, isSynchronous = 0)
default 16:56:27.801137 +0200 ContactsAccountsService [Accounts] Current
connection, <NSXPCCConnection: 0x7f859ff022d0> connection from pid 359, doesn't
have account access.
default 16:56:27.801692 +0200 CalNCService [Accounts] Failed to update
account with identifier 3BCFC0BB-3342-4091-AF67-4E78CE39F56F, error: Error
Domain=ABAddressBookErrorDomain Code=1002 "(null)"
default 16:56:27.808484 +0200 trustd cert[2]: AnchorTrusted =(leaf)[force]>
0
default 16:56:27.814641 +0200 NotificationCenter completed calling plugin
beginUsing: for pid: 465
default 16:56:27.838786 +0200 accountsd "<private> (<private>) received"
error 16:56:27.843679 +0200 accountsd "Cannot check access to a private
account type: com.apple.account.AppleAccount"
default 16:56:27.843719 +0200 accountsd "No TCC state found: <private>,
com.apple.account.AppleAccount"
error 16:56:27.852644 +0200 accountsd "Cannot check access to a private
account type: <private>"
default 16:56:27.852680 +0200 accountsd "No TCC state found: <private>,
<private>"
default 16:56:27.878629 +0200 com.apple.iCal.CalendarNC

```

in _willPerformHostCallback: block
error 16:56:27.879409 +0200 CalendarAgent error: sql cached statement
NSSQLiteStatement <0x7f940e09ceb0> on entity 'Group' with sql text 'SELECT
t0.Z_ENT, t0.Z_PK, t0.Z_OPT, t0.ZCOLORSTRING, t0.ZISENABLED, t0.ZNOTES,
t0.ZOMITSYNCRECORD, t0.ZORDER, t0.ZSYMBOLICCOLORNAME, t0.ZTITLE,
t0.ZUID, t0.ZPUBLICATION, t0.ZALARMSDISABLED, t0.ZCHECKED,
t0.ZHASSHAREES, t0.ZISEVENTCONTAINER,
t0.ZISMARKEDIMMUTABLESHAREES, t0.ZISMARKEDUNDELETABLE,
t0.ZISTASKCONTAINER, t0.ZNOTIFICATIONCOUNT,
t0.ZSHAREDEFAULTALARMSETTINGS,
t0.ZSUPPRESSEVENTSCHEDULINGNOTIFICATIONS, t0.ZDEFAULTALARMSET,
t0.ZGROUP, t0.Z47_GROUP, t0.ZLOCALDEFAULTALARMSET,
t0.ZSUBSCRIPTIONINFO, t0.ZACCOUNTIDFORHEADING,
t0.ZGROUPHEADERTITLE, t0.ZISEDITABLE,
t0.ZISSUGGESTEDEVENTCALENDAR, t0.ZISDELEGATE, t0.ZPERMISSION,
t0.ZPREPUBLISHURLSTRING, t0.ZPUBLISHURLSTRING,
t0.ZSERVERSUBSCRIPTIONURLSTRING, t0.ZSHARINGSTATUS, t0.ZCTAG,
t0.ZCALENDARPATH, t0.ZCANBEPUBLISHED, t0.ZISAFFECTINGAVAILABILITY,
t0.ZISCOLOREDITABLE, t0.ZISFAMILYCALENDAR, t0.ZISRENAMEABLE,
t0.ZOWNERDISPLAYNAME, t0.ZOWNERPRINCIPALPATH, t0.ZPUSHKEY,
t0.ZSYNCTOKEN, t0.ZTIMEZONESTRING, t0.ZETAG, t0.ZCHANGEKEY,
t0.ZFOLDERID, t0.ZISDISTINGUISHED, t0.ZPARENTFOLDERID, t0.ZSYNCSTATE,
t0.ZISEXPANDED, t0.ZDATAFLOWSTOWARDLOCALSTORE, t0.ZPRINCIPAL,
t0.Z51_PRINCIPAL, t0.ZACCOUNTID, t0.ZISDELEGATE1,
t0.ZISINSEPARATEWINDOW, t0.ZKEEPOFFLINE,
t0.ZOVERRIDEBASEURLSTRING, t0.ZREFRESHDATE,
t0.ZSHAREDEFAULTALARMSETTINGS1, t0.ZSUPPORTSDEFAULTALARMS,
t0.ZDEFAULTALARMSET1, t0.ZLOCALDEFAULTALARMSET1,
t0.ZMIGRATIONGROUP, t0.ZALLOWEDCALENDARCREATIONTYPES,
t0.ZAVAILABILITYDATA, t0.ZCALENDARHOMEPATH,
t0.ZCALENDARHOMEPUSHKEY, t0.ZDEFAULTCALENDARPATH,
t0.ZDROPBOXPATH, t0.ZHOMECTAG, t0.ZHOMESYNCTOKEN, t0.ZINBOXCTAG,
t0.ZINBOXPATH, t0.ZINBOXSYNCTOKEN, t0.ZISAUTOSCHEDULESUPPORTED,
t0.ZISCALENDARPROXYSUPPORTED,
t0.ZISCALENDARSERVERPRIVATEEVENTSSUPPORTED,
t0.ZISCALENDARUSERSEARCHREPORTSUPPORTED,
t0.ZISCHECKFORVALIDEMAILSUPPORTED,
t0.ZISCHECKSUMMINGSUPPORTED,
t0.ZISEXPANDPROPERTYREPORTSUPPORTED,
t0.ZISINBOXAVAILABILITYSUPPORTED, t0.ZISJUNKREPORTINGSUPPORTED,
t0.ZISLIKENESSPROPAGATIONSUPPORTED,
t0.ZISMANAGEDATTACHMENTSUPPORTED,
t0.ZISPRIVATECOMMENTSSUPPORTED,
t0.ZISREQUESTCOMPRESSIONSUPPORTED,
t0.ZISSHARINGSCHEDULINGSUPPORTED, t0.ZISSHARINGSUPPORTED,
t0.ZLASTPUSHSUBSCRIPTION, t0.ZNEXTDEEPPREFRESH,
t0.ZNOTIFICATIONCOLLECTIONCTAG, t0.ZNOTIFICATIONCOLLECTIONPATH,
t0.ZNOTIFICATIONCOLLECTIONSYNCTOKEN, t0.ZNOTIFICATIONURLSTRING,
t0.ZOUTBOXPATH, t0.ZPRINCIPALPATH, t0.ZPUSHTRANSPORTS,
t0.ZQUOTAFREEBYTES, t0.ZSUPPORTSCALENDARHOMESYNC,

```

t0.ZSUPPORTSFREEBUSY, t0.ZSUPPORTSNOTSERIALIZINGTIMEZONES,
t0.ZSUPPORTSRECURRENCESPLITONSERVER,
t0.ZSUPPORTSSUBSCRIPTIONCALENDARS, t0.ZSUPPORTSUNBIND,
t0.ZLASTERROR, t0.ZDELETEDITEMSFOLDERID,
t0.ZDELETEDITEMSFOLDERSYNCSTATE,
t0.ZEXCHANGESERVERMAJORBUILDNUMBER,
t0.ZEXCHANGESERVERMAJORVERSION,
t0.ZEXCHANGESERVERMINORBUILDNUMBER,
t0.ZEXCHANGESERVERMINORVERSION, t0.ZEXCHANGESERVERVERSION,
t0.ZMAILBOX, t0.ZROOTFOLDERID, t0.ZLASTERROR1 FROM ZNODE t0 WHERE
( t0.Z_PK IN (SELECT * FROM _Z_intarray0) AND t0.Z_ENT >= ? AND t0.Z_ENT
<= ?) ' failed due to missing variable binding for (null) with expecting bindings (
    "<NSSQLBindVariable: 0x7f940e09d250>",
    "<NSSQLBindVariable: 0x7f940e09d330>"
) but actual substitution variables {
    objects = "{<NSManagedObject: 0x7f940d640320> (entity: CalDAVPrincipal; id:
0x180056b <x-coredata://9EFFEAE4-B665-4D21-9845-9DD5E6B92D51/
CalDAVPrincipal/p6> ; data: <fault>)}";
}

```

error 16:56:27.889317 +0200 com.apple.iCal.CalendarNC Detected missing constraints for <private>. It cannot be placed because there are not enough constraints to fully define the size and origin. Add the missing constraints, or set translatesAutoresizingMaskIntoConstraints=YES and constraints will be generated for you. If this view is laid out manually on macOS 10.12 and later, you may choose to not call [super layout] from your override. Set a breakpoint on DETECTED_MISSING_CONSTRAINTS to debug. This error will only be logged once.

default 16:56:27.910076 +0200 NotificationCenter tearing down extension request for pid 465

default 16:56:27.920459 +0200 SafariDAVClient CFNetwork-AOSKit: Reaching out to AOSKit for X-mobile me token

default 16:56:27.920511 +0200 SafariDAVClient CFNetwork-AOSKit: Applied X-mobile me auth to request

default 16:56:27.923632 +0200 com.apple.WebKit.Networking
0x110c5c400 - NetworkResourceLoader::didFinishLoading: (pageID = 7, frameID = 1, resourceID = 30)

default 16:56:27.923767 +0200 com.apple.WebKit.WebContent
0x113a5ae38 - WebResourceLoader::didFinishResourceLoad: (pageID = 7, frameID = 1, resourceID = 30)

default 16:56:27.926403 +0200 com.apple.WebKit.Networking
0x110c5cc00 - NetworkResourceLoader::didReceiveResponse: (pageID = 7, frameID = 1, resourceID = 31, httpStatusCode = 200, length = 528331)

default 16:56:27.926444 +0200 com.apple.WebKit.Networking
0x110c5cc00 - NetworkResourceLoader::didReceiveResponse: Should not wait for message from WebContent process before continuing resource load (pageID = 7, frameID = 1, resourceID = 31)

default 16:56:27.926519 +0200 com.apple.WebKit.WebContent
0x113bbe348 - WebResourceLoader::didReceiveResponse: (pageID = 7, frameID = 1, resourceID = 31, status = 200)

default 16:56:27.926513 +0200 com.apple.WebKit.Networking

0x110c5cc00 - NetworkResourceLoader::didReceiveBuffer: Started receiving data (pageID = 7, frameID = 1, resourceID = 31)

default 16:56:27.926616 +0200 com.apple.WebKit.WebContent

0x113bbe348 - WebResourceLoader::didReceiveData: Started receiving data (pageID = 7, frameID = 1, resourceID = 31)

default 16:56:28.175973 +0200 callservicesd Ending transaction for <private>. Transaction count is now 0

default 16:56:28.198034 +0200 AppleIDAuthAgent Next time for '<private>': Fri May 26 16:56:28 2017 in 0.000000 seconds

default 16:56:28.198057 +0200 AppleIDAuthAgent Next action time for '<private>': Tue May 30 21:09:08 2017 (not certificate periodic)

default 16:56:28.283211 +0200 gamed TIC TCP Conn Event [2:0x7ffb39e22790]: 1 Err(0)

default 16:56:28.283231 +0200 gamed TIC TCP Conn Connected [2:0x7ffb39e22790]: Err(0)

default 16:56:28.283299 +0200 gamed TIC Enabling TLS [2:0x7ffb39e22790]

default 16:56:28.293119 +0200 com.apple.WebKit.Networking TIC TCP Conn Event [60:0x7fa644d3f8f0]: 2 Err(0)

default 16:56:28.293146 +0200 com.apple.WebKit.Networking TIC TCP Conn Cancel [60:0x7fa644d3f8f0]

default 16:56:28.293172 +0200 com.apple.WebKit.Networking TIC TCP Conn Destroyed [60:0x7fa644d3f8f0]

default 16:56:28.297225 +0200 SafariDAVClient ApplePushService: <APSCConnection: 0x7f88b0800bd0> setEnabledTopics ("com.me.bookmarks") ignoredTopics () opportunisticTopics () sendToDaemon: YES

default 16:56:28.297302 +0200 SafariDAVClient ApplePushService: <APSCConnection: 0x7f88b0800bd0> asked for publicToken, got <3768eb4f4a2cd5a6 422899d6 f49f63a7 e85b9388 e80f29b1 17b6e894 2dd04dc3>

default 16:56:28.297355 +0200 SafariDAVClient ApplePushService: <APSCConnection: 0x7f88b0800bd0> asked for publicToken, got <3768eb4f4a2cd5a6 422899d6 f49f63a7 e85b9388 e80f29b1 17b6e894 2dd04dc3>

default 16:56:28.301034 +0200 SafariDAVClient CFNetwork-AOSKit: Reaching out to AOSKit for X-mobile me token

default 16:56:28.301089 +0200 SafariDAVClient CFNetwork-AOSKit: Applied X-mobile me auth to request

default 16:56:28.450432 +0200 apsd TCP Conn 0x7ff10fe3e7b0 SSL Handshake DONE

default 16:56:28.450854 +0200 apsd <APSCourier: 0x7ff10fe24350>: Connected to courier 5-courier.sandbox.push.apple.com (17.188.165.201) stream: <APSTCPStreamMaster: 0x7ff10fe30730> secureHandshakeEnabled YES

default 16:56:28.450897 +0200 apsd <<APSTokenState: 0x7ff10fe36900>: { tokenName=0 darkWakeEnabled, status=disconnected, willConnect=no, willDisconnect=no, systemUser=<APSSystemUser: 0x7ff1121070e0>, publicToken=<e3f3eb2 b45e2b35 d7eba84f 792ebbf c1923528c c45c7e2e 2f1a15ef bb341cbc>, sentFilterMessage=NO darkWakeEnabled=yes, topicManager=0x7ff10fe26cb0 }>: Status for user 0 darkWakeEnabled is

disconnected, but user will be connected

default 16:56:28.450974 +0200 apsd <<APSTokenState: 0x7ff10fe36900>:
 { tokenName=0 darkWakeEnabled, status=disconnected, willConnect=yes,
 willDisconnect=no, systemUser=<APSSystemUser: 0x7ff1121070e0>,
 publicToken=<e3f3ebb2 b45e2b35 d7eba84f 792ebbf c 1923528c c45c7e2e
 2f1a15ef bb341cbc>, sentFilterMessage=NO darkWakeEnabled=yes,
 topicManager=0x7ff10fe26cb0 }>: Changing status for user 0 darkWakeEnabled
 from disconnected to connecting

default 16:56:28.451016 +0200 apsd <APSCourier: 0x7ff10fe24350>: Sending
 connect message for user 0 darkWakeEnabled with token '<e3f3ebb2 b45e2b35
 d7eba84f 792ebbf c 1923528c c45c7e2e 2f1a15ef bb341cbc>'

default 16:56:28.451037 +0200 gamed TIC TLS Event [2:0x7ffb39e22790]:
 2, Pending(0)

default 16:56:28.451153 +0200 gamed TIC TLS Event [2:0x7ffb39e22790]:
 11, Pending(0)

default 16:56:28.451312 +0200 apsd Failed to talk to secd after 4 attempts.

default 16:56:28.451479 +0200 apsd Generating nonce with timestamp
 1495810588000

default 16:56:28.451489 +0200 gamed TIC TLS Event [2:0x7ffb39e22790]:
 12, Pending(0)

default 16:56:28.451509 +0200 apsd Nonce Signature input is 17 bytes
 (<00000001 5c45423d 600fb487 d665ab08 a5>)

default 16:56:28.451508 +0200 gamed TIC TLS Event [2:0x7ffb39e22790]:
 14, Pending(0)

default 16:56:28.451905 +0200 securityd found a non-proper sample,
 skipping...

default 16:56:28.453494 +0200 apsd Nonce: <00000001 5c45423d 600fb487
 d665ab08 a5> Signed: <01016d5d f4e1b35c ad6d4cb3 809f22ea b2392ea7
 409b11ff 2373e67d 54df07c3 45d0da77 cf3233c6 167dfdd7 34a117ea 191e9653
 81a41a57 9513eac2 9eef946a 5a73fa8e 28bded28 059ebe87 64041b73 9290ed13
 e34e6655 f5240554 9cc9fc70 61337a34 5b74a7bd 248ba736 dc705b58 9de85821
 b27f674e 30ac08d5 02a2a33d 0f8c> Result: 1

default 16:56:28.453541 +0200 apsd <APSCourier: 0x7ff10fe24350> generate
 nonce and sig success? YES

default 16:56:28.453749 +0200 apsd <APSCourier: 0x7ff10fe24350>: Will
 connect user 501 because in full wake

default 16:56:28.453788 +0200 apsd <<APSTokenState: 0x7ff10ff37f30>:
 { tokenName=501, status=disconnected, willConnect=no, willDisconnect=no,
 systemUser=<APSSystemUser: 0x7ff10fe3d420>, publicToken=<495e168a
 a5f94955 15e1eeb7 47a70c56 d379a155 23ddf84a 9c426003 1a278d35>,
 sentFilterMessage=NO darkWakeEnabled=no, topicManager=0x7ff10ff37fb0 }>:
 Status for user 501 is disconnected, but user will be connected

default 16:56:28.454428 +0200 gamed TIC TLS Trust Result
 [2:0x7ffb39e22790]: 0

default 16:56:28.496156 +0200 SafariDAVClient TIC TCP Conn Start
 [2:0x7f88aec31c00]

default 16:56:28.593027 +0200 apsd <APSPreferences: 0x7ff10fe07ab0>:
 Preferences may have changed, checking for any relevant changes

error 16:56:28.612993 +0200 AddressBookSourceSync warning: dynamic
 accessors failed to find @property implementation for 'serialNumber' for entity

ABCDAddressBookSource while resolving selector 'serialNumber' on class 'ABCDAddressBookSource'. Did you remember to declare it @dynamic or @synthesized in the @implementation ?

default	16:56:28.613134 +0200	deleted	sending notification:
CACHE_DELETE_PURGEABLE_UPDATED			
default	16:56:28.613203 +0200	deleted	persistence timer fired
default	16:56:28.613401 +0200	Finder	got a connection for:
com.apple.cache_delete			
default	16:56:28.613492 +0200	Finder	got proxy: <private> for service:
com.apple.cache_delete			
default	16:56:28.613643 +0200	deleted	listener: <private>
default	16:56:28.613662 +0200	deleted	Skipping entitlement check...
default	16:56:28.613797 +0200	deleted	Skipping entitlement check...
default	16:56:28.614046 +0200	deleted	GrandTotal request for urgency: 3
default	16:56:28.614154 +0200	deleted	volume: (null), total: (null)
default	16:56:28.614166 +0200	deleted	updating results for <private>
default	16:56:28.614247 +0200	deleted	Filtering for root only services.
Volume: <private>			
default	16:56:28.614284 +0200	deleted	CACHE_DELETE_URGENCY: 3
default	16:56:28.614318 +0200	Finder	setting target uid to: 501 for service:
com.apple.cache_delete			
default	16:56:28.614300 +0200	deleted	urgency: 3, urgencyLimit: 3
default	16:56:28.614342 +0200	Finder	connection invalidated
default	16:56:28.614336 +0200	deleted	starting purgeable operation
default	16:56:28.614341 +0200	deleted	newConnection invalidated
default	16:56:28.614487 +0200	deleted	callingProcess: (null), refreshAll is
FALSE, servicesToQuery: <private>			
default	16:56:28.614515 +0200	deleted	98 self.urgency: 3, self.urgencyLimit:
3			
default	16:56:28.614568 +0200	deleted	<private>: Completion callback
default	16:56:28.614597 +0200	deleted	Connecting to <private>
default	16:56:28.614741 +0200	deleted	com.apple.TMCacheDelete:
Completion callback			
default	16:56:28.614762 +0200	deleted	Connecting to
com.apple.TMCacheDelete			
default	16:56:28.614857 +0200	deleted	<private>: Completion callback
default	16:56:28.614874 +0200	deleted	Connecting to <private>
default	16:56:28.614981 +0200	deleted	com.apple.installd.CacheDelete:
Completion callback			
default	16:56:28.615007 +0200	deleted	Connecting to
com.apple.installd.CacheDelete			
default	16:56:28.614955 +0200		system_installd listener: <private>
default	16:56:28.615027 +0200		system_installd Skipping entitlement check...
default	16:56:28.615139 +0200	deleted	<private>: Completion callback
default	16:56:28.615055 +0200		TMCacheDelete listener: <private>
default	16:56:28.615165 +0200	deleted	Connecting to <private>
default	16:56:28.615095 +0200		TMCacheDelete Skipping entitlement
check...			
default	16:56:28.615301 +0200	deleted	<private>: Completion callback
default	16:56:28.615388 +0200		mobileassetd listener: <private>

default	16:56:28.615326 +0200	deleted	Connecting to <private>
default	16:56:28.615344 +0200	install	listener: <private>
default	16:56:28.615424 +0200	mobileassetd	Skipping entitlement check...
default	16:56:28.615463 +0200	deleted	<private>: Completion callback
default	16:56:28.615381 +0200	install	Skipping entitlement check...
default	16:56:28.615489 +0200	deleted	Connecting to <private>
default	16:56:28.615630 +0200	cloudphotosd	listener: <private>
default	16:56:28.615636 +0200	deleted	<private>: Completion callback
default	16:56:28.615706 +0200	cloudphotosd	Skipping entitlement check...
default	16:56:28.615862 +0200	pkd	allowing host 311 <private> to use plug-in
<private>(<private>) uuid=03AC9160-A457-47E1-B83C-EEA966C31E17 at			
<private>			
default	16:56:28.615640 +0200	deleted	calling plugIn beginUsing:
default	16:56:28.615911 +0200	bird	listener: <private>
default	16:56:28.615661 +0200	deleted	Connecting to <private>
default	16:56:28.615948 +0200	bird	Skipping entitlement check...
default	16:56:28.615707 +0200	deleted	<private>: Successful Request
default	16:56:28.616276 +0200	revisiond	listener: <private>
default	16:56:28.615739 +0200	deleted	<private>: Completion callback
default	16:56:28.616469 +0200	pkd	allowing host 311 <private> to use plug-in
<private>(<private>) uuid=20C15E64-08E0-4E97-ACA6-59C033F8AC52 at			
<private>			
default	16:56:28.616310 +0200	revisiond	Skipping entitlement check...
default	16:56:28.615783 +0200	deleted	<private> took 0.000666 seconds,
returned: (null)			
default	16:56:28.615799 +0200	deleted	<private>: Completion callback
default	16:56:28.615808 +0200	deleted	<private> returned null result
default	16:56:28.615826 +0200	deleted	Connecting to <private>
default	16:56:28.615834 +0200	deleted	Connection to <private> was
invalidated.			
default	16:56:28.616892 +0200	aslmanager	listener: <private>
default	16:56:28.615864 +0200	deleted	<private> updateInfo: <private>
default	16:56:28.616645 +0200	geodMachServiceBridge	listener: <private>
default	16:56:28.617082 +0200	pkd	allowing host 311 <private> to use plug-in
<private>(<private>) uuid=AE1638EC-FD2D-4C64-BFC5-AAA098218A81 at			
<private>			
default	16:56:28.616925 +0200	aslmanager	Skipping entitlement check...
default	16:56:28.615908 +0200	deleted	ENTRY, operation:
CACHE_DELETE_PURGEABLE_OPERATION, serviceID: <private> info: <private>			
default	16:56:28.616961 +0200	geodMachServiceBridge	Skipping entitlement
check...			
default	16:56:28.617199 +0200	coresymbolicationd	listener: <private>
default	16:56:28.615992 +0200	deleted	<private>: Completion callback
default	16:56:28.617347 +0200	AssetCache	listener: <private>
default	16:56:28.617377 +0200	mds	listener: <private>
default	16:56:28.617261 +0200	coresymbolicationd	Skipping entitlement
check...			
default	16:56:28.616001 +0200	deleted	updating cache for service:
<private>, volume: <private>, amounts: <private>			
default	16:56:28.617390 +0200	AssetCache	Skipping entitlement check...


```

default    16:56:28.617414 +0200   mds Skipping entitlement check...
default    16:56:28.617617 +0200   pkd  allowing host 311 <private> to use plug-in
<private>(<private>) uuid=C5191E04-ABEF-46EE-831A-A9E1626FFC78 at
<private>
default    16:56:28.617556 +0200   com.apple.quicklook.ThumbnailsAgent
listener: <private>
default    16:56:28.616018 +0200   deleted   Connecting to <private>
default    16:56:28.617609 +0200   com.apple.quicklook.ThumbnailsAgent
Skipping entitlement check...
default    16:56:28.616030 +0200   deleted   updating service info amount: 0,
servicelD: <private>, volume: <private>, urgency: 3 pushed: FALSE
default    16:56:28.616159 +0200   deleted   com.apple.activity_tracing.cache-
delete: Completion callback
default    16:56:28.616166 +0200   deleted   calling plugIn beginUsing:
default    16:56:28.616185 +0200   deleted   Connecting to
com.apple.activity_tracing.cache-delete
default    16:56:28.617584 +0200   kernel    SandboxViolation: AssetCache(326)
deny(1) file-read-metadata /Volumes
default    16:56:28.616330 +0200   deleted   calling plugIn beginUsing:
default    16:56:28.616336 +0200   deleted   <private>: Completion callback
default    16:56:28.616341 +0200   deleted   calling plugIn beginUsing:
default    16:56:28.616361 +0200   deleted   Connecting to <private>
default    16:56:28.616496 +0200   deleted   <private>: Completion callback
default    16:56:28.616522 +0200   deleted   Connecting to <private>
default    16:56:28.616657 +0200   deleted   <private>: Completion callback
default    16:56:28.616682 +0200   deleted   Connecting to <private>
default    16:56:28.618666 +0200   iBooksCacheDelete in
_willPerformHostCallback: block
default    16:56:28.616816 +0200   deleted   <private>: Completion callback
default    16:56:28.618750 +0200   iBooksCacheDelete Registering block
callbacks
default    16:56:28.616843 +0200   deleted   Connecting to <private>
default    16:56:28.618798 +0200   iBooksCacheDelete entitlements: <private>
default    16:56:28.617380 +0200   deleted   completed calling plugIn beginUsing:
for pid: 337
default    16:56:28.618837 +0200   iBooksCacheDelete entitlements: <private>
default    16:56:28.618294 +0200   deleted   completed calling plugIn beginUsing:
for pid: 339
default    16:56:28.618875 +0200   iBooksCacheDelete entitlements: <private>
default    16:56:28.618470 +0200   deleted   completed calling plugIn beginUsing:
for pid: 338
default    16:56:28.618909 +0200   iBooksCacheDelete entitlements: <private>
default    16:56:28.618810 +0200   deleted   Connecting to <private>
default    16:56:28.619263 +0200   CacheDeleteExtension in
_willPerformHostCallback: block
default    16:56:28.618945 +0200   iBooksCacheDelete entitlements: <private>
default    16:56:28.619308 +0200   MailCacheDelete in
_willPerformHostCallback: block
default    16:56:28.619321 +0200   CacheDeleteExtension entitlements:
<private>

```

default 16:56:28.619021 +0200 deleted completed calling plugIn beginUsing:
for pid: 335

default 16:56:28.618970 +0200 iBooksCacheDelete Registered:
com.apple.ibooks.CacheDeleteExtension, result: 0

default 16:56:28.619369 +0200 MailCacheDelete entitlements: <private>

default 16:56:28.619423 +0200 CacheDeleteExtension entitlements:
<private>

default 16:56:28.619389 +0200 deleted Connecting to <private>

default 16:56:28.619055 +0200 iBooksCacheDelete purgeable, urgency: 3

default 16:56:28.619405 +0200 MailCacheDelete entitlements: <private>

default 16:56:28.619452 +0200 CacheDeleteExtension Registered:
com.apple.Safari.CacheDeleteExtension, result: 0

default 16:56:28.619555 +0200 deleted Connecting to <private>

default 16:56:28.619736 +0200 IDECacheDeleteAppExtension
in _willPerformHostCallback: block

default 16:56:28.619082 +0200 iBooksCacheDelete Getting asked for
purgeable space

default 16:56:28.619467 +0200 MailCacheDelete entitlements: <private>

default 16:56:28.619675 +0200 deleted <private>: Successful Request

default 16:56:28.619623 +0200 CacheDeleteExtension purgeable, urgency:
3

default 16:56:28.619813 +0200 IDECacheDeleteAppExtension
entitlements: <private>

default 16:56:28.619437 +0200 iBooksCacheDelete Cache files are on a
different volume

default 16:56:28.619495 +0200 MailCacheDelete Registered: <private>,
result: 0

default 16:56:28.619715 +0200 deleted Connection to <private> was
invalidated.

default 16:56:28.619913 +0200 CacheDeleteExtension result: <private>

default 16:56:28.619848 +0200 IDECacheDeleteAppExtension
entitlements: <private>

default 16:56:28.619523 +0200 iBooksCacheDelete result: <private>

default 16:56:28.619757 +0200 MailCacheDelete purgeable, urgency: 3

default 16:56:28.619720 +0200 deleted tearing down extension request for
pid 337

default 16:56:28.619966 +0200 CacheDeleteExtension calling
completeRequestReturningItems

default 16:56:28.619882 +0200 IDECacheDeleteAppExtension
entitlements: <private>

default 16:56:28.619625 +0200 iBooksCacheDelete calling
completeRequestReturningItems

default 16:56:28.619752 +0200 deleted Connection to <private> was
invalidated.

default 16:56:28.619919 +0200 IDECacheDeleteAppExtension
entitlements: <private>

default 16:56:28.619809 +0200 deleted <private> took 0.004166 seconds,
returned: <private>

default 16:56:28.619951 +0200 IDECacheDeleteAppExtension
entitlements: <private>

default 16:56:28.619869 +0200 deleted <private> updateInfo: <private>
 default 16:56:28.619973 +0200 IDECacheDeleteAppExtension
 Registered: <private>, result: 0
 default 16:56:28.619886 +0200 deleted Connecting to <private>
 default 16:56:28.620227 +0200 IDECacheDeleteAppExtension
 purgeable, urgency: 3
 default 16:56:28.619919 +0200 deleted ENTRY, operation:
 CACHE_DELETE_PURGEABLE_OPERATION, serviceID: <private> info: <private>
 default 16:56:28.620349 +0200 IDECacheDeleteAppExtension
 result: <private>
 default 16:56:28.620015 +0200 deleted updating cache for service:
 <private>, volume: <private>, amounts: <private>
 default 16:56:28.620621 +0200 IDECacheDeleteAppExtension
 calling completeRequestReturningItems
 default 16:56:28.620046 +0200 deleted updating service info amount: 0,
 serviceID: <private>, volume: <private>, urgency: 3 pushed: FALSE
 default 16:56:28.621205 +0200 storedownloadaddlistener: <private>
 default 16:56:28.620088 +0200 deleted <private>: Successful Request
 default 16:56:28.621240 +0200 storedownloadaddSkipping entitlement check...
 default 16:56:28.620124 +0200 deleted Connection to <private> was
 invalidated.
 default 16:56:28.620136 +0200 deleted tearing down extension request for
 pid 339
 default 16:56:28.620215 +0200 deleted <private> took 0.004066 seconds,
 returned: <private>
 default 16:56:28.620266 +0200 deleted <private> updateInfo: <private>
 default 16:56:28.621538 +0200 bird newConnection invalidated
 default 16:56:28.620314 +0200 deleted ENTRY, operation:
 CACHE_DELETE_PURGEABLE_OPERATION, serviceID: <private> info: <private>
 default 16:56:28.620332 +0200 deleted Connection to <private> was
 invalidated.
 default 16:56:28.620379 +0200 deleted updating cache for service:
 <private>, volume: <private>, amounts: <private>
 default 16:56:28.620446 +0200 deleted updating service info amount: 0,
 serviceID: <private>, volume: <private>, urgency: 3 pushed: FALSE
 default 16:56:28.620595 +0200 deleted <private>: Successful Request
 default 16:56:28.620634 +0200 deleted Connection to <private> was
 invalidated.
 default 16:56:28.620676 +0200 deleted Connection to <private> was
 invalidated.
 default 16:56:28.620686 +0200 deleted tearing down extension request for
 pid 335
 default 16:56:28.620736 +0200 deleted <private> took 0.004402 seconds,
 returned: <private>
 default 16:56:28.620791 +0200 deleted <private> updateInfo: <private>
 default 16:56:28.620840 +0200 deleted ENTRY, operation:
 CACHE_DELETE_PURGEABLE_OPERATION, serviceID: <private> info: <private>
 default 16:56:28.620918 +0200 deleted updating cache for service:
 <private>, volume: <private>, amounts: <private>
 default 16:56:28.620947 +0200 deleted updating service info amount: 0,

serviceID: <private>, volume: <private>, urgency: 3 pushed: FALSE
 default 16:56:28.621412 +0200 deleted <private>: Successful Request
 default 16:56:28.621447 +0200 deleted <private>: Completion callback
 default 16:56:28.621489 +0200 deleted <private> took 0.006046 seconds,
 returned: (null)
 default 16:56:28.621511 +0200 deleted Connection to <private> was
 invalidated.
 default 16:56:28.621514 +0200 deleted <private> returned null result
 default 16:56:28.621567 +0200 deleted <private> updateInfo: <private>
 default 16:56:28.621605 +0200 deleted <private>: Successful Request
 default 16:56:28.621611 +0200 deleted ENTRY, operation:
 CACHE_DELETE_PURGEABLE_OPERATION, serviceID: <private> info: <private>
 default 16:56:28.622344 +0200 cloudphotosd newConnection invalidated
 default 16:56:28.622372 +0200 TMCachedDelete newConnection
 invalidated
 default 16:56:28.621640 +0200 deleted <private>: Completion callback
 default 16:56:28.621697 +0200 deleted updating cache for service:
 <private>, volume: <private>, amounts: <private>
 default 16:56:28.622534 +0200 revisiond newConnection invalidated
 default 16:56:28.621698 +0200 deleted Connection to <private> was
 invalidated.
 default 16:56:28.621727 +0200 deleted updating service info amount: 0,
 serviceID: <private>, volume: <private>, urgency: 3 pushed: FALSE
 error 16:56:28.622634 +0200 geodMachServiceBridge 6.1 Asked to free space
 for a volume we don't control.
 default 16:56:28.621760 +0200 deleted <private> took 0.005984 seconds,
 returned: (null)
 default 16:56:28.621783 +0200 deleted <private> returned null result
 default 16:56:28.621829 +0200 deleted <private> updateInfo: <private>
 default 16:56:28.621868 +0200 deleted ENTRY, operation:
 CACHE_DELETE_PURGEABLE_OPERATION, serviceID: <private> info: <private>
 default 16:56:28.622817 +0200 mds newConnection invalidated
 default 16:56:28.621933 +0200 deleted updating cache for service:
 <private>, volume: <private>, amounts: <private>
 default 16:56:28.622919 +0200 mobileassetd newConnection invalidated
 default 16:56:28.621961 +0200 deleted updating service info amount: 0,
 serviceID: <private>, volume: <private>, urgency: 3 pushed: FALSE
 default 16:56:28.622176 +0200 deleted <private>: Successful Request
 default 16:56:28.622209 +0200 deleted <private>: Completion callback
 default 16:56:28.622228 +0200 deleted <private>: Successful Request
 default 16:56:28.622229 +0200 deleted com.apple.TMCachedDelete:
 Successful Request
 default 16:56:28.622260 +0200 deleted <private>: Completion callback
 default 16:56:28.622260 +0200 deleted <private> took 0.007404 seconds,
 returned: <private>
 default 16:56:28.622263 +0200 deleted com.apple.TMCachedDelete:
 Completion callback
 default 16:56:28.622302 +0200 deleted Connection to <private> was
 invalidated.
 default 16:56:28.622308 +0200 deleted <private> updateInfo: <private>

default 16:56:28.622326 +0200 deleted Connection to <private> was invalidated.

default 16:56:28.622351 +0200 deleted ENTRY, operation: CACHE_DELETE_PURGEABLE_OPERATION, serviceID: <private> info: <private>

default 16:56:28.622381 +0200 deleted Connection to com.apple.TMCacheDelete was invalidated.

default 16:56:28.622417 +0200 deleted updating cache for service: <private>, volume: <private>, amounts: <private>

default 16:56:28.622446 +0200 deleted updating service info amount: 0, serviceID: <private>, volume: <private>, urgency: 3 pushed: FALSE

default 16:56:28.622479 +0200 deleted <private> took 0.007202 seconds, returned: (null)

default 16:56:28.622500 +0200 deleted <private> returned null result

default 16:56:28.622545 +0200 deleted <private> updateInfo: <private>

default 16:56:28.622584 +0200 deleted ENTRY, operation: CACHE_DELETE_PURGEABLE_OPERATION, serviceID: <private> info: <private>

default 16:56:28.622652 +0200 deleted updating cache for service: <private>, volume: <private>, amounts: <private>

default 16:56:28.622681 +0200 deleted updating service info amount: 0, serviceID: <private>, volume: <private>, urgency: 3 pushed: FALSE

default 16:56:28.623711 +0200 coresymbolicationd newConnection invalidated

default 16:56:28.622709 +0200 deleted <private>: Successful Request

default 16:56:28.622730 +0200 deleted com.apple.TMCacheDelete took 0.008009 seconds, returned: <private>

default 16:56:28.623818 +0200 installd newConnection invalidated

default 16:56:28.623815 +0200 system_installd newConnection invalidated

default 16:56:28.622741 +0200 deleted <private>: Completion callback

default 16:56:28.622777 +0200 deleted com.apple.TMCacheDelete updateInfo: <private>

default 16:56:28.624000 +0200 com.apple.quicklook.ThumbnailsAgent newConnection invalidated

default 16:56:28.622801 +0200 deleted Connection to <private> was invalidated.

default 16:56:28.624042 +0200 geodMachServiceBridge newConnection invalidated

default 16:56:28.622818 +0200 deleted ENTRY, operation: CACHE_DELETE_PURGEABLE_OPERATION, serviceID: com.apple.TMCacheDelete info: <private>

default 16:56:28.622880 +0200 deleted updating cache for service: com.apple.TMCacheDelete, volume: <private>, amounts: <private>

default 16:56:28.622909 +0200 deleted updating service info amount: 0, serviceID: com.apple.TMCacheDelete, volume: <private>, urgency: 3 pushed: FALSE

default 16:56:28.624188 +0200 AssetCache newConnection invalidated

default 16:56:28.622955 +0200 deleted <private> took 0.006306 seconds, returned: <private>

default 16:56:28.622998 +0200 deleted <private> updateInfo: <private>

default 16:56:28.623038 +0200 deleted ENTRY, operation: CACHE_DELETE_PURGEABLE_OPERATION, serviceID: <private> info: <private>

default 16:56:28.623101 +0200 deleted updating cache for service:
<private>, volume: <private>, amounts: <private>

default 16:56:28.623130 +0200 deleted updating service info amount: 0,
servicelD: <private>, volume: <private>, urgency: 3 pushed: FALSE

default 16:56:28.623199 +0200 deleted <private>: Successful Request

default 16:56:28.624447 +0200 storedownloadaddnewConnection invalidated

default 16:56:28.623233 +0200 deleted <private>: Completion callback

default 16:56:28.624510 +0200 aslmanager newConnection invalidated

default 16:56:28.623290 +0200 deleted <private>: Successful Request

default 16:56:28.623290 +0200 deleted <private> took 0.006958 seconds,
returned: <private>

default 16:56:28.623294 +0200 deleted Connection to <private> was
invalidated.

default 16:56:28.623324 +0200 deleted <private>: Completion callback

default 16:56:28.623342 +0200 deleted <private> updateInfo: <private>

default 16:56:28.623387 +0200 deleted ENTRY, operation:
CACHE_DELETE_PURGEABLE_OPERATION, servicelD: <private> info: <private>

default 16:56:28.623387 +0200 deleted Connection to <private> was
invalidated.

default 16:56:28.623462 +0200 deleted updating cache for service:
<private>, volume: <private>, amounts: <private>

default 16:56:28.623483 +0200 deleted <private>: Successful Request

default 16:56:28.623492 +0200 deleted updating service info amount: 0,
servicelD: <private>, volume: <private>, urgency: 3 pushed: FALSE

default 16:56:28.623519 +0200 deleted <private>: Completion callback

default 16:56:28.623546 +0200 deleted <private> took 0.006738 seconds,
returned: <private>

default 16:56:28.623585 +0200 deleted com.apple.installd.CacheDelete:
Successful Request

default 16:56:28.623594 +0200 deleted <private> updateInfo: <private>

default 16:56:28.623599 +0200 deleted Connection to <private> was
invalidated.

default 16:56:28.623617 +0200 deleted com.apple.installd.CacheDelete:
Completion callback

default 16:56:28.623646 +0200 deleted ENTRY, operation:
CACHE_DELETE_PURGEABLE_OPERATION, servicelD: <private> info: <private>

default 16:56:28.623687 +0200 deleted Connection to
com.apple.installd.CacheDelete was invalidated.

default 16:56:28.623711 +0200 deleted updating cache for service:
<private>, volume: <private>, amounts: <private>

default 16:56:28.623741 +0200 deleted updating service info amount: 0,
servicelD: <private>, volume: <private>, urgency: 3 pushed: FALSE

default 16:56:28.623788 +0200 deleted <private> took 0.009230 seconds,
returned: <private>

default 16:56:28.623835 +0200 deleted <private> updateInfo: <private>

default 16:56:28.623856 +0200 deleted <private>: Successful Request

default 16:56:28.623879 +0200 deleted ENTRY, operation:
CACHE_DELETE_PURGEABLE_OPERATION, servicelD: <private> info: <private>

default 16:56:28.623888 +0200 deleted <private>: Completion callback

default 16:56:28.623944 +0200 deleted updating cache for service:

<private>, volume: <private>, amounts: <private>
default 16:56:28.623962 +0200 deleted Connection to <private> was invalidated.
default 16:56:28.623974 +0200 deleted updating service info amount: 0, serviceID: <private>, volume: <private>, urgency: 3 pushed: FALSE
default 16:56:28.624021 +0200 deleted com.apple.installd.CacheDelete took 0.009043 seconds, returned: <private>
default 16:56:28.624068 +0200 deleted com.apple.installd.CacheDelete updateInfo: <private>
default 16:56:28.624070 +0200 deleted <private>: Successful Request
default 16:56:28.624102 +0200 deleted <private>: Completion callback
default 16:56:28.624111 +0200 deleted ENTRY, operation: CACHE_DELETE_PURGEABLE_OPERATION, serviceID: com.apple.installd.CacheDelete info: <private>
default 16:56:28.624163 +0200 deleted Connection to <private> was invalidated.
default 16:56:28.624175 +0200 deleted updating cache for service: com.apple.installd.CacheDelete, volume: <private>, amounts: <private>
default 16:56:28.624203 +0200 deleted updating service info amount: 0, serviceID: com.apple.installd.CacheDelete, volume: <private>, urgency: 3 pushed: FALSE
default 16:56:28.624249 +0200 deleted <private> took 0.008267 seconds, returned: <private>
default 16:56:28.624273 +0200 deleted <private>: Successful Request
default 16:56:28.624295 +0200 deleted <private> updateInfo: <private>
default 16:56:28.624304 +0200 deleted <private>: Completion callback
default 16:56:28.624337 +0200 deleted ENTRY, operation: CACHE_DELETE_PURGEABLE_OPERATION, serviceID: <private> info: <private>
default 16:56:28.624360 +0200 deleted Connection to <private> was invalidated.
default 16:56:28.624397 +0200 deleted com.apple.activity_tracing.cache-delete: Successful Request
default 16:56:28.624401 +0200 deleted updating cache for service: <private>, volume: <private>, amounts: <private>
default 16:56:28.624430 +0200 deleted updating service info amount: 0, serviceID: <private>, volume: <private>, urgency: 3 pushed: FALSE
default 16:56:28.624430 +0200 deleted com.apple.activity_tracing.cache-delete: Completion callback
default 16:56:28.624476 +0200 deleted <private> took 0.007991 seconds, returned: <private>
default 16:56:28.624490 +0200 deleted Connection to com.apple.activity_tracing.cache-delete was invalidated.
default 16:56:28.624521 +0200 deleted <private> updateInfo: <private>
default 16:56:28.624561 +0200 deleted ENTRY, operation: CACHE_DELETE_PURGEABLE_OPERATION, serviceID: <private> info: <private>
default 16:56:28.624623 +0200 deleted updating cache for service: <private>, volume: <private>, amounts: <private>
default 16:56:28.624652 +0200 deleted updating service info amount: 0, serviceID: <private>, volume: <private>, urgency: 3 pushed: FALSE
default 16:56:28.624693 +0200 deleted <private> took 0.009067 seconds,

returned: <private>
default 16:56:28.624737 +0200 deleted <private> updateInfo: <private>
default 16:56:28.624777 +0200 deleted ENTRY, operation:
CACHE_DELETE_PURGEABLE_OPERATION, serviceID: <private> info: <private>
default 16:56:28.624825 +0200 deleted updating cache for service:
<private>, volume: <private>, amounts: <private>
default 16:56:28.624848 +0200 deleted updating service info amount: 0,
serviceID: <private>, volume: <private>, urgency: 3 pushed: FALSE
default 16:56:28.624888 +0200 deleted com.apple.activity_tracing.cache-
delete took 0.008740 seconds, returned: <private>
default 16:56:28.624928 +0200 deleted com.apple.activity_tracing.cache-
delete updateInfo: <private>
default 16:56:28.624967 +0200 deleted ENTRY, operation:
CACHE_DELETE_PURGEABLE_OPERATION, serviceID:
com.apple.activity_tracing.cache-delete info: <private>
default 16:56:28.625020 +0200 deleted updating cache for service:
com.apple.activity_tracing.cache-delete, volume: <private>, amounts: <private>
default 16:56:28.625048 +0200 deleted updating service info amount: 0,
serviceID: com.apple.activity_tracing.cache-delete, volume: <private>, urgency: 3
pushed: FALSE
default 16:56:28.626931 +0200 MailCacheDelete Skipping attachment
directory /Users/craigdenham/Library/Mail/
V4/0AC7B87E-59ED-407A-8F49-5EE5894FC8EE, not in requested volume
default 16:56:28.627079 +0200 MailCacheDelete Skipping attachment
directory /Users/craigdenham/Library/Mail/V4/1F393CDB-B2B7-4C19-
B3B3-9276F02A0E6B, not in requested volume
default 16:56:28.627213 +0200 MailCacheDelete result: <private>
default 16:56:28.627271 +0200 MailCacheDelete calling
completeRequestReturningItems
default 16:56:28.627352 +0200 deleted <private>: Successful Request
default 16:56:28.627388 +0200 deleted Connection to <private> was
invalidated.
default 16:56:28.627394 +0200 deleted tearing down extension request for
pid 338
default 16:56:28.627422 +0200 deleted Connection to <private> was
invalidated.
default 16:56:28.627458 +0200 deleted <private> took 0.011133 seconds,
returned: <private>
default 16:56:28.627511 +0200 deleted <private> updateInfo: <private>
default 16:56:28.627556 +0200 deleted ENTRY, operation:
CACHE_DELETE_PURGEABLE_OPERATION, serviceID: <private> info: <private>
default 16:56:28.627626 +0200 deleted updating cache for service:
<private>, volume: <private>, amounts: <private>
default 16:56:28.627694 +0200 deleted updating service info amount: 0,
serviceID: <private>, volume: <private>, urgency: 3 pushed: FALSE
default 16:56:28.627837 +0200 deleted PurgeableSpace result: <private>
default 16:56:28.627951 +0200 deleted ASYNC purgeable op results:
<private>
default 16:56:28.628067 +0200 deleted updating results for <private>
default 16:56:28.628128 +0200 deleted Filtering for root only services.

Volume: <private>

default	16:56:28.628152 +0200	deleted	CACHE_DELETE_URGENCY: 3
default	16:56:28.628166 +0200	deleted	urgency: 3, urgencyLimit: 3
default	16:56:28.628191 +0200	deleted	starting purgeable operation
default	16:56:28.628243 +0200	deleted	callingProcess: (null), refreshAll is
FALSE, servicesToQuery: <private>			
default	16:56:28.628264 +0200	deleted	[<private>] no servicesToCount.
refreshAll: FALSE			
default	16:56:28.628311 +0200	deleted	PurgeableSpace result: <private>
default	16:56:28.628415 +0200	deleted	ASYNC purgeable op results:
<private>			
default	16:56:28.628440 +0200	deleted	updating results for <private>
default	16:56:28.628492 +0200	deleted	Filtering for root only services.

Volume: <private>

default	16:56:28.628514 +0200	deleted	CACHE_DELETE_URGENCY: 3
default	16:56:28.628528 +0200	deleted	urgency: 3, urgencyLimit: 3
default	16:56:28.628552 +0200	deleted	starting purgeable operation
default	16:56:28.628602 +0200	deleted	callingProcess: (null), refreshAll is
FALSE, servicesToQuery: <private>			
default	16:56:28.628619 +0200	deleted	[<private>] no servicesToCount.
refreshAll: FALSE			
default	16:56:28.628659 +0200	deleted	PurgeableSpace result: <private>
default	16:56:28.628779 +0200	deleted	ASYNC purgeable op results:
<private>			
default	16:56:28.628804 +0200	deleted	updating results for <private>
default	16:56:28.628856 +0200	deleted	Filtering for root only services.

Volume: <private>

default	16:56:28.628877 +0200	deleted	CACHE_DELETE_URGENCY: 3
default	16:56:28.628892 +0200	deleted	urgency: 3, urgencyLimit: 3
default	16:56:28.628916 +0200	deleted	starting purgeable operation
default	16:56:28.628969 +0200	deleted	callingProcess: (null), refreshAll is
FALSE, servicesToQuery: <private>			
default	16:56:28.628986 +0200	deleted	[<private>] no servicesToCount.
refreshAll: FALSE			
default	16:56:28.629028 +0200	deleted	PurgeableSpace result: <private>
default	16:56:28.629140 +0200	deleted	ASYNC purgeable op results:
<private>			
default	16:56:28.636590 +0200	gamed	TIC TLS Event [2:0x7ffb39e22790]:
20, Pending(0)			
default	16:56:28.636834 +0200	apspd	<APSCourier: 0x7ff10fe24350>:
Outstanding data received: <08000000 25010001 00040002 14000500 02000306			
00040000 00030800 023c000a 00080000 015c4542 40a8> (length 42)			
default	16:56:28.636862 +0200	gamed	TIC TCP Conn Event
[2:0x7ffb39e22790]: 8 Err(0)			
default	16:56:28.636891 +0200	apspd	<APSCourier: 0x7ff10fe24350>: Stream
processing: complete yes, invalid no, length parsed 42, parameters {			
APSPProtocolCommand = 8;			
APSPProtocolConnectedResponse = 0;			
APSPProtocolDualChannelSupport = 1;			
APSPProtocolLargeMessageSize = 15360;			

```

APSProtocolMessageSize = 5120;
APSProtocolServerTime = 1495810588840;
}
default 16:56:28.636891 +0200 gamed TIC TLS Handshake Complete
[2:0x7ffb39e22790]
default 16:56:28.637007 +0200 apsd <APSCourier: 0x7ff10fe24350>: Handling
connected message for user 0 darkWakeEnabled
default 16:56:28.637042 +0200 apsd Received connect message
[development]
default 16:56:28.637096 +0200 apsd <APSCourier: 0x7ff10fe24350>: Received
connected response OK
default 16:56:28.637144 +0200 apsd <APSCourier: 0x7ff10fe24350>: Received
message size 5120
default 16:56:28.637186 +0200 apsd <APSCourier: 0x7ff10fe24350>: Received
large message size 15360
default 16:56:28.637238 +0200 apsd <APSCourier: 0x7ff10fe24350>:
Connected user 0 darkWakeEnabled to environment development
default 16:56:28.637275 +0200 apsd <<APSTokenState: 0x7ff10fe36900>:
{ tokenName=0 darkWakeEnabled, status=connecting, willConnect=no,
willDisconnect=no, systemUser=<APSSystemUser: 0x7ff1121070e0>,
publicToken=<e3f3ebb2 b45e2b35 d7eba84f 792ebbf c 1923528c c45c7e2e
2f1a15ef bb341cbc>, sentFilterMessage=NO darkWakeEnabled=yes,
topicManager=0x7ff10fe26cb0 }>: Changing status for user 0 darkWakeEnabled
from connecting to connected
default 16:56:28.637390 +0200 apsd <APSCourier: 0x7ff10fe24350>: Sending
keep alive message via tcpStream: <APSTCPStreamMaster: 0x7ff10fe30730>
default 16:56:28.637545 +0200 apsd <APSOutgoingMessageQueue:
0x7ff10fe26d20> triggering and bumping out low priority send since we just
reconnected
default 16:56:28.637593 +0200 apsd <APSCourier: 0x7ff10fe24350>: Sending
active interval message with send all messages 'YES'
default 16:56:28.637638 +0200 apsd <APSTCPStream: 0x7ff10fe0d3b0>
asked to change isConnected=NO to YES
default 16:56:28.637663 +0200 apsd <APSCourier: 0x7ff10fe24350>
_processStoredIncomingMessages: enabled = YES
default 16:56:28.637730 +0200 apsd <APSCourier: 0x7ff10fe24350>
processing 0 stored incoming messages
default 16:56:28.637762 +0200 apsd <APSCourier: 0x7ff10fe24350> done with
_processStoredIncomingMessages
default 16:56:28.637796 +0200 apsd APSMessageStore -
APSIIncomingMessageRecordDeleteMessagesOlderThanDate environment
development 1 timeThreshold 514911388
default 16:56:28.637829 +0200 apsd <APSCourier: 0x7ff10fe24350>
_processStoredOutgoingMessages - marking outgoing messages as unsent so they
can be processed (we terminated before they were acknowledged).
default 16:56:28.637878 +0200 apsd <APSDaemon: 0x7ff10fe14330> received
courierConnectionStatusDidChange from <APSCourier: 0x7ff10fe24350>.
isConnected? YES
default 16:56:28.638010 +0200 apsd <APSDaemon: 0x7ff10fe14330>: Set
active push connection state to YES

```

```

default 16:56:28.638043 +0200 apsd <APSCourier: 0x7ff10fe24350>: Checking
whether any users can be connected or disconnected
default 16:56:28.638065 +0200 apsd <APSCourier: 0x7ff10fe24350>: Not
connecting 0 darkWakeEnabled because user is already connected
default 16:56:28.638100 +0200 apsd <<APSTokenState: 0x7ff10ff37f30>:
{ tokenName=501, status=disconnected, willConnect=yes, willDisconnect=no,
systemUser=<APSSystemUser: 0x7ff10fe3d420>, publicToken=<495e168a
a5f94955 15e1eeb7 47a70c56 d379a155 23ddf84a 9c426003 1a278d35>,
sentFilterMessage=NO darkWakeEnabled=no, topicManager=0x7ff10ff37fb0 }>:
Changing status for user 501 from disconnected to connecting
default 16:56:28.638125 +0200 apsd <APSCourier: 0x7ff10fe24350>: Sending
connect message for user 501 with token '<495e168a a5f94955 15e1eeb7 47a70c56
d379a155 23ddf84a 9c426003 1a278d35>\'
default 16:56:28.638260 +0200 apsd <APSCourier: 0x7ff10fe24350>: Stream
processing: complete no, invalid no, length parsed 0, parameters (null)
error 16:56:28.678689 +0200 AddressBookSourceSync warning: dynamic
accessors failed to find @property implementation for 'uniqueId' for entity
ABCDAddressBookSource while resolving selector 'uniqueId' on class
'ABCDAddressBookSource'. Did you remember to declare it @dynamic or
@synthesized in the @implementation ?
default 16:56:28.767525 +0200 SafariDAVClient TIC TCP Conn Event
[2:0x7f88aec31c00]: 1 Err(0)
default 16:56:28.767546 +0200 SafariDAVClient TIC TCP Conn
Connected [2:0x7f88aec31c00]: Err(0)
default 16:56:28.767650 +0200 SafariDAVClient TIC Enabling TLS
[2:0x7f88aec31c00]
default 16:56:28.785335 +0200 apsd <APSCourier: 0x7ff10fe24350>:
Outstanding data received: <0d000000 00> (length 5)
default 16:56:28.785377 +0200 apsd <APSCourier: 0x7ff10fe24350>: Stream
processing: complete yes, invalid no, length parsed 5, parameters {
    APSProtocolCommand = 13;
}
default 16:56:28.785402 +0200 apsd <APSCourier: 0x7ff10fe24350>: Received
successful keep-alive response {
    APSProtocolCommand = 13;
}
default 16:56:28.785505 +0200 apsd <APSCourier: 0x7ff10fe24350>: Stream
processing: complete no, invalid no, length parsed 0, parameters (null)
default 16:56:28.802675 +0200 gamed GKDataRequestManager:
endTransaction:
default 16:56:28.803091 +0200 gamed GKStorebag:
_fetchBagWithHandler:
default 16:56:28.803113 +0200 gamed GKStorebag:
_fetchBagWithHandler:
default 16:56:28.803127 +0200 gamed GKStorebag:
_fetchBagWithHandler:
default 16:56:28.803194 +0200 gamed GKStoreBag: getValuesForKeys
default 16:56:28.803238 +0200 gamed GKStorebag: getBagWithHandler
default 16:56:28.803284 +0200 gamed GKStoreBag: getValuesForKeys
default 16:56:28.803304 +0200 gamed GKStorebag: getBagWithHandler

```

```

default    16:56:28.803345 +0200    gamed    GKStoreBag: getValuesForKeys
default    16:56:28.803372 +0200    gamed    GKStorebag: getBagWithHandler
default    16:56:28.803456 +0200    gamed    GKStorebag:
_fetchBagWithHandler:
default    16:56:28.803492 +0200    gamed    GKStorebag:
_fetchBagWithHandler:
default    16:56:28.803531 +0200    gamed    GKStorebag:
_fetchBagWithHandler:
default    16:56:28.803858 +0200    gamed    TIC TCP Conn Start
[3:0x7ffb39c21a70]
default    16:56:28.930199 +0200    SafariDAVClient    TIC TLS Event
[2:0x7f88aec31c00]: 2, Pending(0)
default    16:56:28.930288 +0200    SafariDAVClient    TIC TLS Event
[2:0x7f88aec31c00]: 20, Pending(0)
default    16:56:28.930633 +0200    SafariDAVClient    TIC TCP Conn Event
[2:0x7f88aec31c00]: 8 Err(0)
default    16:56:28.930652 +0200    SafariDAVClient    TIC TLS Handshake
Complete [2:0x7f88aec31c00]
default    16:56:28.930748 +0200    SafariDAVClient    CFNetwork-AOSKit:
Reaching out to AOSKit for X-mobile me token
default    16:56:28.930859 +0200    SafariDAVClient    CFNetwork-AOSKit:
Applied X-mobile me auth to request
default    16:56:28.937115 +0200    apsd <APSCourier: 0x7ff10fe24350>:
Outstanding data received: <08000000 25010001 00040002 14000500 02000306
00040000 00030800 023c000a 00080000 015c4542 41f2> (length 42)
default    16:56:28.937203 +0200    apsd <APSCourier: 0x7ff10fe24350>: Stream
processing: complete yes, invalid no, length parsed 42, parameters {
    APSProtocolCommand = 8;
    APSProtocolConnectedResponse = 0;
    APSProtocolDualChannelSupport = 1;
    APSProtocolLargeMessageSize = 15360;
    APSProtocolMessageSize = 5120;
    APSProtocolServerTime = 1495810589170;
}
default    16:56:28.937289 +0200    apsd <APSCourier: 0x7ff10fe24350>: Handling
connected message for user 501
default    16:56:28.937314 +0200    apsd Received connect message
[development]
default    16:56:28.937356 +0200    apsd <APSCourier: 0x7ff10fe24350>: Received
connected response OK
default    16:56:28.937389 +0200    apsd <APSCourier: 0x7ff10fe24350>: Received
message size 5120
default    16:56:28.937421 +0200    apsd <APSCourier: 0x7ff10fe24350>: Received
large message size 15360
default    16:56:28.937450 +0200    apsd <APSCourier: 0x7ff10fe24350>:
Connected user 501 to environment development
default    16:56:28.937493 +0200    apsd <<APSTokenState: 0x7ff10ff37f30>:
{ tokenName=501, status=connecting, willConnect=no, willDisconnect=no,
systemUser=<APSSystemUser: 0x7ff10fe3d420>, publicToken=<495e168a
a5f94955 15e1eeb7 47a70c56 d379a155 23ddf84a 9c426003 1a278d35>,

```

```

sentFilterMessage=NO darkWakeEnabled=no, topicManager=0x7ff10ff37fb0 }>:
Changing status for user 501 from connecting to connected
default 16:56:28.937540 +0200 apsd <APSDaemon: 0x7ff10fe14330> received
courierConnectionStatusDidChange from <APSCourier: 0x7ff10fe24350>.
isConnected? YES
default 16:56:28.937669 +0200 apsd <APSDaemon: 0x7ff10fe14330>: Set
active push connection state to YES
default 16:56:28.937722 +0200 apsd <APSCourier: 0x7ff10fe24350>: Checking
whether any users can be connected or disconnected
default 16:56:28.937754 +0200 apsd <APSCourier: 0x7ff10fe24350>: Not
connecting 0 darkWakeEnabled because user is already connected
default 16:56:28.937797 +0200 apsd <APSCourier: 0x7ff10fe24350>: Not
connecting 501 because user is already connected
default 16:56:28.937823 +0200 apsd <APSCourier: 0x7ff10fe24350>: Stream
processing: complete no, invalid no, length parsed 0, parameters (null)
default 16:56:28.937866 +0200 apsd Dispatching low priority message:
<OS_xpc_dictionary: <dictionary: 0x7ff10ff25f70> { count = 2, transaction: 0, voucher
= 0x0, contents =
    "isConnected" => <bool: 0x7ffdd7a6aa8>: true
    "message-type" => <int64: 0x7ff10ff0c5a0>: 26
}>
}>
default 16:56:28.938098 +0200 maspushagent ApplePushService:
<StoreAPSCConnection: 0x7f99e8b01500> Delivering connectionStatusChange from
apsd: YES
default 16:56:28.938181 +0200 maspushagent ApplePushService:
<StoreAPSCConnection: 0x7f99e8b01500> seeing if delegate <APSCClient:
0x7f99e75015b0> responds to status changes
default 16:56:28.938234 +0200 maspushagent ApplePushService:
<StoreAPSCConnection: 0x7f99e8b01500> calling <APSCClient: 0x7f99e75015b0>
didChangeConnectedStatus:
default 16:56:28.938301 +0200 maspushagent ApplePushService:
<StoreAPSCConnection: 0x7f99e8b01500> returned from <APSCClient:
0x7f99e75015b0> didChangeConnectedStatus:
default 16:56:28.983795 +0200 com.apple.WebKit.WebContent
0x7f93cd73ab00 - PerformanceMonitor::measurePostLoadMemoryUsage:
Process was using 75329536 bytes of memory after the page load.
default 16:56:29.094200 +0200 gamed TIC TCP Conn Event
[3:0x7ffb39c21a70]: 1 Err(0)
default 16:56:29.094215 +0200 gamed TIC TCP Conn Connected
[3:0x7ffb39c21a70]: Err(0)
default 16:56:29.142705 +0200 apsd unsentLowPriorityMessagesUpToLimit got
0 records
default 16:56:29.142747 +0200 apsd <APSOutgoingMessageQueue:
0x7ff10fe26d20> _lowPriorityTimer fired - request to send 0 low-priority messages.
Over budget? NO cost = 0. IsEfficientToSend? YES
default 16:56:29.488056 +0200 gamed GKClientProxy: clientForBundleID:
default 16:56:29.488079 +0200 gamed GKClientProxy:
updateIfRecentlyInstalled
default 16:56:29.488286 +0200 gamed GKDataRequestManager:
beginTransaction:

```

```

default    16:56:29.489914 +0200  opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default    16:56:29.489976 +0200  opendirectoryd queuing request to connection
- '<private>'
default    16:56:29.490105 +0200  opendirectoryd queuing request to connection
- '<private>'
default    16:56:29.726528 +0200  gamed      GKDataRequestManager:
endTransaction:
default    16:56:29.729921 +0200  gamed      GKClientProxy: clientForBundleID:
default    16:56:29.729941 +0200  gamed      GKClientProxy:
updateIfRecentlyInstalled
default    16:56:29.730061 +0200  gamed      GKDataRequestManager:
beginTransaction:
default    16:56:29.731763 +0200  opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default    16:56:29.731827 +0200  opendirectoryd queuing request to connection
- '<private>'
default    16:56:29.731967 +0200  opendirectoryd queuing request to connection
- '<private>'
default    16:56:29.975401 +0200  gamed      GKDataRequestManager:
endTransaction:
default    16:56:29.975603 +0200  gamed      GKStoreBag: getValuesForKeys
default    16:56:29.975620 +0200  gamed      GKStorebag: getBagWithHandler
default    16:56:29.975655 +0200  gamed      GKStoreBag: getValuesForKeys
default    16:56:29.975675 +0200  gamed      GKStorebag: getBagWithHandler
default    16:56:29.975701 +0200  gamed      GKStoreBag: getValuesForKeys
default    16:56:29.975730 +0200  gamed      GKStorebag: getBagWithHandler
default    16:56:29.977900 +0200  gamed      [AVConference][INFO]
GKSConnSettings: set server: <private>
default    16:56:29.978681 +0200  gamed      [ViceroyTrace][NOTICE]
gVTRTraceErrorLogLevel initialized to NOTICE (6)
default    16:56:29.978939 +0200  gamed      [AVConference][INFO]
GKNATObserver: registerForNetworkChanges
error 16:56:29.979418 +0200  gamed      [AVConference][ERROR]
GKNATObserver: no NAT cache available, running NAT check
default    16:56:29.979455 +0200  gamed      [AVConference][NOTICE]
GKNATObserver: tryNATCheckWithDelay:
default    16:56:29.979483 +0200  gamed      [AVConference][INFO]
GKNATObserverInternal(0x7ffb39f304b0) -init
default    16:56:29.979506 +0200  gamed      [AVConference][NOTICE]
GKNATObserver: start setting up NAT checks (delay: 0.000000)
default    16:56:29.979586 +0200  gamed      [AVConference][WARNING]
GKNATObserver cannot report NAT Type 0 (0/0), delegate is nil!
default    16:56:29.979627 +0200  gamed      [AVConference][INFO]
GKSConnSettings: set server: <private>
default    16:56:29.979691 +0200  gamed      [AVConference][INFO]
GKNATObserver: registerForNetworkChanges
error 16:56:29.979976 +0200  gamed      [AVConference][ERROR]
GKNATObserver: no NAT cache available, running NAT check
default    16:56:29.980006 +0200  gamed      [AVConference][NOTICE]

```

```

GKNATObserver: tryNATCheckWithDelay:
default 16:56:29.980060 +0200 gamed [AVConference][INFO]
GKNATObserverInternal(0x7ffb3b91c610) -init
default 16:56:29.980068 +0200 gamed [AVConference][NOTICE]
GKNATObserver: start setting up NAT checks (delay: 0.000000)
default 16:56:29.980149 +0200 gamed [AVConference][WARNING]
GKNATObserver cannot report NAT Type 0 (0/0), delegate is nil!
default 16:56:29.980202 +0200 gamed [AVConference][INFO]
GKSConnSettings: set server: <private>
default 16:56:29.980271 +0200 gamed [AVConference][INFO]
GKNATObserver: registerForNetworkChanges
default 16:56:29.980472 +0200 gamed [ICE][INFO] void
GetReachableInterfaceListWithOptions(uint32_t **, int *, int, int, int) IPv4 DEFAULT
route, if_idx:5
default 16:56:29.980483 +0200 gamed [ICE][INFO] void
GetReachableInterfaceListWithOptions(uint32_t **, int *, int, int, int) IPv4 DEFAULT
route, if_idx:5
default 16:56:29.980507 +0200 gamed [ICE][INFO] void
GetReachableInterfaceListWithOptions(uint32_t **, int *, int, int, int) found 1
reachable interface(s).
default 16:56:29.980530 +0200 gamed [ICE][INFO] void
GetReachableInterfaceListWithOptions(uint32_t **, int *, int, int, int) found 1
reachable interface(s).
default 16:56:29.980541 +0200 gamed [ICE][INFO] GetCellularInterfaceList:
found 0 cellular interface(s).
default 16:56:29.980569 +0200 gamed [ICE][INFO] GetCellularInterfaceList:
found 0 cellular interface(s).
error 16:56:29.980609 +0200 gamed [AVConference][ERROR]
GKNATObserver: no NAT cache available, running NAT check
default 16:56:29.980660 +0200 gamed [AVConference][NOTICE]
GKNATObserver: tryNATCheckWithDelay:
default 16:56:29.980695 +0200 gamed [AVConference][INFO]
GKNATObserverInternal(0x7ffb3b8076e0) -init
default 16:56:29.980698 +0200 gamed [AVConference][NOTICE]
GKNATObserver: start setting up NAT checks (delay: 0.000000)
default 16:56:29.980777 +0200 gamed [AVConference][INFO]
GKNATObserver _commNATFlagDictionary = <private>
default 16:56:29.980804 +0200 gamed [AVConference][NOTICE]
GKNATObserver reporting NAT Type 0
default 16:56:29.980921 +0200 gamed [ICE][INFO] void
GetReachableInterfaceListWithOptions(uint32_t **, int *, int, int, int) IPv4 DEFAULT
route, if_idx:5
default 16:56:29.980944 +0200 gamed [ICE][INFO] void
GetReachableInterfaceListWithOptions(uint32_t **, int *, int, int, int) found 1
reachable interface(s).
default 16:56:29.980980 +0200 gamed [ICE][INFO] GetCellularInterfaceList:
found 0 cellular interface(s).
default 16:56:29.981237 +0200 gamed [ICE][INFO] 0: v4 interface
"<private>" <private>
default 16:56:29.981238 +0200 gamed [ICE][INFO] 0: v4 interface

```

```

"<private>" <private>
default 16:56:29.981238 +0200 gamed [ICE][INFO] 0: v4 interface
"<private>" <private>
default 16:56:29.981415 +0200 gamed [ICE][INFO] 1: v6 interface
"<private>" <private>
default 16:56:29.981421 +0200 gamed [ICE][INFO] 1: v6 interface
"<private>" <private>
default 16:56:29.981423 +0200 gamed [ICE][INFO] 1: v6 interface
"<private>" <private>
default 16:56:29.982765 +0200 gamed [ICE][INFO] 2: v4 interface
"<private>" <private>
default 16:56:29.982859 +0200 gamed [ICE][INFO] 2: v4 interface
"<private>" <private>
default 16:56:29.983063 +0200 gamed [ICE][INFO] 2: v4 interface
"<private>" <private>
default 16:56:29.983125 +0200 gamed [AVConference][INFO]
VCNAT64ResolverRegisterForPrefixUpdate: begin registration of context 3B8076E0
on interface <private>
default 16:56:29.983137 +0200 gamed [AVConference][INFO]
VCNAT64ResolverRegisterForPrefixUpdate: begin registration of context 39F304B0
on interface <private>
default 16:56:29.983210 +0200 gamed [AVConference][INFO]
VCNAT64ResolverRegisterForPrefixUpdate: begin registration of context 3B91C610
on interface <private>
default 16:56:29.983249 +0200 gamed [AVConference][INFO]
VCNAT64ResolverGetSharedInstance: shared instance of NAT64Resolver does not
exist. Creating it...
default 16:56:29.983515 +0200 gamed [AVConference][INFO]
VCNAT64ResolverRegisterForPrefixUpdate: succesfully registered context
3B8076E0 on interface <private>
default 16:56:29.983542 +0200 gamed [AVConference][INFO]
VCNAT64ResolverRegisterForPrefixUpdate: succesfully registered context
39F304B0 on interface <private>
default 16:56:29.983580 +0200 gamed [AVConference][INFO]
VCNAT64ResolverRegisterForPrefixUpdate: succesfully registered context
3B91C610 on interface <private>
default 16:56:29.983585 +0200 gamed [AVConference][INFO]
VCNAT64ResolveNAT64Prefix: Re-trying in 1 second for Interface <private>,
attempt 1 out of 3
default 16:56:29.983644 +0200 gamed [AVConference][INFO]
GKNATObserver: queued non-carrier NAT check 2@3, <private>
default 16:56:29.983646 +0200 gamed [AVConference][INFO]
GKNATObserver: queued non-carrier NAT check 2@3, <private>
default 16:56:29.983648 +0200 gamed [AVConference][INFO]
GKNATObserver: queued non-carrier NAT check 2@3, <private>
default 16:56:29.983711 +0200 gamed [AVConference][INFO]
GKNATObserver: NATCheckWithIPPort starting for <private>
default 16:56:29.983797 +0200 gamed [AVConference][INFO]
GKNATObserver: NATCheckWithIPPort starting for <private>
default 16:56:29.983868 +0200 gamed [AVConference][INFO]

```


GKNATObserver: NATCheckWithIPPort starting for <private>
default 16:56:29.984047 +0200 gamed [ICE][INFO] void
GetReachableInterfaceListWithOptions(uint32_t **, int *, int, int, int) IPv4 DEFAULT
route, if_idx:5
default 16:56:29.984086 +0200 gamed [ICE][INFO] void
GetReachableInterfaceListWithOptions(uint32_t **, int *, int, int, int) found 1
reachable interface(s).
default 16:56:29.984103 +0200 gamed [AVConference][NOTICE]
GKNATObserver setting flags[000000D0] mask[000027FF]
old[00000000]=>result[000000D0] (cached:1)
default 16:56:29.984124 +0200 gamed [AVConference][NOTICE]
GKNATObserver setting flags[000000D0] mask[000027FF]
old[00000000]=>result[000000D0] (cached:1)
default 16:56:29.984163 +0200 gamed [AVConference][NOTICE]
GKNATObserver setting flags[000000D0] mask[00000800]
old[000000D0]=>result[000000D0] (cached:1)
default 16:56:29.984179 +0200 gamed [AVConference][NOTICE]
GKNATObserver setting flags[000000D0] mask[00000800]
old[000000D0]=>result[000000D0] (cached:1)
default 16:56:29.984206 +0200 gamed [AVConference][NOTICE]
GKNATObserver setting flags[000000D0] mask[00001000]
old[000000D0]=>result[000000D0] (cached:1)
default 16:56:29.984208 +0200 gamed [AVConference][NOTICE]
GKNATObserver setting flags[000000D0] mask[00001000]
old[000000D0]=>result[000000D0] (cached:1)
default 16:56:29.984213 +0200 gamed [ICE][INFO] void
GetReachableInterfaceListWithOptions(uint32_t **, int *, int, int, int) IPv4 DEFAULT
route, if_idx:5
default 16:56:29.984244 +0200 gamed [AVConference][INFO]
GKNATObserver: Cached NAT flags for network "<private>": [000000D0]
default 16:56:29.984245 +0200 gamed [ICE][INFO] GetCellularInterfaceList:
found 0 cellular interface(s).
default 16:56:29.984265 +0200 gamed [ICE][INFO] void
GetReachableInterfaceListWithOptions(uint32_t **, int *, int, int, int) found 1
reachable interface(s).
default 16:56:29.984296 +0200 gamed [AVConference][INFO]
GKNATObserver: Cached NAT flags for network "<private>": [000000D0]
default 16:56:29.984301 +0200 gamed [AVConference][WARNING]
GKSConnSettings getIPPortForService: gk-commnat-main0-name == nil
default 16:56:29.984328 +0200 gamed [ICE][INFO] GetCellularInterfaceList:
found 0 cellular interface(s).
default 16:56:29.984340 +0200 gamed [AVConference][INFO]
GKSConnSettings getIPPortForService: GKS setting for get SNATMAP IP: <private>
default 16:56:29.984382 +0200 gamed [AVConference][WARNING]
GKSConnSettings getIPPortForService: gk-commnat-main0-name == nil
default 16:56:29.984434 +0200 gamed [AVConference][INFO]
GKSConnSettings getIPPortForService: GKS setting for get SNATMAP IP: <private>
default 16:56:29.984444 +0200 gamed [AVConference][INFO]
GKSConnSettings getIPPortForService: gk-commnat-main0 == 11ADFEDE:16384
default 16:56:29.984476 +0200 gamed [AVConference][WARNING]

GKSConnSettings getIPPortForService: gk-commnat-main1-name == nil
default 16:56:29.984501 +0200 gamed [AVConference][INFO]
GKSConnSettings getIPPortForService: gk-commnat-main0 == 11ADFEDE:16384
default 16:56:29.984504 +0200 gamed [AVConference][INFO]
GKSConnSettings getIPPortForService: GKS setting for get SNATMAP IP: <private>
default 16:56:29.984532 +0200 gamed [AVConference][INFO]
GKSConnSettings getIPPortForService: gk-commnat-main1 == 11ADFEDE:16385
default 16:56:29.984569 +0200 gamed [AVConference][WARNING]
GKSConnSettings getIPPortForService: gk-commnat-cohort-name == nil
default 16:56:29.984595 +0200 gamed [AVConference][INFO]
GKSConnSettings getIPPortForService: GKS setting for get SNATMAP IP: <private>
default 16:56:29.984602 +0200 gamed [AVConference][WARNING]
GKSConnSettings getIPPortForService: gk-commnat-main1-name == nil
default 16:56:29.984631 +0200 gamed [AVConference][INFO]
GKSConnSettings getIPPortForService: GKS setting for get SNATMAP IP: <private>
default 16:56:29.984647 +0200 gamed [AVConference][INFO]
GKSConnSettings getIPPortForService: gk-commnat-cohort == 11ADFEDF:16386
default 16:56:29.984672 +0200 gamed [AVConference][INFO]
natchecktimeout set to 60.000000 from bag
default 16:56:29.984670 +0200 gamed [AVConference][INFO]
GKSConnSettings getIPPortForService: gk-commnat-main1 == 11ADFEDE:16385
default 16:56:29.984738 +0200 gamed [AVConference][WARNING]
GKSConnSettings getIPPortForService: gk-commnat-cohort-name == nil
default 16:56:29.985112 +0200 accountsd getting current attributes...
default 16:56:29.984789 +0200 gamed [AVConference][INFO]
GKSConnSettings getIPPortForService: GKS setting for get SNATMAP IP: <private>
default 16:56:29.985141 +0200 accountsd filling 16 attributes for type
2147483648
default 16:56:29.984817 +0200 gamed [AVConference][INFO]
GKSConnSettings getIPPortForService: gk-commnat-cohort == 11ADFEDF:16386
default 16:56:29.984841 +0200 gamed [AVConference][INFO]
natchecktimeout set to 60.000000 from bag
default 16:56:29.984986 +0200 gamed [ICE][INFO] void
GetReachableInterfaceListWithOptions(uint32_t **, int *, int, int, int) IPv4 DEFAULT
route, if_idx:5
default 16:56:29.985043 +0200 gamed [ICE][INFO] void
GetReachableInterfaceListWithOptions(uint32_t **, int *, int, int, int) found 1
reachable interface(s).
default 16:56:29.985111 +0200 gamed [AVConference][NOTICE]
GKNATObserver setting flags[000000D0] mask[000027FF]
old[00000000]=>result[000000D0] (cached:1)
default 16:56:29.985141 +0200 gamed [AVConference][NOTICE]
GKNATObserver setting flags[000000D0] mask[00000800]
old[000000D0]=>result[000000D0] (cached:1)
default 16:56:29.985184 +0200 gamed [AVConference][NOTICE]
GKNATObserver setting flags[000000D0] mask[00001000]
old[000000D0]=>result[000000D0] (cached:1)
default 16:56:29.985217 +0200 gamed [AVConference][INFO]
GKNATObserver: Cached NAT flags for network "<private>": [000000D0]
default 16:56:29.985213 +0200 gamed [ICE][INFO] GetCellularInterfaceList:

```

found 0 cellular interface(s).
default 16:56:29.985572 +0200 accountsd looking at 16 attributes
default 16:56:29.985299 +0200 gamed [AVConference][WARNING]
GKSConnSettings getIPPortForService: gk-commnat-main0-name == nil
default 16:56:29.985330 +0200 gamed [AVConference][INFO]
GKSConnSettings getIPPortForService: GKS setting for get SNATMAP IP: <private>
default 16:56:29.985655 +0200 accountsd finished:
d614dfcc24c6ec5f18910902eb89b6ade6db580dec987d8cade649d410eb0808
default 16:56:29.985375 +0200 gamed [AVConference][INFO]
GKSConnSettings getIPPortForService: gk-commnat-main0 == 11ADFEDE:16384
default 16:56:29.985411 +0200 gamed [AVConference][WARNING]
GKSConnSettings getIPPortForService: gk-commnat-main1-name == nil
default 16:56:29.985401 +0200 gamed [AVConference][WARNING]
GKNATObserver cannot report NAT Type 2 (0/2), delegate is nil!
default 16:56:29.985442 +0200 gamed [AVConference][INFO]
GKSConnSettings getIPPortForService: GKS setting for get SNATMAP IP: <private>
default 16:56:29.985520 +0200 gamed [AVConference][INFO]
GKSConnSettings getIPPortForService: gk-commnat-main1 == 11ADFEDE:16385
default 16:56:29.985622 +0200 gamed [AVConference][WARNING]
GKSConnSettings getIPPortForService: gk-commnat-cohort-name == nil
default 16:56:29.985665 +0200 gamed [AVConference][INFO]
GKSConnSettings getIPPortForService: GKS setting for get SNATMAP IP: <private>
default 16:56:29.985672 +0200 gamed [AVConference][INFO]
GKNATObserver _commNATFlagDictionary = <private>
default 16:56:29.985700 +0200 gamed [AVConference][NOTICE]
GKNATObserver reporting NAT Type 2
default 16:56:29.985703 +0200 gamed [AVConference][INFO]
GKSConnSettings getIPPortForService: gk-commnat-cohort == 11ADFEDF:16386
default 16:56:29.985734 +0200 gamed [AVConference][INFO]
natchecktimeout set to 60.000000 from bag
default 16:56:29.985814 +0200 gamed [AVConference][WARNING]
GKNATObserver cannot report NAT Type 2 (0/2), delegate is nil!
default 16:56:29.986610 +0200 securityd ACL partitionID = <CFArray
0x7fb8fdc0e200 [0x7ffda12eda0]>{type = mutable-small, count = 1, values = (
    0 : apple:
)}
default 16:56:29.986641 +0200 securityd ACL partitions match: apple:
default 16:56:29.986682 +0200 gamed [AVConference][NOTICE]
GKNATObserver: No usable carrier interfaces found.
default 16:56:29.986805 +0200 gamed [AVConference][WARNING]
GKNATObserver cannot report NAT Type 2 (0/2), delegate is nil!
default 16:56:29.987172 +0200 gamed [AVConference][NOTICE]
GKNATObserver: No usable carrier interfaces found.
default 16:56:29.987258 +0200 gamed [AVConference][WARNING]
GKNATObserver cannot report NAT Type 2 (0/2), delegate is nil!
default 16:56:29.987319 +0200 gamed [AVConference][NOTICE]
GKNATObserver: No usable carrier interfaces found.
default 16:56:29.987441 +0200 gamed [AVConference][INFO]
GKNATObserver _commNATFlagDictionary = <private>
default 16:56:29.992426 +0200 securityd keychain reference in server mode

```

default 16:56:30.025879 +0200 accountsd "Idle-exit-preventing transaction ended!"

default 16:56:30.036665 +0200 com.apple.WebKit.Networking
0x110c9fc00 - NetworkResourceLoader::start: Retrieving resource from cache (pageID = 3, frameID = 9, resourceID = 357, isMainResource = 0, isSynchronous = 0)

default 16:56:30.036728 +0200 com.apple.WebKit.Networking
0x110c9fc00 - NetworkResourceLoader::startNetworkLoad: (pageID = 3, frameID = 9, resourceID = 357, isMainResource = 0, isSynchronous = 0)

default 16:56:30.036693 +0200 com.apple.WebKit.WebContent
0x1085f5000 - WebLoaderStrategy::scheduleLoad: Resource has been queued for scheduling with the NetworkProcess (frame = 0x113485a80, priority = 1, pageID = 3, frameID = 9, resourceID = 357, WebResourceLoader = 0x13149f658)

default 16:56:30.302014 +0200 com.apple.WebKit.WebContent
0x7f951fea71b0 - PerformanceMonitor::measurePostLoadMemoryUsage: Process was using 49876992 bytes of memory after the page load.

default 16:56:30.370341 +0200 com.apple.WebKit.WebContent
0x1085f5000 - WebLoaderStrategy::scheduleLoad: Resource has been queued for scheduling with the NetworkProcess (frame = 0x1134dd000, priority = 1, pageID = 3, frameID = 11, resourceID = 358, WebResourceLoader = 0x131486620)

default 16:56:30.370430 +0200 com.apple.WebKit.Networking
0x110c88000 - NetworkResourceLoader::start: Retrieving resource from cache (pageID = 3, frameID = 11, resourceID = 358, isMainResource = 0, isSynchronous = 0)

default 16:56:30.370466 +0200 com.apple.WebKit.Networking
0x110c88000 - NetworkResourceLoader::startNetworkLoad: (pageID = 3, frameID = 11, resourceID = 358, isMainResource = 0, isSynchronous = 0)

default 16:56:30.375100 +0200 com.apple.WebKit.Networking
0x110c9fc00 - NetworkResourceLoader::didReceiveResponse: (pageID = 3, frameID = 9, resourceID = 357, httpStatusCode = 204, length = -1)

default 16:56:30.375135 +0200 com.apple.WebKit.Networking
0x110c9fc00 - NetworkResourceLoader::didReceiveResponse: Should not wait for message from WebContent process before continuing resource load (pageID = 3, frameID = 9, resourceID = 357)

default 16:56:30.375226 +0200 com.apple.WebKit.WebContent
0x13149f658 - WebResourceLoader::didReceiveResponse: (pageID = 3, frameID = 9, resourceID = 357, status = 204)

default 16:56:30.375192 +0200 com.apple.WebKit.Networking
0x110c9fc00 - NetworkResourceLoader::didFinishLoading: (pageID = 3, frameID = 9, resourceID = 357)

default 16:56:30.375285 +0200 com.apple.WebKit.WebContent
0x13149f658 - WebResourceLoader::didFinishResourceLoad: (pageID = 3, frameID = 9, resourceID = 357)

default 16:56:30.526193 +0200 com.apple.WebKit.Networking
0x110c88000 - NetworkResourceLoader::didReceiveResponse: (pageID = 3, frameID = 11, resourceID = 358, httpStatusCode = 204, length = -1)

default 16:56:30.526232 +0200 com.apple.WebKit.Networking
0x110c88000 - NetworkResourceLoader::didReceiveResponse: Should not wait for message from WebContent process before continuing resource load (pageID = 3, frameID = 11, resourceID = 358)

default 16:56:30.526306 +0200 com.apple.WebKit.Networking
0x110c88000 - NetworkResourceLoader::didFinishLoading: (pageID = 3,
frameID = 11, resourceID = 358)

default 16:56:30.526356 +0200 com.apple.WebKit.WebContent
0x131486620 - WebResourceLoader::didReceiveResponse: (pageID = 3,
frameID = 11, resourceID = 358, status = 204)

default 16:56:30.526413 +0200 com.apple.WebKit.WebContent
0x131486620 - WebResourceLoader::didFinishResourceLoad: (pageID = 3,
frameID = 11, resourceID = 358)

default 16:56:30.582814 +0200 CommCenter #I New CTServerConnection
from pid 283 (conn=0x7faa0c71ed20)

default 16:56:30.582999 +0200 CommCenter #I -- connection has
entitlements: <private>

default 16:56:30.599979 +0200 CallHistorySyncHelper ApplePushService:
<APSCConnection: 0x7f9c56a187a0> Flushing any queuedDelegateBlocks 0

default 16:56:30.721901 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0

default 16:56:30.722050 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 20, EGID: 20

default 16:56:30.722278 +0200 opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20

default 16:56:30.730454 +0200 opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20

default 16:56:30.739293 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0

default 16:56:30.771452 +0200 mds directQueryOpenReply 53249
1795162176 0

default 16:56:30.771499 +0200 mds QueryOpen succeeded (0) for store
<private>

default 16:56:30.771571 +0200 mds directQueryOpenReply 53250
1795162176 0

default 16:56:30.771618 +0200 mds QueryOpen succeeded (0) for store
<private>

default 16:56:30.772159 +0200 mds directQueryFetchResultsReply 53249
1795162176 0

default 16:56:30.785241 +0200 mds directQueryFetchResultsReply 53250
1795162176 0

default 16:56:30.857534 +0200 maspushagent ApplePushService:
<StoreAPSCConnection: 0x7f99e7501850> Flushing any queuedDelegateBlocks 0

default 16:56:30.857663 +0200 maspushagent ApplePushService:
<StoreAPSCConnection: 0x7f99e8b01500> Flushing any queuedDelegateBlocks 0

default 16:56:30.864042 +0200 syncdefaults TIC TCP Conn Cancel
[6:0x7fe9f301d800]

default 16:56:30.864095 +0200 syncdefaults TIC TCP Conn Destroyed
[6:0x7fe9f301d800]

default 16:56:30.870061 +0200 syncdefaults Synchronization with server
succeeded for app:<private>/0x7fe9f3010650, scheduler:<private>

default 16:56:30.892535 +0200 SafariDAVClient ApplePushService:
<APSCConnection: 0x7f88b0800bd0> Flushing any queuedDelegateBlocks 0

default 16:56:30.892669 +0200 mapspushd ApplePushService:

<APSCConnection: 0x7ff613402350> Flushing any queuedDelegateBlocks 0
 default 16:56:30.904949 +0200 gamed ApplePushService:
 <APSCConnection 0x7ffb39c09ff0 production com.apple.gamed.aps> Flushing any
 queuedDelegateBlocks 0
 default 16:56:30.905005 +0200 gamed ApplePushService:
 <APSCConnection 0x7ffb3b8061c0 production (null)> Flushing any
 queuedDelegateBlocks 0
 default 16:56:30.905056 +0200 askpermissiond ApplePushService:
 <APSCConnection: 0x7fdd9770f780> Flushing any queuedDelegateBlocks 0
 default 16:56:30.933461 +0200 AddressBookSourceSync ApplePushService:
 <APSCConnection: 0x7fb66fc14ea0> Flushing any queuedDelegateBlocks 0
 default 16:56:30.945677 +0200 passd ApplePushService:
 <APSCConnection: 0x7f834ea0e660> Flushing any queuedDelegateBlocks 0
 default 16:56:30.978520 +0200 cloudpaired ApplePushService:
 <APSCConnection: 0x7fb92c10f9a0> Flushing any queuedDelegateBlocks 0
 default 16:56:31.015716 +0200 com.apple.WebKit.WebContent
 0x10fdf5000 - WebLoaderStrategy::scheduleLoad: Resource has been queued
 for scheduling with the NetworkProcess (frame = 0x10fd61000, priority = 2, pageID =
 7, frameID = 1, resourceID = 32, WebResourceLoader = 0x1131b4310)
 default 16:56:31.015797 +0200 com.apple.WebKit.Networking
 0x110c88400 - NetworkResourceLoader::start: Retrieving resource from cache
 (pageID = 7, frameID = 1, resourceID = 32, isMainResource = 0, isSynchronous = 0)
 default 16:56:31.015855 +0200 com.apple.WebKit.Networking
 0x110c88400 - NetworkResourceLoader::startNetworkLoad: (pageID = 7,
 frameID = 1, resourceID = 32, isMainResource = 0, isSynchronous = 0)
 default 16:56:31.053986 +0200 com.apple.WebKit.Networking
 0x110c88400 - NetworkResourceLoader::didReceiveResponse: (pageID = 7,
 frameID = 1, resourceID = 32, httpStatusCode = 200, length = 236168)
 default 16:56:31.054024 +0200 com.apple.WebKit.Networking
 0x110c88400 - NetworkResourceLoader::didReceiveResponse: Should not
 wait for message from WebContent process before continuing resource load (pageID
 = 7, frameID = 1, resourceID = 32)
 default 16:56:31.054083 +0200 com.apple.WebKit.Networking
 0x110c88400 - NetworkResourceLoader::didReceiveBuffer: Started receiving
 data (pageID = 7, frameID = 1, resourceID = 32)
 default 16:56:31.054091 +0200 com.apple.WebKit.WebContent
 0x1131b4310 - WebResourceLoader::didReceiveResponse: (pageID = 7,
 frameID = 1, resourceID = 32, status = 200)
 default 16:56:31.054197 +0200 com.apple.WebKit.WebContent
 0x1131b4310 - WebResourceLoader::didReceiveData: Started receiving data
 (pageID = 7, frameID = 1, resourceID = 32)
 default 16:56:31.082127 +0200 gamed [AVConference][INFO]
 VCNAT64ResolveNAT64Prefix: Re-trying in 1 second for Interface <private>,
 attempt 2 out of 3
 default 16:56:31.412185 +0200 com.apple.WebKit.Networking
 0x110c5cc00 - NetworkResourceLoader::didFinishLoading: (pageID = 7,
 frameID = 1, resourceID = 31)
 default 16:56:31.412278 +0200 com.apple.WebKit.WebContent
 0x113bbe348 - WebResourceLoader::didFinishResourceLoad: (pageID = 7,
 frameID = 1, resourceID = 31)

default 16:56:31.568073 +0200 com.apple.WebKit.Networking
TIC TCP Conn Event [53:0x7fa644e64f30]: 2 Err(0)

default 16:56:31.568103 +0200 com.apple.WebKit.Networking
TIC TCP Conn Cancel [53:0x7fa644e64f30]

default 16:56:31.568158 +0200 com.apple.WebKit.Networking
TIC TCP Conn Destroyed [53:0x7fa644e64f30]

default 16:56:31.620109 +0200 CommCenter #l
CSIApplInfo.ApplicationActivationObserver: handleLSNotification_sync: Application
exited: <private>

default 16:56:31.733617 +0200 com.apple.WebKit.WebContent
0x10fdf5000 - WebLoaderStrategy::scheduleLoad: Resource has been queued
for scheduling with the NetworkProcess (frame = 0x10fd61000, priority = 2, pageID =
7, frameID = 1, resourceID = 33, WebResourceLoader = 0x1131c99a0)

default 16:56:31.733681 +0200 com.apple.WebKit.Networking
0x110c88800 - NetworkResourceLoader::start: Retrieving resource from cache
(pageID = 7, frameID = 1, resourceID = 33, isMainResource = 0, isSynchronous = 0)

default 16:56:31.733773 +0200 com.apple.WebKit.Networking
0x110c88800 - NetworkResourceLoader::startNetworkLoad: (pageID = 7,
frameID = 1, resourceID = 33, isMainResource = 0, isSynchronous = 0)

default 16:56:31.794162 +0200 ContactsAccountsService [Accounts] Current
connection, <NSXPCConnection: 0x7f85a2300e10> connection from pid 406,
doesn't have account access.

default 16:56:31.794427 +0200 AppleSpell [Accounts] Failed to update
account with identifier 3BCFC0BB-3342-4091-AF67-4E78CE39F56F, error: Error
Domain=ABAddressBookErrorDomain Code=1002 "(null)"

default 16:56:31.914389 +0200 com.apple.WebKit.Networking
0x110c88800 - NetworkResourceLoader::didReceiveResponse: (pageID = 7,
frameID = 1, resourceID = 33, httpStatusCode = 200, length = 1598348)

default 16:56:31.914421 +0200 com.apple.WebKit.Networking
0x110c88800 - NetworkResourceLoader::didReceiveResponse: Should not
wait for message from WebContent process before continuing resource load (pageID
= 7, frameID = 1, resourceID = 33)

default 16:56:31.914516 +0200 com.apple.WebKit.WebContent
0x1131c99a0 - WebResourceLoader::didReceiveResponse: (pageID = 7,
frameID = 1, resourceID = 33, status = 200)

default 16:56:31.914476 +0200 com.apple.WebKit.Networking
0x110c88800 - NetworkResourceLoader::didReceiveBuffer: Started receiving
data (pageID = 7, frameID = 1, resourceID = 33)

default 16:56:31.914578 +0200 com.apple.WebKit.WebContent
0x1131c99a0 - WebResourceLoader::didReceiveData: Started receiving data
(pageID = 7, frameID = 1, resourceID = 33)

default 16:56:31.929675 +0200 UserEventAgent SUBMITTING: <private>

default 16:56:31.929730 +0200 UserEventAgent Registered XPC Activity:
com.apple.photos.icloud.shared-streams.undownloaded-content-check

default 16:56:31.930144 +0200 DuetHeuristic-BM Submitted Activity:
<private>

default 16:56:31.930244 +0200 DuetHeuristic-BM Activity <private>:
Optimal Score 0.4745 at <private> (Valid Until: <private>)

default 16:56:31.930537 +0200 DuetHeuristic-BM <private>:[
<private>] sumScores:37.010000, denominator:39.010000, FinalDecision: Can

```

Proceed FinalScore: 0.948731}
default 16:56:31.930562 +0200 DuetHeuristic-BM '<private>' CurrentScore:
0.948731, ThresholdScore: 0.338355 DecisionToRun:1
default 16:56:31.930606 +0200 DuetHeuristic-BM Running activities :
<private>
default 16:56:31.930791 +0200 UserEventAgent STARTING: <private>
default 16:56:31.995373 +0200 identityservicesd Repair timer fired: (null)
default 16:56:31.995580 +0200 identityservicesd Cleaning up dead
keychain items
default 16:56:31.995605 +0200 identityservicesd Cleaning up keychain
items for service: iMessage
default 16:56:31.996049 +0200 identityservicesd 0x7fb5b66194c0 opened /
Users/craigdenham/Library/Keychains/login.keychain-db: 218248 bytes
default 16:56:31.997056 +0200 identityservicesd 0x7fb5b6640cd0 opened /
Library/Keychains/System.keychain: 37732 bytes
default 16:56:31.999200 +0200 identityservicesd Cleaning up keychain
items for service: com.apple.private.alloy.maps
default 16:56:32.999535 +0200 identityservicesd Cleaning up keychain
items for service: FaceTime
default 16:56:32.999905 +0200 identityservicesd Cleaning up keychain
items for service: FaceTime_temporary
default 16:56:32.000226 +0200 identityservicesd Cleaning up keychain
items for service: iMessage_temporary
default 16:56:32.000556 +0200 identityservicesd Cleaning up keychain
items for service: IDS_temporary
default 16:56:32.000917 +0200 identityservicesd => Done
default 16:56:32.000939 +0200 identityservicesd Account repair timer fired
default 16:56:32.001024 +0200 identityservicesd => Enabled, account
uniqueID: <private>, service name: <private>
default 16:56:32.001093 +0200 identityservicesd => Registered
default 16:56:32.001149 +0200 identityservicesd => Enabled, account
uniqueID: <private>, service name: <private>
default 16:56:32.001186 +0200 identityservicesd => Registered
default 16:56:32.001231 +0200 identityservicesd => Enabled, account
uniqueID: <private>, service name: <private>
default 16:56:32.001257 +0200 identityservicesd => Registered
default 16:56:32.001291 +0200 identityservicesd => Enabled, account
uniqueID: <private>, service name: <private>
default 16:56:32.001314 +0200 identityservicesd => Registered
default 16:56:32.001344 +0200 identityservicesd => Enabled, account
uniqueID: <private>, service name: <private>
default 16:56:32.001373 +0200 identityservicesd => Registered
default 16:56:32.001404 +0200 identityservicesd => Enabled, account
uniqueID: <private>, service name: <private>
default 16:56:32.001420 +0200 identityservicesd => Registered
default 16:56:32.002307 +0200 accountsd "<private> (<private>) received"
default 16:56:32.002751 +0200 identityservicesd Looking for iCloud
accounts with type com.apple.account.AppleAccount in account store <private>
default 16:56:32.005167 +0200 identityservicesd Checking if <private> is
the primary iCloud account...

```


default	16:56:32.005205 +0200	identityservicesd	** Found signed in
iCloud account: <private>			
default	16:56:32.005319 +0200	identityservicesd	Repairing iCloud based
accounts if needed (Primary account: <private>)			
default	16:56:32.005344 +0200	identityservicesd	=> Has SMS Account
active: NO			
default	16:56:32.005401 +0200	identityservicesd	"The connection to
ACDAccountStore was invalidated."			
default	16:56:32.005470 +0200	identityservicesd	Checking account for
deletion: <private>			
default	16:56:32.005502 +0200	identityservicesd	Account is primary, it
should not be deleted			
default	16:56:32.005564 +0200	identityservicesd	Checking account
registration status: <private>			
default	16:56:32.005711 +0200	identityservicesd	Checking account for
deletion: <private>			
default	16:56:32.005734 +0200	identityservicesd	Account is primary, it
should not be deleted			
default	16:56:32.005784 +0200	identityservicesd	Checking account
registration status: <private>			
default	16:56:32.005855 +0200	identityservicesd	Checking account for
deletion: <private>			
default	16:56:32.005879 +0200	identityservicesd	Account is primary, it
should not be deleted			
default	16:56:32.005926 +0200	identityservicesd	Checking account
registration status: <private>			
default	16:56:32.005971 +0200	identityservicesd	=> Done repair attempt
default	16:56:32.005985 +0200	identityservicesd	*** Done
default	16:56:32.030414 +0200	UserEventAgent	Initiating XPC Activity:
com.apple.photos.icloud.shared-streams.undownloaded-content-check			
default	16:56:32.031319 +0200	UserEventAgent	Completed XPC Activity:
com.apple.photos.icloud.shared-streams.undownloaded-content-check			
default	16:56:32.031734 +0200	DuetHeuristic-BM	COMPLETED <private>!
default	16:56:32.032309 +0200	UserEventAgent	Unregistered XPC
Activity: com.apple.photos.icloud.shared-streams.undownloaded-content-check			
default	16:56:32.064537 +0200	com.apple.WebKit.Networking	
0x110c88400 - NetworkResourceLoader::didFinishLoading: (pageID = 7,			
frameID = 1, resourceID = 32)			
default	16:56:32.064621 +0200	com.apple.WebKit.WebContent	
0x1131b4310 - WebResourceLoader::didFinishResourceLoad: (pageID = 7,			
frameID = 1, resourceID = 32)			
default	16:56:32.178831 +0200	gamed	[AVConference][INFO]
VCNAT64ResolveNAT64Prefix: Re-trying in 1 second for Interface <private>,			
attempt 3 out of 3			
default	16:56:32.786299 +0200	com.apple.WebKit.WebContent	
0x7fda8d22d5e0 - PerformanceMonitor::measurePostLoadMemoryUsage:			
Process was using 268554240 bytes of memory after the page load.			
default	16:56:32.813454 +0200	passd	End delaying exit: Archive Tasks (1)
default	16:56:32.814331 +0200	opendirectoryd	Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0			

```

default    16:56:32.814408 +0200  opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default    16:56:32.814510 +0200  opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 20, EGID: 20
default    16:56:32.814651 +0200  opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default    16:56:32.814661 +0200  opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 20, EGID: 20
default    16:56:32.814770 +0200  opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default    16:56:32.814831 +0200  opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 20, EGID: 20
default    16:56:32.814932 +0200  opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default    16:56:32.814937 +0200  opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default    16:56:32.815081 +0200  opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default    16:56:32.815099 +0200  opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 20, EGID: 20
default    16:56:32.815360 +0200  opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default    16:56:32.816082 +0200  passwd      End delaying exit: Archive Tasks (0)
default    16:56:32.820505 +0200  opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default    16:56:32.820604 +0200  opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default    16:56:32.820687 +0200  opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default    16:56:32.820766 +0200  opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default    16:56:33.155182 +0200  com.apple.WebKit.WebContent
0x7fac3c218f00 - PerformanceMonitor::measurePostLoadMemoryUsage:
Process was using 22376448 bytes of memory after the page load.
default    16:56:33.169550 +0200  trustd      cert[2]: AnchorTrusted =(leaf)[force]>
0
default    16:56:33.275695 +0200  gamed       [AVConference][INFO]
VCNAT64ResolveNAT64Prefix: Interface <private> IS NOT behind NAT 64
default    16:56:33.781351 +0200  fud         Nothing left to do, exiting.
default    16:56:33.784829 +0200  fud         Successfully serialized to disk
default    16:56:33.984416 +0200  com.apple.WebKit.WebContent
0x7f93cd73ab00 - PerformanceMonitor::measurePostLoadCPUUsage: Process
was using 0.1% CPU after the page load.
default    16:56:34.152834 +0200  com.apple.WebKit.WebContent
0x7fc5f7079f30 - PerformanceMonitor::measurePostLoadMemoryUsage:
Process was using 52473856 bytes of memory after the page load.
default    16:56:34.201275 +0200  accountsd   "Idle-exit-preventing transaction
ended!"
default    16:56:34.263887 +0200  trustd      cert[2]: AnchorTrusted =(leaf)[force]>
0

```

```

default    16:56:34.264588 +0200    com.apple.iCloudHelper    MacOS error:
-67050
default    16:56:34.265941 +0200    syncdefaultsd    Preparing synchronization with
remote server for app:com.apple.Safari/0x7fe9f3316be0, scheduler:<private>
default    16:56:34.268269 +0200    opendirectoryd    Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default    16:56:34.268336 +0200    opendirectoryd    queuing request to connection
- '<private>'
default    16:56:34.268479 +0200    opendirectoryd    queuing request to connection
- '<private>'
default    16:56:34.274215 +0200    syncdefaultsd    0x7fe9f0f2a540 opened /Users/
craigdenham/Library/Keychains/login.keychain-db: 218248 bytes
default    16:56:34.274358 +0200    syncdefaultsd    0x7fe9f0f32a10 opened /
Library/Keychains/System.keychain: 37732 bytes
default    16:56:34.276914 +0200    syncdefaultsd    TIC TCP Conn Start
[7:0x7fe9f3123960]
default    16:56:34.394059 +0200    com.apple.WebKit.Networking
TIC TCP Conn Event [63:0x7fa644fab110]: 2 Err(0)
default    16:56:34.394089 +0200    com.apple.WebKit.Networking
TIC TCP Conn Cancel [63:0x7fa644fab110]
default    16:56:34.394112 +0200    com.apple.WebKit.Networking
TIC TCP Conn Destroyed [63:0x7fa644fab110]
default    16:56:34.519396 +0200    com.apple.WebKit.WebContent
0x7fcb9b108dc0 - PerformanceMonitor::measurePostLoadMemoryUsage:
Process was using 53121024 bytes of memory after the page load.
default    16:56:34.531155 +0200    com.apple.WebKit.WebContent
0x1085f5000 - WebLoaderStrategy::scheduleLoad: Resource has been queued
for scheduling with the NetworkProcess (frame = 0x108432700, priority = 2, pageID
= 3, frameID = 2, resourceID = 359, WebResourceLoader = 0x1314b3d90)
default    16:56:34.531264 +0200    com.apple.WebKit.Networking
0x110c4a000 - NetworkResourceLoader::start: Retrieving resource from cache
(pageID = 3, frameID = 2, resourceID = 359, isMainResource = 0, isSynchronous =
0)
default    16:56:34.531294 +0200    com.apple.WebKit.Networking
0x110c4a000 - NetworkResourceLoader::startNetworkLoad: (pageID = 3,
frameID = 2, resourceID = 359, isMainResource = 0, isSynchronous = 0)
default    16:56:34.531748 +0200    com.apple.WebKit.Networking
0x7fa644f700c0 opened /Users/craigdenham/Library/Keychains/login.keychain-
db: 218248 bytes
default    16:56:34.531851 +0200    com.apple.WebKit.Networking
0x7fa644f700c0 opened /Library/Keychains/System.keychain: 37732 bytes
default    16:56:34.532661 +0200    syncdefaultsd    TIC TCP Conn Event
[7:0x7fe9f3123960]: 1 Err(0)
default    16:56:34.532678 +0200    syncdefaultsd    TIC TCP Conn Connected
[7:0x7fe9f3123960]: Err(0)
default    16:56:34.532728 +0200    syncdefaultsd    TIC Enabling TLS
[7:0x7fe9f3123960]
default    16:56:34.600545 +0200    SafariDAVClient    ApplePushService:
<APSCConnection: 0x7f88b0800bd0> _shutdownFromDealloc
default    16:56:34.600579 +0200    SafariDAVClient    ApplePushService:

```

```

<APSCConnection: 0x7f88b0800bd0> _flushConnection
default 16:56:34.600711 +0200 SafariDAVClient ApplePushService:
Connection successfully flushed during shutdown
default 16:56:34.600778 +0200 SafariDAVClient ApplePushService:
<APSCConnection: 0x7f88b0800bd0> _cancelConnection called
default 16:56:34.600884 +0200 SafariDAVClient ApplePushService:
Connection Invalid for service com.apple.apsd
default 16:56:34.600906 +0200 apsd peer(449) received
XPC_ERROR_CONNECTION_INVALID
default 16:56:34.825633 +0200 syncdefaultsd TIC TLS Event
[7:0x7fe9f3123960]: 2, Pending(0)
default 16:56:34.830215 +0200 syncdefaultsd TIC TLS Event
[7:0x7fe9f3123960]: 11, Pending(0)
default 16:56:34.830583 +0200 syncdefaultsd TIC TLS Event
[7:0x7fe9f3123960]: 12, Pending(0)
default 16:56:34.830668 +0200 syncdefaultsd TIC TLS Event
[7:0x7fe9f3123960]: 14, Pending(0)
default 16:56:34.830975 +0200 syncdefaultsd CFNetwork-AOSKit: Reaching
out to AOSKit for X-mobile me token
default 16:56:34.831028 +0200 syncdefaultsd CFNetwork-AOSKit: Applied X-
mobile me auth to request
default 16:56:34.833477 +0200 syncdefaultsd TIC TLS Trust Result
[7:0x7fe9f3123960]: 0
default 16:56:34.834683 +0200 com.apple.WebKit.Networking
0x110c4a000 - NetworkResourceLoader::didReceiveResponse: (pageID = 3,
frameID = 2, resourceID = 359, httpStatusCode = 200, length = 16)
default 16:56:34.834719 +0200 com.apple.WebKit.Networking
0x110c4a000 - NetworkResourceLoader::didReceiveResponse: Should not
wait for message from WebContent process before continuing resource load (pageID
= 3, frameID = 2, resourceID = 359)
default 16:56:34.834773 +0200 com.apple.WebKit.Networking
0x110c4a000 - NetworkResourceLoader::didReceiveBuffer: Started receiving
data (pageID = 3, frameID = 2, resourceID = 359)
default 16:56:34.834837 +0200 com.apple.WebKit.Networking
0x110c4a000 - NetworkResourceLoader::didFinishLoading: (pageID = 3,
frameID = 2, resourceID = 359)
default 16:56:34.834829 +0200 com.apple.WebKit.WebContent
0x1314b3d90 - WebResourceLoader::didReceiveResponse: (pageID = 3,
frameID = 2, resourceID = 359, status = 200)
default 16:56:34.834942 +0200 com.apple.WebKit.WebContent
0x1314b3d90 - WebResourceLoader::didReceiveData: Started receiving data
(pageID = 3, frameID = 2, resourceID = 359)
default 16:56:34.834976 +0200 com.apple.WebKit.WebContent
0x1314b3d90 - WebResourceLoader::didFinishResourceLoad: (pageID = 3,
frameID = 2, resourceID = 359)
default 16:56:34.859790 +0200 mds directQueryFetchResultsReply 53251
1795162112 35
default 16:56:34.936468 +0200 com.apple.WebKit.WebContent
0x1113f5000 - WebLoaderStrategy::scheduleLoad: Resource has been queued
for scheduling with the NetworkProcess (frame = 0x1139bb380, priority = 2, pageID

```

```

= 2, frameID = 3, resourceID = 113, WebResourceLoader = 0x113973fc0)
default 16:56:34.936566 +0200 com.apple.WebKit.Networking
    0x110c4a400 - NetworkResourceLoader::start: Retrieving resource from cache
(pageID = 2, frameID = 3, resourceID = 113, isMainResource = 0, isSynchronous =
0)
default 16:56:34.936612 +0200 com.apple.WebKit.WebContent
    0x1113f5000 - WebLoaderStrategy::scheduleLoad: Resource has been queued
for scheduling with the NetworkProcess (frame = 0x1138daa80, priority = 2, pageID
= 2, frameID = 5, resourceID = 114, WebResourceLoader = 0x113958d90)
default 16:56:34.936607 +0200 com.apple.WebKit.Networking
    0x110c4a400 - NetworkResourceLoader::startNetworkLoad: (pageID = 2,
frameID = 3, resourceID = 113, isMainResource = 0, isSynchronous = 0)
default 16:56:34.936751 +0200 com.apple.WebKit.Networking
    0x110c4ac00 - NetworkResourceLoader::start: Retrieving resource from cache
(pageID = 2, frameID = 5, resourceID = 114, isMainResource = 0, isSynchronous =
0)
default 16:56:34.936774 +0200 com.apple.WebKit.Networking
    0x110c4ac00 - NetworkResourceLoader::startNetworkLoad: (pageID = 2,
frameID = 5, resourceID = 114, isMainResource = 0, isSynchronous = 0)
default 16:56:34.936773 +0200 com.apple.WebKit.WebContent
    0x1113f5000 - WebLoaderStrategy::scheduleLoad: Resource has been queued
for scheduling with the NetworkProcess (frame = 0x112b8b000, priority = 2, pageID
= 2, frameID = 2, resourceID = 115, WebResourceLoader = 0x113958968)
default 16:56:34.936927 +0200 com.apple.WebKit.WebContent
    0x1113f5000 - WebLoaderStrategy::scheduleLoad: Resource has been queued
for scheduling with the NetworkProcess (frame = 0x1139a7000, priority = 2, pageID
= 2, frameID = 4, resourceID = 116, WebResourceLoader = 0x111249700)
default 16:56:34.936931 +0200 com.apple.WebKit.Networking
    0x110cce000 - NetworkResourceLoader::start: Retrieving resource from cache
(pageID = 2, frameID = 2, resourceID = 115, isMainResource = 0, isSynchronous =
0)
default 16:56:34.936961 +0200 com.apple.WebKit.Networking
    0x110cce000 - NetworkResourceLoader::startNetworkLoad: (pageID = 2,
frameID = 2, resourceID = 115, isMainResource = 0, isSynchronous = 0)
default 16:56:34.937054 +0200 com.apple.WebKit.Networking
    0x110cce400 - NetworkResourceLoader::start: Retrieving resource from cache
(pageID = 2, frameID = 4, resourceID = 116, isMainResource = 0, isSynchronous =
0)
default 16:56:34.937088 +0200 com.apple.WebKit.Networking
    0x110cce400 - NetworkResourceLoader::startNetworkLoad: (pageID = 2,
frameID = 4, resourceID = 116, isMainResource = 0, isSynchronous = 0)
default 16:56:34.988674 +0200 syncdefaultsd TIC TLS Event
[7:0x7fe9f3123960]: 20, Pending(0)
default 16:56:34.988905 +0200 syncdefaultsd TIC TCP Conn Event
[7:0x7fe9f3123960]: 8 Err(0)
default 16:56:34.988919 +0200 syncdefaultsd TIC TLS Handshake Complete
[7:0x7fe9f3123960]
default 16:56:34.989042 +0200 syncdefaultsd CFNetwork-AOSKit: Reaching
out to AOSKit for X-mobile me token
default 16:56:34.989135 +0200 syncdefaultsd CFNetwork-AOSKit: Applied X-

```

mobile me auth to request

default 16:56:34.989889 +0200 com.apple.Safari.SearchHelper
TIC TCP Conn Event [2:0x7fdab2e10c00]: 2 Err(0)

default 16:56:34.989918 +0200 com.apple.Safari.SearchHelper
TIC TCP Conn Cancel [2:0x7fdab2e10c00]

default 16:56:34.989963 +0200 com.apple.Safari.SearchHelper
TIC TCP Conn Destroyed [2:0x7fdab2e10c00]

default 16:56:34.994111 +0200 com.apple.WebKit.Networking
TIC TCP Conn Event [23:0x7fa644d22bf0]: 2 Err(0)

default 16:56:34.994138 +0200 com.apple.WebKit.Networking
TIC TCP Conn Cancel [23:0x7fa644d22bf0]

default 16:56:34.994161 +0200 com.apple.WebKit.Networking
TIC TCP Conn Destroyed [23:0x7fa644d22bf0]

default 16:56:35.045187 +0200 com.apple.WebKit.WebContent
0x7fcf3b719160 - PerformanceMonitor::measurePostLoadMemoryUsage:
Process was using 60358656 bytes of memory after the page load.

default 16:56:35.150315 +0200 com.apple.WebKit.Networking
0x110c4a400 - NetworkResourceLoader::didReceiveResponse: (pageID = 2,
frameID = 3, resourceID = 113, httpStatusCode = 200, length = 16)

default 16:56:35.150353 +0200 com.apple.WebKit.Networking
0x110c4a400 - NetworkResourceLoader::didReceiveResponse: Should not
wait for message from WebContent process before continuing resource load (pageID
= 2, frameID = 3, resourceID = 113)

default 16:56:35.150433 +0200 com.apple.WebKit.Networking
0x110c4a400 - NetworkResourceLoader::didReceiveBuffer: Started receiving
data (pageID = 2, frameID = 3, resourceID = 113)

default 16:56:35.150481 +0200 com.apple.WebKit.WebContent
0x113973fc0 - WebResourceLoader::didReceiveResponse: (pageID = 2,
frameID = 3, resourceID = 113, status = 200)

default 16:56:35.150498 +0200 com.apple.WebKit.Networking
0x110c4a400 - NetworkResourceLoader::didFinishLoading: (pageID = 2,
frameID = 3, resourceID = 113)

default 16:56:35.150577 +0200 com.apple.WebKit.WebContent
0x113973fc0 - WebResourceLoader::didReceiveData: Started receiving data
(pageID = 2, frameID = 3, resourceID = 113)

default 16:56:35.150636 +0200 com.apple.WebKit.WebContent
0x113973fc0 - WebResourceLoader::didFinishResourceLoad: (pageID = 2,
frameID = 3, resourceID = 113)

default 16:56:35.151761 +0200 com.apple.WebKit.Networking
0x110c4ac00 - NetworkResourceLoader::didReceiveResponse: (pageID = 2,
frameID = 5, resourceID = 114, httpStatusCode = 200, length = 16)

default 16:56:35.151808 +0200 com.apple.WebKit.Networking
0x110c4ac00 - NetworkResourceLoader::didReceiveResponse: Should not wait
for message from WebContent process before continuing resource load (pageID = 2,
frameID = 5, resourceID = 114)

default 16:56:35.151878 +0200 com.apple.WebKit.WebContent
0x113958d90 - WebResourceLoader::didReceiveResponse: (pageID = 2,
frameID = 5, resourceID = 114, status = 200)

default 16:56:35.151876 +0200 com.apple.WebKit.Networking
0x110c4ac00 - NetworkResourceLoader::didReceiveBuffer: Started receiving

data (pageID = 2, frameID = 5, resourceID = 114)
default 16:56:35.151933 +0200 com.apple.WebKit.Networking
0x110c4ac00 - NetworkResourceLoader::didFinishLoading: (pageID = 2,
frameID = 5, resourceID = 114)
default 16:56:35.152015 +0200 com.apple.WebKit.WebContent
0x113958d90 - WebResourceLoader::didReceiveData: Started receiving data
(pageID = 2, frameID = 5, resourceID = 114)
default 16:56:35.152060 +0200 com.apple.WebKit.WebContent
0x113958d90 - WebResourceLoader::didFinishResourceLoad: (pageID = 2,
frameID = 5, resourceID = 114)
default 16:56:35.211510 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default 16:56:35.211717 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 20, EGID: 20
default 16:56:35.211947 +0200 opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default 16:56:35.243878 +0200 filecoordinationd Presenter E89A1BEE-
BF55-490A-B675-C11FDE4E7A44 detected non-coordinated event
default 16:56:35.276850 +0200 com.apple.WebKit.Networking
0x110cce400 - NetworkResourceLoader::didReceiveResponse: (pageID = 2,
frameID = 4, resourceID = 116, httpStatusCode = 200, length = 16)
default 16:56:35.276887 +0200 com.apple.WebKit.Networking
0x110cce400 - NetworkResourceLoader::didReceiveResponse: Should not wait
for message from WebContent process before continuing resource load (pageID = 2,
frameID = 4, resourceID = 116)
default 16:56:35.276953 +0200 com.apple.WebKit.Networking
0x110cce400 - NetworkResourceLoader::didReceiveBuffer: Started receiving
data (pageID = 2, frameID = 4, resourceID = 116)
default 16:56:35.277013 +0200 com.apple.WebKit.WebContent
0x111249700 - WebResourceLoader::didReceiveResponse: (pageID = 2,
frameID = 4, resourceID = 116, status = 200)
default 16:56:35.277004 +0200 com.apple.WebKit.Networking
0x110cce400 - NetworkResourceLoader::didFinishLoading: (pageID = 2,
frameID = 4, resourceID = 116)
default 16:56:35.277086 +0200 com.apple.WebKit.WebContent
0x111249700 - WebResourceLoader::didReceiveData: Started receiving data
(pageID = 2, frameID = 4, resourceID = 116)
default 16:56:35.277123 +0200 com.apple.WebKit.WebContent
0x111249700 - WebResourceLoader::didFinishResourceLoad: (pageID = 2,
frameID = 4, resourceID = 116)
default 16:56:35.277583 +0200 com.apple.WebKit.Networking
0x110cce000 - NetworkResourceLoader::didReceiveResponse: (pageID = 2,
frameID = 2, resourceID = 115, httpStatusCode = 200, length = 16)
default 16:56:35.277610 +0200 com.apple.WebKit.Networking
0x110cce000 - NetworkResourceLoader::didReceiveResponse: Should not wait
for message from WebContent process before continuing resource load (pageID = 2,
frameID = 2, resourceID = 115)
default 16:56:35.277694 +0200 com.apple.WebKit.WebContent
0x113958968 - WebResourceLoader::didReceiveResponse: (pageID = 2,
frameID = 2, resourceID = 115, status = 200)

```

default    16:56:35.277676 +0200    com.apple.WebKit.Networking
           0x110cce000 - NetworkResourceLoader::didReceiveBuffer: Started receiving
data (pageID = 2, frameID = 2, resourceID = 115)
default    16:56:35.277805 +0200    com.apple.WebKit.WebContent
           0x113958968 - WebResourceLoader::didReceiveData: Started receiving data
(pageID = 2, frameID = 2, resourceID = 115)
default    16:56:35.277731 +0200    com.apple.WebKit.Networking
           0x110cce000 - NetworkResourceLoader::didFinishLoading: (pageID = 2,
frameID = 2, resourceID = 115)
default    16:56:35.277836 +0200    com.apple.WebKit.WebContent
           0x113958968 - WebResourceLoader::didFinishResourceLoad: (pageID = 2,
frameID = 2, resourceID = 115)
default    16:56:35.299300 +0200    com.apple.WebKit.Networking
           TIC TCP Conn Event [66:0x7fa644da8400]: 2 Err(0)
default    16:56:35.299327 +0200    com.apple.WebKit.Networking
           TIC TCP Conn Cancel [66:0x7fa644da8400]
default    16:56:35.299356 +0200    com.apple.WebKit.Networking
           TIC TCP Conn Destroyed [66:0x7fa644da8400]
default    16:56:35.300235 +0200    syncdefaultsd    TIC TCP Conn Cancel
[7:0x7fe9f3123960]
default    16:56:35.300313 +0200    syncdefaultsd    TIC TCP Conn Destroyed
[7:0x7fe9f3123960]
default    16:56:35.300364 +0200    syncdefaultsd    Synchronization with server
succeeded for app:com.apple.Safari/0x7fe9f3316be0, scheduler:<private>
default    16:56:35.302132 +0200    com.apple.WebKit.WebContent
           0x7f951fea71b0 - PerformanceMonitor::measurePostLoadCPUUsage: Process
was using 0.1% CPU after the page load.
default    16:56:35.307489 +0200    apsd <APSDaemon: 0x7ff10fe14330>: No
change in users
default    16:56:35.307616 +0200    opendirectoryd    Client: <private>, UID: 0, EUID:
501, GID: 20, EGID: 20
default    16:56:35.307728 +0200    opendirectoryd    Client: <private>, UID: 0, EUID:
501, GID: 20, EGID: 20
default    16:56:35.307828 +0200    opendirectoryd    Client: <private>, UID: 0, EUID:
501, GID: 20, EGID: 20
default    16:56:35.307947 +0200    opendirectoryd    Client: <private>, UID: 0, EUID:
501, GID: 20, EGID: 20
default    16:56:35.308052 +0200    opendirectoryd    Client: <private>, UID: 0, EUID:
501, GID: 20, EGID: 20
default    16:56:35.309104 +0200    loginwindow       It took 0.000514 sec to get the
desktop picture from the Dock
default    16:56:35.309462 +0200    opendirectoryd    Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default    16:56:35.309685 +0200    opendirectoryd    Client: <private>, UID: 0, EUID:
0, GID: 20, EGID: 20
default    16:56:35.309957 +0200    opendirectoryd    Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default    16:56:35.310055 +0200    com.apple.WebKit.Networking
           TIC TCP Conn Event [36:0x7fa644e43620]: 2 Err(0)
default    16:56:35.310091 +0200    com.apple.WebKit.Networking

```



```

TIC TCP Conn Cancel [36:0x7fa644e43620]
default 16:56:35.310143 +0200 com.apple.WebKit.Networking
TIC TCP Conn Destroyed [36:0x7fa644e43620]
default 16:56:35.315164 +0200 opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default 16:56:35.323023 +0200 kernel SandboxViolation:
softwareupdate_n(473) deny(1) file-read-metadata /Users/craigdenham
default 16:56:35.328837 +0200 loginwindow It took 0.019731 sec to
generate the desktop picture image
default 16:56:35.330214 +0200 opendirectoryd Client: <private>, UID: 200,
EUID: 200, GID: 200, EGID: 200
default 16:56:35.333024 +0200 opendirectoryd Client: <private>, UID: 200,
EUID: 200, GID: 200, EGID: 200
default 16:56:35.342542 +0200 trustd cert[2]: AnchorTrusted =(leaf)[force]>
0
default 16:56:35.343880 +0200 authd MacOS error: -67050
default 16:56:35.344156 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default 16:56:35.344257 +0200 opendirectoryd <private> failed with error
'<private>' (2)
default 16:56:35.352331 +0200 FindMyMacd 0x7ff445e04d20 opened /
private/var/db/mds/system/mdsObject.db: 4636 bytes
default 16:56:35.352848 +0200 FindMyMacd 0x7ff445d01420 opened /
private/var/db/mds/system/mdsDirectory.db: 50744 bytes
default 16:56:35.354913 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default 16:56:35.356260 +0200 FindMyMacd 0x7ff445d0aae0 opened /
private/var/db/mds/system/mdsDirectory.db: 50744 bytes
default 16:56:35.357079 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default 16:56:35.358468 +0200 FindMyMacd using system preferences
default 16:56:35.360013 +0200 trustd cert[2]: AnchorTrusted =(leaf)[force]>
0
default 16:56:35.360322 +0200 trustd cert[2]: AnchorTrusted =(leaf)[force]>
0
default 16:56:35.361050 +0200 authd MacOS error: -67050
default 16:56:35.361318 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default 16:56:35.361617 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default 16:56:35.361715 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default 16:56:35.361827 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default 16:56:35.461946 +0200 AddressBookSourceSync -
sourceShouldRefresh: (null)
default 16:56:35.461972 +0200 AddressBookSourceSync -
sourceShouldRefresh: (null)
default 16:56:35.462017 +0200 AddressBookSourceSync -
serverSynclnProgress returning NO

```

default 16:56:35.462018 +0200 AddressBookSourceSync -
 serverSyncInProgress returning NO
 default 16:56:35.462282 +0200 AddressBookSourceSync
 isAccountProperlyInitialized: YES Host: YES User: YES Password: YES
 default 16:56:35.462283 +0200 AddressBookSourceSync
 isAccountProperlyInitialized: YES Host: YES User: YES Password: YES
 default 16:56:35.462316 +0200 AddressBookSourceSync canTalkToServer:
 YES (AcctIsInitialized: YES IsOnline: YES)
 default 16:56:35.462317 +0200 AddressBookSourceSync canTalkToServer:
 YES (AcctIsInitialized: YES IsOnline: YES)
 default 16:56:35.462343 +0200 AddressBookSourceSync -
 sourceShouldRefresh calling [self scheduleFullSync]
 default 16:56:35.462350 +0200 AddressBookSourceSync -
 sourceShouldRefresh calling [self scheduleFullSync]
 default 16:56:35.462462 +0200 AddressBookSourceSync Request to schedule
 sync: (null) from thread: <private>
 default 16:56:35.462463 +0200 AddressBookSourceSync Request to schedule
 sync: (null) from thread: <private>
 default 16:56:35.462513 +0200 AddressBookSourceSync -
 serverSyncInProgress returning NO
 default 16:56:35.462513 +0200 AddressBookSourceSync -
 serverSyncInProgress returning NO
 default 16:56:35.462548 +0200 AddressBookSourceSync Scheduling sync
 from thread: <private>
 default 16:56:35.462575 +0200 AddressBookSourceSync Scheduling sync
 from thread: <private>
 default 16:56:35.462869 +0200 AddressBookSourceSync -startSync
 (<private>) running on thread: <private>
 default 16:56:35.462875 +0200 AddressBookSourceSync -startSync
 (<private>) running on thread: <private>
 default 16:56:35.462910 +0200 AddressBookSourceSync -
 serverSyncInProgress returning YES
 default 16:56:35.462912 +0200 AddressBookSourceSync -
 serverSyncInProgress returning YES
 default 16:56:35.463327 +0200 AddressBookSourceSync
 isAccountProperlyInitialized: YES Host: YES User: YES Password: YES
 default 16:56:35.463331 +0200 AddressBookSourceSync
 isAccountProperlyInitialized: YES Host: YES User: YES Password: YES
 default 16:56:35.463348 +0200 AddressBookSourceSync canTalkToServer:
 YES (AcctIsInitialized: YES IsOnline: YES)
 default 16:56:35.463357 +0200 AddressBookSourceSync canTalkToServer:
 YES (AcctIsInitialized: YES IsOnline: YES)
 error 16:56:35.465850 +0200 AddressBookSourceSync warning: dynamic
 accessors failed to find @property implementation for 'uniqueId' for entity
 ABCDGroup while resolving selector 'uniqueId' on class 'ABCDGroup'. Did you
 remember to declare it @dynamic or @synthesized in the @implementation ?
 default 16:56:35.466137 +0200 AddressBookSourceSync -
 clearHomeContainers
 default 16:56:35.466216 +0200 AddressBookSourceSync -getPrincipalInfo:
 [_controller supportsRequestCompressionAtURL:<private>]

default 16:56:35.466300 +0200 AddressBookSourceSync -[CDXAccount clearAuthMethodsTried]

default 16:56:35.466658 +0200 AddressBookSourceSync Looking up (assumed existing) account with identifier <private>

default 16:56:35.469719 +0200 AddressBookSourceSync - clearHomeContainers

default 16:56:35.469751 +0200 AddressBookSourceSync -getPrincipalInfo: [_controller supportsRequestCompressionAtURL:<private>]

default 16:56:35.469769 +0200 AddressBookSourceSync -[CDXAccount clearAuthMethodsTried]

default 16:56:35.469922 +0200 AddressBookSourceSync Looking up (assumed existing) account with identifier <private>

default 16:56:35.480281 +0200 CommCenter #l
CSIApplInfo.ApplicationActivationObserver: handleLSNotification_sync: Application exited: <private>

default 16:56:35.490699 +0200 apsd <APSCourier: 0x7ff1122051b0>: Finished waiting for user 501 darkWakeEnabled before recreating the courier state

default 16:56:35.490768 +0200 apsd <APSCourier: 0x7ff1122051b0>: Recreating courier state for user 501 darkWakeEnabled

default 16:56:35.490821 +0200 apsd <APSCourier: 0x7ff1122051b0>: Will connect user 501 darkWakeEnabled because in full wake

default 16:56:35.490911 +0200 apsd <<APSTokenState: 0x7ff10fc321c0>: { tokenName=501 darkWakeEnabled, status=disconnected, willConnect=no, willDisconnect=no, systemUser=<APSSystemUser: 0x7ff10fe3d420>, publicToken=<30af8d61 9c2a0b23 7c9c12f8 ee5d2235 1ef69fec 62a75030 2a6642cd a67418a9>, sentFilterMessage=NO darkWakeEnabled=yes, topicManager=0x7ff10fc16cc0 }>: Status for user 501 darkWakeEnabled is disconnected, but user will be connected

default 16:56:35.490956 +0200 apsd <APSCourier: 0x7ff1122051b0>: Adjusting connection with courier connectable

default 16:56:35.490986 +0200 apsd <APSCourier: 0x7ff1122051b0>: Checking whether any users can be connected or disconnected

default 16:56:35.491016 +0200 apsd <APSCourier: 0x7ff1122051b0>: Not disconnecting user 501 because user is already disconnected

default 16:56:35.491046 +0200 apsd <APSCourier: 0x7ff1122051b0>: Not connecting 0 darkWakeEnabled because user is already connected

default 16:56:35.491075 +0200 apsd <APSCourier: 0x7ff1122051b0>: Not connecting 0 because user is already connected

default 16:56:35.491124 +0200 apsd <<APSTokenState: 0x7ff10fc321c0>: { tokenName=501 darkWakeEnabled, status=disconnected, willConnect=yes, willDisconnect=no, systemUser=<APSSystemUser: 0x7ff10fe3d420>, publicToken=<30af8d61 9c2a0b23 7c9c12f8 ee5d2235 1ef69fec 62a75030 2a6642cd a67418a9>, sentFilterMessage=NO darkWakeEnabled=yes, topicManager=0x7ff10fc16cc0 }>: Changing status for user 501 darkWakeEnabled from disconnected to connecting

default 16:56:35.491160 +0200 apsd <APSCourier: 0x7ff1122051b0>: Sending connect message for user 501 darkWakeEnabled with token '<30af8d61 9c2a0b23 7c9c12f8 ee5d2235 1ef69fec 62a75030 2a6642cd a67418a9>'

default 16:56:35.491398 +0200 apsd <APSCourier: 0x7ff1122051b0>: Filter changed

```

default    16:56:35.491544 +0200  apsd <APSDaemon: 0x7ff10fe14330>: Set
active push connection state to YES
default    16:56:35.621516 +0200  accountsd "<private> (<private>) received"
default    16:56:35.668820 +0200  accountsd 0x7fe5b4308690 opened /var/
folders/j8/bbhn9g892k14cv1xw2hp2fy80000gn/C//mds/mdsObject.db: 4636 bytes
default    16:56:35.669163 +0200  accountsd 0x7fe5b422b100 opened /var/
folders/j8/bbhn9g892k14cv1xw2hp2fy80000gn/C//mds/mdsDirectory.db: 50744 bytes
default    16:56:35.669390 +0200  accountsd 0x7fe5b421e3f0 opened /Users/
craigdenham/Library/Keychains/login.keychain-db: 218248 bytes
default    16:56:35.671849 +0200  accountsd getting current attributes...
default    16:56:35.671875 +0200  accountsd filling 16 attributes for type
2147483648
default    16:56:35.672016 +0200  securityd 0x7fb8fdc0ed10(0x7fb8fde138c0) is
unlocked; decoding for makeUnlocked()
default    16:56:35.672234 +0200  accountsd looking at 16 attributes
default    16:56:35.672278 +0200  accountsd finished:
43d68c931c19d154ccabbbf337c79bd3dff8cbf42ce3a5f16be01630c97caacd
default    16:56:35.673003 +0200  securityd ACL partitionID = <CFArray
0x7fb8fdc07dd0 [0x7ffda12eda0]>{type = mutable-small, count = 1, values = (
    0 : apple:
)}}
default    16:56:35.673025 +0200  securityd ACL partitions match: apple:
default    16:56:35.673807 +0200  accountsd getting current attributes...
default    16:56:35.673832 +0200  accountsd filling 16 attributes for type
2147483648
default    16:56:35.674070 +0200  accountsd looking at 16 attributes
default    16:56:35.674111 +0200  accountsd finished:
ecc06ad9efa88a71c4e77368df4bab2310567ef5e03e87b58e24cd67767174ae
default    16:56:35.674715 +0200  securityd ACL partitionID = <CFArray
0x7fb8fdc09530 [0x7ffda12eda0]>{type = mutable-small, count = 1, values = (
    0 : apple:
)}}
default    16:56:35.674734 +0200  securityd ACL partitions match: apple:
default    16:56:35.675369 +0200  accountsd 0x7fe5b422f670 opened /Library/
Keychains/System.keychain: 37732 bytes
default    16:56:35.678213 +0200  accountsd getting current attributes...
default    16:56:35.679027 +0200  securityd keychain reference in server mode
default    16:56:35.679109 +0200  securityd keychain reference in server mode
default    16:56:35.678283 +0200  accountsd filling 16 attributes for type
2147483648
default    16:56:35.680705 +0200  accountsd looking at 16 attributes
default    16:56:35.680807 +0200  accountsd finished:
f88517b7c05aaf65cbc02e865bc3b4897d3a60fe5d2b404381fc667b69db6857
default    16:56:35.681760 +0200  securityd ACL partitionID = <CFArray
0x7fb8ff120520 [0x7ffda12eda0]>{type = mutable-small, count = 1, values = (
    0 : apple:
)}}
default    16:56:35.681789 +0200  securityd ACL partitions match: apple:
default    16:56:35.683220 +0200  accountsd getting current attributes...
default    16:56:35.683245 +0200  accountsd filling 16 attributes for type

```

```

2147483648
default 16:56:35.683508 +0200 accountsd looking at 16 attributes
default 16:56:35.683547 +0200 accountsd finished:
ecc06ad9efa88a71c4e77368df4bab2310567ef5e03e87b58e24cd67767174ae
default 16:56:35.684308 +0200 securityd ACL partitionID = <CFArray
0x7fb8fdc0ac80 [0x7ffda12eda0]>{type = mutable-small, count = 1, values = (
    0 : apple:
)}}
default 16:56:35.684328 +0200 securityd ACL partitions match: apple:
default 16:56:35.685227 +0200 accountsd getting current attributes...
default 16:56:35.685260 +0200 accountsd filling 16 attributes for type
2147483648
default 16:56:35.685564 +0200 accountsd looking at 16 attributes
default 16:56:35.685607 +0200 accountsd finished:
f88517b7c05aaf65cbc02e865bc3b4897d3a60fe5d2b404381fc667b69db6857
default 16:56:35.686399 +0200 securityd ACL partitionID = <CFArray
0x7fb8fdc0ac80 [0x7ffda12eda0]>{type = mutable-small, count = 1, values = (
    0 : apple:
)}}
default 16:56:35.686424 +0200 securityd ACL partitions match: apple:
default 16:56:35.687643 +0200 securityd keychain reference in server mode
default 16:56:35.687708 +0200 securityd keychain reference in server mode
default 16:56:35.687766 +0200 securityd keychain reference in server mode
default 16:56:35.688628 +0200 accountsd getting current attributes...
default 16:56:35.688676 +0200 accountsd filling 16 attributes for type
2147483648
default 16:56:35.689220 +0200 accountsd looking at 16 attributes
default 16:56:35.689250 +0200 locationd Location icon should now be in state
'Inactive'
default 16:56:35.689395 +0200 accountsd finished:
43d68c931c19d154ccabbbf337c79bd3dff8cbf42ce3a5f16be01630c97caacd
default 16:56:35.690163 +0200 com.apple.WebKit.WebContent
    0x10fdf5000 - WebLoaderStrategy::scheduleLoad: Resource has been queued
for scheduling with the NetworkProcess (frame = 0x10fd61000, priority = 1, pageID =
7, frameID = 1, resourceID = 34, WebResourceLoader = 0x114fb5310)
default 16:56:35.690252 +0200 com.apple.WebKit.Networking
    0x110cce800 - NetworkResourceLoader::start: Retrieving resource from cache
(pageID = 7, frameID = 1, resourceID = 34, isMainResource = 0, isSynchronous = 0)
default 16:56:35.690321 +0200 com.apple.WebKit.Networking
    0x110cce800 - NetworkResourceLoader::startNetworkLoad: (pageID = 7,
frameID = 1, resourceID = 34, isMainResource = 0, isSynchronous = 0)
default 16:56:35.690555 +0200 securityd ACL partitionID = <CFArray
0x7fb8ff0181d0 [0x7ffda12eda0]>{type = mutable-small, count = 1, values = (
    0 : apple:
)}}
default 16:56:35.690586 +0200 securityd ACL partitions match: apple:
default 16:56:35.691384 +0200 AddressBookSourceSync Using cached
_acAccount <private>
default 16:56:35.691426 +0200 AddressBookSourceSync _acAccountIdentifier
= <private>

```

```

default    16:56:35.691442 +0200    AddressBookSourceSync Using account with
identifier <private>
default    16:56:35.691497 +0200    AddressBookSourceSync Using cached
_acAccount <private>
default    16:56:35.691529 +0200    AddressBookSourceSync We are a the child of
a Gmail account; deferring to parent
default    16:56:35.691574 +0200    AddressBookSourceSync -
acAccountOrParentGoogleAccount: <private>
default    16:56:35.691629 +0200    AddressBookSourceSync -[CDXAccount
oauth2Token]: Returning oauth token <private> for identifier: <private>
default    16:56:35.695648 +0200    AddressBookSourceSync Using cached
_acAccount <private>
default    16:56:35.696424 +0200    securityd keychain reference in server mode
default    16:56:35.736198 +0200    com.apple.WebKit.Networking
TIC TCP Conn Event [43:0x7fa644f85520]: 2 Err(0)
default    16:56:35.736229 +0200    com.apple.WebKit.Networking
TIC TCP Conn Cancel [43:0x7fa644f85520]
default    16:56:35.736264 +0200    com.apple.WebKit.Networking
TIC TCP Conn Destroyed [43:0x7fa644f85520]
default    16:56:35.736521 +0200    com.apple.WebKit.Networking
TIC TCP Conn Event [44:0x7fa644f5e830]: 2 Err(0)
default    16:56:35.736540 +0200    com.apple.WebKit.Networking
TIC TCP Conn Cancel [44:0x7fa644f5e830]
default    16:56:35.736569 +0200    com.apple.WebKit.Networking
TIC TCP Conn Destroyed [44:0x7fa644f5e830]
default    16:56:35.742035 +0200    apsd <APSCourier: 0x7ff1122051b0>:
Outstanding data received: <08000000 25010001 00040002 14000500 02000306
00040000 00030800 023c000a 00080000 015c4542 5c51> (length 42)
default    16:56:35.742092 +0200    apsd <APSCourier: 0x7ff1122051b0>: Stream
processing: complete yes, invalid no, length parsed 42, parameters {
    APSProtocolCommand = 8;
    APSProtocolConnectedResponse = 0;
    APSProtocolDualChannelSupport = 1;
    APSProtocolLargeMessageSize = 15360;
    APSProtocolMessageSize = 5120;
    APSProtocolServerTime = 1495810595921;
}
default    16:56:35.742162 +0200    apsd <APSCourier: 0x7ff1122051b0>: Handling
connected message for user 501 darkWakeEnabled
default    16:56:35.742206 +0200    apsd Received connect message [production]
default    16:56:35.742232 +0200    apsd <APSCourier: 0x7ff1122051b0>:
Received connected response OK
default    16:56:35.742258 +0200    apsd <APSCourier: 0x7ff1122051b0>:
Received message size 5120
default    16:56:35.742287 +0200    apsd <APSCourier: 0x7ff1122051b0>:
Received large message size 15360
default    16:56:35.742310 +0200    apsd <APSCourier: 0x7ff1122051b0>:
Connected user 501 darkWakeEnabled to environment production
default    16:56:35.742346 +0200    apsd <<APSTokenState: 0x7ff10fc321c0>:
{ tokenName=501 darkWakeEnabled, status=connecting, willConnect=no,

```

willDisconnect=no, systemUser=<APSSystemUser: 0x7ff10fe3d420>, publicToken=<30af8d61 9c2a0b23 7c9c12f8 ee5d2235 1ef69fec 62a75030 2a6642cd a67418a9>, sentFilterMessage=NO darkWakeEnabled=yes, topicManager=0x7ff10fc16cc0 }>: Changing status for user 501 darkWakeEnabled from connecting to connected

default 16:56:35.742375 +0200 apsd <APSDaemon: 0x7ff10fe14330> received courierConnectionStatusDidChange from <APSCourier: 0x7ff1122051b0>.

isConnected? YES

default 16:56:35.742494 +0200 apsd <APSDaemon: 0x7ff10fe14330>: Set active push connection state to YES

default 16:56:35.742644 +0200 apsd <APSCConnectionServer: 0x7ff10fe3ee70>: Missing per-app tokens, re-requesting for user 501 darkWakeEnabled

default 16:56:35.742675 +0200 apsd <APSCConnectionServer: 0x7ff10fe3ee70>: Missing per-app token, requesting for user 501 darkWakeEnabled with topic = com.apple.icloud-container.com.apple.Notes and identifier =

default 16:56:35.742712 +0200 apsd <APSCourier: 0x7ff1122051b0>: Received request from <APSCConnectionServer: 0x7ff10fe3ee70> to generate token for topic "com.apple.icloud-container.com.apple.Notes" and identifier ""

default 16:56:35.742890 +0200 apsd 0x7ff10fe44120 opened /Library/Keychains/apsd.keychain: 606512 bytes

default 16:56:35.743118 +0200 apsd Failed to talk to secd after 4 attempts.

default 16:56:35.743290 +0200 apsd <APSCourier: 0x7ff1122051b0>: Received request to generate token for topic "com.apple.icloud-container.com.apple.Notes" and identifier "", assigned appld "0"

default 16:56:35.743496 +0200 apsd <APSTopicManager: 0x7ff10fc16cc0> asked to performFilterBlock

default 16:56:35.743660 +0200 apsd <APSCourier: 0x7ff1122051b0>: When filter is sent for user 501 darkWakeEnabled, users potentially with messages = 1

default 16:56:35.743766 +0200 apsd <APSCourier: 0x7ff1122051b0>: Sending filter message for user 501 darkWakeEnabled with token <30af8d61 9c2a0b23 7c9c12f8 ee5d2235 1ef69fec 62a75030 2a6642cd a67418a9> with enabled topics = (com.apple.private.alloy.screensharing, com.apple.private.alloy.avconference.icloud, com.apple.private.alloy.maps, com.apple.private.ids, com.apple.private.alloy.safeview, com.apple.private.alloy.accessibility.switchcontrol, com.apple.private.alloy.fmf, com.apple.sharedstreams, com.apple.private.alloy.gamecenter, com.apple.private.alloy.thumper.keys, com.apple.private.alloy.quickrelay, com.apple.private.alloy.continuity.tethering, com.apple.private.alloy.phonecontinuity, com.apple.private.alloy.continuity.unlock, com.apple.madrid, com.me.cal, com.apple.private.alloy.keychainsync, com.apple.private.alloy.applepay, com.apple.ess, com.apple.private.ac, com.apple.private.alloy.electrictouch, com.me.contacts, com.apple.mediastream.subscription.push, com.apple.private.alloy.continuity.activity, com.apple.maps.icloud, com<...>

default 16:56:35.743824 +0200 apsd <APSCourier: 0x7ff1122051b0> _processStoredIncomingMessages: enabled = YES

default 16:56:35.743884 +0200 apsd <APSCourier: 0x7ff1122051b0> processing 0 stored incoming messages

default 16:56:35.743914 +0200 apsd <APSCourier: 0x7ff1122051b0> done with _processStoredIncomingMessages

```

default 16:56:35.743951 +0200 apsd APSMessageStore -
APSIIncomingMessageRecordDeleteMessagesOlderThanDate environment
production 1 timeThreshold 514911395
default 16:56:35.744000 +0200 apsd <APSCourier: 0x7ff1122051b0>
_processStoredOutgoingMessages - marking outgoing messages as unsent so they
can be processed (we terminated before they were acknowledged).
default 16:56:35.744044 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Checking whether any users can be connected or disconnected
default 16:56:35.744090 +0200 apsd <APSCourier: 0x7ff1122051b0>: Not
disconnecting user 501 because user is already disconnected
default 16:56:35.744113 +0200 apsd <APSCourier: 0x7ff1122051b0>: Not
connecting 0 darkWakeEnabled because user is already connected
default 16:56:35.744133 +0200 apsd <APSCourier: 0x7ff1122051b0>: Not
connecting 0 because user is already connected
default 16:56:35.744153 +0200 apsd <APSCourier: 0x7ff1122051b0>: Not
connecting 501 darkWakeEnabled because user is already connected
default 16:56:35.744175 +0200 apsd <APSCourier: 0x7ff1122051b0>: Stream
processing: complete no, invalid no, length parsed 0, parameters (null)
default 16:56:35.744206 +0200 apsd Dispatching low priority message:
<OS_xpc_dictionary: <dictionary: 0x7ff10fe3bac0> { count = 2, transaction: 0,
voucher = 0x0, contents =
    "isConnected" => <bool: 0x7ffdd7a6aa8>: true
    "message-type" => <int64: 0x7ff10fe31080>: 26
}>
default 16:56:35.744237 +0200 apsd Dispatching low priority message:
<OS_xpc_dictionary: <dictionary: 0x7ff10fe3bac0> { count = 2, transaction: 0,
voucher = 0x0, contents =
    "isConnected" => <bool: 0x7ffdd7a6aa8>: true
    "message-type" => <int64: 0x7ff10fe30af0>: 26
}>
default 16:56:35.744305 +0200 identityservicesd ApplePushService:
<APSCConnection: 0x7fb5b8206ae0> Delivering connectionStatusChange from apsd:
YES
default 16:56:35.744283 +0200 apsd Dispatching low priority message:
<OS_xpc_dictionary: <dictionary: 0x7ff10fe3bac0> { count = 2, transaction: 0,
voucher = 0x0, contents =
    "isConnected" => <bool: 0x7ffdd7a6aa8>: true
    "message-type" => <int64: 0x7ff10fe30af0>: 26
}>
default 16:56:35.744364 +0200 identityservicesd ApplePushService:
<APSCConnection: 0x7fb5b661b120> Delivering connectionStatusChange from apsd:
YES
default 16:56:35.744345 +0200 apsd Dispatching low priority message:
<OS_xpc_dictionary: <dictionary: 0x7ff112202db0> { count = 2, transaction: 0,
voucher = 0x0, contents =
    "isConnected" => <bool: 0x7ffdd7a6aa8>: true
    "message-type" => <int64: 0x7ff112200580>: 26
}>
default 16:56:35.744431 +0200 identityservicesd ApplePushService:
<APSCConnection: 0x7fb5b8206ae0> seeing if delegate <IDSPushHandler:

```



```

0x7fb5b8304fc0> responds to status changes
default 16:56:35.744393 +0200 apsd Dispatching low priority message:
<OS_xpc_dictionary: <dictionary: 0x7ff112202db0> { count = 2, transaction: 0,
voucher = 0x0, contents =
    "isConnected" => <bool: 0x7ffdd7a6aa8>: true
    "message-type" => <int64: 0x7ff112200580>: 26
}>
default 16:56:35.744446 +0200 syncdefaults ApplePushService:
<APSCConnection: 0x7fe9f32047f0> Delivering connectionStatusChange from apsd:
YES
default 16:56:35.744468 +0200 identityservicesd ApplePushService:
<APSCConnection: 0x7fb5b8206ae0> calling <IDSPushHandler: 0x7fb5b8304fc0>
didChangeConnectedStatus:
default 16:56:35.744439 +0200 apsd Dispatching low priority message:
<OS_xpc_dictionary: <dictionary: 0x7ff112202db0> { count = 2, transaction: 0,
voucher = 0x0, contents =
    "isConnected" => <bool: 0x7ffdd7a6aa8>: true
    "message-type" => <int64: 0x7ff112200580>: 26
}>
default 16:56:35.744555 +0200 identityservicesd APS Connection status
did change to connected: YES
default 16:56:35.744479 +0200 apsd Dispatching low priority message:
<OS_xpc_dictionary: <dictionary: 0x7ff112202db0> { count = 2, transaction: 0,
voucher = 0x0, contents =
    "isConnected" => <bool: 0x7ffdd7a6aa8>: true
    "message-type" => <int64: 0x7ff112200580>: 26
}>
default 16:56:35.744636 +0200 imagent ApplePushService:
<APSCConnection: 0x7f8ad2a0eef0> Delivering connectionStatusChange from apsd:
YES
default 16:56:35.744624 +0200 identityservicesd ApplePushService:
<APSCConnection: 0x7fb5b8206ae0> returned from <IDSPushHandler:
0x7fb5b8304fc0> didChangeConnectedStatus:
default 16:56:35.744633 +0200 cloudd ApplePushService:
<APSCConnection: 0x7ff288100ee0> Delivering connectionStatusChange from apsd:
YES
default 16:56:35.744699 +0200 usernoted ApplePushService:
<APSCConnection: 0x7fbae4e123f0> Delivering connectionStatusChange from apsd:
YES
default 16:56:35.744521 +0200 apsd Dispatching low priority message:
<OS_xpc_dictionary: <dictionary: 0x7ff112202db0> { count = 2, transaction: 0,
voucher = 0x0, contents =
    "isConnected" => <bool: 0x7ffdd7a6aa8>: true
    "message-type" => <int64: 0x7ff112200580>: 26
}>
default 16:56:35.744685 +0200 imagent ApplePushService:
<APSCConnection: 0x7f8ad280bc80> Delivering connectionStatusChange from apsd:
YES
default 16:56:35.744670 +0200 identityservicesd ApplePushService:
<APSCConnection: 0x7fb5b661b120> seeing if delegate <FTMessageDelivery_APS:

```

```

0x7fb5b661a9b0> responds to status changes
default 16:56:35.744695 +0200 cloudd ApplePushService:
<APSCConnection: 0x7ff288100ee0> seeing if delegate <CKDPushConnection:
0x7ff286400500> responds to status changes
default 16:56:35.744776 +0200 usernoted ApplePushService:
<APSCConnection: 0x7fbae4e123f0>: Re-requesting up-to-date per-app tokens
default 16:56:35.744563 +0200 apsd Dispatching low priority message:
<OS_xpc_dictionary: <dictionary: 0x7ff112202db0> { count = 2, transaction: 0,
voucher = 0x0, contents =
    "isConnected" => <bool: 0x7ffdd7a6aa8>: true
    "message-type" => <int64: 0x7ff112200580>: 26
}>
default 16:56:35.744764 +0200 imagent ApplePushService:
<APSCConnection: 0x7f8ad2a0eef0> seeing if delegate <IDSPushHandler:
0x7f8ad2a0e720> responds to status changes
default 16:56:35.744706 +0200 identityservicesd ApplePushService:
<APSCConnection: 0x7fb5b661b120> calling <FTMessageDelivery_APS:
0x7fb5b661a9b0> didChangeConnectedStatus:
default 16:56:35.744732 +0200 cloudd ApplePushService:
<APSCConnection: 0x7ff288100ee0> calling <CKDPushConnection:
0x7ff286400500> didChangeConnectedStatus:
default 16:56:35.744826 +0200 usernoted ApplePushService:
<APSCConnection: 0x7fbae4e123f0>: Sending request for per-app token for topic
com.apple.icloud-container.com.apple.Notes with identifier
default 16:56:35.744604 +0200 apsd Dispatching low priority message:
<OS_xpc_dictionary: <dictionary: 0x7ff112202db0> { count = 2, transaction: 0,
voucher = 0x0, contents =
    "isConnected" => <bool: 0x7ffdd7a6aa8>: true
    "message-type" => <int64: 0x7ff112200580>: 26
}>
default 16:56:35.745199 +0200 CalendarAgent ApplePushService:
<APSCConnection: 0x7f940e018250> Delivering connectionStatusChange from apsd:
YES
default 16:56:35.745204 +0200 cloudphotosd ApplePushService:
<APSCConnection: 0x7ffb15c1d390> Delivering connectionStatusChange from apsd:
YES
default 16:56:35.744821 +0200 imagent ApplePushService:
<APSCConnection: 0x7f8ad2a0eef0> calling <IDSPushHandler: 0x7f8ad2a0e720>
didChangeConnectedStatus:
default 16:56:35.744739 +0200 identityservicesd ApplePushService:
<APSCConnection: 0x7fb5b661b120> returned from <FTMessageDelivery_APS:
0x7fb5b661a9b0> didChangeConnectedStatus:
default 16:56:35.744646 +0200 apsd Dispatching low priority message:
<OS_xpc_dictionary: <dictionary: 0x7ff112202db0> { count = 2, transaction: 0,
voucher = 0x0, contents =
    "isConnected" => <bool: 0x7ffdd7a6aa8>: true
    "message-type" => <int64: 0x7ff112200580>: 26
}>
default 16:56:35.745394 +0200 mapspushd ApplePushService:
<APSCConnection: 0x7ff613402350> Delivering connectionStatusChange from apsd:

```

YES

default 16:56:35.745422 +0200 AddressBookSourceSync ApplePushService:
<APSCConnection: 0x7fb66fc14ea0> Delivering connectionStatusChange from apsd:
YES

default 16:56:35.744851 +0200 imagent APS Connection status did change
to connected: YES

default 16:56:35.744910 +0200 cloudd ApplePushService:
<APSCConnection: 0x7ff288100ee0> returned from <CKDPushConnection:
0x7ff286400500> didChangeConnectedStatus:

default 16:56:35.744853 +0200 identityservicesd ApplePushService:
<APSCConnection: 0x7fb5b650b5c0> Delivering connectionStatusChange from apsd:
YES

default 16:56:35.744695 +0200 apsd Dispatching low priority message:
<OS_xpc_dictionary: <dictionary: 0x7ff112202db0> { count = 2, transaction: 0,
voucher = 0x0, contents =

"isConnected" => <bool: 0x7ffdd7a6aa8>: true

"message-type" => <int64: 0x7ff112200580>: 26

default 16:56:35.744895 +0200 imagent ApplePushService:
<APSCConnection: 0x7f8ad2a0eef0> returned from <IDSPushHandler:
0x7f8ad2a0e720> didChangeConnectedStatus:

default 16:56:35.744923 +0200 identityservicesd ApplePushService:
<APSCConnection: 0x7fb5b650b5c0> seeing if delegate <FTMessageDelivery_APS:
0x7fb5b650b2f0> responds to status changes

default 16:56:35.744942 +0200 apsd <APSCConnectionServer:
0x7ff10fe3ee70>: Received per-app token request for topic com.apple.icloud-
container.com.apple.Notes with identifier

default 16:56:35.744935 +0200 imagent ApplePushService:
<APSCConnection: 0x7f8ad280bc80> seeing if delegate <FTMessageDelivery_APS:
0x7f8ad280b150> responds to status changes

default 16:56:35.744960 +0200 identityservicesd ApplePushService:
<APSCConnection: 0x7fb5b650b5c0> calling <FTMessageDelivery_APS:
0x7fb5b650b2f0> didChangeConnectedStatus:

default 16:56:35.744985 +0200 apsd <APSCConnectionServer:
0x7ff10fe3ee70>: Missing per-app token, requesting for user 501 darkWakeEnabled
with topic = com.apple.icloud-container.com.apple.Notes and identifier =

default 16:56:35.744972 +0200 imagent ApplePushService:
<APSCConnection: 0x7f8ad280bc80> calling <FTMessageDelivery_APS:
0x7f8ad280b150> didChangeConnectedStatus:

default 16:56:35.744997 +0200 identityservicesd ApplePushService:
<APSCConnection: 0x7fb5b650b5c0> returned from <FTMessageDelivery_APS:
0x7fb5b650b2f0> didChangeConnectedStatus:

default 16:56:35.745018 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff10fe3ee70> to generate token
for topic "com.apple.icloud-container.com.apple.Notes" and identifier ""

default 16:56:35.745007 +0200 imagent ApplePushService:
<APSCConnection: 0x7f8ad280bc80> returned from <FTMessageDelivery_APS:
0x7f8ad280b150> didChangeConnectedStatus:

default 16:56:35.745315 +0200 apsd Failed to talk to secd after 4 attempts.

default 16:56:35.745530 +0200 apsd <APSCourier: 0x7ff1122051b0>:

Received request to generate token for topic "com.apple.icloud-container.com.apple.Notes" and identifier "", assigned appld "0"

default 16:56:35.745559 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-container.com.apple.Notes" and identifier ""

default 16:56:35.848482 +0200 AddressBookSourceSync 0x7fb66fc23620
opened /var/folders/j8/bbhn9g892k14cv1xw2hp2fy80000gn/C//mds/mdsObject.db:
4636 bytes

default 16:56:35.848785 +0200 AddressBookSourceSync 0x7fb671865750
opened /var/folders/j8/bbhn9g892k14cv1xw2hp2fy80000gn/C//mds/mdsDirectory.db:
50744 bytes

default 16:56:35.850156 +0200 AddressBookSourceSync 0x7fb67188cc60
opened /var/folders/j8/bbhn9g892k14cv1xw2hp2fy80000gn/C//mds/mdsDirectory.db:
50744 bytes

default 16:56:35.851490 +0200 AddressBookSourceSync 0x7fb671868630
opened /Users/craigdenham/Library/Keychains/login.keychain-db: 218248 bytes

default 16:56:35.854108 +0200 AddressBookSourceSync 0x7fb671b45050
opened /Library/Keychains/System.keychain: 37732 bytes

default 16:56:35.856885 +0200 AddressBookSourceSync TIC TCP Conn Start
[1:0x7fb671b52600]

default 16:56:35.857159 +0200 AddressBookSourceSync TIC TCP Conn Start
[2:0x7fb66fc2c130]

default 16:56:35.895888 +0200 com.apple.WebKit.Networking
0x110cce800 - NetworkResourceLoader::didReceiveResponse: (pageID = 7,
frameID = 1, resourceID = 34, httpStatusCode = 204, length = -1)

default 16:56:35.895927 +0200 com.apple.WebKit.Networking
0x110cce800 - NetworkResourceLoader::didReceiveResponse: Should not wait
for message from WebContent process before continuing resource load (pageID = 7,
frameID = 1, resourceID = 34)

default 16:56:35.895997 +0200 com.apple.WebKit.Networking
0x110cce800 - NetworkResourceLoader::didFinishLoading: (pageID = 7,
frameID = 1, resourceID = 34)

default 16:56:35.896058 +0200 com.apple.WebKit.WebContent
0x114fb5310 - WebResourceLoader::didReceiveResponse: (pageID = 7,
frameID = 1, resourceID = 34, status = 204)

default 16:56:35.896128 +0200 com.apple.WebKit.WebContent
0x114fb5310 - WebResourceLoader::didFinishResourceLoad: (pageID = 7,
frameID = 1, resourceID = 34)

default 16:56:35.897074 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Outstanding data received: <12000000 3e010001 00020020 8cdbc09e bbc1a4fa
f3d687ec 75c398b0 c2f35cce 65432c19 03f7f75b 925f867a 0300148c c62e5c10
6b0d3196 d29588eb 8ae398c1 3f6d3c> (length 67)

default 16:56:35.897149 +0200 apsd <APSCourier: 0x7ff1122051b0>: Stream
processing: complete yes, invalid no, length parsed 67, parameters {
APSPProtocolAppTokenGenerateResponseCode = 0;
APSPProtocolAppTokenGenerateResponseToken = <8cdbc09e bbc1a4fa f3d687ec
75c398b0 c2f35cce 65432c19 03f7f75b 925f867a>;
APSPProtocolAppTokenGenerateResponseTopicHash = <8cc62e5c 106b0d31
96d29588 eb8ae398 c13f6d3c>;
APSPProtocolCommand = 18;

```

}
default 16:56:35.897201 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received app token generate response {
    APSProtocolAppTokenGenerateResponseCode = 0;
    APSProtocolAppTokenGenerateResponseToken = <8cdbd09e bbc1a4fa f3d687ec
75c398b0 c2f35cce 65432c19 03f7f75b 925f867a>;
    APSProtocolAppTokenGenerateResponseTopicHash = <8cc62e5c 106b0d31
96d29588 eb8ae398 c13f6d3c>;
    APSProtocolCommand = 18;
}
default 16:56:35.897239 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received response for token request for topic com.apple.icloud-
container.com.apple.Notes, appld 0, new token = <8cdbd09e bbc1a4fa f3d687ec
75c398b0 c2f35cce 65432c19 03f7f75b 925f867a>
default 16:56:35.897315 +0200 apsd <APSCConnectionServer:
0x7ff10fe3ee70>: Received token <8cdbd09e bbc1a4fa f3d687ec 75c398b0
c2f35cce 65432c19 03f7f75b 925f867a> for topic com.apple.icloud-
container.com.apple.Notes with identifier
default 16:56:35.897380 +0200 apsd <APSCConnectionServer:
0x7ff10fe3ee70>: Sending token <8cdbd09e bbc1a4fa f3d687ec 75c398b0 c2f35cce
65432c19 03f7f75b 925f867a> for topic com.apple.icloud-container.com.apple.Notes
with identifier
default 16:56:35.897430 +0200 apsd <APSCourier: 0x7ff1122051b0>: Stream
processing: complete no, invalid no, length parsed 0, parameters (null)
default 16:56:35.897496 +0200 apsd Dispatching low priority message:
<OS_xpc_dictionary: <dictionary: 0x7ff10fd30290> { count = 4, transaction: 0,
voucher = 0x0, contents =
    "identifier" => <string: 0x7ff10fd32eb0> { length = 0, contents = "" }
    "token" => <data: 0x7ff10fd2f500>: { length = 32 bytes, contents =
0x8cdbd09ebbc1a4faf3d687ec75c398b0c2f35cce65432c19... }
    "topic" => <string: 0x7ff10fd31940> { length = 42, contents = "com.apple.icloud-
container.com.apple.Notes" }
    "message-type" => <int64: 0x7ff10fd33330>: 30
}>
default 16:56:35.897642 +0200 usernoted ApplePushService:
<APSCConnection: 0x7fbae4e123f0> Received token <8cdbd09e bbc1a4fa f3d687ec
75c398b0 c2f35cce 65432c19 03f7f75b 925f867a> forTopic com.apple.icloud-
container.com.apple.Notes identifier
default 16:56:35.897693 +0200 usernoted ApplePushService:
<APSCConnection: 0x7fbae4e123f0> calling
<_TtCC9usernoted26PushNotificationConnection12PushDelegate:
0x7fbae4d15270> for received token <8cdbd09e bbc1a4fa f3d687ec 75c398b0
c2f35cce 65432c19 03f7f75b 925f867a> for topic com.apple.icloud-
container.com.apple.Notes identifier
default 16:56:35.897725 +0200 usernoted ApplePushService:
<APSCConnection: 0x7fbae4e123f0> returned from
<_TtCC9usernoted26PushNotificationConnection12PushDelegate:
0x7fbae4d15270> didReceiveToken:forTopic:identifier
default 16:56:35.909265 +0200 mds directQueryFetchResultsReply 53251
1795162112 35

```

default 16:56:35.918046 +0200 AddressBookSourceSync TIC TCP Conn
Event [2:0x7fb66fc2c130]: 1 Err(0)

default 16:56:35.918085 +0200 AddressBookSourceSync TIC TCP Conn
Connected [2:0x7fb66fc2c130]: Err(0)

default 16:56:35.918199 +0200 AddressBookSourceSync TIC Enabling TLS
[2:0x7fb66fc2c130]

default 16:56:35.942465 +0200 AddressBookSourceSync TIC TLS Event
[2:0x7fb66fc2c130]: 2, Pending(0)

default 16:56:35.945317 +0200 AddressBookSourceSync TIC TLS Event
[2:0x7fb66fc2c130]: 11, Pending(0)

default 16:56:35.945773 +0200 AddressBookSourceSync TIC TLS Event
[2:0x7fb66fc2c130]: 12, Pending(0)

default 16:56:35.945799 +0200 AddressBookSourceSync TIC TLS Event
[2:0x7fb66fc2c130]: 14, Pending(0)

default 16:56:35.946080 +0200 AddressBookSourceSync -[CDXAccount
handleAuthenticateAgainstProtectionSpace:withConnection:]:<private>
withConnection:<private>

default 16:56:35.946110 +0200 AddressBookSourceSync Using cached
_acAccount <private>

default 16:56:35.946210 +0200 AddressBookSourceSync -[CDXAccount
handleAuthenticateAgainstProtectionSpace:withConnection:] <private> was already
tried 0x

default 16:56:35.946316 +0200 AddressBookSourceSync -[CDXAccount
shouldRetryKerberosAuthWithConnection:]:<private>

default 16:56:35.946405 +0200 AddressBookSourceSync -[CDXAccount
shouldRetryKerberosAuthWithConnection:]:<private> returning NO because last
auth was not NSURLAuthenticationMethodNegotiate

default 16:56:35.946572 +0200 AddressBookSourceSync -[CDXAccount
handleTrustChallenge:withConnection:]:<private> withConnection:<private>

default 16:56:35.946598 +0200 AddressBookSourceSync -[CDXAccount
shouldRetryKerberosAuthWithConnection:]:<private>

default 16:56:35.946657 +0200 AddressBookSourceSync -[CDXAccount
shouldRetryKerberosAuthWithConnection:]:<private> returning NO because last
auth was not NSURLAuthenticationMethodNegotiate

default 16:56:35.946740 +0200 AddressBookSourceSync -[CDXAccount
recordAuthMethod:withConnection:]:<private> withConnection:<private>

default 16:56:35.946878 +0200 AddressBookSourceSync -[CDXAccount
recordAuthMethod:withConnection:]:_authMethodsTried <private>

default 16:56:35.957362 +0200 AddressBookSourceSync TIC TLS Trust
Result [2:0x7fb66fc2c130]: 0

default 16:56:35.963043 +0200 AddressBookSourceSync CFNetwork-AOSKit:
Reaching out to AOSKit for X-mobile me token

default 16:56:35.966650 +0200 trustd cert[2]: AnchorTrusted =(leaf)[force]>
0

default 16:56:35.967547 +0200 com.apple.iCloudHelper AOSKit INFO:
(com.apple.AddressBookSourceSync/10.0) ACCT LOOKUP: Previously performed
ACAccount lookup for user=beyondsemble@gmail.com (nothing found)

default 16:56:36.036806 +0200 com.apple.WebKit.WebContent
0x1085f5000 - WebLoaderStrategy::scheduleLoad: Resource has been queued
for scheduling with the NetworkProcess (frame = 0x115d8f380, priority = 2, pageID =

3, frameID = 14, resourceID = 360, WebResourceLoader = 0x11425ea48)
default 16:56:36.036932 +0200 com.apple.WebKit.Networking
0x110c88000 - NetworkResourceLoader::start: Retrieving resource from cache
(pageID = 3, frameID = 14, resourceID = 360, isMainResource = 0, isSynchronous = 0)
default 16:56:36.036973 +0200 com.apple.WebKit.Networking
0x110c88000 - NetworkResourceLoader::startNetworkLoad: (pageID = 3, frameID = 14, resourceID = 360, isMainResource = 0, isSynchronous = 0)
default 16:56:36.052356 +0200 com.apple.iCloudHelper 0x7f91572273c0
opened /var/folders/j8/bbhn9g892k14cv1xw2hp2fy80000gn/C//mds/mdsObject.db: 4636 bytes
default 16:56:36.052677 +0200 com.apple.iCloudHelper 0x7f9154d22b60
opened /var/folders/j8/bbhn9g892k14cv1xw2hp2fy80000gn/C//mds/mdsDirectory.db: 50744 bytes
default 16:56:36.052866 +0200 com.apple.iCloudHelper 0x7f9154d39d90
opened /Users/craigdenham/Library/Keychains/login.keychain-db: 218248 bytes
default 16:56:36.055411 +0200 com.apple.iCloudHelper AOSKit INFO:
(com.apple.AddressBookSourceSync/10.0) ACCT LOOKUP: No stored info found for user=beyondsemble@gmail.com (acct=0x5720bf60)
default 16:56:36.055692 +0200 AddressBookSourceSync CFNetwork-AOSKit:
Failed to get a X-mobile me token from AOSKit
default 16:56:36.069861 +0200 AddressBookSourceSync TIC TCP Conn
Event [1:0x7fb671b52600]: 1 Err(0)
default 16:56:36.069888 +0200 AddressBookSourceSync TIC TCP Conn
Connected [1:0x7fb671b52600]: Err(0)
default 16:56:36.069991 +0200 AddressBookSourceSync TIC Enabling TLS
[1:0x7fb671b52600]
default 16:56:36.074366 +0200 com.apple.WebKit.WebContent
0x1085f5000 - WebLoaderStrategy::scheduleLoad: Resource has been queued
for scheduling with the NetworkProcess (frame = 0x11563b380, priority = 2, pageID = 3, frameID = 16, resourceID = 361, WebResourceLoader = 0x10a58cfc0)
default 16:56:36.074486 +0200 com.apple.WebKit.Networking
0x110c88400 - NetworkResourceLoader::start: Retrieving resource from cache
(pageID = 3, frameID = 16, resourceID = 361, isMainResource = 0, isSynchronous = 0)
default 16:56:36.074518 +0200 com.apple.WebKit.Networking
0x110c88400 - NetworkResourceLoader::startNetworkLoad: (pageID = 3, frameID = 16, resourceID = 361, isMainResource = 0, isSynchronous = 0)
default 16:56:36.101942 +0200 AddressBookSourceSync TIC TLS Event
[2:0x7fb66fc2c130]: 20, Pending(0)
default 16:56:36.102248 +0200 AddressBookSourceSync TIC TCP Conn
Event [2:0x7fb66fc2c130]: 8 Err(0)
default 16:56:36.102276 +0200 AddressBookSourceSync TIC TLS Handshake
Complete [2:0x7fb66fc2c130]
default 16:56:36.102445 +0200 AddressBookSourceSync CFNetwork-AOSKit:
Reaching out to AOSKit for X-mobile me token
default 16:56:36.104411 +0200 trustd cert[2]: AnchorTrusted =(leaf)[force]>
0
default 16:56:36.105260 +0200 com.apple.iCloudHelper AOSKit INFO:
(com.apple.AddressBookSourceSync/10.0) ACCT LOOKUP: Previously performed

AAccount lookup for user=beyondsemble@gmail.com (nothing found)
 default 16:56:36.105465 +0200 com.apple.iCloudHelper AOSKit INFO:
 (com.apple.AddressBookSourceSync/10.0) ACCT LOOKUP: No stored info found for
 user=beyondsemble@gmail.com (acct=0x5720c860)
 default 16:56:36.105684 +0200 AddressBookSourceSync CFNetwork-AOSKit:
 Failed to get a X-mobile me token from AOSKit
 default 16:56:36.124617 +0200 AddressBookSourceSync TIC TLS Event
 [1:0x7fb671b52600]: 2, Pending(0)
 default 16:56:36.126610 +0200 AddressBookSourceSync TIC TLS Event
 [1:0x7fb671b52600]: 11, Pending(0)
 default 16:56:36.126918 +0200 AddressBookSourceSync TIC TLS Event
 [1:0x7fb671b52600]: 12, Pending(0)
 default 16:56:36.126940 +0200 AddressBookSourceSync TIC TLS Event
 [1:0x7fb671b52600]: 14, Pending(0)
 default 16:56:36.127185 +0200 AddressBookSourceSync -[CDXAccount
 handleAuthenticateAgainstProtectionSpace:withConnection:]:<private>
 withConnection:<private>
 default 16:56:36.127245 +0200 AddressBookSourceSync Using cached
 _acAccount <private>
 default 16:56:36.127302 +0200 AddressBookSourceSync -[CDXAccount
 handleAuthenticateAgainstProtectionSpace:withConnection:] <private> was already
 tried 0x
 default 16:56:36.127333 +0200 AddressBookSourceSync -[CDXAccount
 shouldRetryKerberosAuthWithConnection:]:<private>
 default 16:56:36.127427 +0200 AddressBookSourceSync -[CDXAccount
 shouldRetryKerberosAuthWithConnection:]:<private> returning NO because last
 auth was not NSURLAuthenticationMethodNegotiate
 default 16:56:36.127591 +0200 AddressBookSourceSync -[CDXAccount
 handleTrustChallenge:withConnection:]:<private> withConnection:<private>
 default 16:56:36.127618 +0200 AddressBookSourceSync -[CDXAccount
 shouldRetryKerberosAuthWithConnection:]:<private>
 default 16:56:36.127672 +0200 AddressBookSourceSync -[CDXAccount
 shouldRetryKerberosAuthWithConnection:]:<private> returning NO because last
 auth was not NSURLAuthenticationMethodNegotiate
 default 16:56:36.127759 +0200 AddressBookSourceSync -[CDXAccount
 recordAuthMethod:withConnection:]:<private> withConnection:<private>
 default 16:56:36.127828 +0200 AddressBookSourceSync -[CDXAccount
 recordAuthMethod:withConnection:]:_authMethodsTried <private>
 default 16:56:36.127996 +0200 AddressBookSourceSync CFNetwork-AOSKit:
 Reaching out to AOSKit for X-mobile me token
 default 16:56:36.130214 +0200 trustd cert[2]: AnchorTrusted =(leaf)[force]>
 0
 default 16:56:36.130698 +0200 AddressBookSourceSync TIC TLS Trust
 Result [1:0x7fb671b52600]: 0
 default 16:56:36.132035 +0200 AddressBookSourceSync CFNetwork-AOSKit:
 Applied X-mobile me auth to request
 default 16:56:36.140235 +0200 com.apple.WebKit.Networking
 0x110c88000 - NetworkResourceLoader::didReceiveResponse: (pageID = 3,
 frameID = 14, resourceID = 360, httpStatusCode = 200, length = 17)
 default 16:56:36.140272 +0200 com.apple.WebKit.Networking

0x110c88000 - NetworkResourceLoader::didReceiveResponse: Should not wait for message from WebContent process before continuing resource load (pageID = 3, frameID = 14, resourceID = 360)
default 16:56:36.140350 +0200 com.apple.WebKit.WebContent
0x11425ea48 - WebResourceLoader::didReceiveResponse: (pageID = 3, frameID = 14, resourceID = 360, status = 200)
default 16:56:36.140344 +0200 com.apple.WebKit.Networking
0x110c88000 - NetworkResourceLoader::didReceiveBuffer: Started receiving data (pageID = 3, frameID = 14, resourceID = 360)
default 16:56:36.140404 +0200 com.apple.WebKit.Networking
0x110c88000 - NetworkResourceLoader::didFinishLoading: (pageID = 3, frameID = 14, resourceID = 360)
default 16:56:36.140508 +0200 com.apple.WebKit.WebContent
0x11425ea48 - WebResourceLoader::didReceiveData: Started receiving data (pageID = 3, frameID = 14, resourceID = 360)
default 16:56:36.140547 +0200 com.apple.WebKit.WebContent
0x11425ea48 - WebResourceLoader::didFinishResourceLoad: (pageID = 3, frameID = 14, resourceID = 360)
default 16:56:36.150386 +0200 com.apple.WebKit.Networking
0x110c88400 - NetworkResourceLoader::didReceiveResponse: (pageID = 3, frameID = 16, resourceID = 361, httpStatusCode = 200, length = 16)
default 16:56:36.150426 +0200 com.apple.WebKit.Networking
0x110c88400 - NetworkResourceLoader::didReceiveResponse: Should not wait for message from WebContent process before continuing resource load (pageID = 3, frameID = 16, resourceID = 361)
default 16:56:36.150509 +0200 com.apple.WebKit.WebContent
0x10a58cfc0 - WebResourceLoader::didReceiveResponse: (pageID = 3, frameID = 16, resourceID = 361, status = 200)
default 16:56:36.150481 +0200 com.apple.WebKit.Networking
0x110c88400 - NetworkResourceLoader::didReceiveBuffer: Started receiving data (pageID = 3, frameID = 16, resourceID = 361)
default 16:56:36.150620 +0200 com.apple.WebKit.WebContent
0x10a58cfc0 - WebResourceLoader::didReceiveData: Started receiving data (pageID = 3, frameID = 16, resourceID = 361)
default 16:56:36.150536 +0200 com.apple.WebKit.Networking
0x110c88400 - NetworkResourceLoader::didFinishLoading: (pageID = 3, frameID = 16, resourceID = 361)
default 16:56:36.150654 +0200 com.apple.WebKit.WebContent
0x10a58cfc0 - WebResourceLoader::didFinishResourceLoad: (pageID = 3, frameID = 16, resourceID = 361)
default 16:56:36.169724 +0200 AddressBookSourceSync TIC TLS Event [1:0x7fb671b52600]: 20, Pending(0)
default 16:56:36.169997 +0200 AddressBookSourceSync TIC TCP Conn Event [1:0x7fb671b52600]: 8 Err(0)
default 16:56:36.170021 +0200 AddressBookSourceSync TIC TLS Handshake Complete [1:0x7fb671b52600]
default 16:56:36.170112 +0200 AddressBookSourceSync CFNetwork-AOSKit: Reaching out to AOSKit for X-mobile me token
default 16:56:36.170183 +0200 AddressBookSourceSync CFNetwork-AOSKit: Applied X-mobile me auth to request

```

default    16:56:36.211331 +0200    com.apple.WebKit.Networking
           TIC TCP Conn Event [28:0x7fa64691b080]: 2 Err(0)
default    16:56:36.211359 +0200    com.apple.WebKit.Networking
           TIC TCP Conn Cancel [28:0x7fa64691b080]
default    16:56:36.211382 +0200    com.apple.WebKit.Networking
           TIC TCP Conn Destroyed [28:0x7fa64691b080]
default    16:56:36.216521 +0200    com.apple.WebKit.Networking
           TIC TCP Conn Event [45:0x7fa644d628a0]: 2 Err(0)
default    16:56:36.216544 +0200    com.apple.WebKit.Networking
           TIC TCP Conn Cancel [45:0x7fa644d628a0]
default    16:56:36.216572 +0200    com.apple.WebKit.Networking
           TIC TCP Conn Destroyed [45:0x7fa644d628a0]
default    16:56:36.231007 +0200    com.apple.WebKit.Networking
           TIC TCP Conn Event [30:0x7fa644d459b0]: 2 Err(0)
default    16:56:36.231039 +0200    com.apple.WebKit.Networking
           TIC TCP Conn Cancel [30:0x7fa644d459b0]
default    16:56:36.231104 +0200    com.apple.WebKit.Networking
           TIC TCP Conn Destroyed [30:0x7fa644d459b0]
default    16:56:36.231539 +0200    AddressBookSourceSync -
getPrincipallInfo:_controller.account.compressRequests == NO
default    16:56:36.231576 +0200    AddressBookSourceSync -getPrincipallInfo:
[_controller principalPropertiesAtURL:<private>]
default    16:56:36.231611 +0200    AddressBookSourceSync -[CDXAccount
clearAuthMethodsTried]
default    16:56:36.231872 +0200    AddressBookSourceSync Using cached
_acAccount <private>
default    16:56:36.232121 +0200    AddressBookSourceSync Using cached
_acAccount <private>
default    16:56:36.232173 +0200    AddressBookSourceSync Using cached
_acAccount <private>
default    16:56:36.232230 +0200    AddressBookSourceSync _acAccountIdentifier
= <private>
default    16:56:36.232246 +0200    AddressBookSourceSync Using account with
identifier <private>
default    16:56:36.232302 +0200    AddressBookSourceSync Using cached
_acAccount <private>
default    16:56:36.232353 +0200    AddressBookSourceSync We are a the child of
a Gmail account; deferring to parent
default    16:56:36.232410 +0200    AddressBookSourceSync -
acAccountOrParentGoogleAccount: <private>
default    16:56:36.232465 +0200    AddressBookSourceSync -[CDXAccount
oauth2Token]: Returning oauth token <private> for identifier: <private>
default    16:56:36.232962 +0200    AddressBookSourceSync CFNetwork-AOSKit:
Reaching out to AOSKit for X-mobile me token
default    16:56:36.233873 +0200    com.apple.WebKit.Networking
           TIC TCP Conn Event [31:0x7fa646837180]: 2 Err(0)
default    16:56:36.233908 +0200    com.apple.WebKit.Networking
           TIC TCP Conn Cancel [31:0x7fa646837180]
default    16:56:36.233964 +0200    com.apple.WebKit.Networking
           TIC TCP Conn Destroyed [31:0x7fa646837180]

```

```

default    16:56:36.234204 +0200    com.apple.WebKit.Networking
           TIC TCP Conn Event [33:0x7fa644f73c30]: 2 Err(0)
default    16:56:36.234228 +0200    com.apple.WebKit.Networking
           TIC TCP Conn Cancel [33:0x7fa644f73c30]
default    16:56:36.234258 +0200    com.apple.WebKit.Networking
           TIC TCP Conn Destroyed [33:0x7fa644f73c30]
default    16:56:36.235585 +0200    trustd      cert[2]: AnchorTrusted =(leaf)[force]>
0
default    16:56:36.235642 +0200    com.apple.WebKit.Networking
           TIC TCP Conn Event [32:0x7fa646a2c9e0]: 2 Err(0)
default    16:56:36.235669 +0200    com.apple.WebKit.Networking
           TIC TCP Conn Cancel [32:0x7fa646a2c9e0]
default    16:56:36.235709 +0200    com.apple.WebKit.Networking
           TIC TCP Conn Destroyed [32:0x7fa646a2c9e0]
default    16:56:36.236556 +0200    com.apple.iCloudHelper  AOSKit INFO:
(com.apple.AddressBookSourceSync/10.0) ACCT LOOKUP: Previously performed
ACAccount lookup for user=beyondsemble@gmail.com (nothing found)
default    16:56:36.236731 +0200    com.apple.iCloudHelper  AOSKit INFO:
(com.apple.AddressBookSourceSync/10.0) ACCT LOOKUP: No stored info found for
user=beyondsemble@gmail.com (acct=0x54f2fb50)
default    16:56:36.236912 +0200    AddressBookSourceSync CFNetwork-AOSKit:
Failed to get a X-mobile me token from AOSKit
default    16:56:36.242529 +0200    com.apple.WebKit.WebContent
           0x1085f5000 - WebLoaderStrategy::scheduleLoad: Resource has been queued
for scheduling with the NetworkProcess (frame = 0x116545380, priority = 2, pageID
= 3, frameID = 17, resourceID = 362, WebResourceLoader = 0x10a5786c8)
default    16:56:36.242613 +0200    com.apple.WebKit.Networking
           0x110c4a000 - NetworkResourceLoader::start: Retrieving resource from cache
(pageID = 3, frameID = 17, resourceID = 362, isMainResource = 0, isSynchronous =
0)
default    16:56:36.242647 +0200    com.apple.WebKit.Networking
           0x110c4a000 - NetworkResourceLoader::startNetworkLoad: (pageID = 3,
frameID = 17, resourceID = 362, isMainResource = 0, isSynchronous = 0)
default    16:56:36.245475 +0200    com.apple.WebKit.Networking
           TIC TCP Conn Event [17:0x7fa644f13a60]: 2 Err(0)
default    16:56:36.245479 +0200    com.apple.WebKit.WebContent
           0x1085f5000 - WebLoaderStrategy::scheduleLoad: Resource has been queued
for scheduling with the NetworkProcess (frame = 0x11563b000, priority = 2, pageID
= 3, frameID = 15, resourceID = 363, WebResourceLoader = 0x10a578888)
default    16:56:36.245506 +0200    com.apple.WebKit.Networking
           TIC TCP Conn Cancel [17:0x7fa644f13a60]
default    16:56:36.245525 +0200    com.apple.WebKit.Networking
           0x110c4a400 - NetworkResourceLoader::start: Retrieving resource from cache
(pageID = 3, frameID = 15, resourceID = 363, isMainResource = 0, isSynchronous =
0)
default    16:56:36.245551 +0200    com.apple.WebKit.Networking
           TIC TCP Conn Destroyed [17:0x7fa644f13a60]
default    16:56:36.245562 +0200    com.apple.WebKit.Networking
           0x110c4a400 - NetworkResourceLoader::startNetworkLoad: (pageID = 3,
frameID = 15, resourceID = 363, isMainResource = 0, isSynchronous = 0)

```

```

default    16:56:36.247878 +0200    com.apple.WebKit.WebContent
           0x1085f5000 - WebLoaderStrategy::scheduleLoad: Resource has been queued
for scheduling with the NetworkProcess (frame = 0x1156ba380, priority = 2, pageID
= 3, frameID = 13, resourceID = 364, WebResourceLoader = 0x10a578a48)
default    16:56:36.247987 +0200    com.apple.WebKit.Networking
           0x110c4ac00 - NetworkResourceLoader::start: Retrieving resource from cache
(pageID = 3, frameID = 13, resourceID = 364, isMainResource = 0, isSynchronous =
0)
default    16:56:36.248024 +0200    com.apple.WebKit.Networking
           0x110c4ac00 - NetworkResourceLoader::startNetworkLoad: (pageID = 3,
frameID = 13, resourceID = 364, isMainResource = 0, isSynchronous = 0)
default    16:56:36.254216 +0200    com.apple.WebKit.Networking
           TIC TCP Conn Event [15:0x7fa644e0c150]: 2 Err(0)
default    16:56:36.254246 +0200    com.apple.WebKit.Networking
           TIC TCP Conn Cancel [15:0x7fa644e0c150]
default    16:56:36.254281 +0200    com.apple.WebKit.Networking
           TIC TCP Conn Destroyed [15:0x7fa644e0c150]
default    16:56:36.277953 +0200    apsd <APSCourier: 0x7ff1122051b0>:
Outstanding data received: <0e000000 23010020 30af8d61 9c2a0b23 7c9c12f8
ee5d2235 1ef69fec 62a75030 2a6642cd a67418a9> (length 40)
default    16:56:36.278003 +0200    apsd <APSCourier: 0x7ff1122051b0>: Stream
processing: complete yes, invalid no, length parsed 40, parameters {
    APSProtocolCommand = 14;
    APSProtocolDestination = <30af8d61 9c2a0b23 7c9c12f8 ee5d2235 1ef69fec
62a75030 2a6642cd a67418a9>;
}
default    16:56:36.278035 +0200    apsd <APSCourier: 0x7ff1122051b0>:
Received NoStorage message, users potentially with messages = 0, parameters = {
    APSProtocolCommand = 14;
    APSProtocolDestination = <30af8d61 9c2a0b23 7c9c12f8 ee5d2235 1ef69fec
62a75030 2a6642cd a67418a9>;
}
default    16:56:36.278133 +0200    apsd <APSCourier: 0x7ff1122051b0>: Stream
processing: complete no, invalid no, length parsed 0, parameters (null)
default    16:56:36.307790 +0200    com.apple.WebKit.Networking
           TIC TCP Conn Event [16:0x7fa646a20b20]: 2 Err(0)
default    16:56:36.307817 +0200    com.apple.WebKit.Networking
           TIC TCP Conn Cancel [16:0x7fa646a20b20]
default    16:56:36.307851 +0200    com.apple.WebKit.Networking
           TIC TCP Conn Destroyed [16:0x7fa646a20b20]
default    16:56:36.312774 +0200    AddressBookSourceSync -getHomeInfo:
[_controller containersAtURLs:<private>]
default    16:56:36.313045 +0200    AddressBookSourceSync -[CDXAccount
clearAuthMethodsTried]
default    16:56:36.313198 +0200    AddressBookSourceSync Using cached
_acAccount <private>
default    16:56:36.313463 +0200    AddressBookSourceSync Using cached
_acAccount <private>
default    16:56:36.313500 +0200    AddressBookSourceSync _acAccountIdentifier
= <private>

```

```

default    16:56:36.313530 +0200  AddressBookSourceSync Using account with
identifier <private>
default    16:56:36.313588 +0200  AddressBookSourceSync Using cached
_acAccount <private>
default    16:56:36.313628 +0200  AddressBookSourceSync We are a the child of
a Gmail account; deferring to parent
default    16:56:36.313665 +0200  AddressBookSourceSync -
acAccountOrParentGoogleAccount: <private>
default    16:56:36.313704 +0200  AddressBookSourceSync -[CDXAccount
oauth2Token]: Returning oauth token <private> for identifier: <private>
default    16:56:36.314170 +0200  AddressBookSourceSync CFNetwork-AOSKit:
Reaching out to AOSKit for X-mobile me token
default    16:56:36.316189 +0200  trustd      cert[2]: AnchorTrusted =(leaf)[force]>
0
default    16:56:36.317047 +0200  com.apple.iCloudHelper  AOSKit INFO:
(com.apple.AddressBookSourceSync/10.0) ACCT LOOKUP: Previously performed
ACAccount lookup for user=beyondsemble@gmail.com (nothing found)
default    16:56:36.317167 +0200  com.apple.iCloudHelper  AOSKit INFO:
(com.apple.AddressBookSourceSync/10.0) ACCT LOOKUP: No stored info found for
user=beyondsemble@gmail.com (acct=0x5720bf60)
default    16:56:36.317350 +0200  AddressBookSourceSync CFNetwork-AOSKit:
Failed to get a X-mobile me token from AOSKit
default    16:56:36.321236 +0200  com.apple.WebKit.Networking
0x110c4a000 - NetworkResourceLoader::didReceiveResponse: (pageID = 3,
frameID = 17, resourceID = 362, httpStatusCode = 200, length = 16)
default    16:56:36.321284 +0200  com.apple.WebKit.Networking
0x110c4a000 - NetworkResourceLoader::didReceiveResponse: Should not
wait for message from WebContent process before continuing resource load (pageID
= 3, frameID = 17, resourceID = 362)
default    16:56:36.321353 +0200  com.apple.WebKit.Networking
0x110c4a000 - NetworkResourceLoader::didReceiveBuffer: Started receiving
data (pageID = 3, frameID = 17, resourceID = 362)
default    16:56:36.321384 +0200  com.apple.WebKit.WebContent
0x10a5786c8 - WebResourceLoader::didReceiveResponse: (pageID = 3,
frameID = 17, resourceID = 362, status = 200)
default    16:56:36.321416 +0200  com.apple.WebKit.Networking
0x110c4a000 - NetworkResourceLoader::didFinishLoading: (pageID = 3,
frameID = 17, resourceID = 362)
default    16:56:36.321502 +0200  com.apple.WebKit.WebContent
0x10a5786c8 - WebResourceLoader::didReceiveData: Started receiving data
(pageID = 3, frameID = 17, resourceID = 362)
default    16:56:36.321539 +0200  com.apple.WebKit.WebContent
0x10a5786c8 - WebResourceLoader::didFinishResourceLoad: (pageID = 3,
frameID = 17, resourceID = 362)
default    16:56:36.330408 +0200  com.apple.WebKit.Networking
0x110c4a400 - NetworkResourceLoader::didReceiveResponse: (pageID = 3,
frameID = 15, resourceID = 363, httpStatusCode = 200, length = 16)
default    16:56:36.330441 +0200  com.apple.WebKit.Networking
0x110c4a400 - NetworkResourceLoader::didReceiveResponse: Should not
wait for message from WebContent process before continuing resource load (pageID

```

= 3, frameID = 15, resourceID = 363)
default 16:56:36.330514 +0200 com.apple.WebKit.Networking
0x110c4a400 - NetworkResourceLoader::didReceiveBuffer: Started receiving
data (pageID = 3, frameID = 15, resourceID = 363)
default 16:56:36.330547 +0200 com.apple.WebKit.WebContent
0x10a578888 - WebResourceLoader::didReceiveResponse: (pageID = 3,
frameID = 15, resourceID = 363, status = 200)
default 16:56:36.330578 +0200 com.apple.WebKit.Networking
0x110c4a400 - NetworkResourceLoader::didFinishLoading: (pageID = 3,
frameID = 15, resourceID = 363)
default 16:56:36.330650 +0200 com.apple.WebKit.WebContent
0x10a578888 - WebResourceLoader::didReceiveData: Started receiving data
(pageID = 3, frameID = 15, resourceID = 363)
default 16:56:36.330681 +0200 com.apple.WebKit.WebContent
0x10a578888 - WebResourceLoader::didFinishResourceLoad: (pageID = 3,
frameID = 15, resourceID = 363)
default 16:56:36.331477 +0200 apsd <APSCourier: 0x7ff10fe24350>: Finished
waiting for user 0 before recreating the courier state
default 16:56:36.331511 +0200 apsd <APSCourier: 0x7ff10fe24350>:
Recreating courier state for user 0
default 16:56:36.331619 +0200 apsd <<APSTokenState: 0x7ff10ff35f30>:
{ tokenName=0, status=disconnected, willConnect=no, willDisconnect=no,
systemUser=<APSSystemUser: 0x7ff1121070e0>, publicToken=(null),
sentFilterMessage=NO darkWakeEnabled=no, topicManager=0x7ff10ff35c60 }>:
Initializing token 0
default 16:56:36.331779 +0200 apsd <APSCourier: 0x7ff10fe24350>: Added
token state for token 0
default 16:56:36.331821 +0200 apsd <APSCourier: 0x7ff10fe24350>: Finished
waiting for user 0 darkWakeEnabled before recreating the courier state
default 16:56:36.331858 +0200 apsd <APSCourier: 0x7ff10fe24350>:
Recreating courier state for user 0 darkWakeEnabled
default 16:56:36.331895 +0200 apsd <APSCourier: 0x7ff10fe24350>: Finished
waiting for user 501 darkWakeEnabled before recreating the courier state
default 16:56:36.331943 +0200 apsd <APSCourier: 0x7ff10fe24350>:
Recreating courier state for user 501 darkWakeEnabled
default 16:56:36.332056 +0200 apsd <<APSTokenState: 0x7ff112013550>:
{ tokenName=501 darkWakeEnabled, status=disconnected, willConnect=no,
willDisconnect=no, systemUser=<APSSystemUser: 0x7ff10fe3d420>,
publicToken=(null), sentFilterMessage=NO darkWakeEnabled=yes,
topicManager=0x7ff112016220 }>: Initializing token 501 darkWakeEnabled
default 16:56:36.332190 +0200 apsd <APSCourier: 0x7ff10fe24350>: Added
token state for token 501 darkWakeEnabled
default 16:56:36.332227 +0200 apsd <APSCourier: 0x7ff10fe24350>: Finished
waiting for user 501 before recreating the courier state
default 16:56:36.332388 +0200 apsd <APSCourier: 0x7ff10fe24350>:
Recreating courier state for user 501
default 16:56:36.332417 +0200 apsd <APSCourier: 0x7ff10fe24350>: Adjusting
connection with courier connectable
default 16:56:36.332435 +0200 apsd <APSCourier: 0x7ff10fe24350>: Filter
changed

default 16:56:36.332530 +0200 apsd <APSDaemon: 0x7ff10fe14330>: Set active push connection state to YES

default 16:56:36.332554 +0200 apsd <APSTopicManager: 0x7ff10ff37fb0> asked to performFilterBlock

default 16:56:36.332678 +0200 apsd <APSCourier: 0x7ff10fe24350>: When filter is sent for user 501, users potentially with messages = 1

default 16:56:36.332730 +0200 apsd <APSCourier: 0x7ff10fe24350>: Sending filter message for user 501 with token <495e168a a5f94955 15e1eeb7 47a70c56 d379a155 23ddf84a 9c426003 1a278d35> with enabled topics = (com.apple.maspushagent), opportunistic topics = (), paused topics = (), ignored topics = ()

default 16:56:36.332803 +0200 apsd <APSCourier: 0x7ff10fe24350> _processStoredIncomingMessages: enabled = YES

default 16:56:36.332870 +0200 apsd <APSCourier: 0x7ff10fe24350> processing 0 stored incoming messages

default 16:56:36.332917 +0200 apsd <APSCourier: 0x7ff10fe24350> done with _processStoredIncomingMessages

default 16:56:36.332952 +0200 apsd APSMessageStore - APSIncomingMessageRecordDeleteMessagesOlderThanDate environment development 1 timeThreshold 514911396

default 16:56:36.332990 +0200 apsd <APSCourier: 0x7ff10fe24350> _processStoredOutgoingMessages - marking outgoing messages as unsent so they can be processed (we terminated before they were acknowledged).

default 16:56:36.333136 +0200 apsd <APSCourier: 0x7ff1122051b0>: Finished waiting for user 501 before recreating the courier state

default 16:56:36.333280 +0200 com.apple.WebKit.Networking
0x110c4ac00 - NetworkResourceLoader::didReceiveResponse: (pageID = 3, frameID = 13, resourceID = 364, httpStatusCode = 200, length = 16)

default 16:56:36.333304 +0200 apsd <APSCourier: 0x7ff1122051b0>: Recreating courier state for user 501

default 16:56:36.333336 +0200 com.apple.WebKit.Networking
0x110c4ac00 - NetworkResourceLoader::didReceiveResponse: Should not wait for message from WebContent process before continuing resource load (pageID = 3, frameID = 13, resourceID = 364)

default 16:56:36.333341 +0200 apsd <APSCourier: 0x7ff1122051b0>: Will connect user 501 because in full wake

default 16:56:36.333416 +0200 com.apple.WebKit.WebContent
0x10a578a48 - WebResourceLoader::didReceiveResponse: (pageID = 3, frameID = 13, resourceID = 364, status = 200)

default 16:56:36.333393 +0200 com.apple.WebKit.Networking
0x110c4ac00 - NetworkResourceLoader::didReceiveBuffer: Started receiving data (pageID = 3, frameID = 13, resourceID = 364)

default 16:56:36.333386 +0200 apsd <<APSTokenState: 0x7ff1123078f0>: { tokenName=501, status=disconnected, willConnect=no, willDisconnect=no, systemUser=<APSSystemUser: 0x7ff10fe3d420>, publicToken=<3768eb4f 4a2cd5a6 422899d6 f49f63a7 e85b9388 e80f29b1 17b6e894 2dd04dc3>, sentFilterMessage=NO darkWakeEnabled=no, topicManager=0x7ff112308730 }>: Status for user 501 is disconnected, but user will be connected

default 16:56:36.333537 +0200 com.apple.WebKit.WebContent
0x10a578a48 - WebResourceLoader::didReceiveData: Started receiving data

```

(pageID = 3, frameID = 13, resourceID = 364)
default 16:56:36.333457 +0200 com.apple.WebKit.Networking
0x110c4ac00 - NetworkResourceLoader::didFinishLoading: (pageID = 3,
frameID = 13, resourceID = 364)
default 16:56:36.333421 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Adjusting connection with courier connectable
default 16:56:36.333570 +0200 com.apple.WebKit.WebContent
0x10a578a48 - WebResourceLoader::didFinishResourceLoad: (pageID = 3,
frameID = 13, resourceID = 364)
default 16:56:36.333466 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Checking whether any users can be connected or disconnected
default 16:56:36.333526 +0200 apsd <<APSTokenState: 0x7ff1123078f0>:
{ tokenName=501, status=disconnected, willConnect=yes, willDisconnect=no,
systemUser=<APSSystemUser: 0x7ff10fe3d420>, publicToken=<3768eb4f
4a2cd5a6 422899d6 f49f63a7 e85b9388 e80f29b1 17b6e894 2dd04dc3>,
sentFilterMessage=NO darkWakeEnabled=no, topicManager=0x7ff112308730 }>:
Changing status for user 501 from disconnected to connecting
default 16:56:36.333571 +0200 apsd <APSCourier: 0x7ff1122051b0>: Sending
connect message for user 501 with token '<3768eb4f 4a2cd5a6 422899d6 f49f63a7
e85b9388 e80f29b1 17b6e894 2dd04dc3>\'
default 16:56:36.333751 +0200 apsd <APSCourier: 0x7ff1122051b0>: Filter
changed
default 16:56:36.333867 +0200 apsd <APSDaemon: 0x7ff10fe14330>: Set
active push connection state to YES
default 16:56:36.343113 +0200 filecoordinationd Presenter E89A1BEE-
BF55-490A-B675-C11FDE4E7A44 settling non-coordinated events
default 16:56:36.343361 +0200 TextEdit Making presenter E89A1BEE-
BF55-490A-B675-C11FDE4E7A44 observe change
default 16:56:36.353632 +0200 com.apple.WebKit.Networking
TIC TCP Conn Event [29:0x7fa646914320]: 2 Err(0)
default 16:56:36.353662 +0200 com.apple.WebKit.Networking
TIC TCP Conn Cancel [29:0x7fa646914320]
default 16:56:36.353727 +0200 com.apple.WebKit.Networking
TIC TCP Conn Destroyed [29:0x7fa646914320]
default 16:56:36.360142 +0200 com.apple.WebKit.Networking
TIC TCP Conn Event [22:0x7fa646a07ce0]: 2 Err(0)
default 16:56:36.360165 +0200 com.apple.WebKit.Networking
TIC TCP Conn Cancel [22:0x7fa646a07ce0]
default 16:56:36.360213 +0200 com.apple.WebKit.Networking
TIC TCP Conn Destroyed [22:0x7fa646a07ce0]
default 16:56:36.361366 +0200 AddressBookSourceSync -
getPrincipallInfo:_controller.account.compressRequests == YES
default 16:56:36.361392 +0200 AddressBookSourceSync -getPrincipallInfo:
[_controller principalPropertiesAtURL:<private>]
default 16:56:36.361424 +0200 AddressBookSourceSync -[CDXAccount
clearAuthMethodsTried]
default 16:56:36.361604 +0200 AddressBookSourceSync Using cached
_acAccount <private>
default 16:56:36.361879 +0200 AddressBookSourceSync Using cached
_acAccount <private>

```



```

default 16:56:36.361912 +0200 AddressBookSourceSync Using cached
_acAccount <private>
default 16:56:36.362346 +0200 AddressBookSourceSync CFNetwork-AOSKit:
Reaching out to AOSKit for X-mobile me token
default 16:56:36.362389 +0200 AddressBookSourceSync CFNetwork-AOSKit:
Applied X-mobile me auth to request
default 16:56:36.380176 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Outstanding data received: <08000000 25010001 00040002 14000500 02000306
00040000 00030800 023c000a 00080000 015c4542 5f36> (length 42)
default 16:56:36.380236 +0200 apsd <APSCourier: 0x7ff1122051b0>: Stream
processing: complete yes, invalid no, length parsed 42, parameters {
    APSProtocolCommand = 8;
    APSProtocolConnectedResponse = 0;
    APSProtocolDualChannelSupport = 1;
    APSProtocolLargeMessageSize = 15360;
    APSProtocolMessageSize = 5120;
    APSProtocolServerTime = 1495810596662;
}
default 16:56:36.380322 +0200 apsd <APSCourier: 0x7ff1122051b0>: Handling
connected message for user 501
default 16:56:36.380343 +0200 apsd Received connect message [production]
default 16:56:36.380361 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received connected response OK
default 16:56:36.380381 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received message size 5120
default 16:56:36.380407 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received large message size 15360
default 16:56:36.380437 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Connected user 501 to environment production
default 16:56:36.380486 +0200 apsd <<APSTokenState: 0x7ff1123078f0>:
{ tokenName=501, status=connecting, willConnect=no, willDisconnect=no,
systemUser=<APSSystemUser: 0x7ff10fe3d420>, publicToken=<3768eb4f
4a2cd5a6 422899d6 f49f63a7 e85b9388 e80f29b1 17b6e894 2dd04dc3>,
sentFilterMessage=NO darkWakeEnabled=no, topicManager=0x7ff112308730 }>:
Changing status for user 501 from connecting to connected
default 16:56:36.380543 +0200 apsd <APSDaemon: 0x7ff10fe14330> received
courierConnectionStatusDidChange from <APSCourier: 0x7ff1122051b0>.
isConnected? YES
default 16:56:36.380674 +0200 apsd <APSDaemon: 0x7ff10fe14330>: Set
active push connection state to YES
default 16:56:36.380740 +0200 apsd <APSCConnectionServer:
0x7ff10fd30340>: Missing per-app tokens, re-requesting for user 501
default 16:56:36.380783 +0200 apsd <APSCConnectionServer:
0x7ff10fd30340>: Missing per-app token, requesting for user 501 with topic =
com.apple.idmsauthagent and identifier =
default 16:56:36.380817 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff10fd30340> to generate token
for topic "com.apple.idmsauthagent" and identifier ""
default 16:56:36.381096 +0200 apsd Failed to talk to secd after 4 attempts.
default 16:56:36.381288 +0200 apsd <APSCourier: 0x7ff1122051b0>:

```

Received request to generate token for topic "com.apple.idmsauthagent" and identifier "", assigned appld "0"

default 16:56:36.381393 +0200 apsd <APSCConnectionServer: 0x7ff10fd23970>: Missing per-app tokens, re-requesting for user 501

default 16:56:36.381426 +0200 apsd <APSCConnectionServer: 0x7ff10fd23970>: Missing per-app token, requesting for user 501 with topic = com.apple.icloud-container.com.apple.Safari and identifier =

default 16:56:36.381450 +0200 apsd <APSCCourier: 0x7ff1122051b0>: Received request from <APSCConnectionServer: 0x7ff10fd23970> to generate token for topic "com.apple.icloud-container.com.apple.Safari" and identifier ""

default 16:56:36.381703 +0200 apsd Failed to talk to secld after 4 attempts.

default 16:56:36.381852 +0200 apsd <APSCCourier: 0x7ff1122051b0>: Received request to generate token for topic "com.apple.icloud-container.com.apple.Safari" and identifier "", assigned appld "0"

default 16:56:36.381876 +0200 apsd <APSCCourier: 0x7ff1122051b0>: Rescheduling request to generate token for topic "com.apple.icloud-container.com.apple.Safari" and identifier ""

default 16:56:36.381941 +0200 apsd <APSCConnectionServer: 0x7ff112223fd0>: Missing per-app tokens, re-requesting for user 501

default 16:56:36.381990 +0200 apsd <APSCConnectionServer: 0x7ff112223fd0>: Missing per-app token, requesting for user 501 with topic = com.apple.icloud-container.com.apple.keyboardservicesd and identifier =

default 16:56:36.382040 +0200 apsd <APSCCourier: 0x7ff1122051b0>: Received request from <APSCConnectionServer: 0x7ff112223fd0> to generate token for topic "com.apple.icloud-container.com.apple.keyboardservicesd" and identifier ""

default 16:56:36.382260 +0200 apsd Failed to talk to secld after 4 attempts.

default 16:56:36.382395 +0200 apsd <APSCCourier: 0x7ff1122051b0>: Received request to generate token for topic "com.apple.icloud-container.com.apple.keyboardservicesd" and identifier "", assigned appld "0"

default 16:56:36.382421 +0200 apsd <APSCCourier: 0x7ff1122051b0>: Rescheduling request to generate token for topic "com.apple.icloud-container.com.apple.keyboardservicesd" and identifier ""

default 16:56:36.382503 +0200 apsd <APSCConnectionServer: 0x7ff1121367e0>: Missing per-app tokens, re-requesting for user 501

default 16:56:36.382530 +0200 apsd <APSCConnectionServer: 0x7ff1121367e0>: Missing per-app token, requesting for user 501 with topic = com.apple.icloud-container.com.apple.callhistory.sync-helper and identifier =

default 16:56:36.382563 +0200 apsd <APSCCourier: 0x7ff1122051b0>: Received request from <APSCConnectionServer: 0x7ff1121367e0> to generate token for topic "com.apple.icloud-container.com.apple.callhistory.sync-helper" and identifier ""

default 16:56:36.382775 +0200 apsd Failed to talk to secld after 4 attempts.

default 16:56:36.382893 +0200 apsd <APSCCourier: 0x7ff1122051b0>: Received request to generate token for topic "com.apple.icloud-container.com.apple.callhistory.sync-helper" and identifier "", assigned appld "0"

default 16:56:36.382919 +0200 apsd <APSCCourier: 0x7ff1122051b0>: Rescheduling request to generate token for topic "com.apple.icloud-container.com.apple.callhistory.sync-helper" and identifier ""

default 16:56:36.383068 +0200 apsd <APSCConnectionServer: 0x7ff10fc39740>: Missing per-app tokens, re-requesting for user 501

default 16:56:36.383101 +0200 apsd <APSCConnectionServer: 0x7ff10fc39740>: Missing per-app token, requesting for user 501 with topic = com.apple.icloud-container.com.apple.gamed and identifier =
default 16:56:36.383126 +0200 apsd <APSCourier: 0x7ff1122051b0>: Received request from <APSCConnectionServer: 0x7ff10fc39740> to generate token for topic "com.apple.icloud-container.com.apple.gamed" and identifier ""
default 16:56:36.383350 +0200 apsd Failed to talk to sec2 after 4 attempts.
default 16:56:36.383506 +0200 apsd <APSCourier: 0x7ff1122051b0>: Received request to generate token for topic "com.apple.icloud-container.com.apple.gamed" and identifier "", assigned appld "0"
default 16:56:36.383533 +0200 apsd <APSCourier: 0x7ff1122051b0>: Rescheduling request to generate token for topic "com.apple.icloud-container.com.apple.gamed" and identifier ""
default 16:56:36.383576 +0200 apsd <APSCConnectionServer: 0x7ff1123130c0>: Missing per-app tokens, re-requesting for user 501
default 16:56:36.383616 +0200 apsd <APSCConnectionServer: 0x7ff1123130c0>: Missing per-app token, requesting for user 501 with topic = com.apple.icloud-container.com.apple.cloudpaired and identifier =
default 16:56:36.383685 +0200 apsd <APSCourier: 0x7ff1122051b0>: Received request from <APSCConnectionServer: 0x7ff1123130c0> to generate token for topic "com.apple.icloud-container.com.apple.cloudpaired" and identifier ""
default 16:56:36.383886 +0200 apsd Failed to talk to sec2 after 4 attempts.
default 16:56:36.384039 +0200 apsd <APSCourier: 0x7ff1122051b0>: Received request to generate token for topic "com.apple.icloud-container.com.apple.cloudpaired" and identifier "", assigned appld "0"
default 16:56:36.384065 +0200 apsd <APSCourier: 0x7ff1122051b0>: Rescheduling request to generate token for topic "com.apple.icloud-container.com.apple.cloudpaired" and identifier ""
default 16:56:36.384111 +0200 apsd <APSTopicManager: 0x7ff112308730> asked to performFilterBlock
default 16:56:36.384270 +0200 apsd <APSCourier: 0x7ff1122051b0>: When filter is sent for user 501, users potentially with messages = 1
default 16:56:36.384369 +0200 apsd <APSCourier: 0x7ff1122051b0>: Sending filter message for user 501 with token <3768eb4f 4a2cd5a6 422899d6 f49f63a7 e85b9388 e80f29b1 17b6e894 2dd04dc3> with enabled topics = (com.apple.icloud-container.cloud docs iCloud.com.apple.mobilesafari, com.apple.icloud-container.cloud docs.com.apple.shoebox, com.apple.icloud-container.cloud docs.com.apple.mobilemail, com.apple.icloud-container.com.apple.gamed, com.me.setupservice, com.apple.icloud-container.cloud docs iCloud.com.arfsoftware.voiceplus, com.icloud.quota, com.apple.icloud-container.cloud docs.X6B29J8D22.com.savysoda.documents, com.apple.icloud-container.cloud docs iCloud.com.apple.iBooks.iTunesU, com.apple.icloud-container.com.apple.Safari, com.apple.icloud-container.cloud docs.com.apple.Documents, com.apple.icloud-container.cloud docs.57T9237FN3.net.whatsapp.WhatsApp, com.me.bookmarks, com.apple.icloud-container.cloud docs.com.apple.Preview, com.apple.icloud-container.cloud docs.com.apple.CloudDocs.health, com.apple.icloud-container.cloud docs.com.apple.Cl<...>
default 16:56:36.384440 +0200 apsd <APSCourier: 0x7ff1122051b0> _processStoredIncomingMessages: enabled = YES

```

default    16:56:36.384513 +0200   apsd <APSCourier: 0x7ff1122051b0>
processing 0 stored incoming messages
default    16:56:36.384556 +0200   apsd <APSCourier: 0x7ff1122051b0> done with
_processStoredIncomingMessages
default    16:56:36.384594 +0200   apsd APSMessageStore -
APSIIncomingMessageRecordDeleteMessagesOlderThanDate environment
production 1 timeThreshold 514911396
default    16:56:36.384628 +0200   apsd <APSCourier: 0x7ff1122051b0>
_processStoredOutgoingMessages - marking outgoing messages as unsent so they
can be processed (we terminated before they were acknowledged).
default    16:56:36.384671 +0200   apsd <APSCourier: 0x7ff1122051b0>:
Checking whether any users can be connected or disconnected
default    16:56:36.384707 +0200   apsd <APSCourier: 0x7ff1122051b0>: Not
connecting 501 because user is already connected
default    16:56:36.384739 +0200   apsd <APSCourier: 0x7ff1122051b0>: Not
connecting 0 darkWakeEnabled because user is already connected
default    16:56:36.384778 +0200   apsd <APSCourier: 0x7ff1122051b0>: Not
connecting 0 because user is already connected
default    16:56:36.384817 +0200   apsd <APSCourier: 0x7ff1122051b0>: Not
connecting 501 darkWakeEnabled because user is already connected
default    16:56:36.384851 +0200   apsd <APSCourier: 0x7ff1122051b0>: Stream
processing: complete no, invalid no, length parsed 0, parameters (null)
default    16:56:36.384902 +0200   apsd Dispatching low priority message:
<OS_xpc_dictionary: <dictionary: 0x7ff10fc47d80> { count = 2, transaction: 0,
voucher = 0x0, contents =
    "isConnected" => <bool: 0x7ffdd7a6aa8>: true
    "message-type" => <int64: 0x7ff10fc18a20>: 26
}>
default    16:56:36.384960 +0200   apsd Dispatching low priority message:
<OS_xpc_dictionary: <dictionary: 0x7ff1123103b0> { count = 2, transaction: 0,
voucher = 0x0, contents =
    "isConnected" => <bool: 0x7ffdd7a6aa8>: true
    "message-type" => <int64: 0x7ff11230f260>: 26
}>
default    16:56:36.385005 +0200   apsd Dispatching low priority message:
<OS_xpc_dictionary: <dictionary: 0x7ff1123103b0> { count = 2, transaction: 0,
voucher = 0x0, contents =
    "isConnected" => <bool: 0x7ffdd7a6aa8>: true
    "message-type" => <int64: 0x7ff11230f260>: 26
}>
default    16:56:36.385052 +0200   bird ApplePushService: <APSCConnection:
0x7f8543a20c80> Delivering connectionStatusChange from apsd: YES
default    16:56:36.385054 +0200   apsd Dispatching low priority message:
<OS_xpc_dictionary: <dictionary: 0x7ff1123103b0> { count = 2, transaction: 0,
voucher = 0x0, contents =
    "isConnected" => <bool: 0x7ffdd7a6aa8>: true
    "message-type" => <int64: 0x7ff11230f260>: 26
}>
default    16:56:36.385095 +0200   apsd Dispatching low priority message:
<OS_xpc_dictionary: <dictionary: 0x7ff1123103b0> { count = 2, transaction: 0,

```

```

voucher = 0x0, contents =
    "isConnected" => <bool: 0x7ffdd7a6aa8>: true
    "message-type" => <int64: 0x7ff11230f260>: 26
}>
default 16:56:36.385160 +0200 apsd Dispatching low priority message:
<OS_xpc_dictionary: <dictionary: 0x7ff112003990> { count = 2, transaction: 0,
voucher = 0x0, contents =
    "isConnected" => <bool: 0x7ffdd7a6aa8>: true
    "message-type" => <int64: 0x7ff11200f930>: 26
}>
default 16:56:36.385207 +0200 apsd Dispatching low priority message:
<OS_xpc_dictionary: <dictionary: 0x7ff112003990> { count = 2, transaction: 0,
voucher = 0x0, contents =
    "isConnected" => <bool: 0x7ffdd7a6aa8>: true
    "message-type" => <int64: 0x7ff11200f930>: 26
}>
default 16:56:36.385222 +0200 akd ApplePushService: <APSCConnection:
0x7fd45fe0d0f0> Delivering connectionStatusChange from apsd: YES
default 16:56:36.385317 +0200 akd ApplePushService: <APSCConnection:
0x7fd45fe0d0f0> seeing if delegate <AKAppleIDPushHelperService:
0x7fd461a01280> responds to status changes
default 16:56:36.385356 +0200 akd ApplePushService: <APSCConnection:
0x7fd45fe0d0f0> calling <AKAppleIDPushHelperService: 0x7fd461a01280>
didChangeConnectedStatus:
default 16:56:36.385362 +0200 apsd Dispatching low priority message:
<OS_xpc_dictionary: <dictionary: 0x7ff10fd34f60> { count = 2, transaction: 0,
voucher = 0x0, contents =
    "isConnected" => <bool: 0x7ffdd7a6aa8>: true
    "message-type" => <int64: 0x7ff10fd35010>: 26
}>
default 16:56:36.385404 +0200 akd APNS status changed: 1
default 16:56:36.385477 +0200 apsd Dispatching low priority message:
<OS_xpc_dictionary: <dictionary: 0x7ff10fc47d80> { count = 2, transaction: 0,
voucher = 0x0, contents =
    "isConnected" => <bool: 0x7ffdd7a6aa8>: true
    "message-type" => <int64: 0x7ff10fc18a20>: 26
}>
default 16:56:36.385439 +0200 akd ApplePushService: <APSCConnection:
0x7fd45fe0d0f0> returned from <AKAppleIDPushHelperService: 0x7fd461a01280>
didChangeConnectedStatus:
default 16:56:36.385434 +0200 keyboardservicesd ApplePushService:
<APSCConnection: 0x7f9e86f0e3b0> Delivering connectionStatusChange from apsd:
YES
default 16:56:36.385541 +0200 apsd Dispatching low priority message:
<OS_xpc_dictionary: <dictionary: 0x7ff10fc47d80> { count = 2, transaction: 0,
voucher = 0x0, contents =
    "isConnected" => <bool: 0x7ffdd7a6aa8>: true
    "message-type" => <int64: 0x7ff10fc18a20>: 26
}>
default 16:56:36.385496 +0200 keyboardservicesd ApplePushService:

```

```

<APSCConnection: 0x7f9e86f0e3b0>: Re-requesting up-to-date per-app tokens
default 16:56:36.385595 +0200 apsd Dispatching low priority message:
<OS_xpc_dictionary: <dictionary: 0x7ff11200fa70> { count = 2, transaction: 0,
voucher = 0x0, contents =
    "isConnected" => <bool: 0x7ffdd7a6aa8>: true
    "message-type" => <int64: 0x7ff11200f930>: 26
}>
default 16:56:36.385535 +0200 keyboardservicesd ApplePushService:
<APSCConnection: 0x7f9e86f0e3b0>: Sending request for per-app token for topic
com.apple.icloud-container.com.apple.keyboardservicesd with identifier
default 16:56:36.385648 +0200 apsd Dispatching low priority message:
<OS_xpc_dictionary: <dictionary: 0x7ff11200fa70> { count = 2, transaction: 0,
voucher = 0x0, contents =
    "isConnected" => <bool: 0x7ffdd7a6aa8>: true
    "message-type" => <int64: 0x7ff11200f930>: 26
}>
default 16:56:36.385739 +0200 com.apple.iCloudHelper ApplePushService:
<APSCConnection: 0x7f91573036e0> Delivering connectionStatusChange from apsd:
YES
default 16:56:36.385697 +0200 apsd Dispatching low priority message:
<OS_xpc_dictionary: <dictionary: 0x7ff11200fa70> { count = 2, transaction: 0,
voucher = 0x0, contents =
    "isConnected" => <bool: 0x7ffdd7a6aa8>: true
    "message-type" => <int64: 0x7ff11200f930>: 26
}>
default 16:56:36.385748 +0200 SafariCloudHistoryPushAgent
ApplePushService: <APSCConnection: 0x7f92b740d2c0> Delivering
connectionStatusChange from apsd: YES
default 16:56:36.385742 +0200 apsd Dispatching low priority message:
<OS_xpc_dictionary: <dictionary: 0x7ff11200fa70> { count = 2, transaction: 0,
voucher = 0x0, contents =
    "isConnected" => <bool: 0x7ffdd7a6aa8>: true
    "message-type" => <int64: 0x7ff11200f930>: 26
}>
default 16:56:36.385899 +0200 SafariCloudHistoryPushAgent
ApplePushService: <APSCConnection: 0x7f92b740d2c0>: Re-requesting up-to-
date per-app tokens
default 16:56:36.385964 +0200 AppleIDAuthAgent ApplePushService:
<APSCConnection: 0x7fd38bd03de0> Delivering connectionStatusChange from apsd:
YES
default 16:56:36.385967 +0200 SafariCloudHistoryPushAgent
ApplePushService: <APSCConnection: 0x7f92b740d2c0>: Sending request for
per-app token for topic com.apple.icloud-container.com.apple.Safari with identifier
default 16:56:36.386002 +0200 apsd <APSCConnectionServer:
0x7ff112223fd0>: Received per-app token request for topic com.apple.icloud-
container.com.apple.keyboardservicesd with identifier
default 16:56:36.386069 +0200 apsd <APSCConnectionServer:
0x7ff112223fd0>: Missing per-app token, requesting for user 501 with topic =
com.apple.icloud-container.com.apple.keyboardservicesd and identifier =
default 16:56:36.386111 +0200 apsd <APSCourier: 0x7ff1122051b0>:

```

Received request from <APSCConnectionServer: 0x7ff11223fd0> to generate token for topic "com.apple.icloud-container.com.apple.keyboardservicesd" and identifier ""

default 16:56:36.386129 +0200 AppleIDAuthAgent ApplePushService:
<APSCConnection: 0x7fd38bd03de0>: Re-requesting up-to-date per-app tokens

default 16:56:36.386248 +0200 AppleIDAuthAgent ApplePushService:
<APSCConnection: 0x7fd38bd03de0>: Sending request for per-app token for topic com.apple.idmsauthagent with identifier

default 16:56:36.386319 +0200 maspushagent ApplePushService:
<StoreAPSCConnection: 0x7f99e7501850> Delivering connectionStatusChange from apsd: YES

default 16:56:36.386389 +0200 gamed ApplePushService:
<APSCConnection 0x7ffb39c09ff0 production com.apple.gamed.aps> Delivering connectionStatusChange from apsd: YES

default 16:56:36.386428 +0200 apsd Failed to talk to secd after 4 attempts.

default 16:56:36.386447 +0200 askpermissiond ApplePushService:
<APSCConnection: 0x7fdd9770f780> Delivering connectionStatusChange from apsd: YES

default 16:56:36.386459 +0200 maspushagent ApplePushService:
<StoreAPSCConnection: 0x7f99e7501850> seeing if delegate <APSCClient: 0x7f99e75015b0> responds to status changes

default 16:56:36.386529 +0200 gamed ApplePushService:
<APSCConnection 0x7ffb3b8061c0 production (null)> Delivering connectionStatusChange from apsd: YES

default 16:56:36.386561 +0200 maspushagent ApplePushService:
<StoreAPSCConnection: 0x7f99e7501850> calling <APSCClient: 0x7f99e75015b0> didChangeConnectedStatus:

default 16:56:36.386633 +0200 gamed ApplePushService:
<APSCConnection 0x7ffb3b8061c0 production (null)>: Re-requesting up-to-date per-app tokens

default 16:56:36.386648 +0200 apsd <APSCCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-container.com.apple.keyboardservicesd" and identifier "", assigned appld "0"

default 16:56:36.386687 +0200 apsd <APSCCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-container.com.apple.keyboardservicesd" and identifier ""

default 16:56:36.386734 +0200 maspushagent ApplePushService:
<StoreAPSCConnection: 0x7f99e7501850> returned from <APSCClient: 0x7f99e75015b0> didChangeConnectedStatus:

default 16:56:36.386739 +0200 cloudpaired ApplePushService:
<APSCConnection: 0x7fb92c10f9a0> Delivering connectionStatusChange from apsd: YES

default 16:56:36.386742 +0200 apsd <APSCConnectionServer: 0x7ff10fd23970>: Received per-app token request for topic com.apple.icloud-container.com.apple.Safari with identifier

default 16:56:36.386820 +0200 gamed ApplePushService:
<APSCConnection 0x7ffb3b8061c0 production (null)>: Sending request for per-app token for topic com.apple.icloud-container.com.apple.gamed with identifier

default 16:56:36.386784 +0200 apsd <APSCConnectionServer: 0x7ff10fd23970>: Missing per-app token, requesting for user 501 with topic = com.apple.icloud-container.com.apple.Safari and identifier =

default 16:56:36.386879 +0200 cloudpairedApplePushService:
<APSCConnection: 0x7fb92c10f9a0>: Re-requesting up-to-date per-app tokens
default 16:56:36.386818 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff10fd23970> to generate token
for topic "com.apple.icloud-container.com.apple.Safari" and identifier ""
default 16:56:36.387011 +0200 cloudpairedApplePushService:
<APSCConnection: 0x7fb92c10f9a0>: Sending request for per-app token for topic
com.apple.icloud-container.com.apple.cloudpaired with identifier
default 16:56:36.387084 +0200 apsd Failed to talk to sec2 after 4 attempts.
default 16:56:36.387042 +0200 fmfd ApplePushService: <APSCConnection:
0x7fddd150c760> Delivering connectionStatusChange from apsd: YES
default 16:56:36.387191 +0200 CallHistorySyncHelper ApplePushService:
<APSCConnection: 0x7f9c56a187a0> Delivering connectionStatusChange from apsd:
YES
default 16:56:36.387216 +0200 passd ApplePushService:
<APSCConnection: 0x7f834ea0e660> Delivering connectionStatusChange from apsd:
YES
default 16:56:36.387308 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.Safari" and identifier "", assigned appld "0"
default 16:56:36.387349 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-
container.com.apple.Safari" and identifier ""
default 16:56:36.387356 +0200 CallHistorySyncHelper ApplePushService:
<APSCConnection: 0x7f9c56a187a0>: Re-requesting up-to-date per-app tokens
default 16:56:36.387416 +0200 apsd <APSCConnectionServer:
0x7ff10fd30340>: Received per-app token request for topic
com.apple.idmsauthagent with identifier
default 16:56:36.387476 +0200 apsd <APSCConnectionServer:
0x7ff10fd30340>: Missing per-app token, requesting for user 501 with topic =
com.apple.idmsauthagent and identifier =
default 16:56:36.387516 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff10fd30340> to generate token
for topic "com.apple.idmsauthagent" and identifier ""
default 16:56:36.387519 +0200 CallHistorySyncHelper ApplePushService:
<APSCConnection: 0x7f9c56a187a0>: Sending request for per-app token for topic
com.apple.icloud-container.com.apple.callhistory.sync-helper with identifier
default 16:56:36.387784 +0200 apsd Failed to talk to sec2 after 4 attempts.
default 16:56:36.387992 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.idmsauthagent" and
identifier "", assigned appld "0"
default 16:56:36.388018 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.idmsauthagent" and
identifier ""
default 16:56:36.388106 +0200 apsd <APSCConnectionServer:
0x7ff10fc39740>: Received per-app token request for topic com.apple.icloud-
container.com.apple.gamed with identifier
default 16:56:36.388149 +0200 apsd <APSCConnectionServer:
0x7ff10fc39740>: Missing per-app token, requesting for user 501 with topic =
com.apple.icloud-container.com.apple.gamed and identifier =

default 16:56:36.388183 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff10fc39740> to generate token
for topic "com.apple.icloud-container.com.apple.gamed" and identifier ""

default 16:56:36.388406 +0200 apsd Failed to talk to secd after 4 attempts.

default 16:56:36.388579 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.gamed" and identifier "", assigned appld "0"

default 16:56:36.388608 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-
container.com.apple.gamed" and identifier ""

default 16:56:36.388684 +0200 apsd <APSCConnectionServer:
0x7ff1123130c0>: Received per-app token request for topic com.apple.icloud-
container.com.apple.cloudpaired with identifier

default 16:56:36.388732 +0200 apsd <APSCConnectionServer:
0x7ff1123130c0>: Missing per-app token, requesting for user 501 with topic =
com.apple.icloud-container.com.apple.cloudpaired and identifier =

default 16:56:36.388778 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff1123130c0> to generate token
for topic "com.apple.icloud-container.com.apple.cloudpaired" and identifier ""

default 16:56:36.388996 +0200 apsd Failed to talk to secd after 4 attempts.

default 16:56:36.389143 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.cloudpaired" and identifier "", assigned appld "0"

default 16:56:36.389189 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-
container.com.apple.cloudpaired" and identifier ""

default 16:56:36.389252 +0200 apsd <APSCConnectionServer:
0x7ff1121367e0>: Received per-app token request for topic com.apple.icloud-
container.com.apple.callhistory.sync-helper with identifier

default 16:56:36.389303 +0200 apsd <APSCConnectionServer:
0x7ff1121367e0>: Missing per-app token, requesting for user 501 with topic =
com.apple.icloud-container.com.apple.callhistory.sync-helper and identifier =

default 16:56:36.389375 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff1121367e0> to generate token
for topic "com.apple.icloud-container.com.apple.callhistory.sync-helper" and identifier
""

default 16:56:36.389592 +0200 apsd Failed to talk to secd after 4 attempts.

default 16:56:36.389733 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.callhistory.sync-helper" and identifier "", assigned appld "0"

default 16:56:36.389759 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-
container.com.apple.callhistory.sync-helper" and identifier ""

default 16:56:36.396017 +0200 AddressBookSourceSync self.homeInfo:
<private>

default 16:56:36.396097 +0200 AddressBookSourceSync self.searchInfo:
<private>

default 16:56:36.399285 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0

default 16:56:36.401774 +0200 AddressBookSourceSync Local me name:

```

(null) ll server me: (null)
default 16:56:36.401991 +0200 CommCenter #l
CSIApplInfo.ApplicationActivationObserver: handleLSNotification_sync: Application
exited: <private>
default 16:56:36.402512 +0200 AddressBookSourceSync ###
SYNCHRONIZING <private> ###
error 16:56:36.408491 +0200 AddressBookSourceSync warning: dynamic
accessors failed to find @property implementation for 'uniqueId' for entity
ABCDContact while resolving selector 'uniqueId' on class 'ABCDContact'. Did you
remember to declare it @dynamic or @synthesized in the @implementation ?
default 16:56:36.409300 +0200 AddressBookSourceSync -_fillCache 1
records: 1 people, 0 groups
default 16:56:36.409911 +0200 AddressBookSourceSync -[CDXAccount
clearAuthMethodsTried]
default 16:56:36.410301 +0200 AddressBookSourceSync Using cached
_acAccount <private>
default 16:56:36.410430 +0200 AddressBookSourceSync Using cached
_acAccount <private>
default 16:56:36.410468 +0200 AddressBookSourceSync _acAccountIdentifier
= <private>
default 16:56:36.410494 +0200 AddressBookSourceSync Using account with
identifier <private>
default 16:56:36.410529 +0200 AddressBookSourceSync Using cached
_acAccount <private>
default 16:56:36.410549 +0200 AddressBookSourceSync We are a the child of
a Gmail account; deferring to parent
default 16:56:36.410580 +0200 AddressBookSourceSync -
acAccountOrParentGoogleAccount: <private>
default 16:56:36.410645 +0200 AddressBookSourceSync -[CDXAccount
oauth2Token]: Returning oauth token <private> for identifier: <private>
default 16:56:36.411114 +0200 AddressBookSourceSync CFNetwork-AOSKit:
Reaching out to AOSKit for X-mobile me token
default 16:56:36.413252 +0200 trustd cert[2]: AnchorTrusted =(leaf)[force]>
0
default 16:56:36.414173 +0200 com.apple.iCloudHelper AOSKit INFO:
(com.apple.AddressBookSourceSync/10.0) ACCT LOOKUP: Previously performed
ACAccount lookup for user=beyondsemble@gmail.com (nothing found)
default 16:56:36.414418 +0200 com.apple.iCloudHelper AOSKit INFO:
(com.apple.AddressBookSourceSync/10.0) ACCT LOOKUP: No stored info found for
user=beyondsemble@gmail.com (acct=0x54e15f30)
default 16:56:36.414634 +0200 AddressBookSourceSync CFNetwork-AOSKit:
Failed to get a X-mobile me token from AOSKit
default 16:56:36.416638 +0200 com.apple.WebKit.Networking
TIC TCP Conn Event [2:0x7fa64691ae50]: 2 Err(0)
default 16:56:36.416669 +0200 com.apple.WebKit.Networking
TIC TCP Conn Cancel [2:0x7fa64691ae50]
default 16:56:36.416708 +0200 com.apple.WebKit.Networking
TIC TCP Conn Destroyed [2:0x7fa64691ae50]
default 16:56:36.424920 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Outstanding data received: <12000000 3e010001 00020020 d9c11435 214069b9

```

```

101c5fde a54e7119 fcf1b29f ac27fb6a e7c8a67e 735182bc 03001499 8c5d4c6f
0bb047fc 827e799b b288562a 619642> (length 67)
default 16:56:36.425009 +0200 apsd <APSCourier: 0x7ff1122051b0>: Stream
processing: complete yes, invalid no, length parsed 67, parameters {
    APSProtocolAppTokenGenerateResponseCode = 0;
    APSProtocolAppTokenGenerateResponseToken = <d9c11435 214069b9
101c5fde a54e7119 fcf1b29f ac27fb6a e7c8a67e 735182bc>;
    APSProtocolAppTokenGenerateResponseTopicHash = <998c5d4c 6f0bb047
fc827e79 9bb28856 2a619642>;
    APSProtocolCommand = 18;
}
default 16:56:36.425043 +0200 com.apple.WebKit.Networking
TIC TCP Conn Event [14:0x7fa6468334f0]: 2 Err(0)
default 16:56:36.425080 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received app token generate response {
    APSProtocolAppTokenGenerateResponseCode = 0;
    APSProtocolAppTokenGenerateResponseToken = <d9c11435 214069b9
101c5fde a54e7119 fcf1b29f ac27fb6a e7c8a67e 735182bc>;
    APSProtocolAppTokenGenerateResponseTopicHash = <998c5d4c 6f0bb047
fc827e79 9bb28856 2a619642>;
    APSProtocolCommand = 18;
}
default 16:56:36.425089 +0200 com.apple.WebKit.Networking
TIC TCP Conn Cancel [14:0x7fa6468334f0]
default 16:56:36.425237 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received response for token request for topic com.apple.idmsauthagent, appld 0,
new token = <d9c11435 214069b9 101c5fde a54e7119 fcf1b29f ac27fb6a e7c8a67e
735182bc>
default 16:56:36.425309 +0200 apsd <APSCConnectionServer:
0x7ff10fd30340>: Received token <d9c11435 214069b9 101c5fde a54e7119
fcf1b29f ac27fb6a e7c8a67e 735182bc> for topic com.apple.idmsauthagent with
identifier
default 16:56:36.425126 +0200 com.apple.WebKit.Networking
TIC TCP Conn Destroyed [14:0x7fa6468334f0]
default 16:56:36.425348 +0200 apsd <APSCConnectionServer:
0x7ff10fd30340>: Sending token <d9c11435 214069b9 101c5fde a54e7119 fcf1b29f
ac27fb6a e7c8a67e 735182bc> for topic com.apple.idmsauthagent with identifier
default 16:56:36.425407 +0200 apsd <APSCourier: 0x7ff1122051b0>: Stream
processing: complete no, invalid no, length parsed 0, parameters (null)
default 16:56:36.425463 +0200 apsd Dispatching low priority message:
<OS_xpc_dictionary: <dictionary: 0x7ff112309400> { count = 4, transaction: 0,
voucher = 0x0, contents =
    "identifier" => <string: 0x7ff11230fdb0> { length = 0, contents = "" }
    "token" => <data: 0x7ff112314870>: { length = 32 bytes, contents =
0xd9c11435214069b9101c5fdea54e7119fcf1b29fac27fb6a... }
    "topic" => <string: 0x7ff11230ad00> { length = 23, contents =
"com.apple.idmsauthagent" }
    "message-type" => <int64: 0x7ff1123094b0>: 30
}>
}>
default 16:56:36.425657 +0200 AppleIDAuthAgent ApplePushService:

```

```

<APSCConnection: 0x7fd38bd03de0> Received token <d9c11435 214069b9
101c5fde a54e7119 fcf1b29f ac27fb6a e7c8a67e 735182bc> forTopic
com.apple.idmsauthagent identifier
default 16:56:36.425767 +0200 AppleIDAuthAgent ApplePushService:
<APSCConnection: 0x7fd38bd03de0> calling <AppleIDAuthPushAgent:
0x7fd38be04260> for received token <d9c11435 214069b9 101c5fde a54e7119
fcf1b29f ac27fb6a e7c8a67e 735182bc> for topic com.apple.idmsauthagent identifier
default 16:56:36.425799 +0200 AppleIDAuthAgent Received push token
'<private>', topic '<private>', identifier '<private>'
default 16:56:36.425872 +0200 AppleIDAuthAgent ApplePushService:
<APSCConnection: 0x7fd38bd03de0> returned from <AppleIDAuthPushAgent:
0x7fd38be04260> didReceiveToken:forTopic:identifier
default 16:56:36.428942 +0200 com.apple.WebKit.Networking
TIC TCP Conn Event [13:0x7fa644c2ac90]: 2 Err(0)
default 16:56:36.428984 +0200 com.apple.WebKit.Networking
TIC TCP Conn Cancel [13:0x7fa644c2ac90]
default 16:56:36.429022 +0200 com.apple.WebKit.Networking
TIC TCP Conn Destroyed [13:0x7fa644c2ac90]
default 16:56:36.484722 +0200 cloudpairedZoneCreated check:
MagicCloudPairingAccessoryEncryptionPreferences 1
default 16:56:36.502514 +0200 AddressBookSourceSync ###
SYNCHRONIZATION of ALL (<private>), Error (null), Errors (null) ###
default 16:56:36.502529 +0200 AddressBookSourceSync ###
SYNCHRONIZATION CLEANUP ###
default 16:56:36.502602 +0200 AddressBookSourceSync -doSyncWithServer:
saving <private> on <private>
error 16:56:36.503770 +0200 AddressBookSourceSync warning: dynamic
accessors failed to find @property implementation for 'modificationDate' for entity
ABCDGroup while resolving selector 'modificationDate' on class 'ABCDGroup'. Did
you remember to declare it @dynamic or @synthesized in the @implementation ?
error 16:56:36.503981 +0200 AddressBookSourceSync warning: dynamic
accessors failed to find @property implementation for 'modificationDate' for entity
ABCDInfo while resolving selector 'modificationDate' on class 'ABCDInfo'. Did you
remember to declare it @dynamic or @synthesized in the @implementation ?
default 16:56:36.504510 +0200 AddressBookSourceSync ** -
preprocessChanges(-willUpdateRecords:): ** 1 records for address book: <private>
Thread: <private>
default 16:56:36.504536 +0200 AddressBookSourceSync -
preprocessChanges(-willUpdateRecords:): inAddressBook: <private>,
writeChangesToServer==NO, IGNORING 1 records
default 16:56:36.506102 +0200 AddressBookSourceSync Posting
kABDatabaseChangedNotification while #saving <ABAddressBookChangesNotifier:
0x7fb66ff3b750> (updated: 1, added: 0, deleted: 0): <private>
default 16:56:36.506475 +0200 AddressBookSourceSync Posting
kABDatabaseChangedNotificationPriv while #saving
<ABAddressBookChangesNotifier: 0x7fb66ff3b750> (updated: 2, added: 0, deleted:
0): <private>
default 16:56:36.507076 +0200 AddressBookSourceSync **
didUpdateRecords: ** 1 records for address book: <private> Thread: <private>
default 16:56:36.507113 +0200 AddressBookSourceSync -

```

```

postprocessChanges(-didUpdateRecords:): inAddressBook: <private>,
writeChangesToServer==NO, 1 records
default 16:56:36.507164 +0200 AddressBookSourceSync *** CardDAVSource
mocDidSave ***
default 16:56:36.507319 +0200 AddressBookSourceSync -doSyncWithServer:
done saving <private> on <private>
default 16:56:36.507438 +0200 AddressBookSourceSync ###
SYNCHRONIZATION DONE ###
default 16:56:36.508021 +0200 AddressBookSourceSync push:
addPushObserver for <private> in <private>
default 16:56:36.508825 +0200 AddressBookSourceSync push:
removePushObserver: removing self <private> uid <private> from center (null)
default 16:56:36.508857 +0200 AddressBookSourceSync push: Push not
enabled. No transports:(null) or keys:(null)
default 16:56:36.508885 +0200 AddressBookSourceSync push: -
setPushIsActive: NO, currently NO
default 16:56:36.510210 +0200 AddressBookSourceSync -startSync
(<private>) done
default 16:56:36.551575 +0200 AddressBookSourceSync -getHomeInfo:
[_controller containersAtURLs:<private>]
default 16:56:36.551595 +0200 AddressBookSourceSync -[CDXAccount
clearAuthMethodsTried]
default 16:56:36.551753 +0200 AddressBookSourceSync Using cached
_acAccount <private>
default 16:56:36.552069 +0200 AddressBookSourceSync Using cached
_acAccount <private>
default 16:56:36.552507 +0200 AddressBookSourceSync CFNetwork-AOSKit:
Reaching out to AOSKit for X-mobile me token
default 16:56:36.552550 +0200 AddressBookSourceSync CFNetwork-AOSKit:
Applied X-mobile me auth to request
default 16:56:36.637111 +0200 apsd <APSCourier: 0x7ff10fe24350>:
Outstanding data received: <0e000000 23010020 495e168a a5f94955 15e1eeb7
47a70c56 d379a155 23ddf84a 9c426003 1a278d35> (length 40)
default 16:56:36.637176 +0200 apsd <APSCourier: 0x7ff10fe24350>: Stream
processing: complete yes, invalid no, length parsed 40, parameters {
    APSProtocolCommand = 14;
    APSProtocolDestination = <495e168a a5f94955 15e1eeb7 47a70c56 d379a155
23ddf84a 9c426003 1a278d35>;
}
default 16:56:36.637219 +0200 apsd <APSCourier: 0x7ff10fe24350>: Received
NoStorage message, users potentially with messages = 0, parameters = {
    APSProtocolCommand = 14;
    APSProtocolDestination = <495e168a a5f94955 15e1eeb7 47a70c56 d379a155
23ddf84a 9c426003 1a278d35>;
}
default 16:56:36.637307 +0200 apsd <APSCourier: 0x7ff10fe24350>: Stream
processing: complete no, invalid no, length parsed 0, parameters (null)
default 16:56:36.751148 +0200 AddressBookSourceSync self.homeInfo:
<private>
default 16:56:36.751214 +0200 AddressBookSourceSync self.searchInfo:

```

```

<private>
default 16:56:36.881443 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Outstanding data received: <0e000000 23010020 3768eb4f 4a2cd5a6 422899d6
f49f63a7 e85b9388 e80f29b1 17b6e894 2dd04dc3> (length 40)
default 16:56:36.881492 +0200 apsd <APSCourier: 0x7ff1122051b0>: Stream
processing: complete yes, invalid no, length parsed 40, parameters {
    APSProtocolCommand = 14;
    APSProtocolDestination = <3768eb4f 4a2cd5a6 422899d6 f49f63a7 e85b9388
e80f29b1 17b6e894 2dd04dc3>;
}
default 16:56:36.881522 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received NoStorage message, users potentially with messages = 0, parameters = {
    APSProtocolCommand = 14;
    APSProtocolDestination = <3768eb4f 4a2cd5a6 422899d6 f49f63a7 e85b9388
e80f29b1 17b6e894 2dd04dc3>;
}
default 16:56:36.881632 +0200 apsd <APSCourier: 0x7ff1122051b0>: Stream
processing: complete no, invalid no, length parsed 0, parameters (null)
default 16:56:37.029618 +0200 sharingd Rebroadcasting external notification
ABDistributedDatabaseChangedNotification from process AddressBookSourceSync
(<private>)
default 16:56:37.029707 +0200 sharingd Rebroadcasting external notification
ABDistributedDatabaseChangedNotificationPriv from process
AddressBookSourceSync (<private>)
default 16:56:37.266991 +0200 com.apple.WebKit.Networking
    0x110c88800 - NetworkResourceLoader::didFinishLoading: (pageID = 7,
frameID = 1, resourceID = 33)
default 16:56:37.267080 +0200 com.apple.WebKit.WebContent
    0x1131c99a0 - WebResourceLoader::didFinishResourceLoad: (pageID = 7,
frameID = 1, resourceID = 33)
default 16:56:37.787187 +0200 com.apple.WebKit.WebContent
    0x7fda8d22d5e0 - PerformanceMonitor::measurePostLoadCPUUsage:
Process was using 3.8% CPU after the page load.
default 16:56:37.797634 +0200 accountsd "Idle-exit-preventing transaction
ended!"
default 16:56:38.031505 +0200 securityd 0x7fb8fdc10570 killing session
100025
default 16:56:38.031533 +0200 securityd Killing auth hosts
default 16:56:38.031550 +0200 securityd 0x7fb8fdc10570 Session 100025
destroyed
default 16:56:38.031564 +0200 securityd Session 100025 destroyed
default 16:56:38.079884 +0200 opendirectoryd disconnect module connection
default 16:56:38.130722 +0200 AddressBookSourceSync Local me name:
<private> ll server me: <private>
default 16:56:38.130766 +0200 AddressBookSourceSync ###
SYNCHRONIZING <private> ###
default 16:56:38.156625 +0200 com.apple.WebKit.WebContent
    0x7fac3c218f00 - PerformanceMonitor::measurePostLoadCPUUsage: Process
was using 0.0% CPU after the page load.
default 16:56:38.335101 +0200 AddressBookSourceSync - _fillCache 759

```

```

records: 756 people, 3 groups
default 16:56:38.342098 +0200 AddressBookSourceSync -[CDXAccount
clearAuthMethodsTried]
default 16:56:38.342320 +0200 AddressBookSourceSync Using cached
_acAccount <private>
default 16:56:38.342472 +0200 AddressBookSourceSync Using cached
_acAccount <private>
default 16:56:38.342951 +0200 AddressBookSourceSync CFNetwork-AOSKit:
Reaching out to AOSKit for X-mobile me token
default 16:56:38.343020 +0200 AddressBookSourceSync CFNetwork-AOSKit:
Applied X-mobile me auth to request
default 16:56:38.551592 +0200 AddressBookSourceSync ###
SYNCHRONIZATION of ALL (<private>), Error (null), Errors (null) ###
default 16:56:38.551625 +0200 AddressBookSourceSync ###
SYNCHRONIZATION CLEANUP ###
default 16:56:38.551688 +0200 AddressBookSourceSync -doSyncWithServer:
saving <private> on <private>
default 16:56:38.551767 +0200 AddressBookSourceSync -doSyncWithServer:
done saving <private> on <private>
default 16:56:38.551843 +0200 AddressBookSourceSync ###
SYNCHRONIZATION DONE ###
default 16:56:38.551861 +0200 AddressBookSourceSync push:
addPushObserver for <private> in <private>
default 16:56:38.552498 +0200 AddressBookSourceSync push:
addPushObserver: No change in push state. self.abPushNotificationCenter:
<private>
default 16:56:38.554296 +0200 AddressBookSourceSync -startSync
(<private>) done
default 16:56:38.863439 +0200 symptomsd KnownGood evaluation passed
and it's called a KnownGood; symptom posted
default 16:56:39.034146 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff10fe3ee70> to generate token
for topic "com.apple.icloud-container.com.apple.Notes" and identifier ""
default 16:56:39.034525 +0200 apsd Failed to talk to secd after 4 attempts.
default 16:56:39.034754 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.Notes" and identifier "", assigned appld "0"
default 16:56:39.075745 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Outstanding data received: <12000000 3e010001 00020020 8cdbd09e bbc1a4fa
f3d687ec 75c398b0 c2f35cce 65432c19 03f7f75b 925f867a 0300148c c62e5c10
6b0d3196 d29588eb 8ae398c1 3f6d3c> (length 67)
default 16:56:39.075804 +0200 apsd <APSCourier: 0x7ff1122051b0>: Stream
processing: complete yes, invalid no, length parsed 67, parameters {
    APSProtocolAppTokenGenerateResponseCode = 0;
    APSProtocolAppTokenGenerateResponseToken = <8cdbd09e bbc1a4fa f3d687ec
75c398b0 c2f35cce 65432c19 03f7f75b 925f867a>;
    APSProtocolAppTokenGenerateResponseTopicHash = <8cc62e5c 106b0d31
96d29588 eb8ae398 c13f6d3c>;
    APSProtocolCommand = 18;
}

```

```

default 16:56:39.075840 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received app token generate response {
    APSProtocolAppTokenGenerateResponseCode = 0;
    APSProtocolAppTokenGenerateResponseToken = <8cdbd09e bbc1a4fa f3d687ec
75c398b0 c2f35cce 65432c19 03f7f75b 925f867a>;
    APSProtocolAppTokenGenerateResponseTopicHash = <8cc62e5c 106b0d31
96d29588 eb8ae398 c13f6d3c>;
    APSProtocolCommand = 18;
}
default 16:56:39.075869 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received response for token request for topic com.apple.icloud-
container.com.apple.Notes, appld 0, new token = <8cdbd09e bbc1a4fa f3d687ec
75c398b0 c2f35cce 65432c19 03f7f75b 925f867a>
default 16:56:39.075920 +0200 apsd <APSCConnectionServer:
0x7ff10fe3ee70>: Received token <8cdbd09e bbc1a4fa f3d687ec 75c398b0
c2f35cce 65432c19 03f7f75b 925f867a> for topic com.apple.icloud-
container.com.apple.Notes with identifier
default 16:56:39.075977 +0200 apsd <APSCConnectionServer:
0x7ff10fe3ee70>: Sending token <8cdbd09e bbc1a4fa f3d687ec 75c398b0 c2f35cce
65432c19 03f7f75b 925f867a> for topic com.apple.icloud-container.com.apple.Notes
with identifier
default 16:56:39.076030 +0200 apsd <APSCourier: 0x7ff1122051b0>: Stream
processing: complete no, invalid no, length parsed 0, parameters (null)
default 16:56:39.076070 +0200 apsd Dispatching low priority message:
<OS_xpc_dictionary: <dictionary: 0x7ff10ff11440> { count = 4, transaction: 0,
voucher = 0x0, contents =
    "identifier" => <string: 0x7ff10ff379d0> { length = 0, contents = "" }
    "token" => <data: 0x7ff10ff37eb0>: { length = 32 bytes, contents =
0x8cdbd09ebbc1a4faf3d687ec75c398b0c2f35cce65432c19... }
    "topic" => <string: 0x7ff10ff26090> { length = 42, contents = "com.apple.icloud-
container.com.apple.Notes" }
    "message-type" => <int64: 0x7ff10ff21210>: 30
}>
default 16:56:39.076169 +0200 usernoted ApplePushService:
<APSCConnection: 0x7fb4e4e123f0> Received token <8cdbd09e bbc1a4fa f3d687ec
75c398b0 c2f35cce 65432c19 03f7f75b 925f867a> forTopic com.apple.icloud-
container.com.apple.Notes identifier
default 16:56:39.153437 +0200 com.apple.WebKit.WebContent
0x7fc5f7079f30 - PerformanceMonitor::measurePostLoadCPUUsage: Process
was using 0.2% CPU after the page load.
default 16:56:39.519320 +0200 com.apple.WebKit.WebContent
0x7fcb9b108dc0 - PerformanceMonitor::measurePostLoadCPUUsage: Process
was using 0.1% CPU after the page load.
default 16:56:39.679798 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff10fd23970> to generate token
for topic "com.apple.icloud-container.com.apple.Safari" and identifier ""
default 16:56:39.680070 +0200 apsd Failed to talk to secd after 4 attempts.
default 16:56:39.680228 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.Safari" and identifier "", assigned appld "0"

```


default 16:56:39.680314 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff112223fd0> to generate token
for topic "com.apple.icloud-container.com.apple.keyboardservicesd" and identifier ""
default 16:56:39.680537 +0200 apsd Failed to talk to secd after 4 attempts.
default 16:56:39.680695 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.keyboardservicesd" and identifier "", assigned appld "0"
default 16:56:39.680722 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-
container.com.apple.keyboardservicesd" and identifier ""
default 16:56:39.680757 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff1121367e0> to generate token
for topic "com.apple.icloud-container.com.apple.callhistory.sync-helper" and identifier
""
default 16:56:39.680949 +0200 apsd Failed to talk to secd after 4 attempts.
default 16:56:39.681082 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.callhistory.sync-helper" and identifier "", assigned appld "0"
default 16:56:39.681107 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-
container.com.apple.callhistory.sync-helper" and identifier ""
default 16:56:39.681162 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff10fc39740> to generate token
for topic "com.apple.icloud-container.com.apple.gamed" and identifier ""
default 16:56:39.681392 +0200 apsd Failed to talk to secd after 4 attempts.
default 16:56:39.681547 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.gamed" and identifier "", assigned appld "0"
default 16:56:39.681609 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-
container.com.apple.gamed" and identifier ""
default 16:56:39.681668 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff1123130c0> to generate token
for topic "com.apple.icloud-container.com.apple.cloudpaired" and identifier ""
default 16:56:39.681874 +0200 apsd Failed to talk to secd after 4 attempts.
default 16:56:39.682037 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.cloudpaired" and identifier "", assigned appld "0"
default 16:56:39.682067 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-
container.com.apple.cloudpaired" and identifier ""
default 16:56:39.682131 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff112223fd0> to generate token
for topic "com.apple.icloud-container.com.apple.keyboardservicesd" and identifier ""
default 16:56:39.682350 +0200 apsd Failed to talk to secd after 4 attempts.
default 16:56:39.682484 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.keyboardservicesd" and identifier "", assigned appld "0"
default 16:56:39.682516 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-

container.com.apple.keyboardservicesd" and identifier ""
default 16:56:39.682571 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff10fd23970> to generate token
for topic "com.apple.icloud-container.com.apple.Safari" and identifier ""
default 16:56:39.682808 +0200 apsd Failed to talk to secdd after 4 attempts.
default 16:56:39.682969 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.Safari" and identifier "", assigned appld "0"
default 16:56:39.682996 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-
container.com.apple.Safari" and identifier ""
default 16:56:39.683072 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff10fd30340> to generate token
for topic "com.apple.idmsauthagent" and identifier ""
default 16:56:39.683296 +0200 apsd Failed to talk to secdd after 4 attempts.
default 16:56:39.683433 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.idmsauthagent" and
identifier "", assigned appld "0"
default 16:56:39.683459 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.idmsauthagent" and
identifier ""
default 16:56:39.683501 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff10fc39740> to generate token
for topic "com.apple.icloud-container.com.apple.gamed" and identifier ""
default 16:56:39.683701 +0200 apsd Failed to talk to secdd after 4 attempts.
default 16:56:39.683834 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.gamed" and identifier "", assigned appld "0"
default 16:56:39.683862 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-
container.com.apple.gamed" and identifier ""
default 16:56:39.683911 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff1123130c0> to generate token
for topic "com.apple.icloud-container.com.apple.cloudpaired" and identifier ""
default 16:56:39.684135 +0200 apsd Failed to talk to secdd after 4 attempts.
default 16:56:39.684275 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.cloudpaired" and identifier "", assigned appld "0"
default 16:56:39.684305 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-
container.com.apple.cloudpaired" and identifier ""
default 16:56:39.684343 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff1121367e0> to generate token
for topic "com.apple.icloud-container.com.apple.callhistory.sync-helper" and identifier
""
default 16:56:39.684556 +0200 apsd Failed to talk to secdd after 4 attempts.
default 16:56:39.684678 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.callhistory.sync-helper" and identifier "", assigned appld "0"
default 16:56:39.684709 +0200 apsd <APSCourier: 0x7ff1122051b0>:

```

Rescheduling request to generate token for topic "com.apple.icloud-
container.com.apple.callhistory.sync-helper" and identifier ""
default 16:56:39.722427 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Outstanding data received: <12000000 3e010001 00020020 bab07809 25f49a70
e9b7a51a f733d458 a166dc92 2bdc165e b2a37d3b 96ccf39a 030014cc 839427a0
44caaa43 000d6910 b4b77f6b 57024b> (length 67)
default 16:56:39.722489 +0200 apsd <APSCourier: 0x7ff1122051b0>: Stream
processing: complete yes, invalid no, length parsed 67, parameters {
    APSProtocolAppTokenGenerateResponseCode = 0;
    APSProtocolAppTokenGenerateResponseToken = <bab07809 25f49a70
e9b7a51a f733d458 a166dc92 2bdc165e b2a37d3b 96ccf39a>;
    APSProtocolAppTokenGenerateResponseTopicHash = <cc839427 a044caaa
43000d69 10b4b77f 6b57024b>;
    APSProtocolCommand = 18;
}
default 16:56:39.722525 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received app token generate response {
    APSProtocolAppTokenGenerateResponseCode = 0;
    APSProtocolAppTokenGenerateResponseToken = <bab07809 25f49a70
e9b7a51a f733d458 a166dc92 2bdc165e b2a37d3b 96ccf39a>;
    APSProtocolAppTokenGenerateResponseTopicHash = <cc839427 a044caaa
43000d69 10b4b77f 6b57024b>;
    APSProtocolCommand = 18;
}
default 16:56:39.722565 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received response for token request for topic com.apple.icloud-
container.com.apple.Safari, appld 0, new token = <bab07809 25f49a70 e9b7a51a
f733d458 a166dc92 2bdc165e b2a37d3b 96ccf39a>
default 16:56:39.722637 +0200 apsd <APSCConnectionServer:
0x7ff10fd23970>: Received token <bab07809 25f49a70 e9b7a51a f733d458
a166dc92 2bdc165e b2a37d3b 96ccf39a> for topic com.apple.icloud-
container.com.apple.Safari with identifier
default 16:56:39.722671 +0200 apsd <APSCConnectionServer:
0x7ff10fd23970>: Sending token <bab07809 25f49a70 e9b7a51a f733d458
a166dc92 2bdc165e b2a37d3b 96ccf39a> for topic com.apple.icloud-
container.com.apple.Safari with identifier
default 16:56:39.722714 +0200 apsd <APSCourier: 0x7ff1122051b0>: Stream
processing: complete no, invalid no, length parsed 0, parameters (null)
default 16:56:39.722772 +0200 apsd Dispatching low priority message:
<OS_xpc_dictionary: <dictionary: 0x7ff10fe2cfa0> { count = 4, transaction: 0,
voucher = 0x0, contents =
    "identifier" => <string: 0x7ff10fe441a0> { length = 0, contents = "" }
    "token" => <data: 0x7ff10fe35290>: { length = 32 bytes, contents =
0xbab0780925f49a70e9b7a51af733d458a166dc922bdc165e... }
    "topic" => <string: 0x7ff10fe30700> { length = 43, contents = "com.apple.icloud-
container.com.apple.Safari" }
    "message-type" => <int64: 0x7ff10fe09f60>: 30
}>
default 16:56:39.722950 +0200 SafariCloudHistoryPushAgent
ApplePushService: <APSCConnection: 0x7ff92b740d2c0> Received token

```

```

<bab07809 25f49a70 e9b7a51a f733d458 a166dc92 2bdc165e b2a37d3b
96ccf39a> forTopic com.apple.icloud-container.com.apple.Safari identifier
default 16:56:39.723037 +0200 SafariCloudHistoryPushAgent
    ApplePushService: <APSCConnection: 0x7f92b740d2c0> calling
<WBSCloudHistoryPushAgent: 0x7f92b740bc60> for received token <bab07809
25f49a70 e9b7a51a f733d458 a166dc92 2bdc165e b2a37d3b 96ccf39a> for topic
com.apple.icloud-container.com.apple.Safari identifier
default 16:56:39.723071 +0200 SafariCloudHistoryPushAgent
    ApplePushService: <APSCConnection: 0x7f92b740d2c0> returned from
<WBSCloudHistoryPushAgent: 0x7f92b740bc60>
didReceiveToken:forTopic:identifier
default 16:56:40.047047 +0200 com.apple.WebKit.WebContent
    0x7fcf3b719160 - PerformanceMonitor::measurePostLoadCPUUsage: Process
was using 0.6% CPU after the page load.
default 16:56:41.196598 +0200 UserEventAgent SUBMITTING: <private>
default 16:56:41.196675 +0200 UserEventAgent Registered XPC Activity:
com.apple.mds.1
default 16:56:41.196809 +0200 DuetHeuristic-BM Submitted Activity:
<private>
default 16:56:41.196997 +0200 DuetHeuristic-BM Activity <private>:
Optimal Score 0.4745 at <private> (Valid Until: <private>)
default 16:56:41.197402 +0200 DuetHeuristic-BM <private>:[
<private> ] sumScores:37.010000, denominator:39.010000, FinalDecision: Can
Proceed FinalScore: 0.948731}
default 16:56:41.197428 +0200 DuetHeuristic-BM '<private>' CurrentScore:
0.948731, ThresholdScore: 0.456722 DecisionToRun:1
default 16:56:41.197466 +0200 DuetHeuristic-BM Running activities :
<private>
default 16:56:41.197823 +0200 UserEventAgent SUBMITTING: <private>
default 16:56:41.197879 +0200 UserEventAgent Registered XPC Activity:
com.apple.mds.2
default 16:56:41.198018 +0200 DuetHeuristic-BM Submitted Activity:
<private>
default 16:56:41.198061 +0200 UserEventAgent SUBMITTING: <private>
default 16:56:41.198116 +0200 UserEventAgent Registered XPC Activity:
com.apple.mds.3
default 16:56:41.198190 +0200 DuetHeuristic-BM Activity <private>:
Optimal Score 0.4745 at <private> (Valid Until: <private>)
default 16:56:41.198295 +0200 UserEventAgent SUBMITTING: <private>
default 16:56:41.198357 +0200 UserEventAgent Registered XPC Activity:
com.apple.mds.0
default 16:56:41.198493 +0200 DuetHeuristic-BM <private>:[
<private> ] sumScores:37.010000, denominator:39.010000, FinalDecision: Can
Proceed FinalScore: 0.948731}
default 16:56:41.198518 +0200 DuetHeuristic-BM '<private>' CurrentScore:
0.948731, ThresholdScore: 0.456722 DecisionToRun:1
default 16:56:41.198543 +0200 DuetHeuristic-BM Running activities :
<private>
default 16:56:41.198647 +0200 UserEventAgent STARTING: <private>
default 16:56:41.198714 +0200 DuetHeuristic-BM Submitted Activity:

```

```

<private>
default 16:56:41.198714 +0200 UserEventAgent STARTING: <private>
default 16:56:41.198866 +0200 DuetHeuristic-BM Activity <private>:
Optimal Score 0.4745 at <private> (Valid Until: <private>)
default 16:56:41.199083 +0200 DuetHeuristic-BM <private>:[
<private> ] sumScores:37.010000, denominator:39.010000, FinalDecision: Can
Proceed FinalScore: 0.948731}
default 16:56:41.199111 +0200 DuetHeuristic-BM '<private>' CurrentScore:
0.948731, ThresholdScore: 0.456722 DecisionToRun:1
default 16:56:41.199141 +0200 DuetHeuristic-BM Running activities :
<private>
default 16:56:41.199279 +0200 UserEventAgent STARTING: <private>
default 16:56:41.199341 +0200 DuetHeuristic-BM Submitted Activity:
<private>
default 16:56:41.199491 +0200 DuetHeuristic-BM Activity <private>:
Optimal Score 0.4745 at <private> (Valid Until: <private>)
default 16:56:41.199724 +0200 DuetHeuristic-BM <private>:[
<private> ] sumScores:37.010000, denominator:39.010000, FinalDecision: Can
Proceed FinalScore: 0.948731}
default 16:56:41.199753 +0200 DuetHeuristic-BM '<private>' CurrentScore:
0.948731, ThresholdScore: 0.456722 DecisionToRun:1
default 16:56:41.199784 +0200 DuetHeuristic-BM Running activities :
<private>
default 16:56:41.199914 +0200 UserEventAgent STARTING: <private>
default 16:56:41.293849 +0200 UserEventAgent Initiating XPC Activity:
com.apple.mds.2
default 16:56:41.293985 +0200 UserEventAgent Initiating XPC Activity:
com.apple.mds.0
default 16:56:41.294094 +0200 UserEventAgent Initiating XPC Activity:
com.apple.mds.1
default 16:56:41.294197 +0200 UserEventAgent Initiating XPC Activity:
com.apple.mds.3
default 16:56:41.296239 +0200 UserEventAgent Completed XPC Activity:
com.apple.mds.1
default 16:56:41.296445 +0200 mds directQueryOpenReply 8196 1795162208
0
default 16:56:41.296496 +0200 mds QueryOpen succeeded (0) for store
<private>
default 16:56:41.296524 +0200 mds directQueryOpenReply 8195 1795162144
0
default 16:56:41.296567 +0200 mds QueryOpen succeeded (0) for store
<private>
default 16:56:41.296581 +0200 UserEventAgent Completed XPC Activity:
com.apple.mds.3
default 16:56:41.296732 +0200 mds directQueryOpenReply 8194 1795162176
0
default 16:56:41.296777 +0200 UserEventAgent Completed XPC Activity:
com.apple.mds.2
default 16:56:41.296918 +0200 mds QueryOpen succeeded (0) for store
<private>

```

default 16:56:41.296969 +0200 mds directQueryFetchResultsReply 8195
1795162144 0

default 16:56:41.297098 +0200 DuetHeuristic-BM COMPLETED <private>!
default 16:56:41.297350 +0200 UserEventAgent Unregistered XPC
Activity: com.apple.mds.3

default 16:56:41.297419 +0200 UserEventAgent Unregistered XPC
Activity: com.apple.mds.1

default 16:56:41.297639 +0200 DuetHeuristic-BM COMPLETED <private>!
default 16:56:41.297737 +0200 mds directQueryFetchResultsReply 8194
1795162176 0

default 16:56:41.297915 +0200 mds directQueryFetchResultsReply 8196
1795162208 0

default 16:56:41.297938 +0200 DuetHeuristic-BM COMPLETED <private>!
default 16:56:41.298530 +0200 UserEventAgent Unregistered XPC
Activity: com.apple.mds.2

default 16:56:41.379956 +0200 UserEventAgent Completed XPC Activity:
com.apple.mds.0

default 16:56:41.380126 +0200 mds directQueryOpenReply 8193 1795162112
0

default 16:56:41.380196 +0200 mds QueryOpen succeeded (0) for store
<private>

default 16:56:41.380341 +0200 DuetHeuristic-BM COMPLETED <private>!
default 16:56:41.380757 +0200 UserEventAgent Unregistered XPC
Activity: com.apple.mds.0

default 16:56:41.684955 +0200 mds directQueryFetchResultsReply 8193
1795162112 0

default 16:56:41.746477 +0200 loginwindow CoreAnimation: warning,
deleted thread with uncommitted CATransaction; set
CA_DEBUG_TRANSACTIONS=1 in environment to log backtraces, or set
CA_ASSERT_MAIN_THREAD_TRANSACTIONS=1 to abort when an implicit
transaction isn't created on a main thread.

default 16:56:41.799363 +0200 AddressBookSourceSync -
sourceShouldRefresh: (null)

default 16:56:41.799412 +0200 AddressBookSourceSync -
serverSyncInProgress returning NO

default 16:56:41.799479 +0200 AddressBookSourceSync
isAccountProperlyInitialized: YES Host: YES User: YES Password: YES

default 16:56:41.799552 +0200 AddressBookSourceSync canTalkToServer:
YES (AcctIsInitialized: YES IsOnline: YES)

default 16:56:41.799588 +0200 AddressBookSourceSync -
sourceShouldRefresh calling [self scheduleFullSync]

default 16:56:41.799632 +0200 AddressBookSourceSync Request to schedule
sync: (null) from thread: <Main>

default 16:56:41.799688 +0200 AddressBookSourceSync -
serverSyncInProgress returning NO

default 16:56:41.799723 +0200 AddressBookSourceSync Scheduling sync
from thread: <Main>

default 16:56:41.799849 +0200 AddressBookSourceSync -
sourceShouldRefresh: (null)

default 16:56:41.799889 +0200 AddressBookSourceSync -

serverSyncInProgress returning NO
default 16:56:41.799932 +0200 AddressBookSourceSync
isAccountProperlyInitialized: YES Host: YES User: YES Password: YES
default 16:56:41.799936 +0200 AddressBookSourceSync -startSync
(<private>) running on thread: <private>
default 16:56:41.799958 +0200 AddressBookSourceSync canTalkToServer:
YES (AcctIsInitialized: YES IsOnline: YES)
default 16:56:41.799978 +0200 AddressBookSourceSync -
serverSyncInProgress returning YES
default 16:56:41.799981 +0200 AddressBookSourceSync -
sourceShouldRefresh calling [self scheduleFullSync]
default 16:56:41.800019 +0200 AddressBookSourceSync Request to schedule
sync: (null) from thread: <Main>
default 16:56:41.800056 +0200 AddressBookSourceSync -
serverSyncInProgress returning NO
default 16:56:41.800089 +0200 AddressBookSourceSync Scheduling sync
from thread: <Main>
default 16:56:41.800149 +0200 AddressBookSourceSync
isAccountProperlyInitialized: YES Host: YES User: YES Password: YES
default 16:56:41.800182 +0200 AddressBookSourceSync canTalkToServer:
YES (AcctIsInitialized: YES IsOnline: YES)
default 16:56:41.800222 +0200 AddressBookSourceSync -startSync
(<private>) running on thread: <private>
default 16:56:41.800252 +0200 AddressBookSourceSync -
serverSyncInProgress returning YES
default 16:56:41.800362 +0200 AddressBookSourceSync
isAccountProperlyInitialized: YES Host: YES User: YES Password: YES
default 16:56:41.800380 +0200 AddressBookSourceSync canTalkToServer:
YES (AcctIsInitialized: YES IsOnline: YES)
default 16:56:41.801851 +0200 AddressBookSourceSync -
clearHomeContainers
default 16:56:41.801917 +0200 AddressBookSourceSync -
clearHomeContainers
default 16:56:41.801931 +0200 AddressBookSourceSync -getHomeInfo:
[_controller containersAtURLs:<private>]
default 16:56:41.801995 +0200 AddressBookSourceSync -getHomeInfo:
[_controller containersAtURLs:<private>]
default 16:56:41.802068 +0200 AddressBookSourceSync -[CDXAccount
clearAuthMethodsTried]
default 16:56:41.802100 +0200 AddressBookSourceSync -[CDXAccount
clearAuthMethodsTried]
default 16:56:41.802258 +0200 AddressBookSourceSync Using cached
_acAccount <private>
default 16:56:41.802282 +0200 AddressBookSourceSync Using cached
_acAccount <private>
default 16:56:41.802506 +0200 AddressBookSourceSync Using cached
_acAccount <private>
default 16:56:41.802530 +0200 AddressBookSourceSync _acAccountIdentifier
= <private>
default 16:56:41.802530 +0200 AddressBookSourceSync Using cached

```

_acAccount <private>
default 16:56:41.802546 +0200 AddressBookSourceSync Using account with
identifier <private>
default 16:56:41.802571 +0200 AddressBookSourceSync Using cached
_acAccount <private>
default 16:56:41.802590 +0200 AddressBookSourceSync We are a the child of
a Gmail account; deferring to parent
default 16:56:41.802606 +0200 AddressBookSourceSync -
acAccountOrParentGoogleAccount: <private>
default 16:56:41.802621 +0200 AddressBookSourceSync -[CDXAccount
oauth2Token]: Returning oauth token <private> for identifier: <private>
default 16:56:41.803006 +0200 AddressBookSourceSync CFNetwork-AOSKit:
Reaching out to AOSKit for X-mobile me token
default 16:56:41.805107 +0200 trustd cert[2]: AnchorTrusted =(leaf)[force]>
0
default 16:56:41.806788 +0200 AddressBookSourceSync CFNetwork-AOSKit:
Applied X-mobile me auth to request
default 16:56:41.807327 +0200 AddressBookSourceSync CFNetwork-AOSKit:
Reaching out to AOSKit for X-mobile me token
default 16:56:41.809373 +0200 trustd cert[2]: AnchorTrusted =(leaf)[force]>
0
default 16:56:41.810176 +0200 com.apple.iCloudHelper AOSKit INFO:
(com.apple.AddressBookSourceSync/10.0) ACCT LOOKUP: Previously performed
ACAccount lookup for user=beyondsemble@gmail.com (nothing found)
default 16:56:41.857608 +0200 com.apple.iCloudHelper 0x7f915722ce30
opened /var/folders/j8/bbhn9g892k14cv1xw2hp2fy80000gn/C//mds/mdsObject.db:
4636 bytes
default 16:56:41.857953 +0200 com.apple.iCloudHelper 0x7f9157216170
opened /Users/craigdenham/Library/Keychains/login.keychain-db: 218248 bytes
default 16:56:41.860311 +0200 com.apple.iCloudHelper AOSKit INFO:
(com.apple.AddressBookSourceSync/10.0) ACCT LOOKUP: No stored info found for
user=beyondsemble@gmail.com (acct=0x57221550)
default 16:56:41.860492 +0200 AddressBookSourceSync CFNetwork-AOSKit:
Failed to get a X-mobile me token from AOSKit
default 16:56:41.915736 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default 16:56:41.930326 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default 16:56:41.930538 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 20, EGID: 20
default 16:56:41.930777 +0200 opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default 16:56:41.937196 +0200 opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default 16:56:41.941407 +0200 AddressBookSourceSync self.homeInfo:
<private>
default 16:56:41.941453 +0200 AddressBookSourceSync self.searchInfo:
<private>
default 16:56:41.941605 +0200
appstoreupdateagent ----- Begin --

```


System Version 10.12.4 (Build 16E195)
"appstoreupdateagent" Version ? (?)

```
-----
default 16:56:41.941635 +0200 appstoreupdateagent
appstoreupdateagent: Starting up (uid = 501)...
default 16:56:41.941667 +0200 appstoreupdateagent
appstoreupdateagent: creating XPC listener
default 16:56:41.941725 +0200 appstoreupdateagent
appstoreupdateagent: resuming connection on startup
default 16:56:41.941790 +0200 appstoreupdateagent
appstoreupdateagent: message send is pending, calling dispatch_main
default 16:56:41.941908 +0200 appstoreupdateagent
appstoreupdateagent: received XPC_TYPE_CONNECTION event on listener
default 16:56:41.941964 +0200 appstoreupdateagent
appstoreupdateagent: resuming connection after event
default 16:56:41.942071 +0200 appstoreupdateagent
appstoreupdateagent: received XPC_TYPE_DICTIONARY event on connection:
<dictionary: 0x7fc8acf00a10> { count = 1, transaction: 1, voucher = 0x7fc8acf00460,
contents =
    "UpdateNotificationsOnly" => <bool: 0x7ffdd7a6aa8>: true
}
default 16:56:41.942129 +0200 appstoreupdateagent
appstoreupdateagent: Sending dictionary to storeagent
default 16:56:41.942210 +0200 appstoreupdateagent      CheckForUpdates:
Starting connection to com.apple.storeagent-xpc
default 16:56:41.942304 +0200 appstoreupdateagent      CheckForUpdates:
Sent dictionary to storeagent
default 16:56:41.944245 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default 16:56:41.944391 +0200 AddressBookSourceSync Local me name:
(null) ll server me: (null)
default 16:56:41.944435 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 20, EGID: 20
default 16:56:41.944485 +0200 AddressBookSourceSync ###
SYNCHRONIZING <private> ###
default 16:56:41.944706 +0200 opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default 16:56:41.947832 +0200 AddressBookSourceSync -_fillCache 1
records: 1 people, 0 groups
default 16:56:41.948112 +0200 AddressBookSourceSync -[CDXAccount
clearAuthMethodsTried]
default 16:56:41.948282 +0200 AddressBookSourceSync Using cached
_acAccount <private>
default 16:56:41.948415 +0200 AddressBookSourceSync Using cached
_acAccount <private>
default 16:56:41.948440 +0200 AddressBookSourceSync _acAccountIdentifier
= <private>
default 16:56:41.948453 +0200 AddressBookSourceSync Using account with
```

```

identifier <private>
default 16:56:41.948490 +0200 AddressBookSourceSync Using cached
_acAccount <private>
default 16:56:41.948519 +0200 AddressBookSourceSync We are a the child of
a Gmail account; deferring to parent
default 16:56:41.948562 +0200 AddressBookSourceSync -
acAccountOrParentGoogleAccount: <private>
default 16:56:41.948625 +0200 AddressBookSourceSync -[CDXAccount
oauth2Token]: Returning oauth token <private> for identifier: <private>
default 16:56:41.949103 +0200 AddressBookSourceSync CFNetwork-AOSKit:
Reaching out to AOSKit for X-mobile me token
default 16:56:41.951144 +0200 trustd cert[2]: AnchorTrusted =(leaf)[force]>
0
default 16:56:41.951742 +0200 opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default 16:56:41.952111 +0200 com.apple.iCloudHelper AOSKit INFO:
(com.apple.AddressBookSourceSync/10.0) ACCT LOOKUP: Previously performed
ACAccount lookup for user=beyondsemble@gmail.com (nothing found)
default 16:56:41.952302 +0200 com.apple.iCloudHelper 0x7f9154e175a0
opened /Users/craigdenham/Library/Keychains/login.keychain-db: 218248 bytes
default 16:56:41.955098 +0200 com.apple.iCloudHelper AOSKit INFO:
(com.apple.AddressBookSourceSync/10.0) ACCT LOOKUP: No stored info found for
user=beyondsemble@gmail.com (acct=0x57114dd0)
default 16:56:41.955285 +0200 AddressBookSourceSync CFNetwork-AOSKit:
Failed to get a X-mobile me token from AOSKit
default 16:56:41.964512 +0200
storelegacy ----- Begin --

```

System Version 10.12.4 (Build 16E195)
"storelegacy" Version ? (?)

```

-----
default 16:56:41.964543 +0200 storelegacy storelegacy: Starting up (uid =
501)...
default 16:56:41.966199 +0200 storelegacy StoreLegacy: Sending
dictionary to storeassetd: {
    allowCriticalUpdatesDelay = 0;
    autoInstalledUpdatesCount = 0;
    checkUpdates = 1;
    criticalUpdatesCount = 0;
    criticalUpdatesRequireRestart = 0;
    installCriticalUpdates = 0;
    osUpdatesAvailable = 0;
    osUpdatesCount = 0;
    osUpdatesRequireRestart = 0;
    updateNotificationsOnly = 1;
}
default 16:56:41.988477 +0200 storeassetd UpdateController: No VPP
Licensed product found, no receipt renewal performed
default 16:56:41.989120 +0200 storeassetd UpdateController:

```

```

updateNotificationsOnly=true, setting updateNotificationsOnly=YES on
<UpdateOperation: 0x7f8413a26740>
default 16:56:41.997714 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default 16:56:42.012208 +0200 AddressBookSourceSync self.homeInfo:
<private>
default 16:56:42.012250 +0200 AddressBookSourceSync self.searchInfo:
<private>
default 16:56:42.019340 +0200 AddressBookSourceSync Local me name:
<private> ll server me: <private>
default 16:56:42.019383 +0200 AddressBookSourceSync ###
SYNCHRONIZING <private> ###
default 16:56:42.042637 +0200 AddressBookSourceSync ###
SYNCHRONIZATION of ALL (<private>), Error (null), Errors (null) ###
default 16:56:42.042658 +0200 AddressBookSourceSync ###
SYNCHRONIZATION CLEANUP ###
default 16:56:42.042688 +0200 AddressBookSourceSync -doSyncWithServer:
saving <private> on <private>
default 16:56:42.043241 +0200 AddressBookSourceSync ** -
preprocessChanges(-willUpdateRecords:): ** 1 records for address book: <private>
Thread: <private>
default 16:56:42.043273 +0200 AddressBookSourceSync -
preprocessChanges(-willUpdateRecords:): inAddressBook: <private>,
writeChangesToServer==NO, IGNORING 1 records
default 16:56:42.043929 +0200 AddressBookSourceSync Posting
kABDatabaseChangedNotification while #saving <ABAddressBookChangesNotifier:
0x7fb6718427c0> (updated: 1, added: 0, deleted: 0): <private>
default 16:56:42.044211 +0200 AddressBookSourceSync Posting
kABDatabaseChangedNotificationPriv while #saving
<ABAddressBookChangesNotifier: 0x7fb6718427c0> (updated: 1, added: 0, deleted:
0): <private>
default 16:56:42.044311 +0200 AppleSpell Rebroadcasting external
notification ABDistributedDatabaseChangedNotification from process
AddressBookSourceSync (<private>)
default 16:56:42.044371 +0200 AppleSpell Rebroadcasting external
notification ABDistributedDatabaseChangedNotificationPriv from process
AddressBookSourceSync (<private>)
default 16:56:42.044525 +0200 CalendarAgent Rebroadcasting external
notification ABDistributedDatabaseChangedNotification from process
AddressBookSourceSync (<private>)
default 16:56:42.044525 +0200 callservicesd Rebroadcasting external
notification ABDistributedDatabaseChangedNotification from process
AddressBookSourceSync (<private>)
default 16:56:42.044573 +0200 AddressBookSourceSync **
didUpdateRecords: ** 1 records for address book: <private> Thread: <private>
default 16:56:42.044584 +0200 callservicesd Rebroadcasting external
notification ABDistributedDatabaseChangedNotificationPriv from process
AddressBookSourceSync (<private>)
default 16:56:42.044606 +0200 AddressBookSourceSync -
postprocessChanges(-didUpdateRecords:): inAddressBook: <private>,

```

```

writeChangesToServer==NO, 1 records
default 16:56:42.044689 +0200 CalINCSERVICE Rebroadcasting external
notification ABDistributedDatabaseChangedNotification from process
AddressBookSourceSync (<private>)
default 16:56:42.044633 +0200 AddressBookSourceSync *** CardDAVSource
mocDidSave ***
default 16:56:42.044787 +0200 CalINCSERVICE Rebroadcasting external
notification ABDistributedDatabaseChangedNotificationPriv from process
AddressBookSourceSync (<private>)
default 16:56:42.044699 +0200 AddressBookSourceSync -doSyncWithServer:
done saving <private> on <private>
default 16:56:42.044757 +0200 AddressBookSourceSync ###
SYNCHRONIZATION DONE ###
default 16:56:42.044957 +0200 soagent Rebroadcasting external notification
ABDistributedDatabaseChangedNotification from process AddressBookSourceSync
(<private>)
default 16:56:42.045053 +0200 AddressBookSourceSync push:
addPushObserver for <private> in <private>
default 16:56:42.045106 +0200 soagent Rebroadcasting external notification
ABDistributedDatabaseChangedNotificationPriv from process
AddressBookSourceSync (<private>)
default 16:56:42.045651 +0200 CalendarAgent Rebroadcasting external
notification ABDistributedDatabaseChangedNotificationPriv from process
AddressBookSourceSync (<private>)
default 16:56:42.046656 +0200 AddressBookSourceSync push:
removePushObserver: removing self <private> uid <private> from center (null)
default 16:56:42.046689 +0200 AddressBookSourceSync push: Push not
enabled. No transports:(null) or keys:(null)
default 16:56:42.046715 +0200 AddressBookSourceSync push: -
setPushIsActive: NO, currently NO
default 16:56:42.048005 +0200 AddressBookSourceSync -startSync
(<private>) done
error 16:56:42.049354 +0200 CalendarAgent warning: dynamic accessors failed
to find @property implementation for 'uniqueId' for entity ABCDGroup while resolving
selector 'uniqueId' on class 'ABCDGroup'. Did you remember to declare it
@dynamic or @synthesized in the @implementation ?
default 16:56:42.053695 +0200 CalINCSERVICE Rebroadcasting external
notification ABDistributedDatabaseChangedNotification from process
AddressBookSourceSync (<private>)
default 16:56:42.053753 +0200 CalINCSERVICE Rebroadcasting external
notification ABDistributedDatabaseChangedNotificationPriv from process
AddressBookSourceSync (<private>)
error 16:56:42.063761 +0200 callservicesd warning: dynamic accessors failed
to find @property implementation for 'uniqueId' for entity ABCDGroup while resolving
selector 'uniqueId' on class 'ABCDGroup'. Did you remember to declare it
@dynamic or @synthesized in the @implementation ?
error 16:56:42.064305 +0200 soagent warning: dynamic accessors failed to find
@property implementation for 'uniqueId' for entity ABCDGroup while resolving
selector 'uniqueId' on class 'ABCDGroup'. Did you remember to declare it
@dynamic or @synthesized in the @implementation ?

```

```

default    16:56:42.064939 +0200    callservicesd    Rebroadcasting external
notification ABDistributedDatabaseChangedNotification from process
AddressBookSourceSync (<private>)
default    16:56:42.065411 +0200    soagent    Rebroadcasting external notification
ABDistributedDatabaseChangedNotification from process AddressBookSourceSync
(<private>)
default    16:56:42.065478 +0200    soagent    Rebroadcasting external notification
ABDistributedDatabaseChangedNotificationPriv from process
AddressBookSourceSync (<private>)
default    16:56:42.092057 +0200    opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default    16:56:42.092223 +0200    opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 20, EGID: 20
default    16:56:42.092494 +0200    opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default    16:56:42.100567 +0200    opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default    16:56:42.102680 +0200    trustd      cert[2]: AnchorTrusted =(leaf)[force]>
0
default    16:56:42.104998 +0200    opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default    16:56:42.105704 +0200    opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default    16:56:42.123865 +0200    trustd      cert[2]: AnchorTrusted =(leaf)[force]>
0
default    16:56:42.158525 +0200    trustd      cert[2]: AnchorTrusted =(leaf)[force]>
0
default    16:56:42.166591 +0200    storeassetd    UpdateOperation: Asserted
BackgroundTask power assertion (returned 0)
default    16:56:42.166646 +0200    trustd      cert[2]: AnchorTrusted =(leaf)[force]>
0
default    16:56:42.166731 +0200    storeassetd    <UpdateOperation:
0x7f8413a26740>: Did not check for updates, stage or auto-update due to
self.shouldUpdateNotificationsOnly=1 on <UpdateOperation: 0x7f8413a26740>
default    16:56:42.174115 +0200    parentalcontrolsd    main [157:] -- <private>
default    16:56:42.175407 +0200    parentalcontrolsd    main [175:] -- <private>
default    16:56:42.177811 +0200    trustd      cert[2]: AnchorTrusted =(leaf)[force]>
0
default    16:56:42.178053 +0200    AddressBookSourceSync - _fillCache 759
records: 756 people, 3 groups
default    16:56:42.178613 +0200    authd      MacOS error: -67050
default    16:56:42.181262 +0200    opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default    16:56:42.181630 +0200    opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default    16:56:42.181719 +0200    opendirectoryd queuing request to connection
- '<private>'
default    16:56:42.183618 +0200    callservicesd    Rebroadcasting external
notification ABDistributedDatabaseChangedNotificationPriv from process
AddressBookSourceSync (<private>)

```

```

default    16:56:42.186031 +0200  AddressBookSourceSync  -[CDXAccount
clearAuthMethodsTried]
default    16:56:42.186228 +0200  AddressBookSourceSync  Using cached
_acAccount <private>
default    16:56:42.186487 +0200  AddressBookSourceSync  Using cached
_acAccount <private>
default    16:56:42.186860 +0200  AddressBookSourceSync  CFNetwork-AOSKit:
Reaching out to AOSKit for X-mobile me token
default    16:56:42.186918 +0200  AddressBookSourceSync  CFNetwork-AOSKit:
Applied X-mobile me auth to request
default    16:56:42.188567 +0200  opendirectoryd  Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default    16:56:42.189113 +0200  parentalcontrolsd  -[ActivityTracker
userLoggedIn] [1188:<private>] -- <private>
default    16:56:42.189190 +0200  parentalcontrolsd  -[ActivityTracker
userLoggedIn] [1200:<private>] -- <private>
default    16:56:42.189664 +0200  opendirectoryd  Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default    16:56:42.189793 +0200  parentalcontrolsd  -[ActivityTracker(ALR)
checkApp:csFlags:] [281:<private>] -- <private>
default    16:56:42.190330 +0200  storeassetd  UpdateOperation:
softwareUpdateDidFinishBackgroundScanWithMessage: removing all critical update
notification (except post-install) due to critical update count being 0
default    16:56:42.190959 +0200  storeassetd  UpdateOperation: Message
tracing com.apple.MacAppStore.autoupdate.operation_run - {
    "darkwake_thermal_emergency_count" = 0;
    "elapsed_time" = 0;
    "is_time_to_autoupdate_and_notify" = no;
    "is_time_to_stage" = no;
    "now_is_later" = no;
    "os_updates_to_install_on_restart" = "";
    result = pass;
    "user_initiated" = no;
    "will_restart" = no;
}
default    16:56:42.191051 +0200  storeassetd  UpdateOperation: Released
BackgroundTask power assertion (returned 0)
default    16:56:42.246231 +0200  UserEventAgent  SUBMITTING: <private>
default    16:56:42.246298 +0200  UserEventAgent  Registered XPC Activity:
com.apple.mds.0
default    16:56:42.246409 +0200  DuetHeuristic-BM  Submitted Activity:
<private>
default    16:56:42.246578 +0200  DuetHeuristic-BM  Activity <private>:
Optimal Score 0.4745 at <private> (Valid Until: <private>)
default    16:56:42.246840 +0200  DuetHeuristic-BM  <private>:[
<private> ] sumScores:37.010000, denominator:39.010000, FinalDecision: Can
Proceed FinalScore: 0.948731}
default    16:56:42.246866 +0200  DuetHeuristic-BM  '<private>' CurrentScore:
0.948731, ThresholdScore: 0.421668 DecisionToRun:1
default    16:56:42.246892 +0200  DuetHeuristic-BM  Running activities :

```

```

<private>
default 16:56:42.247039 +0200 UserEventAgent STARTING: <private>
default 16:56:42.333424 +0200 UserEventAgent Initiating XPC Activity:
com.apple.mds.0
default 16:56:42.388633 +0200 AddressBookSourceSync ###
SYNCHRONIZATION of ALL (<private>), Error (null), Errors (null) ###
default 16:56:42.388648 +0200 AddressBookSourceSync ###
SYNCHRONIZATION CLEANUP ###
default 16:56:42.388684 +0200 AddressBookSourceSync -doSyncWithServer:
saving <private> on <private>
default 16:56:42.388709 +0200 AddressBookSourceSync -doSyncWithServer:
done saving <private> on <private>
default 16:56:42.388794 +0200 AddressBookSourceSync ###
SYNCHRONIZATION DONE ###
default 16:56:42.388834 +0200 AddressBookSourceSync push:
addPushObserver for <private> in <private>
default 16:56:42.389398 +0200 AddressBookSourceSync push:
addPushObserver: No change in push state. self.abPushNotificationCenter:
<private>
default 16:56:42.390735 +0200 AddressBookSourceSync -startSync
(<private>) done
default 16:56:42.525830 +0200 sharingd Rebroadcasting external notification
ABDistributedDatabaseChangedNotification from process AddressBookSourceSync
(<private>)
default 16:56:42.526035 +0200 sharingd Rebroadcasting external notification
ABDistributedDatabaseChangedNotificationPriv from process
AddressBookSourceSync (<private>)
default 16:56:42.801558 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default 16:56:42.801751 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 20, EGID: 20
default 16:56:42.802001 +0200 opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default 16:56:42.806705 +0200 opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default 16:56:42.810956 +0200 opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default 16:56:42.979732 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff112223fd0> to generate token
for topic "com.apple.icloud-container.com.apple.keyboardservicesd" and identifier ""
default 16:56:42.979986 +0200 apsd Failed to talk to secld after 4 attempts.
default 16:56:42.980157 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.keyboardservicesd" and identifier "", assigned appId "0"
default 16:56:42.980249 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff1121367e0> to generate token
for topic "com.apple.icloud-container.com.apple.callhistory.sync-helper" and identifier
""
default 16:56:42.980462 +0200 apsd Failed to talk to secld after 4 attempts.
default 16:56:42.980612 +0200 apsd <APSCourier: 0x7ff1122051b0>:

```

Received request to generate token for topic "com.apple.icloud-container.com.apple.callhistory.sync-helper" and identifier "", assigned appld "0"
default 16:56:42.980638 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-container.com.apple.callhistory.sync-helper" and identifier ""
default 16:56:42.980696 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff10fc39740> to generate token for topic "com.apple.icloud-container.com.apple.gamed" and identifier ""
default 16:56:42.980942 +0200 apsd Failed to talk to secdd after 4 attempts.
default 16:56:42.981082 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-container.com.apple.gamed" and identifier "", assigned appld "0"
default 16:56:42.981114 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-container.com.apple.gamed" and identifier ""
default 16:56:42.981152 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff1123130c0> to generate token for topic "com.apple.icloud-container.com.apple.cloudpaired" and identifier ""
default 16:56:42.981363 +0200 apsd Failed to talk to secdd after 4 attempts.
default 16:56:42.981496 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-container.com.apple.cloudpaired" and identifier "", assigned appld "0"
default 16:56:42.981521 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-container.com.apple.cloudpaired" and identifier ""
default 16:56:42.981556 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff112223fd0> to generate token for topic "com.apple.icloud-container.com.apple.keyboardservicesd" and identifier ""
default 16:56:42.981756 +0200 apsd Failed to talk to secdd after 4 attempts.
default 16:56:42.981888 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-container.com.apple.keyboardservicesd" and identifier "", assigned appld "0"
default 16:56:42.981914 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-container.com.apple.keyboardservicesd" and identifier ""
default 16:56:42.981957 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff10fd23970> to generate token for topic "com.apple.icloud-container.com.apple.Safari" and identifier ""
default 16:56:42.982149 +0200 apsd Failed to talk to secdd after 4 attempts.
default 16:56:42.982272 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-container.com.apple.Safari" and identifier "", assigned appld "0"
default 16:56:42.982298 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-container.com.apple.Safari" and identifier ""
default 16:56:42.982332 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff10fd30340> to generate token for topic "com.apple.idmsauthagent" and identifier ""
default 16:56:42.982519 +0200 apsd Failed to talk to secdd after 4 attempts.
default 16:56:42.982646 +0200 apsd <APSCourier: 0x7ff1122051b0>:


```

Received request to generate token for topic "com.apple.idmsauthagent" and
identifier "", assigned appld "0"
default 16:56:42.982672 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.idmsauthagent" and
identifier ""
default 16:56:42.982706 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff10fc39740> to generate token
for topic "com.apple.icloud-container.com.apple.gamed" and identifier ""
default 16:56:42.982895 +0200 apsd Failed to talk to sec2 after 4 attempts.
default 16:56:42.983016 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.gamed" and identifier "", assigned appld "0"
default 16:56:42.983042 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-
container.com.apple.gamed" and identifier ""
default 16:56:42.983078 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff1123130c0> to generate token
for topic "com.apple.icloud-container.com.apple.cloudpaired" and identifier ""
default 16:56:42.983271 +0200 apsd Failed to talk to sec2 after 4 attempts.
default 16:56:42.983408 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.cloudpaired" and identifier "", assigned appld "0"
default 16:56:42.983435 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-
container.com.apple.cloudpaired" and identifier ""
default 16:56:42.983474 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff1121367e0> to generate token
for topic "com.apple.icloud-container.com.apple.callhistory.sync-helper" and identifier
""
default 16:56:42.983667 +0200 apsd Failed to talk to sec2 after 4 attempts.
default 16:56:42.983793 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.callhistory.sync-helper" and identifier "", assigned appld "0"
default 16:56:42.983819 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-
container.com.apple.callhistory.sync-helper" and identifier ""
default 16:56:43.024647 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Outstanding data received: <12000000 3e010001 00020020 aa34ca56 64b9968b
53115084 73403c1f 31c107ee 5b24c75b 3d66fe43 0ec4b7fc 0300141c bf94f9f9
3cdb3377 7a1d16eb b4a0da63 0f4c12> (length 67)
default 16:56:43.024704 +0200 apsd <APSCourier: 0x7ff1122051b0>: Stream
processing: complete yes, invalid no, length parsed 67, parameters {
    APSProtocolAppTokenGenerateResponseCode = 0;
    APSProtocolAppTokenGenerateResponseToken = <aa34ca56 64b9968b
53115084 73403c1f 31c107ee 5b24c75b 3d66fe43 0ec4b7fc>;
    APSProtocolAppTokenGenerateResponseTopicHash = <1cbf94f9 f93cdb33
777a1d16 ebb4a0da 630f4c12>;
    APSProtocolCommand = 18;
}
default 16:56:43.024740 +0200 apsd <APSCourier: 0x7ff1122051b0>:

```

```

Received app token generate response {
    APSPProtocolAppTokenGenerateResponseCode = 0;
    APSPProtocolAppTokenGenerateResponseToken = <aa34ca56 64b9968b
53115084 73403c1f 31c107ee 5b24c75b 3d66fe43 0ec4b7fc>;
    APSPProtocolAppTokenGenerateResponseTopicHash = <1cbf94f9 f93cdb33
777a1d16 ebb4a0da 630f4c12>;
    APSPProtocolCommand = 18;
}
default 16:56:43.024769 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received response for token request for topic com.apple.icloud-
container.com.apple.keyboardservicesd, appld 0, new token = <aa34ca56 64b9968b
53115084 73403c1f 31c107ee 5b24c75b 3d66fe43 0ec4b7fc>
default 16:56:43.024818 +0200 apsd <APSCConnectionServer:
0x7ff112223fd0>: Received token <aa34ca56 64b9968b 53115084 73403c1f
31c107ee 5b24c75b 3d66fe43 0ec4b7fc> for topic com.apple.icloud-
container.com.apple.keyboardservicesd with identifier
default 16:56:43.024861 +0200 apsd <APSCConnectionServer:
0x7ff112223fd0>: Sending token <aa34ca56 64b9968b 53115084 73403c1f
31c107ee 5b24c75b 3d66fe43 0ec4b7fc> for topic com.apple.icloud-
container.com.apple.keyboardservicesd with identifier
default 16:56:43.024924 +0200 apsd <APSCourier: 0x7ff1122051b0>: Stream
processing: complete no, invalid no, length parsed 0, parameters (null)
default 16:56:43.024985 +0200 apsd Dispatching low priority message:
<OS_xpc_dictionary: <dictionary: 0x7ff10fd39940> { count = 4, transaction: 0,
voucher = 0x0, contents =
    "identifier" => <string: 0x7ff10fd32eb0> { length = 0, contents = "" }
    "token" => <data: 0x7ff10fd3e830>: { length = 32 bytes, contents =
0xaa34ca5664b9968b5311508473403c1f31c107ee5b24c75b... }
    "topic" => <string: 0x7ff10fd3ed00> { length = 54, contents = "com.apple.icloud-
container.com.apple.keyboardservicesd" }
    "message-type" => <int64: 0x7ff10fd399f0>: 30
}>
default 16:56:43.025102 +0200 keyboardservicesd ApplePushService:
<APSCConnection: 0x7f9e86f0e3b0> Received token <aa34ca56 64b9968b
53115084 73403c1f 31c107ee 5b24c75b 3d66fe43 0ec4b7fc> forTopic
com.apple.icloud-container.com.apple.keyboardservicesd identifier
default 16:56:43.025184 +0200 keyboardservicesd ApplePushService:
<APSCConnection: 0x7f9e86f0e3b0> calling <_KSTextReplacementServer:
0x7f9e86f0c7a0> for received token <aa34ca56 64b9968b 53115084 73403c1f
31c107ee 5b24c75b 3d66fe43 0ec4b7fc> for topic com.apple.icloud-
container.com.apple.keyboardservicesd identifier
default 16:56:43.025212 +0200 keyboardservicesd ApplePushService:
<APSCConnection: 0x7f9e86f0e3b0> returned from <_KSTextReplacementServer:
0x7f9e86f0c7a0> didReceiveToken:forTopic:identifier
default 16:56:43.360123 +0200 systemsoundserverd 198:
AudioFileReadPackets:result 0
default 16:56:43.361247 +0200 kernel SandboxViolation:
systemsoundserve(260) deny(1) file-read-metadata /
default 16:56:43.362941 +0200 kernel SandboxViolation:
systemsoundserve(260) deny(1) file-read-metadata /

```

default 16:56:43.363642 +0200 kernel SandboxViolation:
systemsoundserve(260) deny(1) file-read-metadata /

default 16:56:43.364306 +0200 kernel SandboxViolation:
systemsoundserve(260) deny(1) file-read-metadata /

default 16:56:43.372108 +0200 kernel SandboxViolation:
systemsoundserve(260) deny(1) file-read-metadata /

default 16:56:43.372222 +0200 kernel SandboxViolation:
systemsoundserve(260) deny(1) file-read-metadata /

default 16:56:43.372300 +0200 kernel SandboxViolation:
systemsoundserve(260) deny(1) file-read-metadata /

default 16:56:43.372337 +0200 kernel SandboxViolation:
systemsoundserve(260) deny(1) file-read-metadata /

default 16:56:43.377400 +0200 coreaudiod HALS_MIGServer.cpp:
1753:HALS_Object_GetPropertyData_DAI32:
HALS_Object_GetPropertyData_DAI32: the object does not implement the property

default 16:56:43.377506 +0200 systemsoundserverd HALC_ProxyObject.cpp:
184:GetPropertyDataSize: HALC_ProxyObject::GetPropertyDataSize ('stm#', 'inpt',
0, AI32): got an error from the server, 0x77686F3F

default 16:56:43.377547 +0200 coreaudiod HALS_MIGServer.cpp:
1753:HALS_Object_GetPropertyData_DAI32:
HALS_Object_GetPropertyData_DAI32: the object does not implement the property

default 16:56:43.377579 +0200 systemsoundserverd HALC_ProxyObject.cpp:
418:GetPropertyData: HALC_ProxyObject::GetPropertyData ('stm#', 'inpt', 0,
DAI32): got an error from the server, 0x77686F3F

default 16:56:43.378183 +0200 coreaudiod
HALS_IOContextDescription.cpp:
1352:___ZN25HALS_IOContextDescription24PushStreamUsageToEnginesEb_block
_invoke: IOContext 153: pushing 1 output stream(s) to 'AppleHDAEngineOutput:1F,
3,0,1,4:3'

default 16:56:43.378204 +0200 coreaudiod
HALS_IOContextDescription.cpp:
1356:___ZN25HALS_IOContextDescription24PushStreamUsageToEnginesEb_block
_invoke: IOContext 153: output stream[0] => Enabled: 'AppleHDAEngineOutput:1F,
3,0,1,4:3'

default 16:56:43.378774 +0200 coreaudiod HALS_MIGServer.cpp:
1753:HALS_Object_GetPropertyData_DAI32:
HALS_Object_GetPropertyData_DAI32: the object does not implement the property

default 16:56:43.378803 +0200 systemsoundserverd HALC_ProxyObject.cpp:
184:GetPropertyDataSize: HALC_ProxyObject::GetPropertyDataSize ('stm#', 'inpt',
0, AI32): got an error from the server, 0x77686F3F

default 16:56:43.378834 +0200 coreaudiod HALS_MIGServer.cpp:
1753:HALS_Object_GetPropertyData_DAI32:
HALS_Object_GetPropertyData_DAI32: the object does not implement the property

default 16:56:43.378865 +0200 systemsoundserverd HALC_ProxyObject.cpp:
418:GetPropertyData: HALC_ProxyObject::GetPropertyData ('stm#', 'inpt', 0,
DAI32): got an error from the server, 0x77686F3F

default 16:56:43.379750 +0200 coreaudiod
HALS_IOContextDescription.cpp:
1352:___ZN25HALS_IOContextDescription24PushStreamUsageToEnginesEb_block
_invoke: IOContext 154: pushing 1 output stream(s) to 'AppleHDAEngineOutput:1F,

3,0,1,3:2'

default 16:56:43.379768 +0200 coreaudiod
HALS_IOContextDescription.cpp:
1356:___ZN25HALS_IOContextDescription24PushStreamUsageToEnginesEb_block
_invoke: IOContext 154: output stream[0] => Enabled: 'AppleHDAEngineOutput:1F,
3,0,1,3:2'

default 16:56:43.380325 +0200 coreaudiod HALS_MIGServer.cpp:
1753:HALS_Object_GetPropertyData_DAI32:
HALS_Object_GetPropertyData_DAI32: the object does not implement the property
default 16:56:43.380352 +0200 systemsoundserverd HALC_ProxyObject.cpp:
184:GetPropertyDataSize: HALC_ProxyObject::GetPropertyDataSize ('stm#', 'inpt',
0, AI32): got an error from the server, 0x77686F3F
default 16:56:43.380385 +0200 coreaudiod HALS_MIGServer.cpp:
1753:HALS_Object_GetPropertyData_DAI32:
HALS_Object_GetPropertyData_DAI32: the object does not implement the property
default 16:56:43.380412 +0200 systemsoundserverd HALC_ProxyObject.cpp:
418:GetPropertyData: HALC_ProxyObject::GetPropertyData ('stm#', 'inpt', 0,
DAI32): got an error from the server, 0x77686F3F
default 16:56:43.381296 +0200 coreaudiod
HALS_IOContextDescription.cpp:
1352:___ZN25HALS_IOContextDescription24PushStreamUsageToEnginesEb_block
_invoke: IOContext 155: pushing 1 output stream(s) to 'AppleHDAEngineOutput:1F,
3,0,1,2:1'

default 16:56:43.381315 +0200 coreaudiod
HALS_IOContextDescription.cpp:
1356:___ZN25HALS_IOContextDescription24PushStreamUsageToEnginesEb_block
_invoke: IOContext 155: output stream[0] => Enabled: 'AppleHDAEngineOutput:1F,
3,0,1,2:1'

default 16:56:43.381863 +0200 coreaudiod HALS_MIGServer.cpp:
1753:HALS_Object_GetPropertyData_DAI32:
HALS_Object_GetPropertyData_DAI32: the object does not implement the property
default 16:56:43.381893 +0200 systemsoundserverd HALC_ProxyObject.cpp:
184:GetPropertyDataSize: HALC_ProxyObject::GetPropertyDataSize ('stm#', 'inpt',
0, AI32): got an error from the server, 0x77686F3F
default 16:56:43.381925 +0200 coreaudiod HALS_MIGServer.cpp:
1753:HALS_Object_GetPropertyData_DAI32:
HALS_Object_GetPropertyData_DAI32: the object does not implement the property
default 16:56:43.381950 +0200 systemsoundserverd HALC_ProxyObject.cpp:
418:GetPropertyData: HALC_ProxyObject::GetPropertyData ('stm#', 'inpt', 0,
DAI32): got an error from the server, 0x77686F3F
default 16:56:43.382906 +0200 coreaudiod
HALS_IOContextDescription.cpp:
1352:___ZN25HALS_IOContextDescription24PushStreamUsageToEnginesEb_block
_invoke: IOContext 156: pushing 1 output stream(s) to 'AppleHDAEngineOutput:1F,
3,0,1,1:0'

default 16:56:43.382924 +0200 coreaudiod
HALS_IOContextDescription.cpp:
1356:___ZN25HALS_IOContextDescription24PushStreamUsageToEnginesEb_block
_invoke: IOContext 156: output stream[0] => Enabled: 'AppleHDAEngineOutput:1F,
3,0,1,1:0'

default 16:56:43.383511 +0200 kernel SandboxViolation:
 systemsoundserve(260) deny(1) file-read-metadata /
 default 16:56:43.383750 +0200 kernel SandboxViolation:
 systemsoundserve(260) deny(1) file-read-metadata /
 default 16:56:43.384649 +0200 kernel +
 IOAudioEngine[0xffffffff802d608680]::newUserClient(0x0xffffffff802c17daa0,
 0xffffffff802c17daa0, 0x0, 0x0, 0xffffffff81f444bd48)
 default 16:56:43.384654 +0200 kernel +
 IOAudioEngineUserClient[0xffffffff8037c3cd80]::initWithAudioEngine(0xffffffff802d60868
 0, 0xffffffff802c17daa0, 0xffffffff802c17daa0, 0x0, 0x0)
 default 16:56:43.384657 +0200 kernel +-
 IOAudioEngineUserClient[0xffffffff8037c3cd80]::setOnline(0)
 default 16:56:43.384660 +0200 kernel ConnectionID:0x66ce4896
 default 16:56:43.384671 +0200 kernel -
 IOAudioEngineUserClient[0xffffffff8037c3cd80]::initWithAudioEngine(0xffffffff802d60868
 0, 0xffffffff802c17daa0, 0xffffffff802c17daa0, 0x0, 0x0) returns 1
 default 16:56:43.384671 +0200 kernel +-
 IOAudioEngineUserClient::withAudioEngine(0xffffffff802d608680, 0xffffffff802c17daa0,
 0xffffffff802c17daa0, 0x0, 0x0) returns 0xffffffff8037c3cd80
 default 16:56:43.384675 +0200 kernel +
 IOAudioEngine::addUserClientAction(0xffffffff802d608680, 0xffffffff8037c3cd80)
 default 16:56:43.384677 +0200 kernel +-
 IOAudioEngine[0xffffffff802d608680]::addUserClient(0xffffffff8037c3cd80) returns 0x0
 default 16:56:43.384678 +0200 kernel -
 IOAudioEngine::addUserClientAction(0xffffffff802d608680, 0xffffffff8037c3cd80) returns
 0x0
 default 16:56:43.384679 +0200 kernel -
 IOAudioEngine[0xffffffff802d608680]::newUserClient(0x0xffffffff802c17daa0,
 0xffffffff802c17daa0, 0x0, 0x0, 0xffffffff81f444bd48)
 default 16:56:43.384687 +0200 kernel -
 IOAudioEngineUserClient[0xffffffff8037c3cd80]::registerFormatNotification(0xffffffff802d
 141690, 0x100) returns 0x0
 default 16:56:43.384688 +0200 kernel -
 IOAudioEngineUserClient::registerNotificationAction(0xffffffff8037c3cd80,
 0xffffffff802d141690) returns 0x0
 default 16:56:43.384690 +0200 kernel -
 IOAudioEngineUserClient[0xffffffff8037c3cd80]::registerNotificationPort(0xffffffff802d141
 690, 0x0, 0x100) returns 0x0
 default 16:56:43.385246 +0200 kernel +
 IOAudioEngine[0xffffffff802d608200]::newUserClient(0x0xffffffff802c17daa0,
 0xffffffff802c17daa0, 0x0, 0x0, 0xffffffff91f68bbd48)
 default 16:56:43.385248 +0200 kernel +
 IOAudioEngineUserClient[0xffffffff8037d5b6c0]::initWithAudioEngine(0xffffffff802d60820
 0, 0xffffffff802c17daa0, 0xffffffff802c17daa0, 0x0, 0x0)
 default 16:56:43.385250 +0200 kernel +-
 IOAudioEngineUserClient[0xffffffff8037d5b6c0]::setOnline(0)
 default 16:56:43.385255 +0200 kernel ConnectionID:0x43f0f079
 default 16:56:43.385261 +0200 kernel -
 IOAudioEngineUserClient[0xffffffff8037d5b6c0]::initWithAudioEngine(0xffffffff802d60820
 0, 0xffffffff802c17daa0, 0xffffffff802c17daa0, 0x0, 0x0) returns 1

```

default    16:56:43.385262 +0200  kernel    +-
IOAudioEngineUserClient::withAudioEngine(0xffffffff802d608200, 0xffffffff802c17daa0,
0xffffffff802c17daa0, 0x0, 0x0) returns 0xffffffff8037d5b6c0
default    16:56:43.385265 +0200  kernel    +
IOAudioEngine::addUserClientAction(0xffffffff802d608200, 0xffffffff8037d5b6c0)
default    16:56:43.385267 +0200  kernel    +-
IOAudioEngine[0xffffffff802d608200]::addUserClient(0xffffffff8037d5b6c0) returns 0x0
default    16:56:43.385268 +0200  kernel    -
IOAudioEngine::addUserClientAction(0xffffffff802d608200, 0xffffffff8037d5b6c0) returns
0x0
default    16:56:43.385269 +0200  kernel    -
IOAudioEngine[0xffffffff802d608200]::newUserClient(0x0xffffffff802c17daa0,
0xffffffff802c17daa0, 0x0, 0x0, 0xffffffff91f68bbd48)
default    16:56:43.385277 +0200  kernel    -
IOAudioEngineUserClient[0xffffffff8037d5b6c0]::registerFormatNotification(0xffffffff802d
141690, 0x101) returns 0x0
default    16:56:43.385278 +0200  kernel    -
IOAudioEngineUserClient::registerNotificationAction(0xffffffff8037d5b6c0,
0xffffffff802d141690) returns 0x0
default    16:56:43.385279 +0200  kernel    -
IOAudioEngineUserClient[0xffffffff8037d5b6c0]::registerNotificationPort(0xffffffff802d14
1690, 0x0, 0x101) returns 0x0
default    16:56:43.385809 +0200  kernel    +
IOAudioEngine[0xffffffff802c9ce480]::newUserClient(0x0xffffffff802c17daa0,
0xffffffff802c17daa0, 0x0, 0x0, 0xffffffff91f683bd48)
default    16:56:43.385810 +0200  kernel    +
IOAudioEngineUserClient[0xffffffff8037d5b900]::initWithAudioEngine(0xffffffff802c9ce48
0, 0xffffffff802c17daa0, 0xffffffff802c17daa0, 0x0, 0x0)
default    16:56:43.385813 +0200  kernel    +-
IOAudioEngineUserClient[0xffffffff8037d5b900]::setOnline(0)
default    16:56:43.385815 +0200  kernel    ConnectionID:0x15d213e0
default    16:56:43.385818 +0200  kernel    -
IOAudioEngineUserClient[0xffffffff8037d5b900]::initWithAudioEngine(0xffffffff802c9ce48
0, 0xffffffff802c17daa0, 0xffffffff802c17daa0, 0x0, 0x0) returns 1
default    16:56:43.385820 +0200  kernel    +-
IOAudioEngineUserClient::withAudioEngine(0xffffffff802c9ce480, 0xffffffff802c17daa0,
0xffffffff802c17daa0, 0x0, 0x0) returns 0xffffffff8037d5b900
default    16:56:43.385822 +0200  kernel    +
IOAudioEngine::addUserClientAction(0xffffffff802c9ce480, 0xffffffff8037d5b900)
default    16:56:43.385823 +0200  kernel    +-
IOAudioEngine[0xffffffff802c9ce480]::addUserClient(0xffffffff8037d5b900) returns 0x0
default    16:56:43.385824 +0200  kernel    -
IOAudioEngine::addUserClientAction(0xffffffff802c9ce480, 0xffffffff8037d5b900) returns
0x0
default    16:56:43.385825 +0200  kernel    -
IOAudioEngine[0xffffffff802c9ce480]::newUserClient(0x0xffffffff802c17daa0,
0xffffffff802c17daa0, 0x0, 0x0, 0xffffffff91f683bd48)
default    16:56:43.385832 +0200  kernel    -
IOAudioEngineUserClient[0xffffffff8037d5b900]::registerFormatNotification(0xffffffff802d
141690, 0x102) returns 0x0

```

```

default    16:56:43.385833 +0200  kernel    -
IOAudioEngineUserClient::registerNotificationAction(0xffffffff8037d5b900,
0xffffffff802d141690) returns 0x0
default    16:56:43.385835 +0200  kernel    -
IOAudioEngineUserClient[0xffffffff8037d5b900]::registerNotificationPort(0xffffffff802d14
1690, 0x0, 0x102) returns 0x0
default    16:56:43.386318 +0200  kernel    +
IOAudioEngine[0xffffffff802c9ced80]::newUserClient(0x0xffffffff802c17daa0,
0xffffffff802c17daa0, 0x0, 0x0, 0xffffffff91f6973d48)
default    16:56:43.386323 +0200  kernel    +
IOAudioEngineUserClient[0xffffffff8037d5b240]::initWithAudioEngine(0xffffffff802c9ced8
0, 0xffffffff802c17daa0, 0xffffffff802c17daa0, 0x0, 0x0)
default    16:56:43.386325 +0200  kernel    +-
IOAudioEngineUserClient[0xffffffff8037d5b240]::setOnline(0)
default    16:56:43.386326 +0200  kernel    ConnectionID:0xd6d29536
default    16:56:43.386330 +0200  kernel    -
IOAudioEngineUserClient[0xffffffff8037d5b240]::initWithAudioEngine(0xffffffff802c9ced8
0, 0xffffffff802c17daa0, 0xffffffff802c17daa0, 0x0, 0x0) returns 1
default    16:56:43.386330 +0200  kernel    +-
IOAudioEngineUserClient::withAudioEngine(0xffffffff802c9ced80, 0xffffffff802c17daa0,
0xffffffff802c17daa0, 0x0, 0x0) returns 0xffffffff8037d5b240
default    16:56:43.386334 +0200  kernel    +
IOAudioEngine::addUserClientAction(0xffffffff802c9ced80, 0xffffffff8037d5b240)
default    16:56:43.386335 +0200  kernel    +-
IOAudioEngine[0xffffffff802c9ced80]::addUserClient(0xffffffff8037d5b240) returns 0x0
default    16:56:43.386336 +0200  kernel    -
IOAudioEngine::addUserClientAction(0xffffffff802c9ced80, 0xffffffff8037d5b240) returns
0x0
default    16:56:43.386337 +0200  kernel    -
IOAudioEngine[0xffffffff802c9ced80]::newUserClient(0x0xffffffff802c17daa0,
0xffffffff802c17daa0, 0x0, 0x0, 0xffffffff91f6973d48)
default    16:56:43.386346 +0200  kernel    -
IOAudioEngineUserClient[0xffffffff8037d5b240]::registerFormatNotification(0xffffffff802d
141690, 0x103) returns 0x0
default    16:56:43.386347 +0200  kernel    -
IOAudioEngineUserClient::registerNotificationAction(0xffffffff8037d5b240,
0xffffffff802d141690) returns 0x0
default    16:56:43.386349 +0200  kernel    -
IOAudioEngineUserClient[0xffffffff8037d5b240]::registerNotificationPort(0xffffffff802d14
1690, 0x0, 0x103) returns 0x0
default    16:56:43.387213 +0200  coreaudiod
HALS_IOContextDescription.cpp:
1352:___ZN25HALS_IOContextDescription24PushStreamUsageToEnginesEb_block
_invoke: IOContext 156: pushing 1 output stream(s) to 'AppleHDAEngineOutput:1F,
3,0,1,1:0'
default    16:56:43.387233 +0200  coreaudiod
HALS_IOContextDescription.cpp:
1356:___ZN25HALS_IOContextDescription24PushStreamUsageToEnginesEb_block
_invoke: IOContext 156: output stream[0] => Enabled: 'AppleHDAEngineOutput:1F,
3,0,1,1:0'

```

```

default    16:56:43.388314 +0200   coreaudiod
HALS_IOContextDescription.cpp:
1352:___ZN25HALS_IOContextDescription24PushStreamUsageToEnginesEb_block
_invoke: IOContext 156: pushing 1 output stream(s) to 'AppleHDAEngineOutput:1F,
3,0,1,1:0'
default    16:56:43.388335 +0200   coreaudiod
HALS_IOContextDescription.cpp:
1356:___ZN25HALS_IOContextDescription24PushStreamUsageToEnginesEb_block
_invoke: IOContext 156: output stream[0] => Enabled: 'AppleHDAEngineOutput:1F,
3,0,1,1:0'
default    16:56:43.388483 +0200   systemsoundserverd 628: -> Incoming
Request : actionID 4096, inClientPID 459(Console), inBehavior 1,
customVibeDataProvided 0, loop 0, loopPeriod 0.000000, inFlags 0,
inClientCompletionToken 1
default    16:56:43.388653 +0200   systemsoundserverd 203: Data was marked
NON-purgeable for actionID: 4096; this: 0x7fb7d1231f50
default    16:56:43.388728 +0200   systemsoundserverd 929: -> Starting audio :
actionID 4096, volume 1.000000 (user vol 1.000000, client vol scalar 1.000000, CM
vol 1.000000), pan 0.000000
default    16:56:43.389666 +0200   kernel      +
IOAudioEngineUserClient::externalMethod, selector=0x0,  arg0 0x0, arg1
0x10b470000, arg2 0x8010 arg3 0x9c
default    16:56:43.389671 +0200   kernel      scalarInputCount=0x4
structureInputSize 0x0, scalarOutputCount 0x0, structureOutputSize 0x0
default    16:56:43.389685 +0200   kernel      +
IOAudioEngineUserClient::registerBuffer64 0x0 0x10b470000 0x8010 0x9c
default    16:56:43.389687 +0200   kernel      +
IOAudioEngineUserClient::safeRegisterClientBuffer64 0xffffffff81f444bae0
default    16:56:43.389688 +0200   kernel      +
IOAudioEngineUserClient[0xffffffff802e312000]::registerClientBuffer64
(0xffffffff802e164200[1], 0x10b470000, 0x8010, 0x9c)
default    16:56:43.389690 +0200   kernel      null clientBufferSetList
default    16:56:43.389691 +0200   kernel      did not find clientBufferSetList for
ID 0x9c
default    16:56:43.389705 +0200   kernel      clientBuffer-
>mAudioClientBuffer32.sourceBuffer before offset: 0xffffffff81f3750000, offset size: 16
default    16:56:43.389705 +0200   kernel      clientBuffer-
>mAudioClientBuffer32.sourceBuffer after offset: 0xffffffff81f3750010
default    16:56:43.389706 +0200   kernel      null clientBufferSetList
default    16:56:43.389707 +0200   kernel      did not find clientBufferSetList for
ID 0x9c
default    16:56:43.389708 +0200   kernel      creating new
IOAudioClientBufferSet
default    16:56:43.389709 +0200   kernel      output
default    16:56:43.389709 +0200   kernel      !isOnline
default    16:56:43.389710 +0200   kernel      -
IOAudioEngineUserClient::registerClientBuffer64() result 0x0
default    16:56:43.389711 +0200   kernel      -
IOAudioEngineUserClient::safeRegisterClientBuffer64 returns 0x0
default    16:56:43.389712 +0200   kernel      -

```



```

IOAudioEngineUserClient::registerBuffer64 0x0 0x10b470000 0x8010 0x9c returns
0x0
default 16:56:43.389713 +0200 kernel -
IOAudioEngineUserClient::externalMethod returns 0x0
default 16:56:43.389726 +0200 kernel +
IOAudioEngineUserClient::externalMethod, selector=0x3, arg0 0x0, arg1 0x0, arg2
0x0 arg3 0x0
default 16:56:43.389727 +0200 kernel scalarInputCount=0x0
structureInputSize 0x0, scalarOutputCount 0x0, structureOutputSize 0x0
default 16:56:43.389736 +0200 kernel +
IOAudioEngineUserClient[0xffffffff802e312000]::startClient() - 0
default 16:56:43.389737 +0200 kernel audioEngine && !isInactive(). State
= 0
default 16:56:43.389738 +0200 kernel audioEngine->getState() !=
kIOAudioEnginePaused
default 16:56:43.389740 +0200 kernel +-
IOAudioEngineUserClient[0xffffffff802e312000]::setOnline(1)
default 16:56:43.389741 +0200 kernel !isOnline() setting online
default 16:56:43.389743 +0200 kernel +
IOAudioEngine[0xffffffff802c9ced80]::startClient(0xffffffff802e312000)
default 16:56:43.389743 +0200 kernel +
IOAudioEngine[0xffffffff802c9ced80]::incrementActiveUserClients() - 0
default 16:56:43.389745 +0200 kernel +
IOAudioEngine[0xffffffff802c9ced80]::startAudioEngine(state = 0)
default 16:56:43.389747 +0200 kernel +
IOAudioDevice[0xffffffff802d53a000]::protectedCompletePowerStateChange() -
current = 2 - pending = 2
default 16:56:43.389748 +0200 kernel -
IOAudioDevice[0xffffffff802d53a000]::protectedCompletePowerStateChange() -
current = 2 - pending = 2 returns 0x0
default 16:56:43.389750 +0200 kernel +
IOAudioDevice[0xffffffff802d53a000]::protectedCompletePowerStateChange() -
current = 2 - pending = 2
default 16:56:43.389752 +0200 kernel -
IOAudioDevice[0xffffffff802d53a000]::protectedCompletePowerStateChange() -
current = 2 - pending = 2 returns 0x0
default 16:56:43.389753 +0200 kernel +
IOAudioDevice[0xffffffff802d53a000]::audioEngineStarting() -
numRunningAudioEngines = 0
default 16:56:43.389754 +0200 kernel -
IOAudioDevice[0xffffffff802d53a000]::audioEngineStarting() -
numRunningAudioEngines = 1
default 16:56:43.389755 +0200 kernel +-
IOAudioEngine[0xffffffff802c9ced80]::resetStatusBuffer()
default 16:56:43.401126 +0200 kernel +-
IOAudioEngine[0xffffffff802c9ced80]::setState(0x1. oldState=0)
default 16:56:43.401131 +0200 kernel -
IOAudioEngine[0xffffffff802c9ced80]::getTimerInterval()
default 16:56:43.401176 +0200 kernel -
IOAudioEngine[0xffffffff802c9ced80]::startAudioEngine() returns 0x0

```

```

default    16:56:43.401178 +0200   kernel    -
IOAudioEngine[0xffffffff802c9ced80]::incrementActiveUserClients() - 1 returns 0
default    16:56:43.401179 +0200   kernel    -
IOAudioEngine[0xffffffff802c9ced80]::startClient(0xffffffff802e312000) returns 0x0
default    16:56:43.401180 +0200   kernel    engine started
default    16:56:43.401182 +0200   kernel    bufferSet 0xffffffff803811ae60
default    16:56:43.401182 +0200   kernel    output clientBuffer
0xffffffff8037e45af0
default    16:56:43.401184 +0200   kernel    +
IOAudioStream[0xffffffff802e164200]::addClient(0xffffffff8037e45af0)
default    16:56:43.401251 +0200   kernel    -
IOAudioStream[0xffffffff802e164200]::addClient(0xffffffff8037e45af0) returns 0x0
default    16:56:43.401253 +0200   kernel    -
IOAudioEngineUserClient[0xffffffff802e312000]::startClient() - 1 returns 0x0
default    16:56:43.401255 +0200   kernel    -
IOAudioEngineUserClient::externalMethod returns 0x0
default    16:56:43.697521 +0200   UserEventAgent    Completed XPC Activity:
com.apple.mds.0
default    16:56:43.697831 +0200   DuetHeuristic-BM    COMPLETED <private>!
default    16:56:43.698480 +0200   UserEventAgent    Unregistered XPC
Activity: com.apple.mds.0
default    16:56:43.738132 +0200   systemsoundserverd 50: Calling completion
proc for token 101, this 0x7fb7cf406990
default    16:56:43.738156 +0200   systemsoundserverd 236: Audio completed for
mActionID 4096, token 101, elapsed time 349
default    16:56:43.738168 +0200   systemsoundserverd 271: System sound
finished playing, mActionID 4096, token 101, total time 349 ms
default    16:56:43.738228 +0200   systemsoundserverd 308: Number of active
sounds remaining 0
default    16:56:43.749864 +0200   kernel    +
IOAudioEngineUserClient::externalMethod, selector=0x4,  arg0 0x0, arg1 0x0, arg2
0x0 arg3 0x0
default    16:56:43.749869 +0200   kernel    scalarInputCount=0x0
structureInputSize 0x0, scalarOutputCount 0x0, structureOutputSize 0x0
default    16:56:43.749886 +0200   kernel    +
IOAudioStream[0xffffffff802e164200]::removeClient(0xffffffff8037e45af0)
default    16:56:43.749889 +0200   kernel    +-
IOAudioStream[0xffffffff802e164200]::safeLogError kErrorLogDumpCounters
mStreamErrorCountsUpdated=0
default    16:56:43.749890 +0200   kernel    -
IOAudioStream[0xffffffff802e164200]::removeClient(0xffffffff8037e45af0)
default    16:56:43.749894 +0200   kernel    +-
IOAudioEngine[0xffffffff802c9ced80]::decrementActiveUserClients() - 0 returns 0x0
default    16:56:43.749895 +0200   kernel    +-
IOAudioEngine[0xffffffff802c9ced80]::stopClient(0xffffffff802e312000) returns 0x0
default    16:56:43.749897 +0200   kernel    +-
IOAudioEngineUserClient[0xffffffff802e312000]::setOnline(0)
default    16:56:43.749898 +0200   kernel    -
IOAudioEngineUserClient::externalMethod returns 0x0
default    16:56:43.749906 +0200   kernel    +

```

IOAudioEngineUserClient::externalMethod, selector=0x1, arg0 0x10B470000, arg1 0x9c, arg2 0x0 arg3 0x0

default 16:56:43.749907 +0200 kernel scalarInputCount=0x2
structureInputSize 0x0, scalarOutputCount 0x0, structureOutputSize 0x0

default 16:56:43.749916 +0200 kernel +
IOAudioEngineUserClient[0xffffffff802e312000]::unregisterClientBuffer64(0x0xffffffff91f69f3b08, 0x9c)

default 16:56:43.749917 +0200 kernel searching for sourceBuffer
0x10b470000

default 16:56:43.749918 +0200 kernel +-
IOAudioEngineUserClient[0xffffffff802e312000]::removeBufferSet(0xffffffff803811ae60)

default 16:56:43.749919 +0200 kernel +
IOAudioStream[0xffffffff802e164200]::removeClient(0xffffffff8037e45af0)

default 16:56:43.749920 +0200 kernel +-
IOAudioStream[0xffffffff802e164200]::safeLogError kErrorLogDumpCounters
mStreamErrorCountsUpdated=0

default 16:56:43.749921 +0200 kernel -
IOAudioStream[0xffffffff802e164200]::removeClient(0xffffffff8037e45af0)

default 16:56:43.749932 +0200 kernel -
IOAudioEngineUserClient::unregisterClientBuffer64 no sourcebuffer returns 0x0

default 16:56:43.749932 +0200 kernel -
IOAudioEngineUserClient::externalMethod returns 0x0

default 16:56:43.907514 +0200 CommCenter #1
CSIApplInfo.ApplicationActivationObserver: handleLSNotification_sync: Application
exited: <private>

default 16:56:44.888409 +0200 kernel +
IOAudioEngine[0xffffffff802c9ced80]::stopAudioEngine()

default 16:56:44.888620 +0200 kernel +-
IOAudioEngine[0xffffffff802c9ced80]::setState(0x0. oldState=0x1)

default 16:56:44.888672 +0200 kernel +
IOAudioDevice[0xffffffff802d53a000]::audioEngineStopped() -
numRunningAudioEngines = 1

default 16:56:44.888675 +0200 kernel +
IOAudioDevice[0xffffffff802d53a000]::scheduleIdleAudioSleep: idleSleepDelayTime =
ffffffffffffffff

default 16:56:44.888676 +0200 kernel -
IOAudioDevice[0xffffffff802d53a000]::scheduleIdleAudioSleep: idleSleepDelayTime =
ffffffffffffffff

default 16:56:44.888681 +0200 kernel -
IOAudioDevice[0xffffffff802d53a000]::audioEngineStopped() -
numRunningAudioEngines = 0

default 16:56:44.888683 +0200 kernel -
IOAudioEngine[0xffffffff802c9ced80]::stopAudioEngine() returns 0x0

default 16:56:44.888696 +0200 kernel +-
IOAudioEngine[0xffffffff802c9ced80]::setState(0x0. oldState=0)

default 16:56:45.413979 +0200 kernel +-
IOAudioEngine[0xffffffff802d5bc000]::removeUserClient(0xffffffff802f679b40) returns
0x0

default 16:56:45.413984 +0200 kernel +-
IOAudioEngine::removeUserClientAction(0xffffffff802d5bc000, 0xffffffff802f679b40)

returns 0x0

default 16:56:45.413986 +0200 kernel +-

IOAudioEngine[0xffffffff802d5bc000]::clientClosed(0xffffffff802f679b40)

default 16:56:45.413987 +0200 kernel +-

IOAudioEngineUserClient[0xffffffff802f679b40]::clientDied() returns 0x0

default 16:56:45.414022 +0200 kernel +-

IOAudioEngine[0xffffffff802c9ced80]::removeUserClient(0xffffffff802f63f900) returns 0x0

default 16:56:45.414024 +0200 kernel +-

IOAudioEngine::removeUserClientAction(0xffffffff802c9ced80, 0xffffffff802f63f900)

returns 0x0

default 16:56:45.414024 +0200 kernel +-

IOAudioEngine[0xffffffff802c9ced80]::clientClosed(0xffffffff802f63f900)

default 16:56:45.414028 +0200 kernel +-

IOAudioEngineUserClient[0xffffffff802f63f900]::clientDied() returns 0x0

default 16:56:45.414037 +0200 kernel +-

IOAudioEngineUserClient[0xffffffff802f679b40]::stop(0xffffffff802d5bc000)

default 16:56:45.414062 +0200 kernel +-

IOAudioEngine[0xffffffff802c9ce480]::removeUserClient(0xffffffff802ee02000) returns 0x0

default 16:56:45.414064 +0200 kernel +-

IOAudioEngine::removeUserClientAction(0xffffffff802c9ce480, 0xffffffff802ee02000)

returns 0x0

default 16:56:45.414065 +0200 kernel +-

IOAudioEngine[0xffffffff802c9ce480]::clientClosed(0xffffffff802ee02000)

default 16:56:45.414066 +0200 kernel +-

IOAudioEngineUserClient[0xffffffff802ee02000]::clientDied() returns 0x0

default 16:56:45.414083 +0200 kernel +-

IOAudioEngineUserClient[0xffffffff802f63f900]::stop(0xffffffff802c9ced80)

default 16:56:45.414089 +0200 kernel +-

IOAudioEngineUserClient[0xffffffff802ee02000]::stop(0xffffffff802c9ce480)

default 16:56:45.414430 +0200 kernel +-

IOAudioEngine[0xffffffff802d608680]::removeUserClient(0xffffffff802f6b1b40) returns 0x0

default 16:56:45.414431 +0200 kernel +-

IOAudioEngine::removeUserClientAction(0xffffffff802d608680, 0xffffffff802f6b1b40)

returns 0x0

default 16:56:45.414433 +0200 kernel +-

IOAudioEngine[0xffffffff802d608680]::clientClosed(0xffffffff802f6b1b40)

default 16:56:45.414434 +0200 kernel +-

IOAudioEngineUserClient[0xffffffff802f6b1b40]::clientDied() returns 0x0

default 16:56:45.414440 +0200 kernel +-

IOAudioEngineUserClient[0xffffffff802f6b1b40]::stop(0xffffffff802d608680)

default 16:56:45.414496 +0200 kernel +-

IOAudioEngine[0xffffffff802d608200]::removeUserClient(0xffffffff802ee02d80) returns 0x0

default 16:56:45.414499 +0200 kernel +-

IOAudioEngine::removeUserClientAction(0xffffffff802d608200, 0xffffffff802ee02d80)

returns 0x0

default 16:56:45.414499 +0200 kernel +-

IOAudioEngine[0xffffffff802d608200]::clientClosed(0xffffffff802ee02d80)

```

default 16:56:45.414502 +0200 kernel +-
IOAudioEngineUserClient[0xffffffff802ee02d80]::clientDied() returns 0x0
default 16:56:45.414508 +0200 kernel +-
IOAudioEngineUserClient[0xffffffff802ee02d80]::stop(0xffffffff802d608200)
default 16:56:45.415735 +0200 CommCenter #1
CSIApplInfo.ApplicationActivationObserver: handleLSNotification_sync: Application
exited: <private>
default 16:56:45.931624 +0200 parsecd TIC TCP Conn Event
[1:0x7f97a8026a40]: 2 Err(0)
default 16:56:45.931718 +0200 parsecd TIC TCP Conn Cancel
[1:0x7f97a8026a40]
default 16:56:45.931775 +0200 parsecd TIC TCP Conn Destroyed
[1:0x7f97a8026a40]
default 16:56:46.279636 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff1121367e0> to generate token
for topic "com.apple.icloud-container.com.apple.callhistory.sync-helper" and identifier
""
default 16:56:46.279933 +0200 apsd Failed to talk to secnd after 4 attempts.
default 16:56:46.280107 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.callhistory.sync-helper" and identifier "", assigned appld "0"
default 16:56:46.280213 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff10fc39740> to generate token
for topic "com.apple.icloud-container.com.apple.gamed" and identifier ""
default 16:56:46.280488 +0200 apsd Failed to talk to secnd after 4 attempts.
default 16:56:46.280657 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.gamed" and identifier "", assigned appld "0"
default 16:56:46.280683 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-
container.com.apple.gamed" and identifier ""
default 16:56:46.280734 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff1123130c0> to generate token
for topic "com.apple.icloud-container.com.apple.cloudpaired" and identifier ""
default 16:56:46.280920 +0200 apsd Failed to talk to secnd after 4 attempts.
default 16:56:46.281034 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.cloudpaired" and identifier "", assigned appld "0"
default 16:56:46.281064 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-
container.com.apple.cloudpaired" and identifier ""
default 16:56:46.281101 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff112223fd0> to generate token
for topic "com.apple.icloud-container.com.apple.keyboardservicesd" and identifier ""
default 16:56:46.281307 +0200 apsd Failed to talk to secnd after 4 attempts.
default 16:56:46.281445 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.keyboardservicesd" and identifier "", assigned appld "0"
default 16:56:46.281472 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-

```

container.com.apple.keyboardservicesd" and identifier ""

default 16:56:46.281518 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff10fd23970> to generate token
for topic "com.apple.icloud-container.com.apple.Safari" and identifier ""

default 16:56:46.281724 +0200 apsd Failed to talk to secld after 4 attempts.

default 16:56:46.281859 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.Safari" and identifier "", assigned appld "0"

default 16:56:46.281885 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-
container.com.apple.Safari" and identifier ""

default 16:56:46.281928 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff10fd30340> to generate token
for topic "com.apple.idmsauthagent" and identifier ""

default 16:56:46.282160 +0200 apsd Failed to talk to secld after 4 attempts.

default 16:56:46.282278 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.idmsauthagent" and
identifier "", assigned appld "0"

default 16:56:46.282302 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.idmsauthagent" and
identifier ""

default 16:56:46.282340 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff10fc39740> to generate token
for topic "com.apple.icloud-container.com.apple.gamed" and identifier ""

default 16:56:46.282528 +0200 apsd Failed to talk to secld after 4 attempts.

default 16:56:46.282657 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.gamed" and identifier "", assigned appld "0"

default 16:56:46.282684 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-
container.com.apple.gamed" and identifier ""

default 16:56:46.282724 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff1123130c0> to generate token
for topic "com.apple.icloud-container.com.apple.cloudpaired" and identifier ""

default 16:56:46.282910 +0200 apsd Failed to talk to secld after 4 attempts.

default 16:56:46.283034 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.cloudpaired" and identifier "", assigned appld "0"

default 16:56:46.283060 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-
container.com.apple.cloudpaired" and identifier ""

default 16:56:46.283095 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff1121367e0> to generate token
for topic "com.apple.icloud-container.com.apple.callhistory.sync-helper" and identifier
""

default 16:56:46.283283 +0200 apsd Failed to talk to secld after 4 attempts.

default 16:56:46.283400 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.callhistory.sync-helper" and identifier "", assigned appld "0"

default 16:56:46.283424 +0200 apsd <APSCourier: 0x7ff1122051b0>:

```

Rescheduling request to generate token for topic "com.apple.icloud-
container.com.apple.callhistory.sync-helper" and identifier ""
default 16:56:46.322855 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Outstanding data received: <12000000 3e010001 00020020 a3b4c19f ba39b203
57e3c3cc 940abc98 70519617 78ba5fed 17bcb956 0162f9e3 03001481 ea80a8e2
92d1e699 6ce771c2 bb099dc2 84f055> (length 67)
default 16:56:46.322913 +0200 apsd <APSCourier: 0x7ff1122051b0>: Stream
processing: complete yes, invalid no, length parsed 67, parameters {
    APSProtocolAppTokenGenerateResponseCode = 0;
    APSProtocolAppTokenGenerateResponseToken = <a3b4c19f ba39b203
57e3c3cc 940abc98 70519617 78ba5fed 17bcb956 0162f9e3>;
    APSProtocolAppTokenGenerateResponseTopicHash = <81ea80a8 e292d1e6
996ce771 c2bb099d c284f055>;
    APSProtocolCommand = 18;
}
default 16:56:46.322950 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received app token generate response {
    APSProtocolAppTokenGenerateResponseCode = 0;
    APSProtocolAppTokenGenerateResponseToken = <a3b4c19f ba39b203
57e3c3cc 940abc98 70519617 78ba5fed 17bcb956 0162f9e3>;
    APSProtocolAppTokenGenerateResponseTopicHash = <81ea80a8 e292d1e6
996ce771 c2bb099d c284f055>;
    APSProtocolCommand = 18;
}
default 16:56:46.322980 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received response for token request for topic com.apple.icloud-
container.com.apple.callhistory.sync-helper, appld 0, new token = <a3b4c19f
ba39b203 57e3c3cc 940abc98 70519617 78ba5fed 17bcb956 0162f9e3>
default 16:56:46.323028 +0200 apsd <APSCConnectionServer:
0x7ff1121367e0>: Received token <a3b4c19f ba39b203 57e3c3cc 940abc98
70519617 78ba5fed 17bcb956 0162f9e3> for topic com.apple.icloud-
container.com.apple.callhistory.sync-helper with identifier
default 16:56:46.323077 +0200 apsd <APSCConnectionServer:
0x7ff1121367e0>: Sending token <a3b4c19f ba39b203 57e3c3cc 940abc98
70519617 78ba5fed 17bcb956 0162f9e3> for topic com.apple.icloud-
container.com.apple.callhistory.sync-helper with identifier
default 16:56:46.323131 +0200 apsd <APSCourier: 0x7ff1122051b0>: Stream
processing: complete no, invalid no, length parsed 0, parameters (null)
default 16:56:46.323181 +0200 apsd Dispatching low priority message:
<OS_xpc_dictionary: <dictionary: 0x7ff10ff37e50> { count = 4, transaction: 0,
voucher = 0x0, contents =
    "identifier" => <string: 0x7ff10ff37f00> { length = 0, contents = "" }
    "token" => <data: 0x7ff10ff355e0>: { length = 32 bytes, contents =
0xa3b4c19fba39b20357e3c3cc940abc987051961778ba5fed... }
    "topic" => <string: 0x7ff10ff36530> { length = 60, contents = "com.apple.icloud-
container.com.apple.callhistory.sync-helper" }
    "message-type" => <int64: 0x7ff10ff03220>: 30
}>
default 16:56:46.323333 +0200 CallHistorySyncHelper ApplePushService:
<APSCConnection: 0x7ff9c56a187a0> Received token <a3b4c19f ba39b203

```

57e3c3cc 940abc98 70519617 78ba5fed 17bcb956 0162f9e3> forTopic
com.apple.icloud-container.com.apple.callhistory.sync-helper identifier
default 16:56:46.323420 +0200 CallHistorySyncHelper ApplePushService:
<APSCConnection: 0x7f9c56a187a0> calling <CHPushConnectionDelegate:
0x7f9c56a07140> for received token <a3b4c19f ba39b203 57e3c3cc 940abc98
70519617 78ba5fed 17bcb956 0162f9e3> for topic com.apple.icloud-
container.com.apple.callhistory.sync-helper identifier
default 16:56:46.323486 +0200 CallHistorySyncHelper received push token
<private> for <private>:
default 16:56:46.323525 +0200 CallHistorySyncHelper ApplePushService:
<APSCConnection: 0x7f9c56a187a0> returned from <CHPushConnectionDelegate:
0x7f9c56a07140> didReceiveToken:forTopic:identifier
default 16:56:46.441394 +0200 com.apple.WebKit.WebContent
Current memory footprint: 71 MB
default 16:56:46.443430 +0200 com.apple.WebKit.WebContent
Current memory footprint: 59 MB
default 16:56:46.443458 +0200 com.apple.WebKit.WebContent
Current memory footprint: 49 MB
default 16:56:46.443546 +0200 com.apple.WebKit.WebContent
Current memory footprint: 206 MB
default 16:56:46.445220 +0200 com.apple.WebKit.WebContent
Current memory footprint: 47 MB
default 16:56:46.649090 +0200 akd TIC TCP Conn Event [1:0x7fd45fe10ba0]:
2 Err(0)
default 16:56:46.649120 +0200 akd TIC TCP Conn Cancel
[1:0x7fd45fe10ba0]
default 16:56:46.649146 +0200 akd TIC TCP Conn Destroyed
[1:0x7fd45fe10ba0]
default 16:56:46.742415 +0200 com.apple.geod TIC TCP Conn Cancel
[2:0x7f9565c208f0]
default 16:56:46.742486 +0200 com.apple.geod TIC TCP Conn Destroyed
[2:0x7f9565c208f0]
default 16:56:46.946839 +0200 Safari TIC TCP Conn Cancel
[1:0x618000186800]
default 16:56:46.946897 +0200 Safari TIC TCP Conn Destroyed
[1:0x618000186800]
default 16:56:47.584580 +0200 com.apple.WebKit.WebContent
Current memory footprint: 50 MB
default 16:56:47.659985 +0200 com.apple.WebKit.WebContent
Current memory footprint: 21 MB
default 16:56:48.026710 +0200 UserEventAgent
[InitBluetoothUserAgentPlugin] Pointing: 1 Keyboards: 1
default 16:56:48.363419 +0200 imagent Saving database.
default 16:56:48.363447 +0200 imagent IMDReplayStorageController
Destroying database.
default 16:56:48.363463 +0200 imagent IMDReplayStorageController Closed
database.
default 16:56:48.440806 +0200 com.apple.WebKit.Networking
TIC TCP Conn Event [54:0x7fa6468582f0]: 2 Err(0)
default 16:56:48.440838 +0200 com.apple.WebKit.Networking


```

TIC TCP Conn Cancel [54:0x7fa6468582f0]
default 16:56:48.440865 +0200 com.apple.WebKit.Networking
TIC TCP Conn Destroyed [54:0x7fa6468582f0]
default 16:56:48.732289 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default 16:56:48.732451 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 20, EGID: 20
default 16:56:48.732684 +0200 opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default 16:56:48.735385 +0200 opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default 16:56:48.736234 +0200 opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default 16:56:48.744637 +0200 kernel SandboxViolation: fontd(321)
deny(1) file-issue-extension target: /Network/Library class: com.apple.app-
sandbox.read
default 16:56:48.899779 +0200 com.apple.WebKit.Networking
TIC TCP Conn Event [10:0x7fa64682fd60]: 2 Err(0)
default 16:56:48.899809 +0200 com.apple.WebKit.Networking
TIC TCP Conn Cancel [10:0x7fa64682fd60]
default 16:56:48.899833 +0200 com.apple.WebKit.Networking
TIC TCP Conn Destroyed [10:0x7fa64682fd60]
default 16:56:49.347055 +0200 identityservicesd Absinthe cleanup timer
hit!
default 16:56:49.347102 +0200 identityservicesd Cleaning up validation
info
default 16:56:49.347125 +0200 identityservicesd ===== Registration
State =====
default 16:56:49.347138 +0200 identityservicesd Last sent message:
(null)
default 16:56:49.347156 +0200 identityservicesd Last registered: (null)
default 16:56:49.347169 +0200 identityservicesd
default 16:56:49.347181 +0200 identityservicesd Message in Flight:
(null)
default 16:56:49.347193 +0200 identityservicesd Messages queued:
(null)
default 16:56:49.347213 +0200 identityservicesd
default 16:56:49.347228 +0200 identityservicesd Queued Auths:
(null)
default 16:56:49.347240 +0200 identityservicesd Queued Reg:
(null)
default 16:56:49.347286 +0200 identityservicesd Current Auths:
<private>
default 16:56:49.347334 +0200 identityservicesd Current Reg:
<private>
default 16:56:49.347353 +0200 identityservicesd
default 16:56:49.347368 +0200 identityservicesd Building Absinthe: NO
default 16:56:49.347380 +0200 identityservicesd Recent Registrations: 0
default 16:56:49.347404 +0200 identityservicesd
=====

```

default 16:56:49.578716 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff10fc39740> to generate token
for topic "com.apple.icloud-container.com.apple.gamed" and identifier ""
default 16:56:49.578996 +0200 apsd Failed to talk to secd after 4 attempts.
default 16:56:49.579168 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.gamed" and identifier "", assigned appld "0"
default 16:56:49.579259 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff1123130c0> to generate token
for topic "com.apple.icloud-container.com.apple.cloudpaired" and identifier ""
default 16:56:49.579506 +0200 apsd Failed to talk to secd after 4 attempts.
default 16:56:49.579660 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.cloudpaired" and identifier "", assigned appld "0"
default 16:56:49.579686 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-
container.com.apple.cloudpaired" and identifier ""
default 16:56:49.579728 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff112223fd0> to generate token
for topic "com.apple.icloud-container.com.apple.keyboardservicesd" and identifier ""
default 16:56:49.579994 +0200 apsd Failed to talk to secd after 4 attempts.
default 16:56:49.580128 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.keyboardservicesd" and identifier "", assigned appld "0"
default 16:56:49.580153 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-
container.com.apple.keyboardservicesd" and identifier ""
default 16:56:49.580203 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff10fd23970> to generate token
for topic "com.apple.icloud-container.com.apple.Safari" and identifier ""
default 16:56:49.580430 +0200 apsd Failed to talk to secd after 4 attempts.
default 16:56:49.580563 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.Safari" and identifier "", assigned appld "0"
default 16:56:49.580589 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-
container.com.apple.Safari" and identifier ""
default 16:56:49.580647 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff10fd30340> to generate token
for topic "com.apple.idmsauthagent" and identifier ""
default 16:56:49.580841 +0200 apsd Failed to talk to secd after 4 attempts.
default 16:56:49.580988 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.idmsauthagent" and
identifier "", assigned appld "0"
default 16:56:49.581015 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.idmsauthagent" and
identifier ""
default 16:56:49.581062 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff10fc39740> to generate token
for topic "com.apple.icloud-container.com.apple.gamed" and identifier ""

```

default    16:56:49.581257 +0200    apsd Failed to talk to secd after 4 attempts.
default    16:56:49.581391 +0200    apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.gamed" and identifier "", assigned appld "0"
default    16:56:49.581417 +0200    apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-
container.com.apple.gamed" and identifier ""
default    16:56:49.581456 +0200    apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff1123130c0> to generate token
for topic "com.apple.icloud-container.com.apple.cloudpaired" and identifier ""
default    16:56:49.581641 +0200    apsd Failed to talk to secd after 4 attempts.
default    16:56:49.581764 +0200    apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.cloudpaired" and identifier "", assigned appld "0"
default    16:56:49.581790 +0200    apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-
container.com.apple.cloudpaired" and identifier ""
default    16:56:49.581828 +0200    apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff1121367e0> to generate token
for topic "com.apple.icloud-container.com.apple.callhistory.sync-helper" and identifier
""
default    16:56:49.582020 +0200    apsd Failed to talk to secd after 4 attempts.
default    16:56:49.582136 +0200    apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.callhistory.sync-helper" and identifier "", assigned appld "0"
default    16:56:49.582160 +0200    apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-
container.com.apple.callhistory.sync-helper" and identifier ""
default    16:56:49.619902 +0200    apsd <APSCourier: 0x7ff1122051b0>:
Outstanding data received: <12000000 3e010001 00020020 5d0b3bbc 3f21c430
7f673285 b914eccc 05ed2711 e0ec6c08 b2c4ff6d d17beca7 0300143e 29ace1c6
ecc8f1bf e260fba2 2bfba5bf d2fd7d> (length 67)
default    16:56:49.619960 +0200    apsd <APSCourier: 0x7ff1122051b0>: Stream
processing: complete yes, invalid no, length parsed 67, parameters {
    APSProtocolAppTokenGenerateResponseCode = 0;
    APSProtocolAppTokenGenerateResponseToken = <5d0b3bbc 3f21c430 7f673285
b914eccc 05ed2711 e0ec6c08 b2c4ff6d d17beca7>;
    APSProtocolAppTokenGenerateResponseTopicHash = <3e29ace1 c6ecc8f1
bfe260fb a22bfba5 bfd2fd7d>;
    APSProtocolCommand = 18;
}
default    16:56:49.619998 +0200    apsd <APSCourier: 0x7ff1122051b0>:
Received app token generate response {
    APSProtocolAppTokenGenerateResponseCode = 0;
    APSProtocolAppTokenGenerateResponseToken = <5d0b3bbc 3f21c430 7f673285
b914eccc 05ed2711 e0ec6c08 b2c4ff6d d17beca7>;
    APSProtocolAppTokenGenerateResponseTopicHash = <3e29ace1 c6ecc8f1
bfe260fb a22bfba5 bfd2fd7d>;
    APSProtocolCommand = 18;
}

```

```

default 16:56:49.620051 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received response for token request for topic com.apple.icloud-
container.com.apple.gamed, appld 0, new token = <5d0b3bbc 3f21c430 7f673285
b914eccc 05ed2711 e0ec6c08 b2c4ff6d d17beca7>
default 16:56:49.620106 +0200 apsd <APSCConnectionServer:
0x7ff10fc39740>: Received token <5d0b3bbc 3f21c430 7f673285 b914eccc
05ed2711 e0ec6c08 b2c4ff6d d17beca7> for topic com.apple.icloud-
container.com.apple.gamed with identifier
default 16:56:49.620144 +0200 apsd <APSCConnectionServer:
0x7ff10fc39740>: Sending token <5d0b3bbc 3f21c430 7f673285 b914eccc
05ed2711 e0ec6c08 b2c4ff6d d17beca7> for topic com.apple.icloud-
container.com.apple.gamed with identifier
default 16:56:49.620200 +0200 apsd <APSCourier: 0x7ff1122051b0>: Stream
processing: complete no, invalid no, length parsed 0, parameters (null)
default 16:56:49.620250 +0200 apsd Dispatching low priority message:
<OS_xpc_dictionary: <dictionary: 0x7ff10ff11440> { count = 4, transaction: 0,
voucher = 0x0, contents =
    "identifier" => <string: 0x7ff10ff379d0> { length = 0, contents = "" }
    "token" => <data: 0x7ff10ff35890>: { length = 32 bytes, contents =
0x5d0b3bbc3f21c4307f673285b914eccc05ed2711e0ec6c08... }
    "topic" => <string: 0x7ff10ff355e0> { length = 42, contents = "com.apple.icloud-
container.com.apple.gamed" }
    "message-type" => <int64: 0x7ff10ff26860>: 30
}>
default 16:56:49.620395 +0200 gamed ApplePushService:
<APSCConnection 0x7ffb3b8061c0 production (null)> Received token <5d0b3bbc
3f21c430 7f673285 b914eccc 05ed2711 e0ec6c08 b2c4ff6d d17beca7> forTopic
com.apple.icloud-container.com.apple.gamed identifier
default 16:56:49.620478 +0200 gamed ApplePushService:
<APSCConnection 0x7ffb3b8061c0 production (null)> calling
<GKDataRequestManager: 0x7ffb3ba02150> for received token <5d0b3bbc
3f21c430 7f673285 b914eccc 05ed2711 e0ec6c08 b2c4ff6d d17beca7> for topic
com.apple.icloud-container.com.apple.gamed identifier
default 16:56:49.620516 +0200 gamed ApplePushService:
<APSCConnection 0x7ffb3b8061c0 production (null)> returned from
<GKDataRequestManager: 0x7ffb3ba02150> didReceiveToken:forTopic:identifier
default 16:56:49.649505 +0200 akd TIC TCP Conn Event
[3:0x7fd46181e9d0]: 2 Err(0)
default 16:56:49.649531 +0200 akd TIC TCP Conn Cancel
[3:0x7fd46181e9d0]
default 16:56:49.649556 +0200 akd TIC TCP Conn Destroyed
[3:0x7fd46181e9d0]
default 16:56:49.923374 +0200 akd TIC TCP Conn Event [2:0x7fd45fc0b500]:
2 Err(0)
default 16:56:49.923404 +0200 akd TIC TCP Conn Cancel
[2:0x7fd45fc0b500]
default 16:56:49.923431 +0200 akd TIC TCP Conn Destroyed
[2:0x7fd45fc0b500]
default 16:56:50.049495 +0200 com.apple.WebKit.Networking
TIC TCP Conn Event [9:0x7fa646a10cc0]: 2 Err(0)

```

default 16:56:50.049529 +0200 com.apple.WebKit.Networking
TIC TCP Conn Cancel [9:0x7fa646a10cc0]
default 16:56:50.049557 +0200 com.apple.WebKit.Networking
TIC TCP Conn Destroyed [9:0x7fa646a10cc0]
default 16:56:50.259502 +0200 cloudphotosd TIC TCP Conn Cancel
[1:0x7ffb18325b10]
default 16:56:50.259585 +0200 AppleIDAuthAgent TIC TCP Conn Cancel
[1:0x7fd38bc0d830]
default 16:56:50.259569 +0200 cloudphotosd TIC TCP Conn Destroyed
[1:0x7ffb18325b10]
default 16:56:50.259629 +0200 AppleIDAuthAgent TIC TCP Conn Destroyed
[1:0x7fd38bc0d830]
default 16:56:50.437532 +0200 com.apple.CommerceKit.TransactionService
TIC TCP Conn Cancel [2:0x7fe97aa0b0d0]
default 16:56:50.437563 +0200 com.apple.CommerceKit.TransactionService
TIC TCP Conn Cancel [1:0x7fe979518f20]
default 16:56:50.437591 +0200 com.apple.CommerceKit.TransactionService
TIC TCP Conn Destroyed [2:0x7fe97aa0b0d0]
default 16:56:50.437600 +0200 com.apple.CommerceKit.TransactionService
TIC TCP Conn Destroyed [1:0x7fe979518f20]
default 16:56:50.948122 +0200 com.apple.WebKit.Networking
TIC TCP Conn Event [4:0x7fa64691cc90]: 2 Err(0)
default 16:56:50.948153 +0200 com.apple.WebKit.Networking
TIC TCP Conn Cancel [4:0x7fa64691cc90]
default 16:56:50.948181 +0200 com.apple.WebKit.Networking
TIC TCP Conn Destroyed [4:0x7fa64691cc90]
default 16:56:51.445339 +0200 pboard Installing local data provider: (uuid:
90DEDF8B-F282-4439-8C5C-9254E2A40F27 gen: 1 item: 789514 flavor:
'public.utf8-plain-text') for gen: 1 index: 0 item: 789514
default 16:56:51.445787 +0200 pboard Initalizing PBIR Converters
default 16:56:51.446887 +0200 pboard Registering converter for type:
public.url -> UAPBIRPublicURLConverter
default 16:56:51.447325 +0200 pboard [Local Pasteboard] Adding alias:
public.text for type: public.utf8-plain-text
default 16:56:51.448022 +0200 useractivityd [PBOARD CONTROLLER]
Received new client connection: <private>
default 16:56:51.448302 +0200 useractivityd [PBOARD CONTROLLER] Got
type update from client, gen: 1, <private>
default 16:56:51.501953 +0200 pboard Sending pasteboard update to
server: <private>
default 16:56:51.501999 +0200 pboard [Local Pasteboard] Adding alias:
public.text for type: public.utf8-plain-text
default 16:56:51.502253 +0200 useractivityd [PBOARD CONTROLLER] Got
type update from client, gen: 1, <private>
default 16:56:51.562100 +0200 com.apple.WebKit.Networking
TIC TCP Conn Event [7:0x7fa646a0d4c0]: 2 Err(0)
default 16:56:51.562129 +0200 com.apple.WebKit.Networking
TIC TCP Conn Cancel [7:0x7fa646a0d4c0]
default 16:56:51.562156 +0200 com.apple.WebKit.Networking
TIC TCP Conn Destroyed [7:0x7fa646a0d4c0]

default 16:56:51.635519 +0200 com.apple.WebKit.Networking
TIC TCP Conn Event [57:0x7fa646b331c0]: 2 Err(0)

default 16:56:51.635549 +0200 com.apple.WebKit.Networking
TIC TCP Conn Cancel [57:0x7fa646b331c0]

default 16:56:51.635576 +0200 com.apple.WebKit.Networking
TIC TCP Conn Destroyed [57:0x7fa646b331c0]

default 16:56:51.928389 +0200 useractivityd PICKING: E1EB6D99-B1DD-46FE-B5C4-033FC7B9281F/<private> as the current item-to-advertise.

default 16:56:51.973481 +0200 com.apple.WebKit.Networking
TIC TCP Conn Event [58:0x7fa644d6c0e0]: 2 Err(0)

default 16:56:51.973533 +0200 com.apple.WebKit.Networking
TIC TCP Conn Cancel [58:0x7fa644d6c0e0]

default 16:56:51.973596 +0200 com.apple.WebKit.Networking
TIC TCP Conn Destroyed [58:0x7fa644d6c0e0]

default 16:56:52.141204 +0200 com.apple.WebKit.Networking
TIC TCP Conn Event [55:0x7fa644f539b0]: 2 Err(0)

default 16:56:52.141232 +0200 com.apple.WebKit.Networking
TIC TCP Conn Cancel [55:0x7fa644f539b0]

default 16:56:52.141264 +0200 com.apple.WebKit.Networking
TIC TCP Conn Destroyed [55:0x7fa644f539b0]

default 16:56:52.849544 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff1123130c0> to generate token
for topic "com.apple.icloud-container.com.apple.cloudpaired" and identifier ""

default 16:56:52.849781 +0200 apsd 0x7ff10fc3b8b0 opened /Library/
Keychains/apsd.keychain: 606512 bytes

default 16:56:52.850006 +0200 apsd Failed to talk to secld after 4 attempts.

default 16:56:52.850174 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.cloudpaired" and identifier "", assigned appld "0"

default 16:56:52.850287 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff112223fd0> to generate token
for topic "com.apple.icloud-container.com.apple.keyboardservicesd" and identifier ""

default 16:56:52.850548 +0200 apsd Failed to talk to secld after 4 attempts.

default 16:56:52.850713 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.keyboardservicesd" and identifier "", assigned appld "0"

default 16:56:52.850740 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-
container.com.apple.keyboardservicesd" and identifier ""

default 16:56:52.850797 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff10fd23970> to generate token
for topic "com.apple.icloud-container.com.apple.Safari" and identifier ""

default 16:56:52.851013 +0200 apsd Failed to talk to secld after 4 attempts.

default 16:56:52.851163 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.Safari" and identifier "", assigned appld "0"

default 16:56:52.851189 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-
container.com.apple.Safari" and identifier ""

default 16:56:52.851235 +0200 apsd <APSCourier: 0x7ff1122051b0>:

Received request from <APSCConnectionServer: 0x7ff10fd30340> to generate token for topic "com.apple.idmsauthagent" and identifier ""

default 16:56:52.851426 +0200 apsd Failed to talk to secdd after 4 attempts.

default 16:56:52.851553 +0200 apsd <APSCCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.idmsauthagent" and identifier "", assigned appld "0"

default 16:56:52.851578 +0200 apsd <APSCCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.idmsauthagent" and identifier ""

default 16:56:52.851616 +0200 apsd <APSCCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff10fc39740> to generate token for topic "com.apple.icloud-container.com.apple.gamed" and identifier ""

default 16:56:52.851825 +0200 apsd Failed to talk to secdd after 4 attempts.

default 16:56:52.851948 +0200 apsd <APSCCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-container.com.apple.gamed" and identifier "", assigned appld "0"

default 16:56:52.851973 +0200 apsd <APSCCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-container.com.apple.gamed" and identifier ""

default 16:56:52.852006 +0200 apsd <APSCCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff1123130c0> to generate token for topic "com.apple.icloud-container.com.apple.cloudpaired" and identifier ""

default 16:56:52.852182 +0200 apsd Failed to talk to secdd after 4 attempts.

default 16:56:52.852307 +0200 apsd <APSCCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-container.com.apple.cloudpaired" and identifier "", assigned appld "0"

default 16:56:52.852331 +0200 apsd <APSCCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-container.com.apple.cloudpaired" and identifier ""

default 16:56:52.852379 +0200 apsd <APSCCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff1121367e0> to generate token for topic "com.apple.icloud-container.com.apple.callhistory.sync-helper" and identifier ""

default 16:56:52.852558 +0200 apsd Failed to talk to secdd after 4 attempts.

default 16:56:52.852683 +0200 apsd <APSCCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-container.com.apple.callhistory.sync-helper" and identifier "", assigned appld "0"

default 16:56:52.852708 +0200 apsd <APSCCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-container.com.apple.callhistory.sync-helper" and identifier ""

default 16:56:52.896288 +0200 apsd <APSCCourier: 0x7ff1122051b0>:
Outstanding data received: <12000000 3e010001 00020020 969a11b3 c92ef82c 6dc34b56 1479173a 89400837 534ff595 ed2484b6 971e4a42 030014e2 225610d1 b716ac87 094ad02a bd95cb72 7975fb> (length 67)

default 16:56:52.896348 +0200 apsd <APSCCourier: 0x7ff1122051b0>: Stream processing: complete yes, invalid no, length parsed 67, parameters {
APSPProtocolAppTokenGenerateResponseCode = 0;
APSPProtocolAppTokenGenerateResponseToken = <969a11b3 c92ef82c 6dc34b56 1479173a 89400837 534ff595 ed2484b6 971e4a42>;
APSPProtocolAppTokenGenerateResponseTopicHash = <e225610 d1b716ac

```

87094ad0 2abd95cb 727975fb>;
    APSProtocolCommand = 18;
}
default    16:56:52.896384 +0200    apsd <APSCourier: 0x7ff1122051b0>:
Received app token generate response {
    APSProtocolAppTokenGenerateResponseCode = 0;
    APSProtocolAppTokenGenerateResponseToken = <969a11b3 c92ef82c
6dc34b56 1479173a 89400837 534ff595 ed2484b6 971e4a42>;
    APSProtocolAppTokenGenerateResponseTopicHash = <e225610 d1b716ac
87094ad0 2abd95cb 727975fb>;
    APSProtocolCommand = 18;
}
default    16:56:52.896413 +0200    apsd <APSCourier: 0x7ff1122051b0>:
Received response for token request for topic com.apple.icloud-
container.com.apple.cloudpaired, appld 0, new token = <969a11b3 c92ef82c
6dc34b56 1479173a 89400837 534ff595 ed2484b6 971e4a42>
default    16:56:52.896457 +0200    apsd <APSCConnectionServer:
0x7ff1123130c0>: Received token <969a11b3 c92ef82c 6dc34b56 1479173a
89400837 534ff595 ed2484b6 971e4a42> for topic com.apple.icloud-
container.com.apple.cloudpaired with identifier
default    16:56:52.896484 +0200    apsd <APSCConnectionServer:
0x7ff1123130c0>: Sending token <969a11b3 c92ef82c 6dc34b56 1479173a
89400837 534ff595 ed2484b6 971e4a42> for topic com.apple.icloud-
container.com.apple.cloudpaired with identifier
default    16:56:52.896529 +0200    apsd <APSCourier: 0x7ff1122051b0>: Stream
processing: complete no, invalid no, length parsed 0, parameters (null)
default    16:56:52.896608 +0200    apsd Dispatching low priority message:
<OS_xpc_dictionary: <dictionary: 0x7ff10fe2cfa0> { count = 4, transaction: 0,
voucher = 0x0, contents =
    "identifier" => <string: 0x7ff10fe30700> { length = 0, contents = "" }
    "token" => <data: 0x7ff10fe3a570>: { length = 32 bytes, contents =
0x969a11b3c92ef82c6dc34b561479173a89400837534ff595... }
    "topic" => <string: 0x7ff10fe44a20> { length = 47, contents = "com.apple.icloud-
container.com.apple.cloudpaired" }
    "message-type" => <int64: 0x7ff10fe2aa50>: 30
}>
default    16:56:52.896790 +0200    cloudpaired ApplePushService:
<APSCConnection: 0x7fb92c10f9a0> Received token <969a11b3 c92ef82c 6dc34b56
1479173a 89400837 534ff595 ed2484b6 971e4a42> forTopic com.apple.icloud-
container.com.apple.cloudpaired identifier
default    16:56:52.896873 +0200    cloudpaired ApplePushService:
<APSCConnection: 0x7fb92c10f9a0> calling <MPCloudKit: 0x7fb92c305270> for
received token <969a11b3 c92ef82c 6dc34b56 1479173a 89400837 534ff595
ed2484b6 971e4a42> for topic com.apple.icloud-container.com.apple.cloudpaired
identifier
default    16:56:52.896986 +0200    cloudpaired Received per-topic push token
"<969a11b3 c92ef82c 6dc34b56 1479173a 89400837 534ff595 ed2484b6
971e4a42>" for topic "com.apple.icloud-container.com.apple.cloudpaired" identifier ""
on connection <APSCConnection: 0x7fb92c10f9a0>
default    16:56:52.897037 +0200    cloudpaired ApplePushService:

```


<APSCConnection: 0x7fb92c10f9a0> returned from <MPCloudKit: 0x7fb92c305270>
didReceiveToken:forTopic:identifier
default 16:56:53.048637 +0200 com.apple.WebKit.Networking
TIC TCP Conn Event [41:0x7fa64684cab0]: 2 Err(0)
default 16:56:53.048669 +0200 com.apple.WebKit.Networking
TIC TCP Conn Cancel [41:0x7fa64684cab0]
default 16:56:53.048696 +0200 com.apple.WebKit.Networking
TIC TCP Conn Destroyed [41:0x7fa64684cab0]
default 16:56:53.249681 +0200 Safari ENCODE: Caching encoded
userInfo to use until we are marked dirty again, returning encoded result <private>
opts={ LSUserActivityContainsFileProviderURL = 0;
LSUserActivityContainsUnsyncronizedCloudDocs = 0;
UAUserActivityContainsCloudDocsKey = 0;}
default 16:56:53.249739 +0200 parentalcontrolsd ScheduledExit [890:] --
<private>
default 16:56:53.610598 +0200 com.apple.WebKit.Networking
TIC TCP Conn Event [48:0x7fa64681d8d0]: 2 Err(0)
default 16:56:53.610632 +0200 com.apple.WebKit.Networking
TIC TCP Conn Cancel [48:0x7fa64681d8d0]
default 16:56:53.610659 +0200 com.apple.WebKit.Networking
TIC TCP Conn Destroyed [48:0x7fa64681d8d0]
default 16:56:53.813847 +0200 pboard Installing local data provider:
(uuid:A771A939-06EA-468D-8080-18010B8BD887 gen: 2 item: 789514 flavor:
'public.utf8-plain-text') for gen: 2 index: 0 item: 789514
default 16:56:53.813921 +0200 pboard [Local Pasteboard] Adding alias:
public.text for type: public.utf8-plain-text
default 16:56:53.814140 +0200 useractivityd [PBOARD CONTROLLER] Got
type update from client, gen: 2, <private>
default 16:56:53.869290 +0200 pboard Sending pasteboard update to
server: <private>
default 16:56:53.869323 +0200 pboard [Local Pasteboard] Adding alias:
public.text for type: public.utf8-plain-text
default 16:56:53.869539 +0200 useractivityd [PBOARD CONTROLLER] Got
type update from client, gen: 2, <private>
default 16:56:54.313927 +0200 useractivityd PICKING: E1EB6D99-
B1DD-46FE-B5C4-033FC7B9281F/<private> as the current item-to-advertise.
default 16:56:54.944143 +0200 com.apple.WebKit.Networking
TIC TCP Conn Event [47:0x7fa646813760]: 2 Err(0)
default 16:56:54.944174 +0200 com.apple.WebKit.Networking
TIC TCP Conn Cancel [47:0x7fa646813760]
default 16:56:54.944198 +0200 com.apple.WebKit.Networking
TIC TCP Conn Destroyed [47:0x7fa646813760]
default 16:56:55.016159 +0200 com.apple.WebKit.Networking
TIC TCP Conn Event [68:0x7fa64694b2e0]: 2 Err(0)
default 16:56:55.016189 +0200 com.apple.WebKit.Networking
TIC TCP Conn Cancel [68:0x7fa64694b2e0]
default 16:56:55.016215 +0200 com.apple.WebKit.Networking
TIC TCP Conn Destroyed [68:0x7fa64694b2e0]
default 16:56:55.625961 +0200 apsd peer(445) received
XPC_ERROR_CONNECTION_INVALID

default 16:56:55.626293 +0200 ContactsAccountsService "The connection to ACDAccountStore was invalidated."
default 16:56:55.628118 +0200 opendirectoryd disconnect module connection
default 16:56:55.656134 +0200 com.apple.WebKit.Networking
TIC TCP Conn Event [70:0x7fa64692a060]: 2 Err(0)
default 16:56:55.656163 +0200 com.apple.WebKit.Networking
TIC TCP Conn Cancel [70:0x7fa64692a060]
default 16:56:55.656198 +0200 com.apple.WebKit.Networking
TIC TCP Conn Destroyed [70:0x7fa64692a060]
default 16:56:56.142375 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff112223fd0> to generate token
for topic "com.apple.icloud-container.com.apple.keyboardservicesd" and identifier ""
default 16:56:56.142632 +0200 apsd Failed to talk to secld after 4 attempts.
default 16:56:56.142791 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.keyboardservicesd" and identifier "", assigned appld "0"
default 16:56:56.142896 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff10fd23970> to generate token
for topic "com.apple.icloud-container.com.apple.Safari" and identifier ""
default 16:56:56.143081 +0200 apsd Failed to talk to secld after 4 attempts.
default 16:56:56.143224 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.Safari" and identifier "", assigned appld "0"
default 16:56:56.143251 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-
container.com.apple.Safari" and identifier ""
default 16:56:56.143295 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff10fd30340> to generate token
for topic "com.apple.idmsauthagent" and identifier ""
default 16:56:56.143486 +0200 apsd Failed to talk to secld after 4 attempts.
default 16:56:56.143603 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.idmsauthagent" and
identifier "", assigned appld "0"
default 16:56:56.143627 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.idmsauthagent" and
identifier ""
default 16:56:56.143669 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff10fc39740> to generate token
for topic "com.apple.icloud-container.com.apple.gamed" and identifier ""
default 16:56:56.143854 +0200 apsd Failed to talk to secld after 4 attempts.
default 16:56:56.144002 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.gamed" and identifier "", assigned appld "0"
default 16:56:56.144029 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-
container.com.apple.gamed" and identifier ""
default 16:56:56.144076 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff1123130c0> to generate token
for topic "com.apple.icloud-container.com.apple.cloudpaired" and identifier ""
default 16:56:56.144280 +0200 apsd Failed to talk to secld after 4 attempts.

```

default 16:56:56.144411 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.cloudpaired" and identifier "", assigned appld "0"
default 16:56:56.144437 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-
container.com.apple.cloudpaired" and identifier ""
default 16:56:56.144473 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff1121367e0> to generate token
for topic "com.apple.icloud-container.com.apple.callhistory.sync-helper" and identifier
""
default 16:56:56.144660 +0200 apsd Failed to talk to secd after 4 attempts.
default 16:56:56.144786 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.callhistory.sync-helper" and identifier "", assigned appld "0"
default 16:56:56.144812 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-
container.com.apple.callhistory.sync-helper" and identifier ""
default 16:56:56.183538 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Outstanding data received: <12000000 3e010001 00020020 aa34ca56 64b9968b
53115084 73403c1f 31c107ee 5b24c75b 3d66fe43 0ec4b7fc 0300141c bf94f9f9
3cdb3377 7a1d16eb b4a0da63 0f4c12> (length 67)
default 16:56:56.183600 +0200 apsd <APSCourier: 0x7ff1122051b0>: Stream
processing: complete yes, invalid no, length parsed 67, parameters {
    APSProtocolAppTokenGenerateResponseCode = 0;
    APSProtocolAppTokenGenerateResponseToken = <aa34ca56 64b9968b
53115084 73403c1f 31c107ee 5b24c75b 3d66fe43 0ec4b7fc>;
    APSProtocolAppTokenGenerateResponseTopicHash = <1cbf94f9 f93cdb33
777a1d16 ebb4a0da 630f4c12>;
    APSProtocolCommand = 18;
}
default 16:56:56.183639 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received app token generate response {
    APSProtocolAppTokenGenerateResponseCode = 0;
    APSProtocolAppTokenGenerateResponseToken = <aa34ca56 64b9968b
53115084 73403c1f 31c107ee 5b24c75b 3d66fe43 0ec4b7fc>;
    APSProtocolAppTokenGenerateResponseTopicHash = <1cbf94f9 f93cdb33
777a1d16 ebb4a0da 630f4c12>;
    APSProtocolCommand = 18;
}
default 16:56:56.183677 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received response for token request for topic com.apple.icloud-
container.com.apple.keyboardservicesd, appld 0, new token = <aa34ca56 64b9968b
53115084 73403c1f 31c107ee 5b24c75b 3d66fe43 0ec4b7fc>
default 16:56:56.183731 +0200 apsd <APSCConnectionServer:
0x7ff112223fd0>: Received token <aa34ca56 64b9968b 53115084 73403c1f
31c107ee 5b24c75b 3d66fe43 0ec4b7fc> for topic com.apple.icloud-
container.com.apple.keyboardservicesd with identifier
default 16:56:56.183765 +0200 apsd <APSCConnectionServer:
0x7ff112223fd0>: Sending token <aa34ca56 64b9968b 53115084 73403c1f
31c107ee 5b24c75b 3d66fe43 0ec4b7fc> for topic com.apple.icloud-

```

```

container.com.apple.keyboardservicesd with identifier
default 16:56:56.183819 +0200 apsd <APSCourier: 0x7ff1122051b0>: Stream
processing: complete no, invalid no, length parsed 0, parameters (null)
default 16:56:56.183860 +0200 apsd Dispatching low priority message:
<OS_xpc_dictionary: <dictionary: 0x7ff10fd30290> { count = 4, transaction: 0,
voucher = 0x0, contents =
    "identifier" => <string: 0x7ff10fd32eb0> { length = 0, contents = "" }
    "token" => <data: 0x7ff10fd3e850>: { length = 32 bytes, contents =
0xaa34ca5664b9968b5311508473403c1f31c107ee5b24c75b... }
    "topic" => <string: 0x7ff10fd33090> { length = 54, contents = "com.apple.icloud-
container.com.apple.keyboardservicesd" }
    "message-type" => <int64: 0x7ff10fd2f5a0>: 30
}>
default 16:56:56.183992 +0200 keyboardservicesd ApplePushService:
<APSCConnection: 0x7f9e86f0e3b0> Received token <aa34ca56 64b9968b
53115084 73403c1f 31c107ee 5b24c75b 3d66fe43 0ec4b7fc> forTopic
com.apple.icloud-container.com.apple.keyboardservicesd identifier
default 16:56:57.690991 +0200 gamed GKClientProxy: clientForBundleID:
default 16:56:57.693074 +0200 gamed GKClientProxy: clientForBundleID:
default 16:56:57.693096 +0200 gamed GKClientProxy:
updateIfRecentlyInstalled
default 16:56:57.698198 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default 16:56:57.698365 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 20, EGID: 20
default 16:56:57.698599 +0200 opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default 16:56:57.701369 +0200 opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default 16:56:57.740861 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default 16:56:57.741001 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 20, EGID: 20
default 16:56:57.741235 +0200 opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default 16:56:57.745967 +0200 opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default 16:56:57.767000 +0200 useractivityd CLIENT: version=1,
[pid=291/292 uid=501/501 gid=20/20 asid=100008 sb=YES] <private> any=NO
sandbox=YES clientInfo=<private>
default 16:56:57.770120 +0200 TextEdit ENCODE: Caching encoded
userInfo to use until we are marked dirty again, returning encoded result <private>
opts={ LSUserActivityContainsFileProviderURL = 0;
LSUserActivityContainsUnsynchronizedCloudDocs = 0;
UAUserActivityContainsCloudDocsKey = 1;}
default 16:56:57.785656 +0200 TextEdit ENCODE: Caching encoded
userInfo to use until we are marked dirty again, returning encoded result <private>
opts={ LSUserActivityContainsFileProviderURL = 0;
LSUserActivityContainsUnsynchronizedCloudDocs = 0;
UAUserActivityContainsCloudDocsKey = 1;}

```

default 16:56:58.267205 +0200 useractivityd PICKING:
6F135D61-372B-4A67-B164-589D04F20736/<private> as the current item-to-advertise.

default 16:56:58.489766 +0200 cloudpairedZoneCreated read:
MagicCloudPairingAccessoryEncryptionPreferences 1

default 16:56:58.489920 +0200 cloudpaired >>> zoneForSubscription
MagicCloudPairingCustomAccessoryZone

default 16:56:58.493905 +0200 cloudd [Operation 0x7ff286521790]
Initialized with context 0x7ff2882268d0. Background: 0, cellular: 1, QOS: 0x19

default 16:56:58.494053 +0200 cloudd [Operation 0x7ff286511c70]
Initialized with context 0x7ff2882268d0. Background: 0, cellular: 1, QOS: 0x19

default 16:56:58.494253 +0200 cloudd [Operation 0x7ff286521790] Starting operation

default 16:56:58.494297 +0200 cloudd [Operation 0x7ff286511c70] Starting operation

default 16:56:58.495098 +0200 cloudd [Operation 0x7ff286521790]
Operation transitioning from state 1 (cancelled=0, stop=0, error=0)

default 16:56:58.495216 +0200 cloudd [Operation 0x7ff286521790]
Operation is now in state 2

default 16:56:58.495350 +0200 cloudd [Operation 0x7ff286511c70]
Operation transitioning from state 1 (cancelled=0, stop=0, error=0)

default 16:56:58.495411 +0200 cloudd [Operation 0x7ff286725890]
Initialized with context 0x7ff2882268d0. Background: 0, cellular: 1, QOS: 0x19

default 16:56:58.495604 +0200 cloudd [Operation 0x7ff286725890] Starting operation

default 16:56:58.496472 +0200 UserEventAgent SUBMITTING: <private>

default 16:56:58.496527 +0200 UserEventAgent Registered XPC Activity:
com.apple.cloudkit.recordCachePool.expireRecords

default 16:56:58.496638 +0200 DuetHeuristic-BM Submitted Activity:
<private>

default 16:56:58.496798 +0200 DuetHeuristic-BM Activity <private>:
Optimal Score 0.4745 at <private> (Valid Until: <private>)

default 16:56:58.500104 +0200 cloudd [Operation 0x7ff286511c70] Request
0x7ff288237e60 set on operation

default 16:56:58.500251 +0200 cloudd [Request 0x7ff288237e60]
Performing

default 16:56:58.500417 +0200 cloudd [Request 0x7ff288237e60] Getting
URL for the user partition

default 16:56:58.500472 +0200 cloudd [Request 0x7ff288237e60] Getting
configuration

default 16:56:58.500505 +0200 cloudd [Operation 0x7ff286511c70]
Operation is now in state 2

default 16:56:58.500630 +0200 cloudd [Operation 0x7ff286725890]
Operation transitioning from state 1 (cancelled=0, stop=0, error=0)

default 16:56:58.505576 +0200 cloudd [Operation 0x7ff286725890]
Operation is now in state 2

default 16:56:58.505695 +0200 cloudd [Request 0x7ff288237e60] Fetching
container scoped user ID

default 16:56:58.505909 +0200 cloudd [Request 0x7ff288237e60] Getting
device ID

```

default    16:56:58.505930 +0200    cloudd    [Operation 0x7ff286725890]
Operation transitioning from state 2 (cancelled=0, stop=0, error=0)
default    16:56:58.505956 +0200    cloudd    [Operation 0x7ff286725890]
Operation is now in state 5
default    16:56:58.505975 +0200    cloudd    [Operation 0x7ff286725890]
Operation transitioning from state 5 (cancelled=0, stop=0, error=0)
default    16:56:58.506204 +0200    cloudd    PCSIdentitySetCreate: BTPairing {
    kPCSSetupDSID = "<<VALUE>>";
}
default    16:56:58.507402 +0200    opendiroryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default    16:56:58.508265 +0200    cloudd    0x7ff28672d400 opened /var/folders/
j8/bbhn9g892k14cv1xw2hp2fy80000gn/C/com.apple.cloudd//mds/mdsObject.db:
4636 bytes
default    16:56:58.508504 +0200    cloudd    0x7ff286732c40 opened /var/folders/
j8/bbhn9g892k14cv1xw2hp2fy80000gn/C/com.apple.cloudd//mds/mdsDirectory.db:
50744 bytes
default    16:56:58.508891 +0200    cloudd    [Operation 0x7ff286725890]
Operation is now in state 6
default    16:56:58.508917 +0200    cloudd    [Operation 0x7ff286725890]
Operation transitioning from state 6 (cancelled=0, stop=0, error=0)
default    16:56:58.509000 +0200    cloudd    [Operation 0x7ff286725890]
Operation is now in state 7
default    16:56:58.509040 +0200    cloudd    [Operation 0x7ff286725890]
Operation transitioning from state 7 (cancelled=0, stop=0, error=0)
default    16:56:58.509073 +0200    cloudd    [Operation 0x7ff286725890]
Operation is now in state 4294967295
default    16:56:58.509185 +0200    cloudd    [Operation 0x7ff286521790]
Operation transitioning from state 2 (cancelled=0, stop=0, error=0)
default    16:56:58.509370 +0200    cloudd    [Operation 0x7ff286521790]
Request 0x7ff28831bef0 set on operation
default    16:56:58.509530 +0200    cloudd    [Request 0x7ff28831bef0]
Performing
default    16:56:58.509748 +0200    cloudd    [Request 0x7ff28831bef0] Getting
URL for the user partition
default    16:56:58.509778 +0200    cloudd    [Request 0x7ff28831bef0] Getting
configuration
default    16:56:58.509808 +0200    cloudd    [Operation 0x7ff286521790]
Operation is now in state 3
default    16:56:58.509833 +0200    cloudd    [Request 0x7ff28831bef0] Fetching
container scoped user ID
default    16:56:58.509883 +0200    cloudd    [Request 0x7ff28831bef0] Getting
device ID
default    16:56:58.510136 +0200    cloudd    0x7ff288246c80 opened /var/folders/
j8/bbhn9g892k14cv1xw2hp2fy80000gn/C/com.apple.cloudd//mds/mdsDirectory.db:
50744 bytes
default    16:56:58.511420 +0200    cloudd    0x7ff28823d2d0 opened /Users/
craigdenham/Library/Keychains/login.keychain-db: 218248 bytes
default    16:56:58.513881 +0200    cloudd    getting current attributes...
default    16:56:58.513905 +0200    cloudd    filling 16 attributes for type

```

2147483648

```
default 16:56:58.514014 +0200 securityd 0x7fb8fdd1a280(0x7fb8fde138c0) is
unlocked; decoding for makeUnlocked()
default 16:56:58.514267 +0200 cloudd looking at 16 attributes
default 16:56:58.514306 +0200 cloudd finished:
d4503533369075cb51061b76fd7e3564521a5f39a5eee960372e47991803b715
default 16:56:58.516102 +0200 trustd cert[2]: AnchorTrusted =(leaf)[force]>
0
default 16:56:58.516923 +0200 securityd ACL partitionID = <CFArray
0x7fb8ff1052c0 [0x7ffda12eda0]>{type = mutable-small, count = 1, values = (
0 : apple:
)}
default 16:56:58.517045 +0200 securityd ACL partitions match: apple:
default 16:56:58.517397 +0200 cloudd [Request 0x7ff288237e60] Getting
zone gates
default 16:56:58.517454 +0200 cloudd [Request 0x7ff28831bef0] Getting
zone gates
default 16:56:58.517618 +0200 cloudd [Request 0x7ff288237e60] Getting
push token
default 16:56:58.517718 +0200 cloudd Creating a new client context
0x7ff286748650
default 16:56:58.517746 +0200 cloudd [Request 0x7ff288237e60]
Performing request. Background=0, cellular=1
default 16:56:58.522928 +0200 securityd keychain reference in server mode
default 16:56:58.524992 +0200 opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default 16:56:58.525087 +0200 opendirectoryd initiating reconnect of module
connection
default 16:56:58.525466 +0200 opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default 16:56:58.525524 +0200 opendirectoryd queuing request to connection
- '<private>'
default 16:56:58.525730 +0200 opendirectoryd queuing request to connection
- '<private>'
default 16:56:58.531136 +0200 opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
error 16:56:58.532116 +0200 cloudd
nw_parameters_set_source_application_by_bundle_id Failed to convert from bundle
ID (com.apple.cloudpaired) to UUID. This could lead to wrong data usage accounting.
default 16:56:58.532165 +0200 cloudd TIC TCP Conn Start
[1:0x7ff28652a230]
error 16:56:58.558616 +0200 cloudd nw_socket_set_common_sockopts DATA
ACCOUNTING LEAK: Invalid Bundle ID "com.apple.cloudpaired" [M]
default 16:56:58.594654 +0200 cloudd TIC TCP Conn Event
[1:0x7ff28652a230]: 1 Err(0)
default 16:56:58.594677 +0200 cloudd TIC TCP Conn Connected
[1:0x7ff28652a230]: Err(0)
default 16:56:58.594783 +0200 cloudd TIC Enabling TLS
[1:0x7ff28652a230]
default 16:56:58.636603 +0200 cloudd TIC TLS Event [1:0x7ff28652a230]:
```

```

2, Pending(0)
default 16:56:58.638120 +0200 cloudd TIC TLS Event [1:0x7ff28652a230]:
11, Pending(0)
default 16:56:58.639322 +0200 cloudd TIC TLS Event [1:0x7ff28652a230]:
22, Pending(0)
default 16:56:58.639403 +0200 cloudd TIC TLS Event [1:0x7ff28652a230]:
12, Pending(0)
default 16:56:58.639444 +0200 cloudd TIC TLS Event [1:0x7ff28652a230]:
14, Pending(0)
default 16:56:58.650120 +0200 trustd 0x7fe3b4f172a0 opened /var/folders/
j8/bbhn9g892k14cv1xw2hp2fy80000gn/C//mds/mdsObject.db: 4636 bytes
default 16:56:58.652857 +0200 trustd 0x7fe3b6b078d0 opened /var/
folders/j8/bbhn9g892k14cv1xw2hp2fy80000gn/C//mds/mdsDirectory.db: 50744 bytes
default 16:56:58.652994 +0200 trustd 0x7fe3b6b0d370 opened /Users/
craigdenham/Library/Keychains/login.keychain-db: 218248 bytes
default 16:56:58.655214 +0200 trustd 0x7fe3b4c0d3c0 opened /Library/
Keychains/System.keychain: 37732 bytes
default 16:56:58.657369 +0200 trustd 0x7fe3b4e34160 opened /System/
Library/Keychains/SystemRootCertificates.keychain: 385940 bytes
default 16:56:58.662850 +0200 trustd ocsp responder: (null) did not
include status of requested cert
default 16:56:58.664706 +0200 cloudd TIC TLS Trust Result
[1:0x7ff28652a230]: 0
default 16:56:58.710516 +0200 cloudd TIC TLS Event [1:0x7ff28652a230]:
20, Pending(0)
default 16:56:58.710696 +0200 cloudd TIC TCP Conn Event
[1:0x7ff28652a230]: 8 Err(0)
default 16:56:58.710718 +0200 cloudd TIC TLS Handshake Complete
[1:0x7ff28652a230]
default 16:56:58.711047 +0200 cloudd [Request 0x7ff288237e60]
requestForEstablishedConnection
default 16:56:58.714435 +0200 opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default 16:56:58.714499 +0200 opendirectoryd queuing request to connection
- '<private>'
default 16:56:58.714606 +0200 opendirectoryd queuing request to connection
- '<private>'
default 16:56:58.871892 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default 16:56:58.871933 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default 16:56:58.939927 +0200 cloudd [Request 0x7ff288237e60]
URLSession:dataTask:didReceiveResponse:completionHandler:
default 16:56:58.940284 +0200 cloudd [Request 0x7ff288237e60]
URLSession:dataTask:didReceiveData:
default 16:56:58.940875 +0200 cloudd [Request 0x7ff288237e60] Received
a server error (3)
default 16:56:58.941127 +0200 cloudd [Request 0x7ff288237e60] Node
level failure encountered while parsing
default 16:56:58.941907 +0200 cloudd client.trigger:#N Comes to

```



```

_setConfiguration for component 0x35
default 16:56:58.941926 +0200 cloudd client.trigger:#N CCFG has # of
profiles: 0
default 16:56:58.942034 +0200 cloudd [Request 0x7ff288237e60]
URLSession:task:didCompleteWithError:
default 16:56:58.942180 +0200 cloudd [Request 0x7ff288237e60] Finishing
request with no error
default 16:56:58.942432 +0200 cloudd [Operation 0x7ff286511c70] Request
0x0 set on operation
default 16:56:58.942504 +0200 cloudd [Operation 0x7ff286511c70]
Operation transitioning from state 2 (cancelled=0, stop=0, error=0)
default 16:56:58.942571 +0200 cloudd [Operation 0x7ff286511c70]
Operation is now in state 3
default 16:56:58.942597 +0200 cloudd [Operation 0x7ff286511c70]
Operation transitioning from state 3 (cancelled=0, stop=0, error=0)
default 16:56:58.942647 +0200 cloudd [Operation 0x7ff286511c70]
Operation is now in state 4294967295
default 16:56:58.942693 +0200 cloudd [Request 0x7ff28831bef0] Getting
push token
default 16:56:58.942759 +0200 cloudd Creating a new client context
0x7ff286637700
default 16:56:58.942810 +0200 cloudd [Request 0x7ff28831bef0]
Performing request. Background=0, cellular=1
default 16:56:58.943323 +0200 cloudpaired
MagicCloudPairingProtectedAccessoryBlob fetch:error <CKError 0x7fb929602e20:
"Unknown Item" (11/2003); server message = "Record not found"; uuid =
706BC7BA-7A1D-450D-B28B-2B74FDCE81E9; container ID =
"com.apple.bluetooth">
default 16:56:58.943373 +0200 cloudpaired
MagicCloudPairingProtectedAccessoryBlob sending to blued (null)
default 16:56:58.943609 +0200 blued deletedAllMagicCloudDevice
self.gMagicPairingTable (
)
default 16:56:58.945612 +0200 opendiroryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default 16:56:58.945679 +0200 opendiroryd queuing request to connection
- '<private>'
default 16:56:58.945834 +0200 opendiroryd queuing request to connection
- '<private>'
default 16:56:58.952059 +0200 cloudd [Request 0x7ff28831bef0]
requestForEstablishedConnection
default 16:56:58.954004 +0200 opendiroryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default 16:56:58.954075 +0200 opendiroryd queuing request to connection
- '<private>'
default 16:56:58.954205 +0200 opendiroryd queuing request to connection
- '<private>'
default 16:56:59.171398 +0200 cloudd [Request 0x7ff28831bef0]
URLSession:dataTask:didReceiveResponse:completionHandler:
default 16:56:59.171662 +0200 cloudd [Request 0x7ff28831bef0]

```

URLSession:dataTask:didReceiveData:
default 16:56:59.171816 +0200 cloudd [Request 0x7ff28831bef0]
URLSession:task:didCompleteWithError:
default 16:56:59.174162 +0200 cloudd [Request 0x7ff28831bef0] Finishing
request with no error
default 16:56:59.174261 +0200 cloudd [Operation 0x7ff286521790]
Operation transitioning from state 3 (cancelled=0, stop=0, error=0)
default 16:56:59.174290 +0200 cloudd [Operation 0x7ff286521790]
Operation is now in state 4294967295
default 16:56:59.195331 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff10fd23970> to generate token
for topic "com.apple.icloud-container.com.apple.Safari" and identifier ""
default 16:56:59.195641 +0200 apsd Failed to talk to secdd after 4 attempts.
default 16:56:59.195830 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.Safari" and identifier "", assigned appld "0"
default 16:56:59.195962 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff10fd30340> to generate token
for topic "com.apple.idmsauthagent" and identifier ""
default 16:56:59.196211 +0200 apsd Failed to talk to secdd after 4 attempts.
default 16:56:59.196368 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.idmsauthagent" and
identifier "", assigned appld "0"
default 16:56:59.196395 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.idmsauthagent" and
identifier ""
default 16:56:59.196459 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff10fc39740> to generate token
for topic "com.apple.icloud-container.com.apple.gamed" and identifier ""
default 16:56:59.196668 +0200 apsd Failed to talk to secdd after 4 attempts.
default 16:56:59.196820 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.gamed" and identifier "", assigned appld "0"
default 16:56:59.196863 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-
container.com.apple.gamed" and identifier ""
default 16:56:59.196924 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff1123130c0> to generate token
for topic "com.apple.icloud-container.com.apple.cloudpaired" and identifier ""
default 16:56:59.197145 +0200 apsd Failed to talk to secdd after 4 attempts.
default 16:56:59.197286 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.cloudpaired" and identifier "", assigned appld "0"
default 16:56:59.197313 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-
container.com.apple.cloudpaired" and identifier ""
default 16:56:59.197353 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff1121367e0> to generate token
for topic "com.apple.icloud-container.com.apple.callhistory.sync-helper" and identifier
""

```

default    16:56:59.197586 +0200    apsd Failed to talk to secd after 4 attempts.
default    16:56:59.197717 +0200    apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.callhistory.sync-helper" and identifier "", assigned appld "0"
default    16:56:59.197743 +0200    apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-
container.com.apple.callhistory.sync-helper" and identifier ""
default    16:56:59.240839 +0200    apsd <APSCourier: 0x7ff1122051b0>:
Outstanding data received: <12000000 3e010001 00020020 bab07809 25f49a70
e9b7a51a f733d458 a166dc92 2bdc165e b2a37d3b 96ccf39a 030014cc 839427a0
44caaa43 000d6910 b4b77f6b 57024b> (length 67)
default    16:56:59.240898 +0200    apsd <APSCourier: 0x7ff1122051b0>: Stream
processing: complete yes, invalid no, length parsed 67, parameters {
    APSProtocolAppTokenGenerateResponseCode = 0;
    APSProtocolAppTokenGenerateResponseToken = <bab07809 25f49a70
e9b7a51a f733d458 a166dc92 2bdc165e b2a37d3b 96ccf39a>;
    APSProtocolAppTokenGenerateResponseTopicHash = <cc839427 a044caaa
43000d69 10b4b77f 6b57024b>;
    APSProtocolCommand = 18;
}
default    16:56:59.240936 +0200    apsd <APSCourier: 0x7ff1122051b0>:
Received app token generate response {
    APSProtocolAppTokenGenerateResponseCode = 0;
    APSProtocolAppTokenGenerateResponseToken = <bab07809 25f49a70
e9b7a51a f733d458 a166dc92 2bdc165e b2a37d3b 96ccf39a>;
    APSProtocolAppTokenGenerateResponseTopicHash = <cc839427 a044caaa
43000d69 10b4b77f 6b57024b>;
    APSProtocolCommand = 18;
}
default    16:56:59.240971 +0200    apsd <APSCourier: 0x7ff1122051b0>:
Received response for token request for topic com.apple.icloud-
container.com.apple.Safari, appld 0, new token = <bab07809 25f49a70 e9b7a51a
f733d458 a166dc92 2bdc165e b2a37d3b 96ccf39a>
default    16:56:59.241029 +0200    apsd <APSCConnectionServer:
0x7ff10fd23970>: Received token <bab07809 25f49a70 e9b7a51a f733d458
a166dc92 2bdc165e b2a37d3b 96ccf39a> for topic com.apple.icloud-
container.com.apple.Safari with identifier
default    16:56:59.241075 +0200    apsd <APSCConnectionServer:
0x7ff10fd23970>: Sending token <bab07809 25f49a70 e9b7a51a f733d458
a166dc92 2bdc165e b2a37d3b 96ccf39a> for topic com.apple.icloud-
container.com.apple.Safari with identifier
default    16:56:59.241125 +0200    apsd <APSCourier: 0x7ff1122051b0>: Stream
processing: complete no, invalid no, length parsed 0, parameters (null)
default    16:56:59.241171 +0200    apsd Dispatching low priority message:
<OS_xpc_dictionary: <dictionary: 0x7ff10fd30290> { count = 4, transaction: 0,
voucher = 0x0, contents =
    "identifier" => <string: 0x7ff10fd32eb0> { length = 0, contents = "" }
    "token" => <data: 0x7ff10fd31020>: { length = 32 bytes, contents =
0xbab0780925f49a70e9b7a51af733d458a166dc922bdc165e... }
    "topic" => <string: 0x7ff10fd32cd0> { length = 43, contents = "com.apple.icloud-

```

```

container.com.apple.Safari" }
    "message-type" => <int64: 0x7ff10fd33110>: 30
}>
default    16:56:59.241311 +0200    SafariCloudHistoryPushAgent
    ApplePushService: <APSCConnection: 0x7f92b740d2c0> Received token
<bab07809 25f49a70 e9b7a51a f733d458 a166dc92 2bdc165e b2a37d3b
96ccf39a> forTopic com.apple.icloud-container.com.apple.Safari identifier
default    16:57:01.946065 +0200    filecoordinationd    Added presenter
99F1E8F3-3E20-4CAF-A9B0-B7C04A8D9A27
default    16:57:01.946124 +0200    filecoordinationd    Ignored new presenter
99F1E8F3-3E20-4CAF-A9B0-B7C04A8D9A27, because one with the same ID
already exists
default    16:57:01.948627 +0200    opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default    16:57:01.948785 +0200    opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 20, EGID: 20
default    16:57:01.949008 +0200    opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default    16:57:01.953662 +0200    opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default    16:57:01.960776 +0200    trustd    cert[2]: AnchorTrusted =(leaf)[force]>
0
default    16:57:01.974130 +0200    trustd    cert[2]: AnchorTrusted =(leaf)[force]>
0
error 16:57:01.985101 +0200    TextEdit    Detected missing constraints for
<private>. It cannot be placed because there are not enough constraints to fully
define the size and origin. Add the missing constraints, or set
translatesAutoresizingMaskIntoConstraints=YES and constraints will be generated
for you. If this view is laid out manually on macOS 10.12 and later, you may choose
to not call [super layout] from your override. Set a breakpoint on
DETECTED_MISSING_CONSTRAINTS to debug. This error will only be logged
once.
default    16:57:01.985294 +0200    trustd    cert[2]: AnchorTrusted =(leaf)[force]>
0
default    16:57:01.992658 +0200    filecoordinationd    Added presenter
6726FA12-B1BD-4020-A027-2FCA8CE32774
default    16:57:02.007212 +0200    opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default    16:57:02.019184 +0200
com.apple.appkit.xpc.openAndSavePanelService    got a connection for:
com.apple.cache_delete
default    16:57:02.019391 +0200
com.apple.appkit.xpc.openAndSavePanelService    got proxy: <private> for
service: com.apple.cache_delete
default    16:57:02.019617 +0200    deleted    listener: <private>
default    16:57:02.019640 +0200    deleted    Skipping entitlement check...
default    16:57:02.019800 +0200    deleted    Skipping entitlement check...
default    16:57:02.019878 +0200    deleted    returning cached results, and
asynchronously refreshing any stale results
default    16:57:02.019946 +0200    deleted    volume: <private>, total:

```

12411152402

```
default    16:57:02.020017 +0200    deleted    CACHE_DELETE_URGENCY: 3
default    16:57:02.020043 +0200    deleted    urgency: 3, urgencyLimit: 3
default    16:57:02.020161 +0200    deleted    callingProcess: (null), refreshAll is
FALSE, servicesToQuery: <private>
default    16:57:02.020206 +0200
com.apple.appkit.xpc.openAndSavePanelService    setting target uid to: 501 for
service: com.apple.cache_delete
default    16:57:02.020190 +0200    deleted    [<private>] no servicesToCount.
refreshAll: FALSE
default    16:57:02.020230 +0200
com.apple.appkit.xpc.openAndSavePanelService    connection invalidated
default    16:57:02.020231 +0200    deleted    newConnection invalidated
default    16:57:02.020251 +0200    deleted    PurgeableSpace result: <private>
default    16:57:02.020426 +0200    deleted    SYNC purgeable op results:
<private>
default    16:57:02.021271 +0200
com.apple.appkit.xpc.openAndSavePanelService    got a connection for:
com.apple.cache_delete
default    16:57:02.021390 +0200
com.apple.appkit.xpc.openAndSavePanelService    got proxy: <private> for
service: com.apple.cache_delete
default    16:57:02.021533 +0200    deleted    listener: <private>
default    16:57:02.021570 +0200    deleted    Skipping entitlement check...
default    16:57:02.021746 +0200    deleted    Skipping entitlement check...
default    16:57:02.021827 +0200    deleted    returning cached results, and
asynchronously refreshing any stale results
default    16:57:02.021882 +0200    deleted    volume: <private>, total:
12411152402
default    16:57:02.021933 +0200    deleted    CACHE_DELETE_URGENCY: 3
default    16:57:02.021963 +0200    deleted    urgency: 3, urgencyLimit: 3
default    16:57:02.022067 +0200    deleted    callingProcess: (null), refreshAll is
FALSE, servicesToQuery: <private>
default    16:57:02.022059 +0200
com.apple.appkit.xpc.openAndSavePanelService    setting target uid to: 501 for
service: com.apple.cache_delete
default    16:57:02.022081 +0200    deleted    newConnection invalidated
default    16:57:02.022080 +0200
com.apple.appkit.xpc.openAndSavePanelService    connection invalidated
default    16:57:02.022096 +0200    deleted    [<private>] no servicesToCount.
refreshAll: FALSE
default    16:57:02.022145 +0200    deleted    PurgeableSpace result: <private>
default    16:57:02.022290 +0200    deleted    SYNC purgeable op results:
<private>
default    16:57:02.022343 +0200
com.apple.appkit.xpc.openAndSavePanelService    got a connection for:
com.apple.cache_delete
default    16:57:02.022410 +0200
com.apple.appkit.xpc.openAndSavePanelService    got proxy: <private> for
service: com.apple.cache_delete
```

default	16:57:02.022527 +0200	deleted	listener: <private>
default	16:57:02.022562 +0200	deleted	Skipping entitlement check...
default	16:57:02.022690 +0200	deleted	Skipping entitlement check...
default	16:57:02.022745 +0200	deleted	returning cached results, and
asynchronously refreshing any stale results			
default	16:57:02.022786 +0200	deleted	volume: <private>, total:
12411152402			
default	16:57:02.022847 +0200	deleted	CACHE_DELETE_URGENCY: 3
default	16:57:02.022875 +0200	deleted	urgency: 3, urgencyLimit: 3
default	16:57:02.022944 +0200		
com.apple.appkit.xpc.openAndSavePanelService			setting target uid to: 501 for
service: com.apple.cache_delete			
default	16:57:02.022974 +0200	deleted	newConnection invalidated
default	16:57:02.022966 +0200		
com.apple.appkit.xpc.openAndSavePanelService			connection invalidated
default	16:57:02.022978 +0200	deleted	callingProcess: (null), refreshAll is
FALSE, servicesToQuery: <private>			
default	16:57:02.023003 +0200	deleted	[<private>] no servicesToCount.
refreshAll: FALSE			
default	16:57:02.023051 +0200	deleted	PurgeableSpace result: <private>
default	16:57:02.023217 +0200	deleted	SYNC purgeable op results:
<private>			
default	16:57:02.026580 +0200	opendirectoryd	Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0			
default	16:57:02.027327 +0200		
com.apple.appkit.xpc.openAndSavePanelService			<private> is not MNT_LOCAL!
default	16:57:02.027377 +0200		
com.apple.appkit.xpc.openAndSavePanelService			<private>
default	16:57:02.027667 +0200		
com.apple.appkit.xpc.openAndSavePanelService			<private> is not MNT_LOCAL!
default	16:57:02.027698 +0200		
com.apple.appkit.xpc.openAndSavePanelService			<private>
default	16:57:02.028284 +0200		
com.apple.appkit.xpc.openAndSavePanelService			got a connection for:
com.apple.cache_delete			
default	16:57:02.028465 +0200		
com.apple.appkit.xpc.openAndSavePanelService			got proxy: <private> for
service: com.apple.cache_delete			
default	16:57:02.028679 +0200	deleted	listener: <private>
default	16:57:02.028713 +0200	deleted	Skipping entitlement check...
default	16:57:02.028944 +0200	deleted	Skipping entitlement check...
default	16:57:02.029057 +0200	deleted	returning cached results, and
asynchronously refreshing any stale results			
default	16:57:02.029128 +0200	deleted	volume: <private>, total: 0
default	16:57:02.029184 +0200	deleted	Filtering for root only services.
Volume: <private>			
default	16:57:02.029222 +0200	deleted	CACHE_DELETE_URGENCY: 3
default	16:57:02.029245 +0200	deleted	urgency: 3, urgencyLimit: 3
default	16:57:02.029357 +0200	deleted	callingProcess: (null), refreshAll is
FALSE, servicesToQuery: <private>			

```

default      16:57:02.029351 +0200
com.apple.appkit.xpc.openAndSavePanelService    setting target uid to: 501 for
service: com.apple.cache_delete
default      16:57:02.029384 +0200    deleted    [<private>] no servicesToCount.
refreshAll: FALSE
default      16:57:02.029374 +0200
com.apple.appkit.xpc.openAndSavePanelService    connection invalidated
default      16:57:02.029443 +0200    deleted    PurgeableSpace result: <private>
default      16:57:02.029471 +0200    deleted    newConnection invalidated
default      16:57:02.029604 +0200    deleted    SYNC purgeable op results:
<private>
default      16:57:02.039690 +0200
com.apple.appkit.xpc.openAndSavePanelService    got a connection for:
com.apple.cache_delete
default      16:57:02.039980 +0200
com.apple.appkit.xpc.openAndSavePanelService    got proxy: <private> for
service: com.apple.cache_delete
default      16:57:02.040254 +0200    deleted    listener: <private>
default      16:57:02.040314 +0200    deleted    Skipping entitlement check...
default      16:57:02.040532 +0200    deleted    Skipping entitlement check...
default      16:57:02.040637 +0200    deleted    returning cached results, and
asynchronously refreshing any stale results
default      16:57:02.040702 +0200    deleted    volume: <private>, total: 8192
default      16:57:02.040763 +0200    deleted    Filtering for root only services.
Volume: <private>
default      16:57:02.040803 +0200    deleted    CACHE_DELETE_URGENCY: 3
default      16:57:02.040954 +0200
com.apple.appkit.xpc.openAndSavePanelService    setting target uid to: 501 for
service: com.apple.cache_delete
default      16:57:02.040828 +0200    deleted    urgency: 3, urgencyLimit: 3
default      16:57:02.040977 +0200
com.apple.appkit.xpc.openAndSavePanelService    connection invalidated
default      16:57:02.040942 +0200    deleted    callingProcess: (null), refreshAll is
FALSE, servicesToQuery: <private>
default      16:57:02.040971 +0200    deleted    [<private>] no servicesToCount.
refreshAll: FALSE
default      16:57:02.041025 +0200    deleted    PurgeableSpace result: <private>
default      16:57:02.041180 +0200    deleted    SYNC purgeable op results:
<private>
default      16:57:02.041786 +0200
com.apple.appkit.xpc.openAndSavePanelService    got a connection for:
com.apple.cache_delete
default      16:57:02.041905 +0200
com.apple.appkit.xpc.openAndSavePanelService    got proxy: <private> for
service: com.apple.cache_delete
default      16:57:02.042031 +0200    deleted    newConnection invalidated
default      16:57:02.042047 +0200    deleted    listener: <private>
default      16:57:02.042101 +0200    deleted    Skipping entitlement check...
default      16:57:02.042267 +0200    deleted    Skipping entitlement check...
default      16:57:02.042349 +0200    deleted    returning cached results, and

```

asynchronously refreshing any stale results

default 16:57:02.042410 +0200 deleted volume: <private>, total: 12411152402

default 16:57:02.042466 +0200 deleted CACHE_DELETE_URGENCY: 3

default 16:57:02.042590 +0200

com.apple.appkit.xpc.openAndSavePanelService setting target uid to: 501 for service: com.apple.cache_delete

default 16:57:02.042493 +0200 deleted urgency: 3, urgencyLimit: 3

default 16:57:02.042612 +0200

com.apple.appkit.xpc.openAndSavePanelService connection invalidated

default 16:57:02.042611 +0200 deleted newConnection invalidated

default 16:57:02.042616 +0200 deleted callingProcess: (null), refreshAll is FALSE, servicesToQuery: <private>

default 16:57:02.042640 +0200 deleted [<private>] no servicesToCount.

refreshAll: FALSE

default 16:57:02.042693 +0200 deleted PurgeableSpace result: <private>

default 16:57:02.042862 +0200 deleted SYNC purgeable op results: <private>

default 16:57:02.043353 +0200

com.apple.appkit.xpc.openAndSavePanelService got a connection for: com.apple.cache_delete

default 16:57:02.043460 +0200

com.apple.appkit.xpc.openAndSavePanelService got proxy: <private> for service: com.apple.cache_delete

default 16:57:02.043657 +0200 deleted listener: <private>

default 16:57:02.043720 +0200 deleted Skipping entitlement check...

default 16:57:02.043896 +0200 deleted Skipping entitlement check...

default 16:57:02.044014 +0200 deleted returning cached results, and asynchronously refreshing any stale results

default 16:57:02.044082 +0200 deleted volume: <private>, total: 125015

default 16:57:02.044248 +0200

com.apple.appkit.xpc.openAndSavePanelService setting target uid to: 501 for service: com.apple.cache_delete

default 16:57:02.044152 +0200 deleted Filtering for root only services.

Volume: <private>

default 16:57:02.044269 +0200

com.apple.appkit.xpc.openAndSavePanelService connection invalidated

default 16:57:02.044187 +0200 deleted CACHE_DELETE_URGENCY: 3

default 16:57:02.044211 +0200 deleted urgency: 3, urgencyLimit: 3

default 16:57:02.044279 +0200 deleted newConnection invalidated

default 16:57:02.044876 +0200 cloudphotosd listener: <private>

default 16:57:02.044345 +0200 deleted callingProcess: (null), refreshAll is FALSE, servicesToQuery: <private>

default 16:57:02.044952 +0200 cloudphotosd Skipping entitlement check...

default 16:57:02.044375 +0200 deleted 98 self.urgency: 3, self.urgencyLimit: 3

default 16:57:02.044437 +0200 deleted <private>: Completion callback

default 16:57:02.044462 +0200 deleted Connecting to <private>

default 16:57:02.045146 +0200 symptomsd dampened wifi dns symptom fires

default	16:57:02.045325 +0200	deleted	<private>: Successful Request
default	16:57:02.045359 +0200	deleted	<private>: Completion callback
default	16:57:02.045398 +0200	deleted	<private> took 0.000988 seconds, returned: (null)
default	16:57:02.045420 +0200	deleted	<private> returned null result
default	16:57:02.045461 +0200	deleted	Connection to <private> was invalidated.
default	16:57:02.045469 +0200	deleted	<private> updateInfo: <private>
default	16:57:02.045506 +0200	deleted	ENTRY, operation: CACHE_DELETE_PURGEABLE_OPERATION, serviceID: <private> info: <private>
default	16:57:02.045596 +0200	deleted	updating cache for service: <private>, volume: <private>, amounts: <private>
default	16:57:02.045625 +0200	deleted	updating service info amount: 0, serviceID: <private>, volume: <private>, urgency: 3 pushed: FALSE
default	16:57:02.045697 +0200	deleted	PurgeableSpace result: <private>
default	16:57:02.045825 +0200	cloudphotosd	newConnection invalidated
default	16:57:02.045873 +0200	deleted	SYNC purgeable op results: <private>
default	16:57:02.047529 +0200	pkd	No plugins found to match query <private>
default	16:57:02.048189 +0200	accountsd	"<private> (<private>) received"
default	16:57:02.050237 +0200		
		com.apple.appkit.xpc.openAndSavePanelService	discovered extensions
default	16:57:02.050427 +0200		
		com.apple.appkit.xpc.openAndSavePanelService	discovered extensions
default	16:57:02.051780 +0200	bird	"The connection to ACDAccountStore was invalidated."
default	16:57:02.078621 +0200	opendirectoryd	Client: <private>, UID: 0, EUID: 0, GID: 0, EGID: 0
default	16:57:02.078881 +0200	opendirectoryd	Client: <private>, UID: 0, EUID: 0, GID: 0, EGID: 0
default	16:57:02.078923 +0200	opendirectoryd	queuing request to connection - '<private>'
default	16:57:02.079698 +0200	opendirectoryd	Client: <private>, UID: 0, EUID: 0, GID: 0, EGID: 0
default	16:57:02.079746 +0200	opendirectoryd	queuing request to connection - '<private>'
default	16:57:02.083399 +0200	opendirectoryd	Client: <private>, UID: 0, EUID: 0, GID: 0, EGID: 0
default	16:57:02.083446 +0200	opendirectoryd	queuing request to connection - '<private>'
default	16:57:02.084027 +0200	opendirectoryd	Client: <private>, UID: 0, EUID: 0, GID: 0, EGID: 0
default	16:57:02.084072 +0200	opendirectoryd	queuing request to connection - '<private>'
default	16:57:02.084683 +0200	opendirectoryd	Client: <private>, UID: 0, EUID: 0, GID: 0, EGID: 0
default	16:57:02.084726 +0200	opendirectoryd	queuing request to connection - '<private>'
default	16:57:02.085266 +0200	opendirectoryd	Client: <private>, UID: 0, EUID: 0, GID: 0, EGID: 0

```

0, GID: 0, EGID: 0
default 16:57:02.085310 +0200 opendirectoryd queuing request to connection
- '<private>'
default 16:57:02.085835 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default 16:57:02.085879 +0200 opendirectoryd queuing request to connection
- '<private>'
default 16:57:02.086422 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default 16:57:02.086473 +0200 opendirectoryd queuing request to connection
- '<private>'
default 16:57:02.091136 +0200 trustd cert[2]: AnchorTrusted =(leaf)[force]>
0
default 16:57:02.092223 +0200 tccd MacOS error: -67050
default 16:57:02.093999 +0200 trustd cert[2]: AnchorTrusted =(leaf)[force]>
0
default 16:57:02.094969 +0200 trustd cert[2]: AnchorTrusted =(leaf)[force]>
0
default 16:57:02.095828 +0200 tccd MacOS error: -67050
default 16:57:02.096663 +0200 mds directQueryOpenReply 131073
1795162176 0
default 16:57:02.096708 +0200 mds QueryOpen succeeded (0) for store
<private>
default 16:57:02.096732 +0200 mds directQueryOpenReply 131073
1795162208 0
default 16:57:02.096766 +0200 mds QueryOpen succeeded (0) for store
<private>
default 16:57:02.096788 +0200 mds directQueryOpenReply 131073
1795162144 0
default 16:57:02.096819 +0200 mds QueryOpen succeeded (0) for store
<private>
default 16:57:02.096843 +0200 mds directQueryOpenReply 131073
1795162112 0
default 16:57:02.096884 +0200 mds QueryOpen succeeded (0) for store
<private>
default 16:57:02.096987 +0200 mds directQueryFetchResultsReply 131073
1795162176 0
default 16:57:02.097279 +0200 mds directQueryFetchResultsReply 131073
1795162208 0
default 16:57:02.097510 +0200 mds directQueryFetchResultsReply 131073
1795162144 0
default 16:57:02.097803 +0200 mds directQueryFetchResultsReply 131073
1795162112 0
default 16:57:02.108142 +0200 com.apple.WebKit.Networking
TIC TCP Conn Event [67:0x7fa644d832f0]: 2 Err(0)
default 16:57:02.108171 +0200 com.apple.WebKit.Networking
TIC TCP Conn Cancel [67:0x7fa644d832f0]
default 16:57:02.108196 +0200 com.apple.WebKit.Networking
TIC TCP Conn Destroyed [67:0x7fa644d832f0]
default 16:57:02.119537 +0200 kernel SandboxViolation: bird(315) deny(1)

```

```

file-read-data /Users/craigdenham
default 16:57:02.121176 +0200 kernel SandboxViolation: bird(315) deny(1)
file-read-data /Users/craigdenham
default 16:57:02.125533 +0200 bird ApplePushService: <APSCConnection:
0x7f8543a20c80> setting delegate <BRCCContainerScheduler: 0x7f854390aa30>
default 16:57:02.125565 +0200 bird ApplePushService: <APSCConnection:
0x7f8543a20c80> setEnabledTopics (
    "com.apple.icloud-container.cloudDocs.X6B29J8D22.com.savysoda.documents",
    "com.apple.icloud-container.cloudDocs.com.apple.mobilemail",
    "com.apple.icloud-container.cloudDocs.com.apple.Preview",
    "com.apple.icloud-container.cloudDocs.com.apple.mail",
    "com.apple.icloud-container.cloudDocs.com.apple.CloudDocs.health",
    "com.apple.icloud-container.cloudDocs.iCloud.com.arfsoftware.voiceplus",
    "com.apple.icloud-container.cloudDocs.iCloud.com.apple.iBooks",
    "com.apple.icloud-container.cloudDocs.com.apple.TextInput",
    "com.apple.icloud-container.cloudDocs.com.apple.CloudDocs.container-
metadata",
    "com.apple.icloud-container.cloudDocs.iCloud.com.viber",
    "com.apple.icloud-container.cloudDocs.57T9237FN3.net.whatsapp.WhatsApp",
    "com.apple.icloud-container.cloudDocs.iCloud.com.xmeinc.beatpad",
    "com.apple.icloud-container.cloudDocs.iCloud.com.apple.iBooks.iTunesU",
    "com.apple.icloud-container.clo<...>
default 16:57:02.125690 +0200 coreduetd For attribute 45099, deducting 0
from associated budget 42.
default 16:57:02.125752 +0200 bird ApplePushService: <APSCConnection:
0x7f8543a20c80> setEnabledTopics (
    "com.apple.icloud-container.cloudDocs.X6B29J8D22.com.savysoda.documents",
    "com.apple.icloud-container.cloudDocs.com.apple.mobilemail",
    "com.apple.icloud-container.cloudDocs.com.apple.Preview",
    "com.apple.icloud-container.cloudDocs.com.apple.mail",
    "com.apple.icloud-container.cloudDocs.com.apple.CloudDocs.health",
    "com.apple.icloud-container.cloudDocs.iCloud.com.arfsoftware.voiceplus",
    "com.apple.icloud-container.cloudDocs.iCloud.com.apple.iBooks",
    "com.apple.icloud-container.cloudDocs.com.apple.TextInput",
    "com.apple.icloud-container.cloudDocs.com.apple.CloudDocs.container-
metadata",
    "com.apple.icloud-container.cloudDocs.iCloud.com.viber",
    "com.apple.icloud-container.cloudDocs.57T9237FN3.net.whatsapp.WhatsApp",
    "com.apple.icloud-container.cloudDocs.iCloud.com.xmeinc.beatpad",
    "com.apple.icloud-container.cloudDocs.iCloud.com.apple.iBooks.iTunesU",
    "com.apple.icloud-container.clo<...>
default 16:57:02.125843 +0200 bird ApplePushService: <APSCConnection:
0x7f8543a20c80> Delivering queued delegate calls: 0
default 16:57:02.125900 +0200 bird ApplePushService: <APSCConnection:
0x7f8543a20c80> _setEnabledStatusNotifications NO sendToDaemon YES
default 16:57:02.126377 +0200 kernel SandboxViolation: bird(315) deny(1)
file-read-data /Users/craigdenham
default 16:57:02.128911 +0200 kernel SandboxViolation: bird(315) deny(1)
file-read-data /Users/craigdenham
default 16:57:02.130227 +0200 coreduetd For attribute 45098, deducting 0

```

from associated budget 40.
default 16:57:02.130777 +0200 coreduetd For attribute 45082, deducting 0
from associated budget 6.
default 16:57:02.131304 +0200 coreduetd For attribute 45083, deducting 0
from associated budget 10.
default 16:57:02.131745 +0200 coreduetd For attribute 45084, deducting 0
from associated budget 12.
default 16:57:02.132154 +0200 coreduetd For attribute 45104, deducting 0
from associated budget 46.
default 16:57:02.132780 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default 16:57:02.134412 +0200 coreduetd For attribute 45105, deducting 0
from associated budget 48.
default 16:57:02.134534 +0200 kernel SandboxViolation: bird(315) deny(1)
file-read-data /Users/craigdenham
default 16:57:02.136074 +0200 kernel SandboxViolation: bird(315) deny(1)
file-read-data /Users/craigdenham
default 16:57:02.142022 +0200 kernel SandboxViolation: bird(315) deny(1)
file-read-data /Users/craigdenham
default 16:57:02.145881 +0200 kernel SandboxViolation: bird(315) deny(1)
file-read-data /Users/craigdenham
default 16:57:02.156271 +0200
com.apple.appkit.xpc.openAndSavePanelService Connection to sharingd
became invalid
default 16:57:02.198013 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff10fd30340> to generate token
for topic "com.apple.idmsauthagent" and identifier ""
default 16:57:02.198308 +0200 apsd Failed to talk to secld after 4 attempts.
default 16:57:02.198481 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.idmsauthagent" and
identifier "", assigned appld "0"
default 16:57:02.198583 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff10fc39740> to generate token
for topic "com.apple.icloud-container.com.apple.gamed" and identifier ""
default 16:57:02.198787 +0200 apsd Failed to talk to secld after 4 attempts.
default 16:57:02.198922 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.gamed" and identifier "", assigned appld "0"
default 16:57:02.198948 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-
container.com.apple.gamed" and identifier ""
default 16:57:02.198989 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff1123130c0> to generate token
for topic "com.apple.icloud-container.com.apple.cloudpaired" and identifier ""
default 16:57:02.199218 +0200 apsd Failed to talk to secld after 4 attempts.
default 16:57:02.199345 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.cloudpaired" and identifier "", assigned appld "0"
default 16:57:02.199371 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-

```

container.com.apple.cloudpaired" and identifier ""
default 16:57:02.199409 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff1121367e0> to generate token
for topic "com.apple.icloud-container.com.apple.callhistory.sync-helper" and identifier
""
default 16:57:02.199628 +0200 apsd Failed to talk to sec2 after 4 attempts.
default 16:57:02.199775 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.callhistory.sync-helper" and identifier "", assigned appId "0"
default 16:57:02.199806 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-
container.com.apple.callhistory.sync-helper" and identifier ""
default 16:57:02.239098 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Outstanding data received: <12000000 3e010001 00020020 d9c11435 214069b9
101c5fde a54e7119 fcf1b29f ac27fb6a e7c8a67e 735182bc 03001499 8c5d4c6f
0bb047fc 827e799b b288562a 619642> (length 67)
default 16:57:02.239153 +0200 apsd <APSCourier: 0x7ff1122051b0>: Stream
processing: complete yes, invalid no, length parsed 67, parameters {
    APSProtocolAppTokenGenerateResponseCode = 0;
    APSProtocolAppTokenGenerateResponseToken = <d9c11435 214069b9
101c5fde a54e7119 fcf1b29f ac27fb6a e7c8a67e 735182bc>;
    APSProtocolAppTokenGenerateResponseTopicHash = <998c5d4c 6f0bb047
fc827e79 9bb28856 2a619642>;
    APSProtocolCommand = 18;
}
default 16:57:02.239188 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received app token generate response {
    APSProtocolAppTokenGenerateResponseCode = 0;
    APSProtocolAppTokenGenerateResponseToken = <d9c11435 214069b9
101c5fde a54e7119 fcf1b29f ac27fb6a e7c8a67e 735182bc>;
    APSProtocolAppTokenGenerateResponseTopicHash = <998c5d4c 6f0bb047
fc827e79 9bb28856 2a619642>;
    APSProtocolCommand = 18;
}
default 16:57:02.239221 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received response for token request for topic com.apple.idmsauthagent, appId 0,
new token = <d9c11435 214069b9 101c5fde a54e7119 fcf1b29f ac27fb6a e7c8a67e
735182bc>
default 16:57:02.239297 +0200 apsd <APSCConnectionServer:
0x7ff10fd30340>: Received token <d9c11435 214069b9 101c5fde a54e7119
fcf1b29f ac27fb6a e7c8a67e 735182bc> for topic com.apple.idmsauthagent with
identifier
default 16:57:02.239347 +0200 apsd <APSCConnectionServer:
0x7ff10fd30340>: Sending token <d9c11435 214069b9 101c5fde a54e7119 fcf1b29f
ac27fb6a e7c8a67e 735182bc> for topic com.apple.idmsauthagent with identifier
default 16:57:02.239400 +0200 apsd <APSCourier: 0x7ff1122051b0>: Stream
processing: complete no, invalid no, length parsed 0, parameters (null)
default 16:57:02.239457 +0200 apsd Dispatching low priority message:
<OS_xpc_dictionary: <dictionary: 0x7ff10fc3ba90> { count = 4, transaction: 0,
voucher = 0x0, contents =

```

```

"identifier" => <string: 0x7ff10fc22520> { length = 0, contents = "" }
"token" => <data: 0x7ff10fc10270>: { length = 32 bytes, contents =
0xd9c11435214069b9101c5fdea54e7119fcf1b29fac27fb6a... }
"topic" => <string: 0x7ff10fc21ec0> { length = 23, contents =
"com.apple.idmsauthagent" }
"message-type" => <int64: 0x7ff10fc31cc0>: 30
}>
default 16:57:02.239598 +0200 AppleIDAuthAgent ApplePushService:
<APSCConnection: 0x7fd38bd03de0> Received token <d9c11435 214069b9
101c5fde a54e7119 fcf1b29f ac27fb6a e7c8a67e 735182bc> forTopic
com.apple.idmsauthagent identifier
default 16:57:03.863573 +0200 ocspd CSSM Exception: -2147413737
CSSMERR_DL_DATASTORE_DOESNOT_EXIST
default 16:57:03.863661 +0200 ocspd 0x7f9004706320 opened /private/
var/db/crls/crlcache2.db: 32444 bytes
default 16:57:04.244995 +0200 accountsd "Idle-exit-preventing transaction
ended!"
default 16:57:04.245040 +0200 locationd checkAppInstallationStatus() called
unexpectedly on OSX... ignoring
default 16:57:04.245122 +0200 locationd checkAppInstallationStatus() called
unexpectedly on OSX... ignoring
default 16:57:04.632369 +0200 filecoordinationd Received claim <private>
default 16:57:04.632430 +0200 filecoordinationd Claim 09FC76F2-
ACEE-4E3F-9976-C11FC8D2D072 granted in server
default 16:57:04.632530 +0200 filecoordinationd Claim 09FC76F2-
ACEE-4E3F-9976-C11FC8D2D072 invoked in server
default 16:57:04.632623 +0200 TextEdit Claim 09FC76F2-ACEE-4E3F-9976-
C11FC8D2D072 granted in client
default 16:57:04.632645 +0200 TextEdit Claim 09FC76F2-ACEE-4E3F-9976-
C11FC8D2D072 invoked in client
default 16:57:04.635316 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default 16:57:04.635465 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 20, EGID: 20
default 16:57:04.635684 +0200 opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default 16:57:04.643421 +0200 opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default 16:57:04.750242 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default 16:57:04.751517 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default 16:57:04.751607 +0200 opendirectoryd queuing request to connection
- '<private>'
default 16:57:04.751680 +0200 opendirectoryd queuing request to connection
- '<private>'
default 16:57:04.752118 +0200 opendirectoryd queuing request to connection
- '<private>'
default 16:57:04.752199 +0200 opendirectoryd queuing request to connection
- '<private>'

```

default	16:57:04.752528 +0200	opendirectoryd Client: <private>, UID: 0, EUID: 0, GID: 0, EGID: 0
default	16:57:04.752606 +0200	opendirectoryd queuing request to connection
- '<private>'		
default	16:57:04.752633 +0200	opendirectoryd queuing request to connection
- '<private>'		
default	16:57:04.752678 +0200	opendirectoryd queuing request to connection
- '<private>'		
default	16:57:04.752729 +0200	opendirectoryd queuing request to connection
- '<private>'		
default	16:57:04.753306 +0200	opendirectoryd Client: <private>, UID: 0, EUID: 0, GID: 0, EGID: 0
default	16:57:04.754336 +0200	cupsd using system preferences
default	16:57:04.785117 +0200	opendirectoryd Client: <private>, UID: 0, EUID: 0, GID: 0, EGID: 0
default	16:57:04.785283 +0200	opendirectoryd Client: <private>, UID: 0, EUID: 0, GID: 20, EGID: 20
default	16:57:04.785566 +0200	opendirectoryd Client: <private>, UID: 501, EUID: 501, GID: 20, EGID: 20
default	16:57:04.785582 +0200	trustd cert[2]: AnchorTrusted =(leaf)[force]> 0
default	16:57:04.786488 +0200	tccd MacOS error: -67050
default	16:57:04.788587 +0200	trustd cert[2]: AnchorTrusted =(leaf)[force]> 0
default	16:57:04.788809 +0200	opendirectoryd Client: <private>, UID: 0, EUID: 0, GID: 0, EGID: 0
default	16:57:04.788876 +0200	opendirectoryd Client: <private>, UID: 0, EUID: 0, GID: 0, EGID: 0
default	16:57:04.789608 +0200	tccd MacOS error: -67050
default	16:57:04.791782 +0200	trustd cert[2]: AnchorTrusted =(leaf)[force]> 0
default	16:57:04.792769 +0200	tccd MacOS error: -67050
default	16:57:04.796174 +0200	opendirectoryd Client: <private>, UID: 501, EUID: 501, GID: 20, EGID: 20
default	16:57:04.801515 +0200	opendirectoryd Client: <private>, UID: 501, EUID: 501, GID: 20, EGID: 20
default	16:57:04.814091 +0200	mdwrite 0x7f9896a08ae0 opened /var/folders/j8/bbhn9g892k14cv1xw2hp2fy80000gn/C//mds/mdsObject.db: 4636 bytes
default	16:57:04.814333 +0200	mdwrite 0x7f9896a0e3b0 opened /var/folders/j8/bbhn9g892k14cv1xw2hp2fy80000gn/C//mds/mdsDirectory.db: 50744 bytes
default	16:57:04.815811 +0200	mdwrite 0x7f9896a23900 opened /var/folders/j8/bbhn9g892k14cv1xw2hp2fy80000gn/C//mds/mdsDirectory.db: 50744 bytes
default	16:57:04.816865 +0200	mdwrite 0x7f9896a26fd0 opened /Users/craigdenham/Library/Keychains/metadata.keychain-db: 60712 bytes
default	16:57:04.822754 +0200	securityd global integrity not set, defaulting to on
default	16:57:04.825582 +0200	mdwrite 0x7f9895e0b370 created /Users/craigdenham/Library/Keychains/metadata.keychain-db.sb-0682d11c-XUv0Sw
default	16:57:04.825668 +0200	mdwrite 0x7f9896900080 opened /Users/craigdenham/Library/Keychains/metadata.keychain-db: 60712 bytes

```

default 16:57:04.825810 +0200 mdwrite committing to /Users/craigdenham/
Library/Keychains/metadata.keychain-db
default 16:57:04.826285 +0200 mdwrite 0x7f9895e0b370 committed /Users/
craigdenham/Library/Keychains/metadata.keychain-db.sb-0682d11c-XUv0Sw to /
Users/craigdenham/Library/Keychains/metadata.keychain-db
default 16:57:04.826384 +0200 mdwrite 0x7f9895e043e0 opened /var/
folders/j8/bbhn9g892k14cv1xw2hp2fy80000gn/C//mds/mdsDirectory.db: 50744 bytes
default 16:57:04.828890 +0200 trustd cert[2]: AnchorTrusted =(leaf)[force]>
0
default 16:57:04.829566 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default 16:57:04.831011 +0200 securityd keychain reference in server mode
default 16:57:04.833069 +0200 mdwrite 0x7f9896b11200 opened /Users/
craigdenham/Library/Keychains/metadata.keychain-db: 60712 bytes
default 16:57:04.834421 +0200 mdwrite getting current attributes...
default 16:57:04.834444 +0200 mdwrite filling 16 attributes for type
2147483648
default 16:57:04.834778 +0200 mdwrite looking at 16 attributes
default 16:57:04.834826 +0200 mdwrite finished:
5a38a50924bd94af5bec9aaa35c5a9d0bb2a5be949977416b9ba95251330bb68
default 16:57:04.836723 +0200 trustd cert[2]: AnchorTrusted =(leaf)[force]>
0
default 16:57:04.837489 +0200 securityd ACL partitionID = <CFArray
0x7fb8fdc08f10 [0x7ffda12eda0]>{type = mutable-small, count = 1, values = (
0 : apple:
)}
default 16:57:04.837616 +0200 securityd ACL partitions match: apple:
default 16:57:04.840200 +0200 mdwrite MacOS error: -25294
default 16:57:04.840740 +0200 securityd added partition apple: to new key
default 16:57:04.841012 +0200 mdwrite 0x7f9895c149a0 created /Users/
craigdenham/Library/Keychains/metadata.keychain-db.sb-0682d11c-OVyyu3
default 16:57:04.841043 +0200 mdwrite 0x7f9895c156a0 opened /Users/
craigdenham/Library/Keychains/metadata.keychain-db: 60712 bytes
default 16:57:04.841567 +0200 mdwrite committing to /Users/craigdenham/
Library/Keychains/metadata.keychain-db
default 16:57:04.842234 +0200 mdwrite 0x7f9895c149a0 committed /Users/
craigdenham/Library/Keychains/metadata.keychain-db.sb-0682d11c-OVyyu3 to /
Users/craigdenham/Library/Keychains/metadata.keychain-db
default 16:57:04.842286 +0200 mdwrite 0x7f9895c10220 opened /Users/
craigdenham/Library/Keychains/metadata.keychain-db: 61868 bytes
default 16:57:04.843235 +0200 securityd keychain reference in server mode
default 16:57:04.843997 +0200 mdwrite skipping integrity add due to
keychain version
default 16:57:04.845506 +0200 filecoordinationd Presenter
99F1E8F3-3E20-4CAF-A9B0-B7C04A8D9A27 has been tied to a URL for the first
time -- <private>
default 16:57:04.845637 +0200 filecoordinationd Claim 09FC76F2-
ACEE-4E3F-9976-C11FC8D2D072 was revoked
default 16:57:04.847057 +0200 coreduetd For attribute 45099, deducting 0
from associated budget 42.

```


default 16:57:04.852357 +0200 filecoordinationd Received claim <private>
default 16:57:04.852414 +0200 filecoordinationd Claim
CCA2B3F8-8A11-4600-B0A6-4EC394AD494B granted in server
default 16:57:04.852454 +0200 filecoordinationd Claimer for
CCA2B3F8-8A11-4600-B0A6-4EC394AD494B is waiting for presenter
99F1E8F3-3E20-4CAF-A9B0-B7C04A8D9A27 on the same item to relinquish
default 16:57:04.852508 +0200 filecoordinationd Presenter
99F1E8F3-3E20-4CAF-A9B0-B7C04A8D9A27 has finished relinquishing, unblocking
claimer for CCA2B3F8-8A11-4600-B0A6-4EC394AD494B
default 16:57:04.852567 +0200 filecoordinationd Claim
CCA2B3F8-8A11-4600-B0A6-4EC394AD494B invoked in server
default 16:57:04.852714 +0200 TextEdit Claim CCA2B3F8-8A11-4600-
B0A6-4EC394AD494B granted in client
default 16:57:04.852739 +0200 TextEdit Claim CCA2B3F8-8A11-4600-
B0A6-4EC394AD494B invoked in client
default 16:57:04.853587 +0200 filecoordinationd Claim
CCA2B3F8-8A11-4600-B0A6-4EC394AD494B was revoked
default 16:57:04.853613 +0200 filecoordinationd Making presenter
99F1E8F3-3E20-4CAF-A9B0-B7C04A8D9A27 reacquire after claim
CCA2B3F8-8A11-4600-B0A6-4EC394AD494B
default 16:57:04.862562 +0200 filecoordinationd Received claim <private>
default 16:57:04.862611 +0200 filecoordinationd Claim CBDBB0A8-
B7EF-4306-8357-6BDDD8A0E647 is blocked waiting for claim
CCA2B3F8-8A11-4600-B0A6-4EC394AD494B to finish.
error 16:57:04.863233 +0200 TextEdit ICLOUD: Error encoding url <private>,
Error Domain=BRCloudDocsErrorDomain Code=7 "Document hasn't yet been
synced to the server" UserInfo={NSDescription=Document hasn't yet been synced to
the server, NSFilePath=/Users/craigdenham/Library/Mobile Documents/
com~apple~TextEdit/Documents/Untitled 2.rtf}, so failing with error Error
Domain=UAContinuityErrorDomain Code=-114 "(null)"
UserInfo={NSUnderlyingError=0x6100002568f0 {Error
Domain=BRCloudDocsErrorDomain Code=7 "Document hasn't yet been synced to
the server" UserInfo={NSDescription=Document hasn't yet been synced to the
server, NSFilePath=/Users/craigdenham/Library/Mobile Documents/
com~apple~TextEdit/Documents/Untitled 2.rtf}}}
opts={ LSUserActivityContainsUnsynchronizedCloudDocs = 1;
UAUserActivityContainsCloudDocsKey = 1;}.
default 16:57:05.158821 +0200 AppleSpell Rebroadcasting external
notification ABDistributedDatabaseChangedNotification from process
AddressBookSourceSync (<private>)
default 16:57:05.158902 +0200 AppleSpell Rebroadcasting external
notification ABDistributedDatabaseChangedNotificationPriv from process
AddressBookSourceSync (<private>)
default 16:57:05.238940 +0200 AppleSpell Lexicon creation failed: Lexicon
resources not found
default 16:57:05.313974 +0200 kernel [IOAppleBluetoothHIDDriver]
[AppleHSBluetoothDevice][getExtendedReport] Could not retrieve information for
BatteryPercent feature
default 16:57:05.313979 +0200 kernel [IOAppleBluetoothHIDDriver]
[AppleHSBluetoothDevice][updateBatteryLevel] Couldn't get battery percentage from

device
default 16:57:05.346154 +0200 useractivityd PICKING:
41F23575-8D2B-48B0-8FCD-C77DA62FDE2E/<private> as the current item-to-
advertise.
default 16:57:05.398364 +0200 filecoordinationd Claim CBDBB0A8-
B7EF-4306-8357-6BDDD8A0E647 granted in server
default 16:57:05.398394 +0200 filecoordinationd Claimer for CBDBB0A8-
B7EF-4306-8357-6BDDD8A0E647 is waiting for presenter 99F1E8F3-3E20-4CAF-
A9B0-B7C04A8D9A27 on the same item to relinquish
default 16:57:05.398432 +0200 filecoordinationd Asking presenter
99F1E8F3-3E20-4CAF-A9B0-B7C04A8D9A27 to relinquish to claim CBDBB0A8-
B7EF-4306-8357-6BDDD8A0E647
default 16:57:05.398662 +0200 TextEdit Asking presenter
99F1E8F3-3E20-4CAF-A9B0-B7C04A8D9A27 to relinquish to claim CBDBB0A8-
B7EF-4306-8357-6BDDD8A0E647 via relinquishPresentedItemToReader:
default 16:57:05.398738 +0200 TextEdit Presenter 99F1E8F3-3E20-4CAF-
A9B0-B7C04A8D9A27 relinquished
default 16:57:05.398961 +0200 filecoordinationd Received relinquishment
reply for presenter 99F1E8F3-3E20-4CAF-A9B0-B7C04A8D9A27 to claim
CBDBB0A8-B7EF-4306-8357-6BDDD8A0E647
default 16:57:05.398982 +0200 filecoordinationd Presenter
99F1E8F3-3E20-4CAF-A9B0-B7C04A8D9A27 has finished relinquishing, unblocking
claimer for CBDBB0A8-B7EF-4306-8357-6BDDD8A0E647
default 16:57:05.399020 +0200 filecoordinationd Claim CBDBB0A8-
B7EF-4306-8357-6BDDD8A0E647 invoked in server
default 16:57:05.399153 +0200 bird Claim CBDBB0A8-
B7EF-4306-8357-6BDDD8A0E647 granted in client
default 16:57:05.399194 +0200 bird Claim CBDBB0A8-
B7EF-4306-8357-6BDDD8A0E647 invoked in client
default 16:57:05.403828 +0200 filecoordinationd Claim CBDBB0A8-
B7EF-4306-8357-6BDDD8A0E647 was revoked
default 16:57:05.403852 +0200 filecoordinationd Making presenter
99F1E8F3-3E20-4CAF-A9B0-B7C04A8D9A27 reacquire after claim CBDBB0A8-
B7EF-4306-8357-6BDDD8A0E647
default 16:57:05.403872 +0200 filecoordinationd Telling presenter
99F1E8F3-3E20-4CAF-A9B0-B7C04A8D9A27 to reacquire after claim CBDBB0A8-
B7EF-4306-8357-6BDDD8A0E647
default 16:57:05.405676 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff10fc39740> to generate token
for topic "com.apple.icloud-container.com.apple.gamed" and identifier ""
default 16:57:05.405918 +0200 apsd opened keychain, keychain status 0x7
default 16:57:05.406090 +0200 apsd 0x7ff1123103b0 opened /Library/
Keychains/apsd.keychain: 606512 bytes
default 16:57:05.406403 +0200 apsd Failed to talk to secd after 4 attempts.
default 16:57:05.406650 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.gamed" and identifier "", assigned appld "0"
default 16:57:05.406796 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff1123130c0> to generate token
for topic "com.apple.icloud-container.com.apple.cloudpaired" and identifier ""

default 16:57:05.407082 +0200 apsd Failed to talk to secd after 4 attempts.
default 16:57:05.407305 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.cloudpaired" and identifier "", assigned appld "0"
default 16:57:05.407346 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-
container.com.apple.cloudpaired" and identifier ""
default 16:57:05.407401 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff1121367e0> to generate token
for topic "com.apple.icloud-container.com.apple.callhistory.sync-helper" and identifier
""
default 16:57:05.407687 +0200 apsd Failed to talk to secd after 4 attempts.
default 16:57:05.407902 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.callhistory.sync-helper" and identifier "", assigned appld "0"
default 16:57:05.407940 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-
container.com.apple.callhistory.sync-helper" and identifier ""
default 16:57:05.409343 +0200 bird [NOTICE] uploading 1 documents in
com.apple.TextEdit
default 16:57:05.413048 +0200 cloudd Creating a new client context
0x7ff288263070
default 16:57:05.416940 +0200 cloudd [Operation 0x7ff28832d180]
Initialized with context 0x7ff288263070. Background: 1, cellular: 1, QOS: 0x11
default 16:57:05.417439 +0200 cloudd [Operation 0x7ff28832d180] Starting
operation
default 16:57:05.417847 +0200 cloudd [Operation 0x7ff28832d180]
Operation transitioning from state 1 (cancelled=0, stop=0, error=0)
default 16:57:05.417927 +0200 cloudd [Operation 0x7ff28832d180]
Operation is now in state 2
default 16:57:05.417960 +0200 cloudd [Operation 0x7ff28832d180]
Operation transitioning from state 2 (cancelled=0, stop=0, error=0)
default 16:57:05.418032 +0200 cloudd [Operation 0x7ff28832d180]
Operation is now in state 3
default 16:57:05.418092 +0200 cloudd [Operation 0x7ff28832d180]
Operation transitioning from state 3 (cancelled=0, stop=0, error=0)
default 16:57:05.418126 +0200 cloudd [Operation 0x7ff28832d180]
Operation is now in state 4
default 16:57:05.418159 +0200 cloudd [Operation 0x7ff28832d180]
Operation transitioning from state 4 (cancelled=0, stop=0, error=0)
default 16:57:05.418280 +0200 cloudd [Operation 0x7ff28832d180]
Operation is now in state 5
default 16:57:05.418299 +0200 cloudd [Operation 0x7ff28832d180]
Operation transitioning from state 5 (cancelled=0, stop=0, error=0)
default 16:57:05.418332 +0200 cloudd [Operation 0x7ff28832d180]
Operation is now in state 6
default 16:57:05.418372 +0200 cloudd [Operation 0x7ff28832d180]
Operation transitioning from state 6 (cancelled=0, stop=0, error=0)
default 16:57:05.418425 +0200 cloudd [Operation 0x7ff28832d180]
Operation is now in state 8

```

default    16:57:05.418459 +0200    cloudd    [Operation 0x7ff28832d180]
Operation transitioning from state 8 (cancelled=0, stop=0, error=0)
default    16:57:05.418556 +0200    cloudd    [Operation 0x7ff28832d180]
Operation is now in state 7
default    16:57:05.418699 +0200    cloudd    [Operation 0x7ff288331c10]
Initialized with context 0x7ff288263070. Background: 1, cellular: 1, QOS: 0x11
default    16:57:05.418813 +0200    cloudd    [Operation 0x7ff288331c10] Starting
operation
default    16:57:05.418979 +0200    cloudd    [Operation 0x7ff288331c10]
Operation transitioning from state 1 (cancelled=0, stop=0, error=0)
default    16:57:05.425557 +0200    cloudd    [Operation 0x7ff288331c10]
Operation is now in state 2
default    16:57:05.425738 +0200    cloudd    [Operation 0x7ff288331c10]
Operation transitioning from state 2 (cancelled=0, stop=0, error=0)
default    16:57:05.425794 +0200    cloudd    [Operation 0x7ff288331c10]
Operation is now in state 2
default    16:57:05.425843 +0200    cloudd    [Operation 0x7ff288331c10]
Operation transitioning from state 2 (cancelled=0, stop=1, error=0)
default    16:57:05.426181 +0200    cloudd    [Operation 0x7ff286429420]
Initialized with context 0x7ff288263070. Background: 1, cellular: 1, QOS: 0x11
default    16:57:05.426352 +0200    cloudd    [Operation 0x7ff286429420] Starting
operation
default    16:57:05.426527 +0200    cloudd    [Operation 0x7ff286429420]
Operation transitioning from state 1 (cancelled=0, stop=0, error=0)
default    16:57:05.426567 +0200    cloudd    [Operation 0x7ff286429420]
Operation is now in state 2
default    16:57:05.426712 +0200    cloudd    [Operation 0x7ff286429420]
Operation transitioning from state 2 (cancelled=0, stop=0, error=0)
default    16:57:05.426747 +0200    cloudd    [Operation 0x7ff286429420]
Operation is now in state 5
default    16:57:05.426780 +0200    cloudd    [Operation 0x7ff286429420]
Operation transitioning from state 5 (cancelled=0, stop=0, error=0)
default    16:57:05.426860 +0200    cloudd    PCSIdentitySetCreate: iCloudDrive {
    kPCSSetupDSID = "<<VALUE>>";
}
default    16:57:05.429303 +0200    cloudd    [Operation 0x7ff286429420]
Operation is now in state 6
default    16:57:05.429327 +0200    cloudd    [Operation 0x7ff286429420]
Operation transitioning from state 6 (cancelled=0, stop=0, error=0)
default    16:57:05.429353 +0200    cloudd    [Operation 0x7ff286429420]
Operation is now in state 7
default    16:57:05.429399 +0200    cloudd    [Operation 0x7ff286429420]
Operation transitioning from state 7 (cancelled=0, stop=0, error=0)
default    16:57:05.429449 +0200    cloudd    [Operation 0x7ff286429420]
Operation is now in state 4294967295
default    16:57:05.430761 +0200    cloudd    PCSError: 27 : Identity of service
type Raw missing in memory keyset
default    16:57:05.433035 +0200    cloudd    PCSError: 27 : Identity of service
type Raw missing in memory keyset
default    16:57:05.433412 +0200    cloudd    [Operation 0x7ff28832d180]

```

Operation transitioning from state 7 (cancelled=0, stop=0, error=0)

default 16:57:05.433763 +0200 cloudd [Operation 0x7ff2867310a0]

Initialized with context 0x7ff288263070. Background: 1, cellular: 1, QOS: 0x11

default 16:57:05.434066 +0200 cloudd [Operation 0x7ff28832d180]

Operation is now in state 9

default 16:57:05.434085 +0200 cloudd [Operation 0x7ff2867310a0] Starting operation

default 16:57:05.436836 +0200 cloudd #713c34fb

ACSLocateCachingServer(assetURL=https://www.apple.com, locateTimeout=30.000, options={

 capabilities = {

 import = 1;

 namespaces = 1;

 personalCaching = 1;

 };

 quickMiss = 1;

}, callbackQueue=0x0, callback=0x0)

default 16:57:05.436891 +0200 cloudd #713c34fb

runningInAgentContext=YES

default 16:57:05.437623 +0200 AssetCacheLocatorService

 #713c34fb [AssetCacheLocatorService.queue] early hit: no caching servers

default 16:57:05.451817 +0200 cloudd Created mmcs engine

(0x7ff288239380) 'com.apple.CloudKit/(null)' com.apple.Dataclass.CloudKit

DebugLevel:0

default 16:57:05.451843 +0200 cloudd mmcs_engine verifySentChunks: true

default 16:57:05.451863 +0200 cloudd mmcs_engine

maxConsecutiveNetworkErrors: 3

default 16:57:05.451898 +0200 cloudd mmcs_engine enableGetResume: true

default 16:57:05.451948 +0200 cloudd mmcs_engine

enableLocallySatisfiedGets: true

default 16:57:05.451969 +0200 cloudd mmcs_engine enableGetChunks: true

default 16:57:05.451987 +0200 cloudd mmcs_engine

enableAttemptedPersistedConnections: true

default 16:57:05.452021 +0200 cloudd mmcs_engine

enableCollapsedContainerGets: true

default 16:57:05.452335 +0200 cloudd File System hfs, Sparse Files Not Supported, Block Size 4096, Free Blocks 115573239

default 16:57:05.453061 +0200 cloudd client.trigger:#N Comes to _setConfiguration for component 0x20

default 16:57:05.453093 +0200 cloudd client.trigger:#N CCFG has # of profiles: 0

default 16:57:05.453604 +0200 cloudd [Operation 0x7ff2867310a0]

Operation transitioning from state 1 (cancelled=0, stop=0, error=0)

default 16:57:05.454338 +0200 cloudd [Operation 0x7ff2867310a0]

Operation is now in state 2

error 16:57:05.455998 +0200 cloudd request via cloudkit does not have a container identifier

```

default 16:57:05.456047 +0200 cloudd #40e3a115
ACSMightCurrentNetworkHaveCachingServer(options={
  capabilities = {
    import = 1;
    namespaces = 1;
    personalCaching = 1;
  };
  quickMiss = 1;
  "x-apple-persistent-identifier" = "";
}, callbackQueue=0x0, callback=0x700005eff890)
default 16:57:05.456315 +0200 cloudd #40e3a115
ACSMightCurrentNetworkHaveCachingServer -> [new] mightHave NO, error (null),
elapsed 0.000
default 16:57:05.458869 +0200 cloudd Chunking finished for itemId 202 of
346803 bytes in 0.0019 sec.
default 16:57:05.458992 +0200 cloudd Engine 0x7ff288239380 completed
request <register req0001 0x7ff28672a6a0 pri0(default)> ([202 chunk ==>
01db8aff09466f04dd1d0c8e71f2556dba761e9778 346803 bytes 22 chunks])
default 16:57:05.459937 +0200 cloudd [Operation 0x7ff2867310a0]
Operation transitioning from state 2 (cancelled=0, stop=0, error=0)
default 16:57:05.460130 +0200 cloudd [Operation 0x7ff286794ff0] Initialized
with context 0x7ff288263070. Background: 1, cellular: 1, QOS: 0x11
default 16:57:05.460274 +0200 cloudd [Operation 0x7ff286794ff0] Request
0x7ff288333080 set on operation
default 16:57:05.460392 +0200 cloudd [Operation 0x7ff2867310a0]
Operation is now in state 3
default 16:57:05.460459 +0200 cloudd [Operation 0x7ff286794ff0] Starting
operation
default 16:57:05.460679 +0200 cloudd [Request 0x7ff288333080]
Performing
default 16:57:05.461757 +0200 cloudd [Request 0x7ff288333080] Getting
URL for the user partition
default 16:57:05.461805 +0200 cloudd [Request 0x7ff288333080] Getting
configuration
default 16:57:05.461919 +0200 cloudd [Request 0x7ff288333080] Fetching
container scoped user ID
default 16:57:05.462000 +0200 cloudd [Request 0x7ff288333080] Getting
device ID
default 16:57:05.462801 +0200 cloudd 0x7ff2882411c0 opened /var/folders/
j8/bbhn9g892k14cv1xw2hp2fy80000gn/C/com.apple.cloudd//mds/mdsObject.db:
4636 bytes
default 16:57:05.463039 +0200 cloudd 0x7ff286783ad0 opened /var/folders/
j8/bbhn9g892k14cv1xw2hp2fy80000gn/C/com.apple.cloudd//mds/mdsDirectory.db:
50744 bytes
default 16:57:05.463168 +0200 cloudd 0x7ff28676b330 opened /Users/
craigdenham/Library/Keychains/login.keychain-db: 218248 bytes
default 16:57:05.465429 +0200 cloudd getting current attributes...
default 16:57:05.465494 +0200 cloudd filling 16 attributes for type
2147483648
default 16:57:05.465665 +0200 securityd 0x7fb8fde06f10(0x7fb8fde138c0) is

```

```

unlocked; decoding for makeUnlocked()
default 16:57:05.465911 +0200 cloudd looking at 16 attributes
default 16:57:05.465974 +0200 cloudd finished:
678313478805ef2e0cddc4f7857c6143d54a87a2e8c8e6fdf18925c96170c628
default 16:57:05.466596 +0200 securityd ACL partitionID = <CFArray
0x7fb8fdd22d80 [0x7ffda12eda0]>{type = mutable-small, count = 1, values = (
    0 : apple:
)}}
default 16:57:05.466616 +0200 securityd ACL partitions match: apple:
default 16:57:05.467026 +0200 cloudd [Request 0x7ff288333080] Getting
push token
default 16:57:05.467065 +0200 cloudd Creating a new client context
0x7ff288254600
default 16:57:05.467153 +0200 cloudd [Request 0x7ff288333080]
Performing request. Background=1, cellular=1
default 16:57:05.468865 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default 16:57:05.472296 +0200 securityd keychain reference in server mode
default 16:57:05.483648 +0200 nsurlsessiond Current discretionary status for
<private> is discretionary (opt-in:0
default 16:57:05.483882 +0200 nsurlsessiond Enqueueing Task 1 with UUID
<private> for client <private>, session <private>
default 16:57:05.483961 +0200 nsurlsessiond Task 1 requesting URL
<private>
default 16:57:05.484691 +0200 nsurlsessiond Client <private> resume for
task 1
default 16:57:05.486273 +0200 nsurlsessiond client.trigger:#N Comes to
_setConfiguration for component 0x35
default 16:57:05.486296 +0200 nsurlsessiond client.trigger:#N CCFG has # of
profiles: 0
default 16:57:05.486436 +0200 nsurlsessiond Task 1 for client <private> will
be retried after error - code: 6
default 16:57:05.486565 +0200 nsurlsessiond Current discretionary status for
<private> is non-discretionary
default 16:57:05.568892 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Outstanding data received: <12000000 3e010001 00020020 5d0b3bbc 3f21c430
7f673285 b914eccc 05ed2711 e0ec6c08 b2c4ff6d d17beca7 0300143e 29ace1c6
ecc8f1bf e260fba2 2bfba5bf d2fd7d> (length 67)
default 16:57:05.568948 +0200 apsd <APSCourier: 0x7ff1122051b0>: Stream
processing: complete yes, invalid no, length parsed 67, parameters {
    APSProtocolAppTokenGenerateResponseCode = 0;
    APSProtocolAppTokenGenerateResponseToken = <5d0b3bbc 3f21c430 7f673285
b914eccc 05ed2711 e0ec6c08 b2c4ff6d d17beca7>;
    APSProtocolAppTokenGenerateResponseTopicHash = <3e29ace1 c6ecc8f1
bfe260fb a22bfba5 bfd2fd7d>;
    APSProtocolCommand = 18;
}
default 16:57:05.568983 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received app token generate response {
    APSProtocolAppTokenGenerateResponseCode = 0;

```

```

APSPProtocolAppTokenGenerateResponseToken = <5d0b3bbc 3f21c430 7f673285
b914eccc 05ed2711 e0ec6c08 b2c4ff6d d17beca7>;
APSPProtocolAppTokenGenerateResponseTopicHash = <3e29ace1 c6ecc8f1
bfe260fb a22bfba5 bfd2fd7d>;
APSPProtocolCommand = 18;
}
default 16:57:05.569016 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received response for token request for topic com.apple.icloud-
container.com.apple.gamed, appld 0, new token = <5d0b3bbc 3f21c430 7f673285
b914eccc 05ed2711 e0ec6c08 b2c4ff6d d17beca7>
default 16:57:05.569086 +0200 apsd <APSCConnectionServer:
0x7ff10fc39740>: Received token <5d0b3bbc 3f21c430 7f673285 b914eccc
05ed2711 e0ec6c08 b2c4ff6d d17beca7> for topic com.apple.icloud-
container.com.apple.gamed with identifier
default 16:57:05.569113 +0200 apsd <APSCConnectionServer:
0x7ff10fc39740>: Sending token <5d0b3bbc 3f21c430 7f673285 b914eccc
05ed2711 e0ec6c08 b2c4ff6d d17beca7> for topic com.apple.icloud-
container.com.apple.gamed with identifier
default 16:57:05.569166 +0200 apsd <APSCourier: 0x7ff1122051b0>: Stream
processing: complete no, invalid no, length parsed 0, parameters (null)
default 16:57:05.569214 +0200 apsd Dispatching low priority message:
<OS_xpc_dictionary: <dictionary: 0x7ff10fd30290> { count = 4, transaction: 0,
voucher = 0x0, contents =
    "identifier" => <string: 0x7ff10fd32eb0> { length = 0, contents = "" }
    "token" => <data: 0x7ff10fd2c720>: { length = 32 bytes, contents =
0x5d0b3bbc3f21c4307f673285b914eccc05ed2711e0ec6c08... }
    "topic" => <string: 0x7ff10fd3e860> { length = 42, contents = "com.apple.icloud-
container.com.apple.gamed" }
    "message-type" => <int64: 0x7ff10fd31fe0>: 30
}>
default 16:57:05.569392 +0200 gamed ApplePushService:
<APSCConnection 0x7ffb3b8061c0 production (null)> Received token <5d0b3bbc
3f21c430 7f673285 b914eccc 05ed2711 e0ec6c08 b2c4ff6d d17beca7> forTopic
com.apple.icloud-container.com.apple.gamed identifier
default 16:57:05.969337 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default 16:57:06.259651 +0200 loginwindow No more connected processes
and no UI is showing
default 16:57:06.327422 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default 16:57:06.331448 +0200 corecaptured pruneDirectoryOnOSUpgrade:
activity enabled; snapshot <private>, osversion <private>
default 16:57:06.579325 +0200 opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default 16:57:06.579408 +0200 opendirectoryd queuing request to connection
- '<private>'
default 16:57:06.579536 +0200 opendirectoryd queuing request to connection
- '<private>'
default 16:57:06.587198 +0200 nsurlsessiond CCDS: requirements <private>
DASActivityProperties (null)

```



```

default    16:57:06.587388 +0200    nsurlsessiond    activity [0x7f97287080c0]
<private> submitted to pool <private>
default    16:57:06.587411 +0200    nsurlsessiond    SUBMITTING: <private>
default    16:57:06.587718 +0200    nsurlsessiond    TIC [0x7f9728707950]: DAS
scheduler submitted activity 0x7f97287080c0
default    16:57:06.588046 +0200    DuetHeuristic-BM    Submitted Activity:
<private>
default    16:57:06.588119 +0200    DuetHeuristic-BM    Start network path
monitoring for '<private>'
default    16:57:06.589094 +0200    DuetHeuristic-BM    <private>:[
<private> ] sumScores:32.700000, denominator:34.700000, FinalDecision: Can
Proceed FinalScore: 0.942363}
default    16:57:06.589138 +0200    DuetHeuristic-BM    '<private>'
DecisionToRun:1 (Bypasses Predictions)
default    16:57:06.589176 +0200    DuetHeuristic-BM    With <private> ...Tasks
running in group <private> are 1!
default    16:57:06.589203 +0200    DuetHeuristic-BM    Stop network path
monitoring for '<private>'
default    16:57:06.589268 +0200    DuetHeuristic-BM    Running activities :
<private>
default    16:57:06.589471 +0200    nsurlsessiond    STARTING: <private>
default    16:57:06.589493 +0200    nsurlsessiond    TIC [0x7f9728707950]: activity
0x7f97287080c0 start handler called
default    16:57:06.589507 +0200    nsurlsessiond    TIC TCP Conn Start
[1:0x7f9728707950]
default    16:57:06.762770 +0200    nsurlsessiond    TIC TCP Conn Event
[1:0x7f9728707950]: 1 Err(0)
default    16:57:06.762786 +0200    nsurlsessiond    TIC TCP Conn Connected
[1:0x7f9728707950]: Err(0)
default    16:57:06.763473 +0200    nsurlsessiond    TIC Enabling TLS
[1:0x7f9728707950]
default    16:57:06.931570 +0200    nsurlsessiond    TIC TLS Event
[1:0x7f9728707950]: 2, Pending(0)
default    16:57:06.944898 +0200    nsurlsessiond    TIC TLS Event
[1:0x7f9728707950]: 11, Pending(0)
default    16:57:06.946254 +0200    nsurlsessiond    0x7f972850a280 opened /var/
folders/j8/bbhn9g892k14cv1xw2hp2fy80000gn/C//mds/mdsObject.db: 4636 bytes
default    16:57:06.948747 +0200    nsurlsessiond    0x7f972850f5e0 opened /var/
folders/j8/bbhn9g892k14cv1xw2hp2fy80000gn/C//mds/mdsDirectory.db: 50744 bytes
default    16:57:06.950390 +0200    nsurlsessiond    0x7f972850e760 opened /var/
folders/j8/bbhn9g892k14cv1xw2hp2fy80000gn/C//mds/mdsDirectory.db: 50744 bytes
default    16:57:07.551127 +0200    com.apple.WebKit.Networking
TIC TCP Conn Event [69:0x7fa644da6020]: 2 Err(0)
default    16:57:07.551156 +0200    com.apple.WebKit.Networking
TIC TCP Conn Cancel [69:0x7fa644da6020]
default    16:57:07.551181 +0200    com.apple.WebKit.Networking
TIC TCP Conn Destroyed [69:0x7fa644da6020]
default    16:57:07.693827 +0200    nsurlsessiond    TIC TLS Event
[1:0x7f9728707950]: 22, Pending(0)
default    16:57:07.693913 +0200    nsurlsessiond    TIC TLS Event

```

```

[1:0x7f9728707950]: 12, Pending(0)
default 16:57:07.693976 +0200 nsurlsessiond TIC TLS Event
[1:0x7f9728707950]: 14, Pending(0)
default 16:57:07.694209 +0200 nsurlsessiond Task 1 for client <private>
received auth challenge with type NSURLAuthenticationMethodServerTrust
default 16:57:07.698197 +0200 trustd ocsp responder: (null) did not
include status of requested cert
default 16:57:07.710568 +0200 nsurlsessiond TIC TLS Trust Result
[1:0x7f9728707950]: 0
default 16:57:07.754987 +0200 nsurlsessiond TIC TLS Event
[1:0x7f9728707950]: 20, Pending(0)
default 16:57:07.755293 +0200 nsurlsessiond TIC TCP Conn Event
[1:0x7f9728707950]: 8 Err(0)
default 16:57:07.755307 +0200 nsurlsessiond TIC TLS Handshake Complete
[1:0x7f9728707950]
default 16:57:07.755607 +0200 nsurlsessiond Task 1 for client <private> has
a connection
default 16:57:07.756067 +0200 cloudd [Request 0x7ff288333080]
requestForEstablishedConnection
default 16:57:07.758845 +0200 opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default 16:57:07.758918 +0200 opendirectoryd queuing request to connection
- '<private>'
default 16:57:07.759077 +0200 opendirectoryd queuing request to connection
- '<private>'
default 16:57:08.068426 +0200 loginwindow There is no connection to
release
default 16:57:08.360947 +0200 nsurlsessiond Task 1 for client <private>
received response, status code: 200
default 16:57:08.361429 +0200 cloudd [Request 0x7ff288333080]
URLSession:dataTask:didReceiveResponse:completionHandler:
default 16:57:08.361929 +0200 cloudd [Request 0x7ff288333080]
URLSession:dataTask:didReceiveData:
default 16:57:08.362043 +0200 nsurlsessiond Task 1 for client <private>
completed successfully
default 16:57:08.362342 +0200 cloudd [Request 0x7ff288333080]
URLSession:task:didCompleteWithError:
default 16:57:08.362557 +0200 cloudd [Request 0x7ff288333080] Finishing
request with no error
default 16:57:08.362827 +0200 cloudd [Operation 0x7ff2867310a0]
Operation transitioning from state 3 (cancelled=0, stop=0, error=0)
default 16:57:08.363035 +0200 cloudd [Operation 0x7ff2867310a0]
Operation is now in state 4
default 16:57:08.363962 +0200 cloudd #41517153
ACSMightCurrentNetworkHaveCachingServer(options={
    capabilities = {
        import = 1;
        namespaces = 1;
        personalCaching = 1;
    };
};

```

```

quickMiss = 1;
"x-apple-persistent-identifier" = 61fd;
}, callbackQueue=0x0, callback=0x700005eff720)
default 16:57:08.364186 +0200 cloudd #41517153
ACSMightCurrentNetworkHaveCachingServer -> [new] mightHave NO, error (null),
elapsed 0.000
default 16:57:08.364520 +0200 cloudd Chunking item (202) 1 of 1
default 16:57:08.364994 +0200 cloudd Chunking finished for itemId 202 of
346803 bytes in 0.0000 sec.
default 16:57:08.365173 +0200 cloudd Container
UBm2Zs4BXEVC23gCD_fG
default 16:57:08.366060 +0200 cloudd PutComplete at Edge Protocol :
false
default 16:57:08.368735 +0200 cloudd HttpSession <MMCSHTTPSession:
0x7ff2865482d0><uuid:A5184EA4-69F7-4A61-B3EA-7DBBF4F4145F
session:s3_eu_irl, z:background-infers-discretionary,
connectionPoolName:com.apple.cloudkit.BackgroundConnectionPool,
sourceID:com.apple.TextEdit, 2ndSourceID:4/
com.apple.clouddocs.com.apple.TextEdit:2,%, adaptiveReadTimeout:3,
adaptiveWriteTimeout:3>
default 16:57:08.368824 +0200 cloudd HttpURL (https://eu-
irl-00001.s3.amazonaws.com:443/UBm2Zs4BXEVC23gCD_fG?x-client-request-
id=BED97576-D25E-4DE3-
A023-34EB7B21D8A2-138764119&bin=203000001&Signature=CfXZ%2B1qXdw14i
TkllctltgVnRy8%3D&AWSAccessKeyId=AKIAI3LLM7P3DRGCUSIA&Expires=14958
13988&region=emea)
default 16:57:08.368924 +0200 cloudd RequestHeader (x-apple-request-
uuid:092C6762-AAA2-42D5-80F8-11FBBFA38487)
default 16:57:08.369119 +0200 cloudd Faulting in NSHTTPCookieStorage
singleton
default 16:57:08.369137 +0200 cloudd Faulting in CFHTTPCookieStorage
singleton
default 16:57:08.369150 +0200 cloudd Creating default cookie storage with
process/bundle identifier
default 16:57:08.369967 +0200 nsurlsessiond Current discretionary status for
<private> is non-discretionary
default 16:57:08.370109 +0200 nsurlsessiond Enqueueing Task 1 with UUID
<private> for client <private>, session <private>
default 16:57:08.370132 +0200 nsurlsessiond Task 1 requesting URL
<private>
default 16:57:08.370389 +0200 cloudd no containers were eligible for
putComplete.
default 16:57:08.370595 +0200 nsurlsessiond Client <private> resume for
task 1
default 16:57:08.371713 +0200 nsurlsessiond 0x7f972871aa80 opened /
Users/craigdenham/Library/Keychains/login.keychain-db: 218248 bytes
default 16:57:08.374059 +0200 nsurlsessiond 0x7f972850c5a0 opened /
Library/Keychains/System.keychain: 37732 bytes
default 16:57:08.376528 +0200 nsurlsessiond TIC TCP [0x0] working for task
<private>

```

default 16:57:08.377027 +0200 nsurlsessiond CCDS: requirements <private>
DASActivityProperties <private>
default 16:57:08.377121 +0200 nsurlsessiond activity [0x7f9728525760]
<private> submitted to pool <private>
default 16:57:08.377178 +0200 nsurlsessiond SUBMITTING: <private>
default 16:57:08.377384 +0200 nsurlsessiond TIC [0x7f97298399d0]: DAS
scheduler submitted activity 0x7f9728525760
default 16:57:08.377727 +0200 DuetHeuristic-BM Submitted Activity:
<private>
default 16:57:08.377813 +0200 DuetHeuristic-BM Start network path
monitoring for '<private>'
default 16:57:08.378047 +0200 DuetHeuristic-BM <private>:[
<private>] sumScores:32.700000, denominator:34.700000, FinalDecision: Can
Proceed FinalScore: 0.942363}
default 16:57:08.378079 +0200 DuetHeuristic-BM '<private>'
DecisionToRun:1 (Bypasses Predictions)
default 16:57:08.378103 +0200 DuetHeuristic-BM With <private> ...Tasks
running in group <private> are 2!
default 16:57:08.378151 +0200 DuetHeuristic-BM Stop network path
monitoring for '<private>'
default 16:57:08.378216 +0200 DuetHeuristic-BM Running activities :
<private>
default 16:57:08.378394 +0200 nsurlsessiond STARTING: <private>
default 16:57:08.378414 +0200 nsurlsessiond TIC [0x7f97298399d0]: activity
0x7f9728525760 start handler called
default 16:57:08.378428 +0200 nsurlsessiond TIC TCP Conn Start
[2:0x7f97298399d0]
default 16:57:08.408231 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff1123130c0> to generate token
for topic "com.apple.icloud-container.com.apple.cloudpaired" and identifier ""
default 16:57:08.408555 +0200 apsd Failed to talk to secd after 4 attempts.
default 16:57:08.408759 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.cloudpaired" and identifier "", assigned appld "0"
default 16:57:08.408850 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff1121367e0> to generate token
for topic "com.apple.icloud-container.com.apple.callhistory.sync-helper" and identifier
""
default 16:57:08.409054 +0200 apsd Failed to talk to secd after 4 attempts.
default 16:57:08.409185 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.callhistory.sync-helper" and identifier "", assigned appld "0"
default 16:57:08.409213 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Rescheduling request to generate token for topic "com.apple.icloud-
container.com.apple.callhistory.sync-helper" and identifier ""
default 16:57:08.453884 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Outstanding data received: <12000000 3e010001 00020020 969a11b3 c92ef82c
6dc34b56 1479173a 89400837 534ff595 ed2484b6 971e4a42 030014e2 225610d1
b716ac87 094ad02a bd95cb72 7975fb> (length 67)
default 16:57:08.453939 +0200 apsd <APSCourier: 0x7ff1122051b0>: Stream

```

processing: complete yes, invalid no, length parsed 67, parameters {
    APSPProtocolAppTokenGenerateResponseCode = 0;
    APSPProtocolAppTokenGenerateResponseToken = <969a11b3 c92ef82c
6dc34b56 1479173a 89400837 534ff595 ed2484b6 971e4a42>;
    APSPProtocolAppTokenGenerateResponseTopicHash = <e2225610 d1b716ac
87094ad0 2abd95cb 727975fb>;
    APSPProtocolCommand = 18;
}
default 16:57:08.453981 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received app token generate response {
    APSPProtocolAppTokenGenerateResponseCode = 0;
    APSPProtocolAppTokenGenerateResponseToken = <969a11b3 c92ef82c
6dc34b56 1479173a 89400837 534ff595 ed2484b6 971e4a42>;
    APSPProtocolAppTokenGenerateResponseTopicHash = <e2225610 d1b716ac
87094ad0 2abd95cb 727975fb>;
    APSPProtocolCommand = 18;
}
default 16:57:08.454020 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received response for token request for topic com.apple.icloud-
container.com.apple.cloudpaired, appld 0, new token = <969a11b3 c92ef82c
6dc34b56 1479173a 89400837 534ff595 ed2484b6 971e4a42>
default 16:57:08.454097 +0200 apsd <APSCConnectionServer:
0x7ff1123130c0>: Received token <969a11b3 c92ef82c 6dc34b56 1479173a
89400837 534ff595 ed2484b6 971e4a42> for topic com.apple.icloud-
container.com.apple.cloudpaired with identifier
default 16:57:08.454130 +0200 apsd <APSCConnectionServer:
0x7ff1123130c0>: Sending token <969a11b3 c92ef82c 6dc34b56 1479173a
89400837 534ff595 ed2484b6 971e4a42> for topic com.apple.icloud-
container.com.apple.cloudpaired with identifier
default 16:57:08.454187 +0200 apsd <APSCourier: 0x7ff1122051b0>: Stream
processing: complete no, invalid no, length parsed 0, parameters (null)
default 16:57:08.454233 +0200 apsd Dispatching low priority message:
<OS_xpc_dictionary: <dictionary: 0x7ff10ff11440> { count = 4, transaction: 0,
voucher = 0x0, contents =
    "identifier" => <string: 0x7ff10ff36530> { length = 0, contents = "" }
    "token" => <data: 0x7ff10ff359a0>: { length = 32 bytes, contents =
0x969a11b3c92ef82c6dc34b561479173a89400837534ff595... }
    "topic" => <string: 0x7ff10ff37da0> { length = 47, contents = "com.apple.icloud-
container.com.apple.cloudpaired" }
    "message-type" => <int64: 0x7ff10ff357a0>: 30
}>
default 16:57:08.454420 +0200 cloudpaired ApplePushService:
<APSCConnection: 0x7fb92c10f9a0> Received token <969a11b3 c92ef82c 6dc34b56
1479173a 89400837 534ff595 ed2484b6 971e4a42> forTopic com.apple.icloud-
container.com.apple.cloudpaired identifier
default 16:57:08.466133 +0200 nsurlsessiond TIC TCP Conn Event
[2:0x7f97298399d0]: 1 Err(0)
default 16:57:08.466154 +0200 nsurlsessiond TIC TCP Conn Connected
[2:0x7f97298399d0]: Err(0)
default 16:57:08.466493 +0200 nsurlsessiond TIC Enabling TLS

```

```

[2:0x7f97298399d0]
default    16:57:08.527558 +0200    nsurlsessiond    TIC TLS Event
[2:0x7f97298399d0]: 2, Pending(0)
default    16:57:08.534058 +0200    nsurlsessiond    TIC TLS Event
[2:0x7f97298399d0]: 11, Pending(0)
default    16:57:08.537192 +0200    nsurlsessiond    TIC TLS Event
[2:0x7f97298399d0]: 12, Pending(0)
default    16:57:08.540147 +0200    nsurlsessiond    TIC TLS Event
[2:0x7f97298399d0]: 14, Pending(0)
default    16:57:08.540330 +0200    nsurlsessiond    Task 1 for client <private>
received auth challenge with type NSURLAuthenticationMethodServerTrust
default    16:57:08.541249 +0200    trustd          0x7fe3b4f16c50 opened /var/folders/
j8/bbhn9g892k14cv1xw2hp2fy80000gn/C//mds/mdsObject.db: 4636 bytes
default    16:57:08.544057 +0200    trustd          0x7fe3b6b137d0 opened /var/
folders/j8/bbhn9g892k14cv1xw2hp2fy80000gn/C//mds/mdsDirectory.db: 50744 bytes
default    16:57:08.544247 +0200    trustd          0x7fe3b4f1af00 opened /Users/
craigdenham/Library/Keychains/login.keychain-db: 218248 bytes
default    16:57:08.546582 +0200    trustd          0x7fe3b4f063f0 opened /Library/
Keychains/System.keychain: 37732 bytes
default    16:57:08.548720 +0200    trustd          0x7fe3b6b09fb0 opened /System/
Library/Keychains/SystemRootCertificates.keychain: 385940 bytes
default    16:57:08.552904 +0200    nsurlsessiond    TIC TLS Trust Result
[2:0x7f97298399d0]: 0
default    16:57:08.620032 +0200    nsurlsessiond    TIC TLS Event
[2:0x7f97298399d0]: 20, Pending(0)
default    16:57:08.620307 +0200    nsurlsessiond    TIC TCP Conn Event
[2:0x7f97298399d0]: 8 Err(0)
default    16:57:08.620339 +0200    nsurlsessiond    TIC TLS Handshake Complete
[2:0x7f97298399d0]
default    16:57:08.620514 +0200    nsurlsessiond    TIC TCP [0x7f97298399d0]
working for task <private>
default    16:57:08.620950 +0200    nsurlsessiond    TIC TCP [0x7f97298399d0]
working for task <private>
default    16:57:08.621147 +0200    nsurlsessiond    Task 1 for client <private> has
a connection
default    16:57:08.622032 +0200    nsurlsessiond    TIC TCP [0x7f97298399d0]
working for task <private>
default    16:57:08.622474 +0200    nsurlsessiond    TIC TCP [0x7f97298399d0]
working for task <private>
default    16:57:09.719627 +0200    nsurlsessiond    TIC TCP Conn Cancel
[1:0x7f9728707950]
default    16:57:09.719664 +0200    nsurlsessiond    TIC TCP [0x7f9728707950]
completing activity 0x7f97287080c0
default    16:57:09.719862 +0200    nsurlsessiond    TIC TCP Conn Destroyed
[1:0x7f9728707950]
default    16:57:09.720075 +0200    DuetHeuristic-BM    COMPLETED <private>!
default    16:57:09.720101 +0200    DuetHeuristic-BM    Stop network path
monitoring for '<private>'
default    16:57:09.720129 +0200    DuetHeuristic-BM    NO LONGER RUNNING
<private> ...Tasks running in group [<private>] are 1!

```

```

default    16:57:10.275992 +0200    nsurlsessiond    Task 1 for client <private>
received response, status code: 200
default    16:57:10.276544 +0200    cloudd          HttpStatus (HTTP/1.1 200 no error)
default    16:57:10.276575 +0200    cloudd          ResponseHeader
(Server:AmazonS3)
default    16:57:10.276711 +0200    nsurlsessiond    Task 1 for client <private>
completed successfully
default    16:57:10.277053 +0200    cloudd          Observed 1.4521 Mbps over 1.9106
seconds for 346803 bytes. 0.0047 seconds in queue.
default    16:57:10.277102 +0200    cloudd          Handling Vendor Response
default    16:57:10.277235 +0200    cloudd          Adding container
UBm2Zs4BXEVC23gCD_fG to putComplete.
default    16:57:10.277487 +0200    cloudd          HttpSession <MMCSHTTPSession:
0x7ff286761860><uuid:1F724D4C-8C95-44FE-8033-7336B7C14EA0
session:default, z:foreground, adaptiveReadTimeout:3, adaptiveWriteTimeout:3>
default    16:57:10.277572 +0200    cloudd          HttpURL (https://p46-
content.icloud.com:443/1023422711/putComplete)
default    16:57:10.277655 +0200    cloudd          RequestHeader (x-apple-request-
uuid:A4273004-A561-4166-90B8-6EF369608EA8)
default    16:57:10.278323 +0200    cloudd          0x7ff288243450 opened /Library/
Keychains/System.keychain: 37732 bytes
default    16:57:10.280665 +0200    cloudd          TIC TCP Conn Start
[2:0x7ff288265ac0]
default    16:57:10.289510 +0200    UserEventAgent    SUBMITTING: <private>
default    16:57:10.289569 +0200    UserEventAgent    Registered XPC Activity:
com.apple.mds.0
default    16:57:10.289766 +0200    DuetHeuristic-BM    Submitted Activity:
<private>
default    16:57:10.289954 +0200    DuetHeuristic-BM    Activity <private>:
Optimal Score 0.4745 at <private> (Valid Until: <private>)
default    16:57:10.290233 +0200    DuetHeuristic-BM    <private>:[
<private> ] sumScores:37.010000, denominator:39.010000, FinalDecision: Can
Proceed FinalScore: 0.948731}
default    16:57:10.290261 +0200    DuetHeuristic-BM    '<private>' CurrentScore:
0.948731, ThresholdScore: 0.421668 DecisionToRun:1
default    16:57:10.290287 +0200    DuetHeuristic-BM    Running activities :
<private>
default    16:57:10.290423 +0200    UserEventAgent    STARTING: <private>
default    16:57:10.335791 +0200    cloudd          TIC TCP Conn Event
[2:0x7ff288265ac0]: 1 Err(0)
default    16:57:10.335810 +0200    cloudd          TIC TCP Conn Connected
[2:0x7ff288265ac0]: Err(0)
default    16:57:10.335904 +0200    cloudd          TIC Enabling TLS
[2:0x7ff288265ac0]
default    16:57:10.377218 +0200    cloudd          TIC TLS Event [2:0x7ff288265ac0]:
2, Pending(0)
default    16:57:10.384301 +0200    UserEventAgent    Initiating XPC Activity:
com.apple.mds.0
default    16:57:10.384328 +0200    cloudd          TIC TLS Event [2:0x7ff288265ac0]:
11, Pending(0)

```

default	16:57:10.384643 +0200	cloudd	TIC TLS Event [2:0x7ff288265ac0]: 22, Pending(0)
default	16:57:10.384743 +0200	cloudd	TIC TLS Event [2:0x7ff288265ac0]: 12, Pending(0)
default	16:57:10.384770 +0200	cloudd	TIC TLS Event [2:0x7ff288265ac0]: 14, Pending(0)
default	16:57:10.385193 +0200	cloudd	could not disable pinning: not an internal release
default	16:57:10.385443 +0200	UserEventAgent	Completed XPC Activity: com.apple.mds.0
default	16:57:10.385971 +0200	DuetHeuristic-BM	COMPLETED <private>!
default	16:57:10.386004 +0200	cloudd	could not enable test cert: AppleServerAuthenticationAllowUATMMCS not true
default	16:57:10.386048 +0200	cloudd	could not enable test hierarchy: AppleServerAuthenticationAllowUAT not true
default	16:57:10.386336 +0200	UserEventAgent	Unregistered XPC Activity: com.apple.mds.0
default	16:57:10.386914 +0200	trustd	0x7fe3b6b16d80 opened /System/ Library/Keychains/SystemRootCertificates.keychain: 385940 bytes
default	16:57:10.392170 +0200	trustd	ocsp responder: (null) did not include status of requested cert
default	16:57:10.394253 +0200	cloudd	TIC TLS Trust Result [2:0x7ff288265ac0]: 0
default	16:57:10.430969 +0200	cloudd	TIC TLS Event [2:0x7ff288265ac0]: 20, Pending(0)
default	16:57:10.431155 +0200	cloudd	TIC TCP Conn Event [2:0x7ff288265ac0]: 8 Err(0)
default	16:57:10.431171 +0200	cloudd	TIC TLS Handshake Complete [2:0x7ff288265ac0]
default	16:57:10.630512 +0200	cloudd	HttpStatus (HTTP/1.1 200 no error)
default	16:57:10.630551 +0200	cloudd	ResponseHeader (X-Apple- Request-UUID:A4273004-A561-4166-90B8-6EF369608EA8)
default	16:57:10.630568 +0200	cloudd	ResponseHeader (Via:xrail:mr90p00ic-zteu08120301:8301:16G93:p21, icloudedge:br30p00ic- zteu01132101:7401:17C49:Berlin)
default	16:57:10.630585 +0200	cloudd	ResponseHeader (Server:AppleHttpServer/1dad28f)
default	16:57:10.630600 +0200	cloudd	ResponseHeader (X-Responding- Instance:content.34600501.mr25p46ic-tydg01161401:8001.17D46)
default	16:57:10.630899 +0200	cloudd	Observed 0.0164 Mbps over 0.3535 seconds for 725 bytes. 0.0006 seconds in queue.
default	16:57:10.630971 +0200	cloudd	Server Receipt Received. itemId:202 receipt:Ay2QDdj5elc/emY7 sig:01db8aff09466f04dd1d0c8e71f2556dba761e9778 ref:010c75512f82f86ba2ad0739ded136bccd74e26033 len:346803
default	16:57:10.631105 +0200	cloudd	Uploads complete. All done! (Put request 0x7ff288333080)
default	16:57:10.631705 +0200	cloudd	[Operation 0x7ff2867310a0] Operation transitioning from state 4 (cancelled=0, stop=0, error=0)
default	16:57:10.631736 +0200	cloudd	[Operation 0x7ff2867310a0] Operation is now in state 4294967295


```

default 16:57:10.631810 +0200 cloudd [Operation 0x7ff28832d180]
Operation transitioning from state 9 (cancelled=0, stop=0, error=0)
default 16:57:10.631847 +0200 cloudd [Operation 0x7ff28832d180]
Operation is now in state 15
default 16:57:10.631888 +0200 cloudd [Operation 0x7ff28832d180]
Operation transitioning from state 15 (cancelled=0, stop=0, error=0)
default 16:57:10.631934 +0200 cloudd [Operation 0x7ff28832d180]
Operation is now in state 4294967295
default 16:57:10.635637 +0200 bird [NOTICE] finished uploading 1 items
(<private>) in com.apple.TextEdit
default 16:57:10.636785 +0200 cloudd [Operation 0x7ff28831b930]
Initialized with context 0x7ff288263070. Background: 1, cellular: 1, QOS: 0x11
default 16:57:10.637115 +0200 cloudd [Operation 0x7ff28831b930] Starting
operation
default 16:57:10.637479 +0200 cloudd [Operation 0x7ff2867a2940]
Initialized with context 0x7ff288263070. Background: 1, cellular: 1, QOS: 0x11
default 16:57:10.637676 +0200 cloudd [Operation 0x7ff2867a2940] Starting
operation
default 16:57:10.637915 +0200 cloudd [Operation 0x7ff28831b930]
Request 0x7ff28827f7d0 set on operation
default 16:57:10.638034 +0200 cloudd [Request 0x7ff28827f7d0]
Performing
default 16:57:10.638195 +0200 cloudd [Request 0x7ff28827f7d0] Getting
URL for the user partition
default 16:57:10.638252 +0200 cloudd [Request 0x7ff28827f7d0] Getting
configuration
default 16:57:10.638351 +0200 cloudd [Request 0x7ff28827f7d0] Fetching
container scoped user ID
default 16:57:10.638435 +0200 cloudd [Request 0x7ff28827f7d0] Getting
device ID
default 16:57:10.638491 +0200 cloudd [Request 0x7ff28827f7d0] Getting
zone gates
default 16:57:10.638714 +0200 cloudd [Request 0x7ff28827f7d0] Getting
push token
default 16:57:10.638794 +0200 cloudd Creating a new client context
0x7ff288003550
default 16:57:10.638814 +0200 cloudd [Request 0x7ff28827f7d0]
Performing request. Background=1, cellular=1
default 16:57:10.639834 +0200 nsurlsessiond Current discretionary status for
<private> is non-discretionary
default 16:57:10.639936 +0200 nsurlsessiond Enqueueing Task 2 with UUID
<private> for client <private>, session <private>
default 16:57:10.639971 +0200 nsurlsessiond Task 2 requesting URL
<private>
default 16:57:10.640330 +0200 nsurlsessiond Client <private> resume for
task 2
default 16:57:10.642770 +0200 opendiroryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default 16:57:10.642846 +0200 opendiroryd queuing request to connection
- '<private>'

```

default 16:57:10.642990 +0200 opendirectoryd queuing request to connection - '<private>'

default 16:57:10.648250 +0200 nsurlsessiond TIC TCP [0x0] working for task <private>

default 16:57:10.648609 +0200 nsurlsessiond CCDS: requirements <private> DASActivityProperties <private>

default 16:57:10.648648 +0200 nsurlsessiond activity [0x7f9728411350] <private> submitted to pool <private>

default 16:57:10.648694 +0200 nsurlsessiond SUBMITTING: <private>

default 16:57:10.648840 +0200 nsurlsessiond TIC [0x7f9729816f70]: DAS scheduler submitted activity 0x7f9728411350

default 16:57:10.649096 +0200 DuetHeuristic-BM Submitted Activity: <private>

default 16:57:10.649178 +0200 DuetHeuristic-BM Start network path monitoring for '<private>'

default 16:57:10.649387 +0200 DuetHeuristic-BM <private>:[<private>] sumScores:32.700000, denominator:34.700000, FinalDecision: Can Proceed FinalScore: 0.942363}

default 16:57:10.649427 +0200 DuetHeuristic-BM '<private>' DecisionToRun:1 (Bypasses Predictions)

default 16:57:10.649467 +0200 DuetHeuristic-BM With <private> ...Tasks running in group <private> are 2!

default 16:57:10.649513 +0200 DuetHeuristic-BM Stop network path monitoring for '<private>'

default 16:57:10.649590 +0200 DuetHeuristic-BM Running activities : <private>

default 16:57:10.649806 +0200 nsurlsessiond STARTING: <private>

default 16:57:10.649856 +0200 nsurlsessiond TIC [0x7f9729816f70]: activity 0x7f9728411350 start handler called

default 16:57:10.649900 +0200 nsurlsessiond TIC TCP Conn Start [3:0x7f9729816f70]

default 16:57:10.718947 +0200 nsurlsessiond TIC TCP Conn Event [3:0x7f9729816f70]: 1 Err(0)

default 16:57:10.718961 +0200 nsurlsessiond TIC TCP Conn Connected [3:0x7f9729816f70]: Err(0)

default 16:57:10.719302 +0200 nsurlsessiond TIC Enabling TLS [3:0x7f9729816f70]

default 16:57:10.761467 +0200 nsurlsessiond TIC TLS Event [3:0x7f9729816f70]: 2, Pending(0)

default 16:57:10.764820 +0200 nsurlsessiond TIC TLS Event [3:0x7f9729816f70]: 11, Pending(0)

default 16:57:10.767450 +0200 nsurlsessiond TIC TLS Event [3:0x7f9729816f70]: 22, Pending(0)

default 16:57:10.767563 +0200 nsurlsessiond TIC TLS Event [3:0x7f9729816f70]: 12, Pending(0)

default 16:57:10.767619 +0200 nsurlsessiond TIC TLS Event [3:0x7f9729816f70]: 14, Pending(0)

default 16:57:10.767804 +0200 nsurlsessiond Task 2 for client <private> received auth challenge with type NSURLAuthenticationMethodServerTrust

default 16:57:10.771581 +0200 trustd ocsp responder: (null) did not

include status of requested cert
default 16:57:10.774581 +0200 nsurlsessiond TIC TLS Trust Result
[3:0x7f9729816f70]: 0
default 16:57:10.810148 +0200 nsurlsessiond TIC TLS Event
[3:0x7f9729816f70]: 20, Pending(0)
default 16:57:10.810452 +0200 nsurlsessiond TIC TCP Conn Event
[3:0x7f9729816f70]: 8 Err(0)
default 16:57:10.810473 +0200 nsurlsessiond TIC TLS Handshake Complete
[3:0x7f9729816f70]
default 16:57:10.810629 +0200 nsurlsessiond TIC TCP [0x7f9729816f70]
working for task <private>
default 16:57:10.810679 +0200 nsurlsessiond TIC TCP [0x7f9729816f70]
working for task <private>
default 16:57:10.810815 +0200 nsurlsessiond Task 2 for client <private> has
a connection
default 16:57:10.811208 +0200 cloudd [Request 0x7ff28827f7d0]
requestForEstablishedConnection
default 16:57:10.813377 +0200 opendiroryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default 16:57:10.813438 +0200 opendiroryd queuing request to connection
- '<private>'
default 16:57:10.813540 +0200 opendiroryd queuing request to connection
- '<private>'
default 16:57:10.818817 +0200 nsurlsessiond TIC TCP [0x7f9729816f70]
working for task <private>
default 16:57:10.818864 +0200 nsurlsessiond TIC TCP [0x7f9729816f70]
working for task <private>
default 16:57:11.040086 +0200 nsurlsessiond Task 2 for client <private>
received response, status code: 200
default 16:57:11.040466 +0200 cloudd [Request 0x7ff28827f7d0]
URLSession:dataTask:didReceiveResponse:completionHandler:
default 16:57:11.040938 +0200 cloudd [Request 0x7ff28827f7d0]
URLSession:dataTask:didReceiveData:
default 16:57:11.041049 +0200 nsurlsessiond Task 2 for client <private>
completed successfully
default 16:57:11.041287 +0200 cloudd [Request 0x7ff28827f7d0]
URLSession:task:didCompleteWithError:
default 16:57:11.041378 +0200 cloudd [Request 0x7ff28827f7d0] Finishing
request with no error
default 16:57:11.042021 +0200 bird [NOTICE] received 0 edited items from
the cloud for com.apple.TextEdit
default 16:57:11.049355 +0200 bird [NOTICE] sending 1 items to the cloud for
com.apple.TextEdit
default 16:57:11.231206 +0200 cloudd [Operation 0x7ff288267050]
Initialized with context 0x7ff288263070. Background: 1, cellular: 1, QOS: 0x11
default 16:57:11.231545 +0200 cloudd [Operation 0x7ff288267050] Starting
operation
default 16:57:11.231741 +0200 cloudd [Operation 0x7ff288267050]
Operation transitioning from state 1 (cancelled=0, stop=0, error=0)
default 16:57:11.231774 +0200 cloudd [Operation 0x7ff288267050]

Operation is now in state 2
default 16:57:11.231806 +0200 cloudd [Operation 0x7ff288267050]
Operation transitioning from state 2 (cancelled=0, stop=0, error=0)
default 16:57:11.231835 +0200 cloudd [Operation 0x7ff288267050]
Operation is now in state 3
default 16:57:11.231875 +0200 cloudd [Operation 0x7ff288267050]
Operation transitioning from state 3 (cancelled=0, stop=0, error=0)
default 16:57:11.231918 +0200 cloudd [Operation 0x7ff288267050]
Operation is now in state 4
default 16:57:11.231950 +0200 cloudd [Operation 0x7ff288267050]
Operation transitioning from state 4 (cancelled=0, stop=0, error=0)
default 16:57:11.231996 +0200 cloudd [Operation 0x7ff288267050]
Operation is now in state 5
default 16:57:11.232069 +0200 cloudd [Operation 0x7ff288267050]
Operation transitioning from state 5 (cancelled=0, stop=0, error=0)
default 16:57:11.232133 +0200 cloudd [Operation 0x7ff288267050]
Operation is now in state 6
default 16:57:11.232173 +0200 cloudd [Operation 0x7ff288267050]
Operation transitioning from state 6 (cancelled=0, stop=0, error=0)
default 16:57:11.232220 +0200 cloudd [Operation 0x7ff288267050]
Operation is now in state 8
default 16:57:11.232264 +0200 cloudd [Operation 0x7ff288267050]
Operation transitioning from state 8 (cancelled=0, stop=0, error=0)
default 16:57:11.232421 +0200 cloudd [Operation 0x7ff288267050]
Operation is now in state 7
default 16:57:11.232542 +0200 cloudd [Operation 0x7ff28654ab80]
Initialized with context 0x7ff288263070. Background: 1, cellular: 1, QOS: 0x11
default 16:57:11.232691 +0200 cloudd [Operation 0x7ff28654ab80] Starting
operation
default 16:57:11.232907 +0200 cloudd [Operation 0x7ff28654ab80]
Operation transitioning from state 1 (cancelled=0, stop=0, error=0)
default 16:57:11.232953 +0200 cloudd [Operation 0x7ff28654ab80]
Operation is now in state 2
default 16:57:11.233044 +0200 cloudd [Operation 0x7ff28654ab80]
Operation transitioning from state 2 (cancelled=0, stop=0, error=0)
default 16:57:11.233081 +0200 cloudd [Operation 0x7ff28654ab80]
Operation is now in state 2
default 16:57:11.233129 +0200 cloudd [Operation 0x7ff28654ab80]
Operation transitioning from state 2 (cancelled=0, stop=1, error=0)
default 16:57:11.234556 +0200 cloudd [Operation 0x7ff286432a90]
Initialized with context 0x7ff288263070. Background: 1, cellular: 1, QOS: 0x11
default 16:57:11.234704 +0200 cloudd [Operation 0x7ff286432a90] Starting
operation
default 16:57:11.234857 +0200 cloudd [Operation 0x7ff286432a90]
Operation transitioning from state 1 (cancelled=0, stop=0, error=0)
default 16:57:11.234894 +0200 cloudd [Operation 0x7ff286432a90]
Operation is now in state 2
default 16:57:11.234979 +0200 cloudd [Operation 0x7ff286432a90]
Operation transitioning from state 2 (cancelled=0, stop=0, error=0)
default 16:57:11.235040 +0200 cloudd [Operation 0x7ff286432a90]

Operation is now in state 3

```
default 16:57:11.235290 +0200 cloudd [Operation 0x7ff288233de0]
Initialized with context 0x7ff288263070. Background: 1, cellular: 1, QOS: 0x11
default 16:57:11.235366 +0200 cloudd [Operation 0x7ff288233de0] Starting
operation
default 16:57:11.235560 +0200 cloudd [Operation 0x7ff288233de0]
Operation transitioning from state 1 (cancelled=0, stop=0, error=0)
default 16:57:11.236182 +0200 cloudd PCSError: 27 : Identity of service
type Raw missing in memory keyset
default 16:57:11.238698 +0200 cloudd PCSError: 27 : Identity of service
type Raw missing in memory keyset
default 16:57:11.255331 +0200 cloudd [Operation 0x7ff288233de0]
Request 0x7ff2882803a0 set on operation
default 16:57:11.255467 +0200 cloudd [Request 0x7ff2882803a0]
Performing
default 16:57:11.255675 +0200 cloudd [Request 0x7ff2882803a0] Getting
URL for the user partition
default 16:57:11.255756 +0200 cloudd [Request 0x7ff2882803a0] Getting
configuration
default 16:57:11.255843 +0200 cloudd [Operation 0x7ff288233de0]
Operation is now in state 2
default 16:57:11.255905 +0200 cloudd [Request 0x7ff2882803a0] Fetching
container scoped user ID
default 16:57:11.256014 +0200 cloudd [Request 0x7ff2882803a0] Getting
device ID
default 16:57:11.256075 +0200 cloudd [Request 0x7ff2882803a0] Getting
zone gates
default 16:57:11.256320 +0200 cloudd [Request 0x7ff2882803a0] Getting
push token
default 16:57:11.256409 +0200 cloudd Creating a new client context
0x7ff28654ab80
default 16:57:11.256453 +0200 cloudd [Request 0x7ff2882803a0]
Performing request. Background=1, cellular=1
default 16:57:11.257513 +0200 nsurlsessiond Current discretionary status for
<private> is non-discretionary
default 16:57:11.257668 +0200 nsurlsessiond Enqueueing Task 3 with UUID
<private> for client <private>, session <private>
default 16:57:11.257720 +0200 nsurlsessiond Task 3 requesting URL
<private>
default 16:57:11.258092 +0200 nsurlsessiond Client <private> resume for
task 3
default 16:57:11.260669 +0200 opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default 16:57:11.260754 +0200 opendirectoryd queuing request to connection
- '<private>'
default 16:57:11.260921 +0200 opendirectoryd queuing request to connection
- '<private>'
default 16:57:11.266350 +0200 nsurlsessiond TIC TCP [0x7f9729816f70]
working for task <private>
default 16:57:11.266401 +0200 nsurlsessiond TIC TCP [0x7f9729816f70]
```

working for task <private>
default 16:57:11.266570 +0200 nsurlsessiond Task 3 for client <private> has a connection
default 16:57:11.266957 +0200 cloudd [Request 0x7ff2882803a0] requestForEstablishedConnection
default 16:57:11.269345 +0200 opendirirectoryd Client: <private>, UID: 501, EUID: 501, GID: 20, EGID: 20
default 16:57:11.269443 +0200 opendirirectoryd queuing request to connection - '<private>'
default 16:57:11.269633 +0200 opendirirectoryd queuing request to connection - '<private>'
default 16:57:11.275265 +0200 nsurlsessiond TIC TCP [0x7f9729816f70] working for task <private>
default 16:57:11.275315 +0200 nsurlsessiond TIC TCP [0x7f9729816f70] working for task <private>
default 16:57:11.486723 +0200 nsurlsessiond Task 3 for client <private> received response, status code: 200
default 16:57:11.487108 +0200 cloudd [Request 0x7ff2882803a0] URLSession:dataTask:didReceiveResponse:completionHandler:
default 16:57:11.487529 +0200 cloudd [Request 0x7ff2882803a0] URLSession:dataTask:didReceiveData:
default 16:57:11.487606 +0200 nsurlsessiond Task 3 for client <private> completed successfully
default 16:57:11.487828 +0200 cloudd [Request 0x7ff2882803a0] Received a server error (3)
default 16:57:11.487855 +0200 cloudd [Request 0x7ff2882803a0] URLSession:task:didCompleteWithError:
default 16:57:11.487979 +0200 cloudd [Request 0x7ff2882803a0] Node level failure encountered while parsing
default 16:57:11.488201 +0200 cloudd [Request 0x7ff2882803a0] Finishing request with no error
default 16:57:11.488263 +0200 cloudd [Operation 0x7ff286432a90] Operation transitioning from state 3 (cancelled=0, stop=0, error=0)
default 16:57:11.488300 +0200 cloudd [Operation 0x7ff286432a90] Operation is now in state 3
default 16:57:11.488330 +0200 cloudd [Operation 0x7ff286432a90] Operation transitioning from state 3 (cancelled=0, stop=1, error=0)
default 16:57:11.488568 +0200 cloudd [Operation 0x7ff288233de0] Request 0x0 set on operation
default 16:57:11.488632 +0200 cloudd [Operation 0x7ff288233de0] Operation transitioning from state 2 (cancelled=0, stop=0, error=0)
default 16:57:11.488656 +0200 cloudd [Operation 0x7ff288233de0] Operation is now in state 3
default 16:57:11.488680 +0200 cloudd [Operation 0x7ff288233de0] Operation transitioning from state 3 (cancelled=0, stop=0, error=0)
default 16:57:11.488735 +0200 cloudd [Operation 0x7ff288233de0] Operation is now in state 4294967295
default 16:57:11.489738 +0200 cloudd PCSError: 27 : Identity of service type Raw missing in memory keyset
default 16:57:11.490145 +0200 cloudd [Operation 0x7ff288267050]

Operation transitioning from state 7 (cancelled=0, stop=0, error=0)
default 16:57:11.490290 +0200 cloudd [Operation 0x7ff288279b00]
Initialized with context 0x7ff288263070. Background: 1, cellular: 1, QOS: 0x11
default 16:57:11.490393 +0200 cloudd [Operation 0x7ff288267050]
Operation is now in state 9
default 16:57:11.490440 +0200 cloudd [Operation 0x7ff288279b00] Starting operation
default 16:57:11.490679 +0200 cloudd [Operation 0x7ff288279b00]
Operation transitioning from state 1 (cancelled=0, stop=0, error=0)
default 16:57:11.491090 +0200 cloudd [Operation 0x7ff288279b00]
Operation is now in state 2
error 16:57:11.491684 +0200 cloudd request via cloudkit does not have a container identifier
default 16:57:11.491732 +0200 cloudd #df83c4d7
ACSMightCurrentNetworkHaveCachingServer(options={
capabilities = {
import = 1;
namespaces = 1;
personalCaching = 1;
};
quickMiss = 1;
"x-apple-persistent-identifier" = "";
}, callbackQueue=0x0, callback=0x700005eff890)
default 16:57:11.492015 +0200 cloudd #df83c4d7
ACSMightCurrentNetworkHaveCachingServer -> [new] mightHave NO, error (null), elapsed 0.000
default 16:57:11.492440 +0200 cloudd Chunking finished for itemId 203 of 203 bytes in 0.0001 sec.
default 16:57:11.492518 +0200 cloudd Engine 0x7ff288239380 completed request <register req0003 0x7ff2865268c0 pri0(default)> ([203 chunk ==> 01b022081853a10e3424cbff54db298e38001fa598 203 bytes 1 chunks])
default 16:57:11.492944 +0200 cloudd [Operation 0x7ff288279b00]
Operation transitioning from state 2 (cancelled=0, stop=0, error=0)
default 16:57:11.493023 +0200 cloudd [Operation 0x7ff2865268c0]
Initialized with context 0x7ff288263070. Background: 1, cellular: 1, QOS: 0x11
default 16:57:11.493101 +0200 cloudd [Operation 0x7ff2865268c0]
Request 0x7ff2867ab210 set on operation
default 16:57:11.493174 +0200 cloudd [Operation 0x7ff288279b00]
Operation is now in state 3
default 16:57:11.493198 +0200 cloudd [Operation 0x7ff2865268c0] Starting operation
default 16:57:11.493370 +0200 cloudd [Request 0x7ff2867ab210]
Performing
default 16:57:11.493466 +0200 cloudd [Request 0x7ff2867ab210] Getting URL for the user partition
default 16:57:11.493491 +0200 cloudd [Request 0x7ff2867ab210] Getting configuration
default 16:57:11.493524 +0200 cloudd [Request 0x7ff2867ab210] Fetching container scoped user ID
default 16:57:11.493585 +0200 cloudd [Request 0x7ff2867ab210] Getting

```

device ID
default 16:57:11.493742 +0200 cloudd [Request 0x7ff2867ab210] Getting
push token
default 16:57:11.493778 +0200 cloudd Creating a new client context
0x7ff28654f2e0
default 16:57:11.493813 +0200 cloudd [Request 0x7ff2867ab210]
Performing request. Background=1, cellular=1
default 16:57:11.494698 +0200 nsurlsessiond Current discretionary status for
<private> is non-discretionary
default 16:57:11.494792 +0200 nsurlsessiond Enqueueing Task 4 with UUID
<private> for client <private>, session <private>
default 16:57:11.494813 +0200 nsurlsessiond Task 4 requesting URL
<private>
default 16:57:11.495115 +0200 nsurlsessiond Client <private> resume for
task 4
default 16:57:11.497414 +0200 opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default 16:57:11.497474 +0200 opendirectoryd queuing request to connection
- '<private>'
default 16:57:11.497594 +0200 opendirectoryd queuing request to connection
- '<private>'
default 16:57:11.503108 +0200 nsurlsessiond TIC TCP [0x7f9729816f70]
working for task <private>
default 16:57:11.503159 +0200 nsurlsessiond TIC TCP [0x7f9729816f70]
working for task <private>
default 16:57:11.503292 +0200 nsurlsessiond Task 4 for client <private> has
a connection
default 16:57:11.503680 +0200 cloudd [Request 0x7ff2867ab210]
requestForEstablishedConnection
default 16:57:11.506071 +0200 opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default 16:57:11.506153 +0200 opendirectoryd queuing request to connection
- '<private>'
default 16:57:11.506291 +0200 opendirectoryd queuing request to connection
- '<private>'
default 16:57:11.511593 +0200 nsurlsessiond TIC TCP [0x7f9729816f70]
working for task <private>
default 16:57:11.511640 +0200 nsurlsessiond TIC TCP [0x7f9729816f70]
working for task <private>
default 16:57:11.618438 +0200 apsd TIC TCP Conn Cancel [3:0x7ff10fc3b760]
default 16:57:11.618439 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request from <APSCConnectionServer: 0x7ff1121367e0> to generate token
for topic "com.apple.icloud-container.com.apple.callhistory.sync-helper" and identifier
""
default 16:57:11.618492 +0200 apsd TIC TCP Conn Destroyed
[3:0x7ff10fc3b760]
default 16:57:11.618492 +0200 apsd TIC TCP Conn Cancel [1:0x7ff10fc28df0]
default 16:57:11.618540 +0200 apsd TIC TCP Conn Destroyed
[1:0x7ff10fc28df0]
default 16:57:11.618833 +0200 apsd Failed to talk to secd after 4 attempts.

```



```

default 16:57:11.619033 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received request to generate token for topic "com.apple.icloud-
container.com.apple.callhistory.sync-helper" and identifier "", assigned appld "0"
default 16:57:11.630528 +0200 nsurlsessiond TIC TCP Conn Cancel
[2:0x7f97298399d0]
default 16:57:11.630571 +0200 nsurlsessiond TIC TCP [0x7f97298399d0]
completing activity 0x7f9728525760
default 16:57:11.630984 +0200 DuetHeuristic-BM COMPLETED <private>!
default 16:57:11.631014 +0200 DuetHeuristic-BM Stop network path
monitoring for '<private>'
default 16:57:11.631042 +0200 DuetHeuristic-BM NO LONGER RUNNING
<private> ...Tasks running in group [<private>] are 1!
default 16:57:11.658848 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Outstanding data received: <12000000 3e010001 00020020 a3b4c19f ba39b203
57e3c3cc 940abc98 70519617 78ba5fed 17bcb956 0162f9e3 03001481 ea80a8e2
92d1e699 6ce771c2 bb099dc2 84f055> (length 67)
default 16:57:11.658911 +0200 apsd <APSCourier: 0x7ff1122051b0>: Stream
processing: complete yes, invalid no, length parsed 67, parameters {
    APSProtocolAppTokenGenerateResponseCode = 0;
    APSProtocolAppTokenGenerateResponseToken = <a3b4c19f ba39b203
57e3c3cc 940abc98 70519617 78ba5fed 17bcb956 0162f9e3>;
    APSProtocolAppTokenGenerateResponseTopicHash = <81ea80a8 e292d1e6
996ce771 c2bb099d c284f055>;
    APSProtocolCommand = 18;
}
default 16:57:11.658946 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received app token generate response {
    APSProtocolAppTokenGenerateResponseCode = 0;
    APSProtocolAppTokenGenerateResponseToken = <a3b4c19f ba39b203
57e3c3cc 940abc98 70519617 78ba5fed 17bcb956 0162f9e3>;
    APSProtocolAppTokenGenerateResponseTopicHash = <81ea80a8 e292d1e6
996ce771 c2bb099d c284f055>;
    APSProtocolCommand = 18;
}
default 16:57:11.658974 +0200 apsd <APSCourier: 0x7ff1122051b0>:
Received response for token request for topic com.apple.icloud-
container.com.apple.callhistory.sync-helper, appld 0, new token = <a3b4c19f
ba39b203 57e3c3cc 940abc98 70519617 78ba5fed 17bcb956 0162f9e3>
default 16:57:11.659036 +0200 apsd <APSCConnectionServer:
0x7ff1121367e0>: Received token <a3b4c19f ba39b203 57e3c3cc 940abc98
70519617 78ba5fed 17bcb956 0162f9e3> for topic com.apple.icloud-
container.com.apple.callhistory.sync-helper with identifier
default 16:57:11.659083 +0200 apsd <APSCConnectionServer:
0x7ff1121367e0>: Sending token <a3b4c19f ba39b203 57e3c3cc 940abc98
70519617 78ba5fed 17bcb956 0162f9e3> for topic com.apple.icloud-
container.com.apple.callhistory.sync-helper with identifier
default 16:57:11.659135 +0200 apsd <APSCourier: 0x7ff1122051b0>: Stream
processing: complete no, invalid no, length parsed 0, parameters (null)
default 16:57:11.659179 +0200 apsd Dispatching low priority message:
<OS_xpc_dictionary: <dictionary: 0x7ff10fe30560> { count = 4, transaction: 0,

```

```

voucher = 0x0, contents =
    "identifier" => <string: 0x7ff10fe3b420> { length = 0, contents = "" }
    "token" => <data: 0x7ff10fe21620>: { length = 32 bytes, contents =
0xa3b4c19fba39b20357e3c3cc940abc987051961778ba5fed... }
    "topic" => <string: 0x7ff10fe2ee30> { length = 60, contents = "com.apple.icloud-
container.com.apple.callhistory.sync-helper" }
    "message-type" => <int64: 0x7ff10fe2aa50>: 30
}>
default 16:57:11.659328 +0200 CallHistorySyncHelper ApplePushService:
<APSCConnection: 0x7f9c56a187a0> Received token <a3b4c19f ba39b203
57e3c3cc 940abc98 70519617 78ba5fed 17bcb956 0162f9e3> forTopic
com.apple.icloud-container.com.apple.callhistory.sync-helper identifier
default 16:57:11.732192 +0200 nsurlsessiond Task 4 for client <private>
received response, status code: 200
default 16:57:11.732591 +0200 cloudd [Request 0x7ff2867ab210]
NSURLSession:dataTask:didReceiveResponse:completionHandler:
default 16:57:11.733000 +0200 cloudd [Request 0x7ff2867ab210]
NSURLSession:dataTask:didReceiveData:
default 16:57:11.733093 +0200 nsurlsessiond Task 4 for client <private>
completed successfully
default 16:57:11.733346 +0200 cloudd [Request 0x7ff2867ab210]
NSURLSession:task:didCompleteWithError:
default 16:57:11.733454 +0200 cloudd [Request 0x7ff2867ab210] Finishing
request with no error
default 16:57:11.733620 +0200 cloudd [Operation 0x7ff288279b00]
Operation transitioning from state 3 (cancelled=0, stop=0, error=0)
default 16:57:11.733761 +0200 cloudd [Operation 0x7ff288279b00]
Operation is now in state 4
default 16:57:11.734591 +0200 cloudd #4b30e217
ACSMightCurrentNetworkHaveCachingServer(options={
    capabilities = {
        import = 1;
        namespaces = 1;
        personalCaching = 1;
    };
    quickMiss = 1;
    "x-apple-persistent-identifier" = 61fd;
}, callbackQueue=0x0, callback=0x700005eff720)
default 16:57:11.734847 +0200 cloudd #4b30e217
ACSMightCurrentNetworkHaveCachingServer -> [new] mightHave NO, error (null),
elapsed 0.000
default 16:57:11.735068 +0200 cloudd Chunking item (203) 1 of 1
default 16:57:11.735514 +0200 cloudd Chunking finished for itemId 203 of
203 bytes in 0.0000 sec.
default 16:57:11.735582 +0200 cloudd Container
SclcrbYBXEVC6QMCD_Vv
default 16:57:11.735660 +0200 cloudd PutComplete at Edge Protocol :
false
default 16:57:11.735860 +0200 cloudd HttpSession <MMCSHTTPSession:
0x7ff2865482d0><uuid:A5184EA4-69F7-4A61-B3EA-7DBBF4F4145F

```

```

session:s3_eu_irl, z:background-infers-discretionary,
connectionPoolName:com.apple.cloudkit.BackgroundConnectionPool,
sourceID:com.apple.TextEdit, 2ndSourceID:4/
com.apple.clouddocs.com.apple.TextEdit:2,%, adaptiveReadTimeout:3,
adaptiveWriteTimeout:3>
default 16:57:11.735914 +0200 cloudd HttpURL (https://eu-
irl-00001.s3.amazonaws.com:443/ScIcrbYBXEVC6QMCD_Vv?x-client-request-
id=C1B722D3-6C3C-4FB1-8C0B-
C2CA64E7FFA8-452224875&bin=203000001&Signature=flH7w3flw6LKr2o4NQ8bn
k11Kqk%3D&AWSAccessKeyId=AKIAI3LLM7P3DRGCUSIA&Expires=1495813991
&region=emea)
default 16:57:11.735986 +0200 cloudd RequestHeader (x-apple-request-
uuid:A28F1D8B-D884-49CC-89C7-E62673193C76)
default 16:57:11.736401 +0200 nsurlsessiond Current discretionary status for
<private> is non-discretionary
default 16:57:11.736512 +0200 nsurlsessiond Enqueueing Task 2 with UUID
<private> for client <private>, session <private>
default 16:57:11.736537 +0200 nsurlsessiond Task 2 requesting URL
<private>
default 16:57:11.736717 +0200 cloudd no containers were eligible for
putComplete.
default 16:57:11.736787 +0200 nsurlsessiond Client <private> resume for
task 2
default 16:57:11.737523 +0200 nsurlsessiond TIC TCP [0x0] working for task
<private>
default 16:57:11.737834 +0200 nsurlsessiond CCDS: requirements <private>
DASActivityProperties <private>
default 16:57:11.737892 +0200 nsurlsessiond activity [0x7f9729908f20]
<private> submitted to pool <private>
default 16:57:11.737925 +0200 nsurlsessiond SUBMITTING: <private>
default 16:57:11.738089 +0200 nsurlsessiond TIC [0x7f97298399d0]: DAS
scheduler submitted activity 0x7f9729908f20
default 16:57:11.738348 +0200 DuetHeuristic-BM Submitted Activity:
<private>
default 16:57:11.738437 +0200 DuetHeuristic-BM Start network path
monitoring for '<private>'
default 16:57:11.738633 +0200 DuetHeuristic-BM <private>:[
<private> ] sumScores:32.700000, denominator:34.700000, FinalDecision: Can
Proceed FinalScore: 0.942363}
default 16:57:11.738659 +0200 DuetHeuristic-BM '<private>'
DecisionToRun:1 (Bypasses Predictions)
default 16:57:11.738681 +0200 DuetHeuristic-BM With <private> ...Tasks
running in group <private> are 2!
default 16:57:11.738758 +0200 DuetHeuristic-BM Stop network path
monitoring for '<private>'
default 16:57:11.738842 +0200 DuetHeuristic-BM Running activities :
<private>
default 16:57:11.738985 +0200 nsurlsessiond STARTING: <private>
default 16:57:11.739003 +0200 nsurlsessiond TIC [0x7f97298399d0]: activity
0x7f9729908f20 start handler called

```

default 16:57:11.739040 +0200 [4:0x7f97298399d0]	nsurlsessiond	TIC TCP Conn Start
default 16:57:11.801118 +0200 [4:0x7f97298399d0]: 1 Err(0)	nsurlsessiond	TIC TCP Conn Event
default 16:57:11.801137 +0200 [4:0x7f97298399d0]: Err(0)	nsurlsessiond	TIC TCP Conn Connected
default 16:57:11.801487 +0200 [4:0x7f97298399d0]	nsurlsessiond	TIC Enabling TLS
default 16:57:11.864233 +0200 [4:0x7f97298399d0]: 2, Pending(0)	nsurlsessiond	TIC TLS Event
default 16:57:11.867535 +0200 [4:0x7f97298399d0]: 11, Pending(0)	nsurlsessiond	TIC TLS Event
default 16:57:11.867857 +0200 [4:0x7f97298399d0]: 12, Pending(0)	nsurlsessiond	TIC TLS Event
default 16:57:11.867896 +0200 [4:0x7f97298399d0]: 14, Pending(0)	nsurlsessiond	TIC TLS Event
default 16:57:11.868151 +0200 received auth challenge with type NSURLAuthenticationMethodServerTrust	nsurlsessiond	Task 2 for client <private>
default 16:57:11.870616 +0200 [4:0x7f97298399d0]: 0	nsurlsessiond	TIC TLS Trust Result
default 16:57:11.936702 +0200 [4:0x7f97298399d0]: 20, Pending(0)	nsurlsessiond	TIC TLS Event
default 16:57:11.937652 +0200 [4:0x7f97298399d0]: 8 Err(0)	nsurlsessiond	TIC TCP Conn Event
default 16:57:11.937681 +0200 [4:0x7f97298399d0]	nsurlsessiond	TIC TLS Handshake Complete
default 16:57:11.937902 +0200 working for task <private>	nsurlsessiond	TIC TCP [0x7f97298399d0]
default 16:57:11.938325 +0200 working for task <private>	nsurlsessiond	TIC TCP [0x7f97298399d0]
default 16:57:11.938474 +0200 a connection	nsurlsessiond	Task 2 for client <private> has
default 16:57:11.939348 +0200 working for task <private>	nsurlsessiond	TIC TCP [0x7f97298399d0]
default 16:57:11.939804 +0200 working for task <private>	nsurlsessiond	TIC TCP [0x7f97298399d0]
default 16:57:12.020544 +0200 received response, status code: 200	nsurlsessiond	Task 2 for client <private>
default 16:57:12.021045 +0200	cloudd	HttpStatus (HTTP/1.1 200 no error)
default 16:57:12.021099 +0200 (Server:AmazonS3)	cloudd	ResponseHeader
default 16:57:12.021275 +0200 completed successfully	nsurlsessiond	Task 2 for client <private>
default 16:57:12.021640 +0200	cloudd	Observed 0.0057 Mbps over 0.2858
default 16:57:12.021694 +0200	cloudd	seconds for 203 bytes. 0.0013 seconds in queue.
default 16:57:12.021694 +0200	cloudd	Handling Vendor Response
default 16:57:12.021859 +0200 SclcrbYBXEVC6QMCD_Vv to putComplete.	cloudd	Adding container
default 16:57:12.022119 +0200	cloudd	HttpSession <MMCSHTTPSession:
0x7ff286761860><uuid:1F724D4C-8C95-44FE-8033-7336B7C14EA0		

session:default, z:foreground, adaptiveReadTimeout:3, adaptiveWriteTimeout:3>
default 16:57:12.022202 +0200 cloudd HttpURL (https://p46-content.icloud.com:443/1023422711/putComplete)
default 16:57:12.022311 +0200 cloudd RequestHeader (x-apple-request-uuid:7D83DDA4-1182-409C-AD29-66825D7801C5)
default 16:57:12.182656 +0200 TextEdit <private> marked as needing layout, even though it received and enqueued needing layout for the past 3 cycle(s). Future marking as needing layout might be ignored. <private>
default 16:57:12.185630 +0200 TextEdit <private> marked as needing updateConstraints, even though it received and enqueued needing updateConstraints for the past 3 cycle(s). Future marking as needing updateConstraints might be ignored. <private>
default 16:57:12.322359 +0200 cloudd HttpStatus (HTTP/1.1 200 no error)
default 16:57:12.322396 +0200 cloudd ResponseHeader (X-Apple-Request-UUID:7D83DDA4-1182-409C-AD29-66825D7801C5)
default 16:57:12.322414 +0200 cloudd ResponseHeader (Via:xrail:mr90p00ic-zteu08130101:8301:16G93:p21, icloudedge:br30p00ic-zteu01132101:7401:17C49:Berlin)
default 16:57:12.322464 +0200 cloudd ResponseHeader (Server:AppleHttpServer/1dad28f)
default 16:57:12.322498 +0200 cloudd ResponseHeader (X-Responding-Instance:content.34600602.mr25p46ic-tydg01073201:8002.17D46)
default 16:57:12.322766 +0200 cloudd Observed 0.0190 Mbps over 0.3007 seconds for 714 bytes. 0.0011 seconds in queue.
default 16:57:12.322836 +0200 cloudd Server Receipt Received. itemId:203 receipt:A2fZfCKRkzb3emY7 sig:01b022081853a10e3424cbff54db298e38001fa598 ref:01f251667d87b80b4db20680fe8e8d14b26e834d2e len:203
default 16:57:12.322945 +0200 cloudd Uploads complete. All done! (Put request 0x7ff28651d710)
default 16:57:12.323377 +0200 cloudd [Operation 0x7ff288279b00]
Operation transitioning from state 4 (cancelled=0, stop=0, error=0)
default 16:57:12.323427 +0200 cloudd [Operation 0x7ff288279b00]
Operation is now in state 4294967295
default 16:57:12.323484 +0200 cloudd [Operation 0x7ff288267050]
Operation transitioning from state 9 (cancelled=0, stop=0, error=0)
default 16:57:12.323725 +0200 cloudd [Operation 0x7ff288267050]
Operation is now in state 10
default 16:57:12.323759 +0200 cloudd [Operation 0x7ff288267050]
Operation transitioning from state 10 (cancelled=0, stop=0, error=0)
default 16:57:12.323944 +0200 cloudd [Operation 0x7ff288267050]
Request 0x7ff2882866a0 set on operation
default 16:57:12.324031 +0200 cloudd [Request 0x7ff2882866a0]
Performing
default 16:57:12.324230 +0200 cloudd [Request 0x7ff2882866a0] Getting URL for the user partition
default 16:57:12.324264 +0200 cloudd [Request 0x7ff2882866a0] Getting configuration
default 16:57:12.324329 +0200 cloudd [Operation 0x7ff288267050]
Operation is now in state 13
default 16:57:12.324313 +0200 cloudd [Request 0x7ff2882866a0] Fetching

container scoped user ID

default 16:57:12.324449 +0200 cloudd [Request 0x7ff2882866a0] Getting device ID

default 16:57:12.324520 +0200 cloudd [Request 0x7ff2882866a0] Getting zone gates

default 16:57:12.324763 +0200 cloudd [Request 0x7ff2882866a0] Getting push token

default 16:57:12.324826 +0200 cloudd Creating a new client context 0x7ff288276c20

default 16:57:12.324890 +0200 cloudd [Request 0x7ff2882866a0] Performing request. Background=1, cellular=1

default 16:57:12.325809 +0200 nsurlsessiond Current discretionary status for <private> is non-discretionary

default 16:57:12.325950 +0200 nsurlsessiond Enqueueing Task 5 with UUID <private> for client <private>, session <private>

default 16:57:12.325988 +0200 nsurlsessiond Task 5 requesting URL <private>

default 16:57:12.326371 +0200 nsurlsessiond Client <private> resume for task 5

default 16:57:12.328777 +0200 opendirectoryd Client: <private>, UID: 501, EUID: 501, GID: 20, EGID: 20

default 16:57:12.328861 +0200 opendirectoryd queuing request to connection - '<private>'

default 16:57:12.329006 +0200 opendirectoryd queuing request to connection - '<private>'

default 16:57:12.334425 +0200 nsurlsessiond TIC TCP [0x7f9729816f70] working for task <private>

default 16:57:12.334475 +0200 nsurlsessiond TIC TCP [0x7f9729816f70] working for task <private>

default 16:57:12.334611 +0200 nsurlsessiond Task 5 for client <private> has a connection

default 16:57:12.334984 +0200 cloudd [Request 0x7ff2882866a0] requestForEstablishedConnection

default 16:57:12.338165 +0200 opendirectoryd Client: <private>, UID: 501, EUID: 501, GID: 20, EGID: 20

default 16:57:12.338291 +0200 opendirectoryd queuing request to connection - '<private>'

default 16:57:12.338488 +0200 opendirectoryd queuing request to connection - '<private>'

default 16:57:12.345022 +0200 nsurlsessiond TIC TCP [0x7f9729816f70] working for task <private>

default 16:57:12.345073 +0200 nsurlsessiond TIC TCP [0x7f9729816f70] working for task <private>

default 16:57:12.623152 +0200 nsurlsessiond Task 5 for client <private> received response, status code: 200

default 16:57:12.623519 +0200 cloudd [Request 0x7ff2882866a0] URLSession:dataTask:didReceiveResponse:completionHandler:

default 16:57:12.623947 +0200 cloudd [Request 0x7ff2882866a0] URLSession:dataTask:didReceiveData:

default 16:57:12.624051 +0200 nsurlsessiond Task 5 for client <private>

completed successfully

default 16:57:12.624319 +0200 cloudd [Request 0x7ff2882866a0]
URLSession:task:didCompleteWithError:

default 16:57:12.624805 +0200 cloudd [Request 0x7ff2882866a0] Finishing
request with no error

default 16:57:12.624903 +0200 cloudd [Operation 0x7ff288267050]
Request 0x0 set on operation

default 16:57:12.624941 +0200 cloudd [Operation 0x7ff288267050]
Operation transitioning from state 13 (cancelled=0, stop=0, error=0)

default 16:57:12.624990 +0200 cloudd [Operation 0x7ff288267050]
Operation is now in state 15

default 16:57:12.625021 +0200 cloudd [Operation 0x7ff288267050]
Operation transitioning from state 15 (cancelled=0, stop=0, error=0)

default 16:57:12.625055 +0200 cloudd [Operation 0x7ff288267050]
Operation is now in state 4294967295

default 16:57:12.629136 +0200 cloudd [Operation 0x7ff288232090]
Initialized with context 0x7ff288263070. Background: 1, cellular: 1, QOS: 0x11

default 16:57:12.629464 +0200 cloudd [Operation 0x7ff288232090] Starting
operation

default 16:57:12.629715 +0200 cloudd [Operation 0x7ff2865320e0]
Initialized with context 0x7ff288263070. Background: 1, cellular: 1, QOS: 0x11

default 16:57:12.629856 +0200 cloudd [Operation 0x7ff2865320e0] Starting
operation

default 16:57:12.630026 +0200 cloudd [Operation 0x7ff288232090]
Request 0x7ff2881288a0 set on operation

default 16:57:12.630108 +0200 cloudd [Request 0x7ff2881288a0]
Performing

default 16:57:12.630239 +0200 cloudd [Request 0x7ff2881288a0] Getting
URL for the user partition

default 16:57:12.630267 +0200 cloudd [Request 0x7ff2881288a0] Getting
configuration

default 16:57:12.630336 +0200 cloudd [Request 0x7ff2881288a0] Fetching
container scoped user ID

default 16:57:12.630424 +0200 cloudd [Request 0x7ff2881288a0] Getting
device ID

default 16:57:12.630469 +0200 cloudd [Request 0x7ff2881288a0] Getting
zone gates

default 16:57:12.630677 +0200 cloudd [Request 0x7ff2881288a0] Getting
push token

default 16:57:12.630721 +0200 cloudd Creating a new client context
0x7ff2867a25f0

default 16:57:12.630800 +0200 cloudd [Request 0x7ff2881288a0]
Performing request. Background=1, cellular=1

default 16:57:12.631733 +0200 nsurlsessiond Current discretionary status for
<private> is non-discretionary

default 16:57:12.631876 +0200 nsurlsessiond Enqueueing Task 6 with UUID
<private> for client <private>, session <private>

default 16:57:12.631913 +0200 nsurlsessiond Task 6 requesting URL
<private>

default 16:57:12.632249 +0200 nsurlsessiond Client <private> resume for

task 6

```
default    16:57:12.635072 +0200    opendiroryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default    16:57:12.635156 +0200    opendiroryd queuing request to connection
- '<private>'
default    16:57:12.635318 +0200    opendiroryd queuing request to connection
- '<private>'
default    16:57:12.641154 +0200    nsurlsessiond  TIC TCP [0x7f9729816f70]
working for task <private>
default    16:57:12.641205 +0200    nsurlsessiond  TIC TCP [0x7f9729816f70]
working for task <private>
default    16:57:12.641375 +0200    nsurlsessiond  Task 6 for client <private> has
a connection
default    16:57:12.641896 +0200    cloudd        [Request 0x7ff2881288a0]
requestForEstablishedConnection
default    16:57:12.644600 +0200    opendiroryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default    16:57:12.644724 +0200    opendiroryd queuing request to connection
- '<private>'
default    16:57:12.644886 +0200    opendiroryd queuing request to connection
- '<private>'
default    16:57:12.650390 +0200    nsurlsessiond  TIC TCP [0x7f9729816f70]
working for task <private>
default    16:57:12.650476 +0200    nsurlsessiond  TIC TCP [0x7f9729816f70]
working for task <private>
default    16:57:12.870894 +0200    nsurlsessiond  Task 6 for client <private>
received response, status code: 200
default    16:57:12.871283 +0200    cloudd        [Request 0x7ff2881288a0]
URLSession:dataTask:didReceiveResponse:completionHandler:
default    16:57:12.871735 +0200    cloudd        [Request 0x7ff2881288a0]
URLSession:dataTask:didReceiveData:
default    16:57:12.871839 +0200    nsurlsessiond  Task 6 for client <private>
completed successfully
default    16:57:12.872095 +0200    cloudd        [Request 0x7ff2881288a0]
URLSession:task:didCompleteWithError:
default    16:57:12.872422 +0200    cloudd        [Operation 0x7ff288247fe0]
Initialized with context 0x7ff288263070. Background: 1, cellular: 1, QOS: 0x11
default    16:57:12.872530 +0200    cloudd        [Operation 0x7ff288247fe0] Starting
operation
default    16:57:12.872594 +0200    cloudd        [Request 0x7ff2881288a0] Finishing
request with no error
default    16:57:12.872711 +0200    cloudd        [Operation 0x7ff288247fe0]
Operation transitioning from state 1 (cancelled=0, stop=0, error=0)
default    16:57:12.874901 +0200    cloudd        [Operation 0x7ff288339ae0]
Initialized with context 0x7ff288263070. Background: 1, cellular: 1, QOS: 0x11
default    16:57:12.875085 +0200    cloudd        [Operation 0x7ff288339ae0] Starting
operation
default    16:57:12.875170 +0200    cloudd        [Operation 0x7ff288247fe0]
Operation is now in state 2
default    16:57:12.877043 +0200    cloudd        [Operation 0x7ff288247fe0]
```


Operation transitioning from state 2 (cancelled=0, stop=0, error=0)
default 16:57:12.877065 +0200 cloudd [Operation 0x7ff288247fe0]
Operation is now in state 3
default 16:57:12.877082 +0200 cloudd [Operation 0x7ff288247fe0]
Operation transitioning from state 3 (cancelled=0, stop=0, error=0)
default 16:57:12.877114 +0200 cloudd [Operation 0x7ff288247fe0]
Operation is now in state 4294967295
default 16:57:12.877254 +0200 cloudd [Operation 0x7ff288003550]
Initialized with context 0x7ff288263070. Background: 1, cellular: 1, QOS: 0x11
default 16:57:12.877411 +0200 cloudd [Operation 0x7ff288003550] Starting
operation
default 16:57:12.877545 +0200 cloudd [Operation 0x7ff288003550]
Operation transitioning from state 1 (cancelled=0, stop=0, error=0)
default 16:57:12.878140 +0200 cloudd [Operation 0x7ff288339ae0]
Initialized with context 0x7ff288263070. Background: 1, cellular: 1, QOS: 0x11
default 16:57:12.878298 +0200 cloudd [Operation 0x7ff288339ae0] Starting
operation
default 16:57:12.878345 +0200 cloudd [Operation 0x7ff288003550]
Operation is now in state 2
default 16:57:12.880091 +0200 cloudd [Operation 0x7ff288003550]
Operation transitioning from state 2 (cancelled=0, stop=0, error=0)
default 16:57:12.880111 +0200 cloudd [Operation 0x7ff288003550]
Operation is now in state 3
default 16:57:12.880132 +0200 cloudd [Operation 0x7ff288003550]
Operation transitioning from state 3 (cancelled=0, stop=0, error=0)
default 16:57:12.880156 +0200 cloudd [Operation 0x7ff288003550]
Operation is now in state 4294967295
default 16:57:12.881433 +0200 cloudd [Operation 0x7ff288247fe0]
Initialized with context 0x7ff288263070. Background: 1, cellular: 1, QOS: 0x11
default 16:57:12.881722 +0200 cloudd [Operation 0x7ff288247fe0] Starting
operation
default 16:57:12.881883 +0200 cloudd [Operation 0x7ff288247fe0]
Operation transitioning from state 1 (cancelled=0, stop=0, error=0)
default 16:57:12.882203 +0200 cloudd [Operation 0x7ff288247fe0] Request
0x7ff28833f400 set on operation
default 16:57:12.882288 +0200 cloudd [Request 0x7ff28833f400]
Performing
default 16:57:12.882403 +0200 cloudd [Request 0x7ff28833f400] Getting
URL for the user partition
default 16:57:12.882427 +0200 cloudd [Request 0x7ff28833f400] Getting
configuration
default 16:57:12.882468 +0200 cloudd [Operation 0x7ff288247fe0]
Operation is now in state 2
default 16:57:12.882496 +0200 cloudd [Request 0x7ff28833f400] Fetching
container scoped user ID
default 16:57:12.882586 +0200 cloudd [Request 0x7ff28833f400] Getting
device ID
default 16:57:12.882619 +0200 cloudd [Request 0x7ff28833f400] Getting
zone gates
default 16:57:12.882865 +0200 cloudd [Request 0x7ff28833f400] Getting

push token

```
default 16:57:12.882914 +0200 cloudd Creating a new client context
0x7ff288232090
default 16:57:12.882974 +0200 cloudd [Request 0x7ff28833f400]
Performing request. Background=1, cellular=1
default 16:57:12.883901 +0200 nsurlsessiond Current discretionary status for
<private> is non-discretionary
default 16:57:12.884036 +0200 nsurlsessiond Enqueueing Task 7 with UUID
<private> for client <private>, session <private>
default 16:57:12.884074 +0200 nsurlsessiond Task 7 requesting URL
<private>
default 16:57:12.884395 +0200 nsurlsessiond Client <private> resume for
task 7
default 16:57:12.886910 +0200 opendirirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default 16:57:12.887017 +0200 opendirirectoryd queuing request to connection
- '<private>'
default 16:57:12.887167 +0200 opendirirectoryd queuing request to connection
- '<private>'
default 16:57:12.892815 +0200 nsurlsessiond TIC TCP [0x7f9729816f70]
working for task <private>
default 16:57:12.892863 +0200 nsurlsessiond TIC TCP [0x7f9729816f70]
working for task <private>
default 16:57:12.893000 +0200 nsurlsessiond Task 7 for client <private> has
a connection
default 16:57:12.893387 +0200 cloudd [Request 0x7ff28833f400]
requestForEstablishedConnection
default 16:57:12.893628 +0200 cloudd Stream 0x7ff286546960 is sending
an event before being opened
default 16:57:12.895903 +0200 opendirirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default 16:57:12.895987 +0200 opendirirectoryd queuing request to connection
- '<private>'
default 16:57:12.896141 +0200 opendirirectoryd queuing request to connection
- '<private>'
default 16:57:12.901537 +0200 nsurlsessiond TIC TCP [0x7f9729816f70]
working for task <private>
default 16:57:12.901613 +0200 nsurlsessiond TIC TCP [0x7f9729816f70]
working for task <private>
default 16:57:13.108047 +0200 nsurlsessiond Task 7 for client <private>
received response, status code: 200
default 16:57:13.108467 +0200 cloudd [Request 0x7ff28833f400]
URLSession:dataTask:didReceiveResponse:completionHandler:
default 16:57:13.108886 +0200 cloudd [Request 0x7ff28833f400]
URLSession:dataTask:didReceiveData:
default 16:57:13.108952 +0200 nsurlsessiond Task 7 for client <private>
completed successfully
default 16:57:13.109246 +0200 cloudd [Request 0x7ff28833f400]
URLSession:task:didCompleteWithError:
default 16:57:13.109499 +0200 cloudd [Operation 0x7ff28833efb0]
```

Initialized with context 0x7ff288263070. Background: 1, cellular: 1, QOS: 0x11
 default 16:57:13.109650 +0200 cloudd [Operation 0x7ff28833efb0] Starting operation
 default 16:57:13.109698 +0200 cloudd [Request 0x7ff28833f400] Finishing request with no error
 default 16:57:13.109909 +0200 cloudd [Operation 0x7ff288247fe0] Request 0x0 set on operation
 default 16:57:13.111518 +0200 cloudd [Operation 0x7ff288247fe0] Operation transitioning from state 2 (cancelled=0, stop=0, error=0)
 default 16:57:13.111651 +0200 cloudd [Operation 0x7ff2865320e0] Initialized with context 0x7ff288263070. Background: 1, cellular: 1, QOS: 0x11
 default 16:57:13.111795 +0200 cloudd [Operation 0x7ff288247fe0] Operation is now in state 3
 default 16:57:13.111821 +0200 cloudd [Operation 0x7ff2865320e0] Starting operation
 default 16:57:13.112025 +0200 cloudd [Operation 0x7ff2865320e0] Operation transitioning from state 1 (cancelled=0, stop=0, error=0)
 default 16:57:13.112110 +0200 cloudd [Operation 0x7ff2865320e0] Operation is now in state 2
 default 16:57:13.112163 +0200 cloudd [Operation 0x7ff2865320e0] Operation transitioning from state 2 (cancelled=0, stop=0, error=0)
 default 16:57:13.112261 +0200 cloudd [Operation 0x7ff2865320e0] Operation is now in state 3
 default 16:57:13.113031 +0200 cloudd #ed8685cf
 ACSMightCurrentNetworkHaveCachingServer(options={
 capabilities = {
 import = 1;
 namespaces = 1;
 personalCaching = 1;
 };
 quickMiss = 1;
 "x-apple-persistent-identifier" = 61fd;
 }, callbackQueue=0x0, callback=0x700005eff7f0)
 default 16:57:13.113050 +0200 cloudd #ed8685cf
 ACSMightCurrentNetworkHaveCachingServer -> [same] mightHave NO, error (null), elapsed 0.000
 default 16:57:13.113118 +0200 cloudd file content validation disabled by default for dataclass com.apple.Dataclass.CloudKit. Does not impact chunk validation.
 default 16:57:13.115168 +0200 cloudd HttpSession <MMCSHTTPSession: 0x7ff2882323b0><uuid:B9BA58B6-5AE8-4B11-99E4-4A72B2076BC8 session:default, z:background-infers-discretionary, connectionPoolName:com.apple.cloudkit.BackgroundConnectionPool, sourceID:com.apple.TextEdit, 2ndSourceID:4/com.apple.clouddocs.com.apple.TextEdit:2,%, adaptiveReadTimeout:3, adaptiveWriteTimeout:3>
 default 16:57:13.115211 +0200 cloudd HttpURL (https://p46-content.icloud.com:443/1023422711/authorizeGet)
 default 16:57:13.115304 +0200 cloudd RequestHeader (x-apple-request-uuid:9DA08429-3CA8-462F-8047-89C57C5D7055)

default	16:57:13.115780 +0200	nsurlsessiond	Current discretionary status for <private> is non-discretionary
default	16:57:13.115876 +0200	nsurlsessiond	Enqueueing Task 1 with UUID <private> for client <private>, session <private>
default	16:57:13.115896 +0200	nsurlsessiond	Task 1 requesting URL <private>
default	16:57:13.116308 +0200	nsurlsessiond	Client <private> resume for task 1
default	16:57:13.117067 +0200	nsurlsessiond	TIC TCP [0x0] working for task <private>
default	16:57:13.117361 +0200	nsurlsessiond	CCDS: requirements <private> DASActivityProperties <private>
default	16:57:13.117397 +0200	nsurlsessiond	activity [0x7f972852bc20] <private> submitted to pool <private>
default	16:57:13.117431 +0200	nsurlsessiond	SUBMITTING: <private>
default	16:57:13.117563 +0200	nsurlsessiond	TIC [0x7f972852b560]: DAS scheduler submitted activity 0x7f972852bc20
default	16:57:13.117797 +0200	DuetHeuristic-BM	Submitted Activity: <private>
default	16:57:13.117857 +0200	DuetHeuristic-BM	Start network path monitoring for '<private>'
default	16:57:13.118024 +0200	DuetHeuristic-BM	<private>:[<private>] sumScores:32.700000, denominator:34.700000, FinalDecision: Can Proceed FinalScore: 0.942363}
default	16:57:13.118050 +0200	DuetHeuristic-BM	'<private>' DecisionToRun:1 (Bypasses Predictions)
default	16:57:13.118072 +0200	DuetHeuristic-BM	With <private> ...Tasks running in group <private> are 3!
default	16:57:13.118091 +0200	DuetHeuristic-BM	Stop network path monitoring for '<private>'
default	16:57:13.118187 +0200	DuetHeuristic-BM	Running activities : <private>
default	16:57:13.118341 +0200	nsurlsessiond	STARTING: <private>
default	16:57:13.118359 +0200	nsurlsessiond	TIC [0x7f972852b560]: activity 0x7f972852bc20 start handler called
default	16:57:13.118373 +0200	nsurlsessiond	TIC TCP Conn Start [5:0x7f972852b560]
default	16:57:13.119198 +0200	nsurlsessiond	TIC TCP Conn Cancel [4:0x7f97298399d0]
default	16:57:13.119221 +0200	nsurlsessiond	TIC TCP [0x7f97298399d0] completing activity 0x7f9729908f20
default	16:57:13.119387 +0200	nsurlsessiond	TIC TCP Conn Destroyed [4:0x7f97298399d0]
default	16:57:13.119586 +0200	DuetHeuristic-BM	COMPLETED <private>!
default	16:57:13.119609 +0200	DuetHeuristic-BM	Stop network path monitoring for '<private>'
default	16:57:13.119649 +0200	DuetHeuristic-BM	NO LONGER RUNNING <private> ...Tasks running in group [<private>] are 2!
default	16:57:13.152851 +0200	nsurlsessiond	TIC TCP Conn Event [5:0x7f972852b560]: 1 Err(0)

default	16:57:13.152869 +0200	nsurlsessiond	TIC TCP Conn Connected
[5:0x7f972852b560]: Err(0)			
default	16:57:13.153196 +0200	nsurlsessiond	TIC Enabling TLS
[5:0x7f972852b560]			
default	16:57:13.191035 +0200	nsurlsessiond	TIC TLS Event
[5:0x7f972852b560]: 2, Pending(0)			
default	16:57:13.197397 +0200	nsurlsessiond	TIC TLS Event
[5:0x7f972852b560]: 11, Pending(0)			
default	16:57:13.197830 +0200	nsurlsessiond	TIC TLS Event
[5:0x7f972852b560]: 22, Pending(0)			
default	16:57:13.197925 +0200	nsurlsessiond	TIC TLS Event
[5:0x7f972852b560]: 12, Pending(0)			
default	16:57:13.197952 +0200	nsurlsessiond	TIC TLS Event
[5:0x7f972852b560]: 14, Pending(0)			
default	16:57:13.198131 +0200	nsurlsessiond	Task 1 for client <private>
received auth challenge with type NSURLAuthenticationMethodServerTrust			
default	16:57:13.201622 +0200	trustd	ocsp responder: (null) did not
include status of requested cert			
default	16:57:13.204663 +0200	cloudd	could not disable pinning: not an
internal release			
default	16:57:13.204696 +0200	cloudd	could not enable test cert:
AppleServerAuthenticationAllowUATMMCS not true			
default	16:57:13.204713 +0200	cloudd	could not enable test hierarchy:
AppleServerAuthenticationAllowUAT not true			
default	16:57:13.206043 +0200	nsurlsessiond	could not disable pinning: not
an internal release			
default	16:57:13.206793 +0200	nsurlsessiond	could not enable test cert:
AppleServerAuthenticationAllowUATMMCS not true			
default	16:57:13.206861 +0200	nsurlsessiond	could not enable test hierarchy:
AppleServerAuthenticationAllowUAT not true			
default	16:57:13.207131 +0200	nsurlsessiond	TIC TLS Trust Result
[5:0x7f972852b560]: 0			
default	16:57:13.242985 +0200	nsurlsessiond	TIC TLS Event
[5:0x7f972852b560]: 20, Pending(0)			
default	16:57:13.243255 +0200	nsurlsessiond	TIC TCP Conn Event
[5:0x7f972852b560]: 8 Err(0)			
default	16:57:13.243273 +0200	nsurlsessiond	TIC TLS Handshake Complete
[5:0x7f972852b560]			
default	16:57:13.243463 +0200	nsurlsessiond	TIC TCP [0x7f972852b560]
working for task <private>			
default	16:57:13.243813 +0200	nsurlsessiond	TIC TCP [0x7f972852b560]
working for task <private>			
default	16:57:13.243971 +0200	nsurlsessiond	Task 1 for client <private> has
a connection			
default	16:57:13.244768 +0200	nsurlsessiond	TIC TCP [0x7f972852b560]
working for task <private>			
default	16:57:13.245068 +0200	nsurlsessiond	TIC TCP [0x7f972852b560]
working for task <private>			
default	16:57:13.432847 +0200	nsurlsessiond	Task 1 for client <private>
received response, status code: 200			

default 16:57:13.433449 +0200 cloudd HttpStatus (HTTP/1.1 200 no error)

default 16:57:13.433487 +0200 cloudd ResponseHeader (X-Apple-Request-UUID:9DA08429-3CA8-462F-8047-89C57C5D7055)

default 16:57:13.433520 +0200 cloudd ResponseHeader (Via:xrail:mr90p00ic-zteu08130401:8301:16G93:p21, icloudedge:br30p00ic-zteu01132101:7401:17C49:Berlin)

default 16:57:13.433561 +0200 cloudd ResponseHeader (Server:AppleHttpServer/1dad28f)

default 16:57:13.433606 +0200 cloudd ResponseHeader (X-Responding-Instance:content.34600803.mr25p46ic-tydg01091801:8003.17D46)

default 16:57:13.434071 +0200 nsurlsessiond Task 1 for client <private> completed successfully

default 16:57:13.434435 +0200 cloudd Observed 0.0163 Mbps over 0.3211 seconds for 654 bytes. 0.0032 seconds in queue.

default 16:57:13.435318 +0200 cloudd PutComplete at Edge Protocol : false

error 16:57:13.435997 +0200 cloudd Unregistering item without an asset handle for itemID=203

default 16:57:13.436145 +0200 cloudd getItemReaderWriterForItemCallback did not succeed

default 16:57:13.436229 +0200 cloudd itemId:204 local fulfillment took 0.0005 seconds for 0 bytes. Validated for Resume (0 bytes), Resumed (0 bytes), Fullfilled Locally (0 bytes)

default 16:57:13.436397 +0200 cloudd HttpSession <MMCSHTTPSession: 0x7ff2865482d0><uuid:A5184EA4-69F7-4A61-B3EA-7DBBF4F4145F session:s3_eu_irl, z:background-infers-discretionary, connectionPoolName:com.apple.cloudkit.BackgroundConnectionPool, sourceID:com.apple.TextEdit, 2ndSourceID:4/com.apple.clouddocs.com.apple.TextEdit:2,%, adaptiveReadTimeout:3, adaptiveWriteTimeout:3>

default 16:57:13.436468 +0200 cloudd HttpURL (http://eu-irl-00001.s3.amazonaws.com:80/SclcrbYBXEVC6QMCD_Vv?x-client-request-id=9DA08429-3CA8-462F-8047-89C57C5D7055&bin=203000001&Signature=qEPYxF%2Fe0H8iNctjZDqZiE%2B7Jsw%3D&byte-range=0-202&AWSAccessKeyId=AKIAI3LLM7P3DRGCUSIA&Expires=1495813993 ®ion=emea)

default 16:57:13.436554 +0200 cloudd RequestHeader (x-apple-request-uuid:AA876006-96E9-4E72-B3D8-3F90942040C2)

default 16:57:13.436965 +0200 nsurlsessiond Current discretionary status for <private> is non-discretionary

default 16:57:13.437113 +0200 nsurlsessiond Enqueueing Task 3 with UUID <private> for client <private>, session <private>

default 16:57:13.437139 +0200 nsurlsessiond Task 3 requesting URL <private>

default 16:57:13.437388 +0200 nsurlsessiond Client <private> resume for task 3

default 16:57:13.437906 +0200 nsurlsessiond TIC TCP [0x0] working for task <private>

default 16:57:13.438253 +0200 nsurlsessiond CCDS: requirements <private> DASActivityProperties <private>

default 16:57:13.438299 +0200 nsurlsessiond activity [0x7f9729903dc0]
 <private> submitted to pool <private>
 default 16:57:13.438339 +0200 nsurlsessiond SUBMITTING: <private>
 default 16:57:13.438496 +0200 nsurlsessiond TIC [0x7f972841b540]: DAS
 scheduler submitted activity 0x7f9729903dc0
 default 16:57:13.438846 +0200 DuetHeuristic-BM Submitted Activity:
 <private>
 default 16:57:13.438941 +0200 DuetHeuristic-BM Start network path
 monitoring for '<private>'
 default 16:57:13.439134 +0200 DuetHeuristic-BM <private>:[
 <private>] sumScores:32.700000, denominator:34.700000, FinalDecision: Can
 Proceed FinalScore: 0.942363}
 default 16:57:13.439192 +0200 DuetHeuristic-BM '<private>'
 DecisionToRun:1 (Bypasses Predictions)
 default 16:57:13.439251 +0200 DuetHeuristic-BM With <private> ...Tasks
 running in group <private> are 3!
 default 16:57:13.439303 +0200 DuetHeuristic-BM Stop network path
 monitoring for '<private>'
 default 16:57:13.439426 +0200 DuetHeuristic-BM Running activities :
 <private>
 default 16:57:13.439575 +0200 nsurlsessiond STARTING: <private>
 default 16:57:13.439594 +0200 nsurlsessiond TIC [0x7f972841b540]: activity
 0x7f9729903dc0 start handler called
 default 16:57:13.439637 +0200 nsurlsessiond TIC TCP Conn Start
 [6:0x7f972841b540]
 default 16:57:13.502216 +0200 nsurlsessiond TIC TCP Conn Event
 [6:0x7f972841b540]: 1 Err(0)
 default 16:57:13.502237 +0200 nsurlsessiond TIC TCP Conn Connected
 [6:0x7f972841b540]: Err(0)
 default 16:57:13.502656 +0200 nsurlsessiond TIC TCP [0x7f972841b540]
 working for task <private>
 default 16:57:13.502690 +0200 nsurlsessiond TIC TCP [0x7f972841b540]
 working for task <private>
 default 16:57:13.502854 +0200 nsurlsessiond Task 3 for client <private> has
 a connection
 default 16:57:13.503568 +0200 nsurlsessiond TIC TCP [0x7f972841b540]
 working for task <private>
 default 16:57:13.503598 +0200 nsurlsessiond TIC TCP [0x7f972841b540]
 working for task <private>
 default 16:57:13.575448 +0200 nsurlsessiond Task 3 for client <private>
 received response, status code: 206
 default 16:57:13.575957 +0200 cloudd HttpStatus (HTTP/1.1 206 partial
 content)
 default 16:57:13.575989 +0200 cloudd ResponseHeader
 (Server:AmazonS3)
 default 16:57:13.576374 +0200 nsurlsessiond Task 3 for client <private>
 completed successfully
 default 16:57:13.576470 +0200 cloudd Renaming <private> to <private> for
 item 204
 default 16:57:13.576646 +0200 cloudd itemId 204 completed

default 16:57:13.576994 +0200 cloudd Observed 0.0116 Mbps over 0.1406 seconds for 203 bytes. 0.0016 seconds in queue.

default 16:57:13.577330 +0200 cloudd HttpSession <MMCSHTTPSession: 0x7ff286761860><uuid:1F724D4C-8C95-44FE-8033-7336B7C14EA0 session:default, z:foreground, adaptiveReadTimeout:3, adaptiveWriteTimeout:3>

default 16:57:13.577412 +0200 cloudd HttpURL (https://p46-content.icloud.com:443/1023422711/getComplete)

default 16:57:13.577515 +0200 cloudd RequestHeader (x-apple-request-uuid:DF062928-4931-49BF-A571-25EEB23918A0)

default 16:57:13.772612 +0200 cloudd HttpStatus (HTTP/1.1 200 no error)

default 16:57:13.772647 +0200 cloudd ResponseHeader (Server:AppleHttpServer/1dad28f)

default 16:57:13.772664 +0200 cloudd ResponseHeader (X-Apple-Request-UUID:DF062928-4931-49BF-A571-25EEB23918A0)

default 16:57:13.772701 +0200 cloudd ResponseHeader (Via:xrail:mr90p00ic-zteu08130101:8301:16G93:p21, icloudedge:br30p00ic-zteu01132101:7401:17C49:Berlin)

default 16:57:13.772738 +0200 cloudd ResponseHeader (X-Responding-Instance:content.34600904.mr25p46ic-tydg01101501:8004.17D46)

default 16:57:13.772957 +0200 cloudd Observed 0.0246 Mbps over 0.1956 seconds for 602 bytes. 0.0009 seconds in queue.

default 16:57:13.773812 +0200 cloudd [Operation 0x7ff2865320e0] Operation transitioning from state 3 (cancelled=0, stop=0, error=0)

default 16:57:13.773845 +0200 cloudd [Operation 0x7ff2865320e0] Operation is now in state 4294967295

default 16:57:13.773970 +0200 cloudd [Operation 0x7ff288247fe0] Operation transitioning from state 3 (cancelled=0, stop=0, error=0)

default 16:57:13.774000 +0200 cloudd [Operation 0x7ff288247fe0] Operation is now in state 4294967295

default 16:57:13.776724 +0200 bird [NOTICE] received 2 edited items from the cloud for com.apple.TextEdit

default 16:57:14.335386 +0200 nsurlsessiond TIC TCP Conn Cancel [3:0x7f9729816f70]

default 16:57:14.335418 +0200 nsurlsessiond TIC TCP [0x7f9729816f70] completing activity 0x7f9728411350

default 16:57:14.335832 +0200 DuetHeuristic-BM COMPLETED <private>!

default 16:57:14.335857 +0200 DuetHeuristic-BM Stop network path monitoring for '<private>'

default 16:57:14.335887 +0200 DuetHeuristic-BM NO LONGER RUNNING <private> ...Tasks running in group [<private>] are 2!

default 16:57:14.761953 +0200 nsurlsessiond TIC TCP Conn Cancel [6:0x7f972841b540]

default 16:57:14.762005 +0200 nsurlsessiond TIC TCP [0x7f972841b540] completing activity 0x7f9729903dc0

default 16:57:14.762408 +0200 DuetHeuristic-BM COMPLETED <private>!

default 16:57:14.762435 +0200 DuetHeuristic-BM Stop network path monitoring for '<private>'

default 16:57:14.762468 +0200 DuetHeuristic-BM NO LONGER RUNNING <private> ...Tasks running in group [<private>] are 1!

default 16:57:14.881593 +0200 opendiroryd Client: <private>, UID: 0, EUID:


```

0, GID: 0, EGID: 0
default 16:57:14.881682 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default 16:57:14.881770 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 89, EGID: 89
default 16:57:14.881874 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default 16:57:14.881880 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 89, EGID: 89
default 16:57:14.881998 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default 16:57:14.882034 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 89, EGID: 89
default 16:57:14.882056 +0200 opendirectoryd queuing request to connection
- '<private>'
default 16:57:14.882162 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 89, EGID: 89
default 16:57:14.882500 +0200 opendirectoryd queuing request to connection
- '<private>'
default 16:57:14.883304 +0200 opendirectoryd Client: <private>, UID: 89,
EUID: 89, GID: 89, EGID: 89
default 16:57:14.883316 +0200 opendirectoryd Client: <private>, UID: 89,
EUID: 89, GID: 89, EGID: 89
default 16:57:14.883325 +0200 opendirectoryd Client: <private>, UID: 89,
EUID: 89, GID: 89, EGID: 89
default 16:57:14.883334 +0200 opendirectoryd Client: <private>, UID: 89,
EUID: 89, GID: 89, EGID: 89
default 16:57:14.888401 +0200 opendirectoryd Client: <private>, UID: 89,
EUID: 89, GID: 89, EGID: 89
default 16:57:14.888491 +0200 opendirectoryd Client: <private>, UID: 89,
EUID: 89, GID: 89, EGID: 89
default 16:57:14.888564 +0200 opendirectoryd Client: <private>, UID: 89,
EUID: 89, GID: 89, EGID: 89
default 16:57:14.888634 +0200 opendirectoryd Client: <private>, UID: 89,
EUID: 89, GID: 89, EGID: 89
default 16:57:14.902706 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default 16:57:14.903875 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default 16:57:14.904041 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 89, EGID: 89
default 16:57:14.904330 +0200 opendirectoryd Client: <private>, UID: 89,
EUID: 89, GID: 89, EGID: 89
default 16:57:14.906652 +0200 opendirectoryd Client: <private>, UID: 89,
EUID: 89, GID: 89, EGID: 89
default 16:57:14.907390 +0200 distnoted # distnote server agent absolute
time: 74.021615644 civil time: Fri May 26 16:57:14 2017 pid: 495 uid: 89 root: no
default 16:57:15.530708 +0200 securityd CSSM Exception: 70
CSSM_ERRCODE_INVALID_DATA
default 16:57:15.530759 +0200 securityd CSSM Exception: -2147415994

```

CSSMERR_CSP_INVALID_DATA
default 16:57:15.531774 +0200 mdwrite CSSM Exception: -2147415994
CSSMERR_CSP_INVALID_DATA
default 16:57:15.534970 +0200 opendirectoryd Client: <private>, UID: 0, EUID: 0, GID: 0, EGID: 0
default 16:57:15.535152 +0200 opendirectoryd Client: <private>, UID: 0, EUID: 0, GID: 20, EGID: 20
default 16:57:15.535434 +0200 opendirectoryd Client: <private>, UID: 501, EUID: 501, GID: 20, EGID: 20
default 16:57:15.537331 +0200 filecoordinationd Presenter E89A1BEE-BF55-490A-B675-C11FDE4E7A44 detected non-coordinated event
default 16:57:15.541141 +0200 opendirectoryd Client: <private>, UID: 501, EUID: 501, GID: 20, EGID: 20
default 16:57:15.546181 +0200 opendirectoryd Client: <private>, UID: 501, EUID: 501, GID: 20, EGID: 20
default 16:57:15.561331 +0200 filecoordinationd Presenter BC4B3C1D-C727-4CD7-8712-6BAFFE23554F detected non-coordinated event
default 16:57:15.563846 +0200 mdworker MacOS error: -67062
default 16:57:15.563953 +0200 mdworker MacOS error: -67062
default 16:57:15.564388 +0200 mdworker MacOS error: -67062
default 16:57:15.564420 +0200 mdworker MacOS error: -67062
default 16:57:15.587733 +0200 mds directQueryFetchResultsReply 53251 1795162112 35
default 16:57:15.680322 +0200 CalendarAgent Rebroadcasting external notification ABDistributedDatabaseChangedNotification from process AddressBookSourceSync (<private>)
default 16:57:15.680602 +0200 CalendarAgent Rebroadcasting external notification ABDistributedDatabaseChangedNotificationPriv from process AddressBookSourceSync (<private>)
default 16:57:15.704863 +0200 identityservicesd Beginning cleanup of outgoing message database
default 16:57:15.705141 +0200 identityservicesd Cleaned up 0 expired messages
default 16:57:15.705186 +0200 identityservicesd Delayed background file removal took 0.000348 seconds
default 16:57:15.705305 +0200 identityservicesd Beginning cleanup of outgoing message database for quickswitched messages
default 16:57:15.705508 +0200 identityservicesd Ending cleanup of outgoing message database for quickswitched messages
default 16:57:15.705526 +0200 identityservicesd Beginning cleanup of outgoing message database for messages older than 2 days past enqueue date
default 16:57:15.705555 +0200 identityservicesd Using Time Interval 517330635.705541
default 16:57:15.705711 +0200 identityservicesd Ending cleanup of 0 outgoing message database for older than 2 days past enqueue date
default 16:57:15.706222 +0200 identityservicesd Ending cleanup of outgoing message database
default 16:57:15.912554 +0200 nsurlsessiond TIC TCP Conn Cancel [5:0x7f972852b560]
default 16:57:15.912593 +0200 nsurlsessiond TIC TCP [0x7f972852b560]

```

completing activity 0x7f972852bc20
default 16:57:15.912809 +0200 nsurlsessiond TIC TCP Conn Destroyed
[5:0x7f972852b560]
default 16:57:15.913006 +0200 DuetHeuristic-BM COMPLETED <private>!
default 16:57:15.913032 +0200 DuetHeuristic-BM Stop network path
monitoring for '<private>'
default 16:57:15.913065 +0200 DuetHeuristic-BM NO LONGER RUNNING
<private> ...Tasks running in group [<private>] are 0!
default 16:57:16.999669 +0200 AppleSpell Lexicon creation failed: Lexicon
resources not found
default 16:57:16.300944 +0200 AppleSpell Lexicon creation failed: Lexicon
resources not found
default 16:57:16.440991 +0200 com.apple.WebKit.WebContent
Current memory footprint: 71 MB
default 16:57:16.442839 +0200 com.apple.WebKit.WebContent
Current memory footprint: 57 MB
default 16:57:16.443948 +0200 com.apple.WebKit.WebContent
Current memory footprint: 49 MB
default 16:57:16.444519 +0200 com.apple.WebKit.WebContent
Current memory footprint: 204 MB
default 16:57:16.444547 +0200 com.apple.WebKit.WebContent
Current memory footprint: 47 MB
default 16:57:16.578107 +0200 filecoordinationd Presenter E89A1BEE-
BF55-490A-B675-C11FDE4E7A44 settling non-coordinated events
default 16:57:16.578209 +0200 filecoordinationd Presenter BC4B3C1D-
C727-4CD7-8712-6BAFFE23554F settling non-coordinated events
default 16:57:16.578242 +0200 TextEdit Making presenter E89A1BEE-
BF55-490A-B675-C11FDE4E7A44 observe change
default 16:57:16.578665 +0200 Preview Making presenter BC4B3C1D-
C727-4CD7-8712-6BAFFE23554F observe change
default 16:57:16.578700 +0200 mds directQueryOpenReply 53249
1795162112 0
default 16:57:16.578793 +0200 mds QueryOpen succeeded (0) for store
<private>
default 16:57:16.578853 +0200 mds directQueryOpenReply 53250
1795162112 0
default 16:57:16.578897 +0200 mds QueryOpen succeeded (0) for store
<private>
default 16:57:16.581813 +0200 mds directQueryFetchResultsReply 53249
1795162112 0
default 16:57:16.595206 +0200 mds directQueryFetchResultsReply 53250
1795162112 0
default 16:57:16.743034 +0200 com.apple.geod TIC TCP Conn Cancel
[1:0x7f9565c1e8f0]
default 16:57:16.743145 +0200 com.apple.geod TIC TCP Conn Destroyed
[1:0x7f9565c1e8f0]
default 16:57:16.846989 +0200 mobileassetd 0x7f87d1253c10 Main Listener:
XPC_TYPE_CONNECTION <connection: 0x7f87d1253c10> { name =
com.apple.mobileassetd (peer), listener = false, pid = 406, euid = 501, egid = 20,
asid = 100008 }

```

```

default 16:57:16.847100 +0200 mobileassetd 0x7f87cf704ef0 Client
connection: XPC_TYPE_DICTIONARY <dictionary: 0x7f87cf704ef0> { count = 5,
transaction: 1, voucher = 0x7f87cf7051e0, contents =
    "AssetType" => <string: 0x7f87cf70ea00> { length = 36, contents =
"com.apple.MobileAsset.LinguisticData" }
    "Local Cache Only" => <bool: 0x7ffdd7a6ac8>: false
    "Timeout" => <double: 0x7f87cf7023b0>: 15.000000
    "_IPC_TYPE" => <uint64: 0x7f87cf702b10>: 13
    "ClientName" => <string: 0x7f87cf70e630> { length = 10, contents =
"AppleSpell" }
}
default 16:57:16.847176 +0200 mobileassetd HANDLER - assetQuery
[com.apple.MobileAsset.LinguisticData]: (local=0) [(null)]
default 16:57:16.847426 +0200 mobileassetd starting metadata download
default 16:57:16.847504 +0200 mobileassetd Performing GET request on
https://mesu.apple.com/assets/macos/com_apple_MobileAsset_LinguisticData/
com_apple_MobileAsset_LinguisticData.xml with If-Modified-Since field
default 16:57:16.848254 +0200 mobileassetd creating session
default 16:57:16.883124 +0200 nsurlsessiond Current discretionary status for
<private> is non-discretionary
default 16:57:16.886336 +0200 nsurlsessiond Enqueueing Task 1 with UUID
<private> for client <private>, session <private>
default 16:57:16.886361 +0200 nsurlsessiond Task 1 requesting URL
<private>
default 16:57:16.887040 +0200 nsurlsessiond Client <private> resume for
task 1
default 16:57:16.905050 +0200 nsurlsessiond 0x7f9ac41301d0 opened /var/
folders/zz/zyxvpqvq6csfxvn_n00000y800007k/C//mds/mdsObject.db: 4636 bytes
default 16:57:16.905356 +0200 nsurlsessiond 0x7f9ac2440820 opened /var/
folders/zz/zyxvpqvq6csfxvn_n00000y800007k/C//mds/mdsDirectory.db: 50744 bytes
default 16:57:16.905515 +0200 nsurlsessiond 0x7f9ac243da80 opened /
Library/Keychains/System.keychain: 37732 bytes
default 16:57:16.908079 +0200 nsurlsessiond TIC TCP [0x0] working for task
<private>
default 16:57:16.909233 +0200 nsurlsessiond CCDS: requirements <private>
DASActivityProperties <private>
default 16:57:16.909278 +0200 nsurlsessiond activity [0x7f9ac263a270]
<private> submitted to pool NSURLSessionBackgroundPoolName
default 16:57:16.909309 +0200 nsurlsessiond SUBMITTING: <private>
default 16:57:16.909481 +0200 nsurlsessiond TIC [0x7f9ac262c6f0]: DAS
scheduler submitted activity 0x7f9ac263a270
default 16:57:16.909728 +0200 DuetHeuristic-BM Submitted Activity:
<private>
default 16:57:16.909787 +0200 DuetHeuristic-BM Start network path
monitoring for '<private>'
default 16:57:16.910735 +0200 DuetHeuristic-BM <private>:[
<private> ] sumScores:32.700000, denominator:34.700000, FinalDecision: Can
Proceed FinalScore: 0.942363}
default 16:57:16.910803 +0200 DuetHeuristic-BM '<private>'
DecisionToRun:1 (Bypasses Predictions)

```

default	16:57:16.910842 +0200	DuetHeuristic-BM	With <private> ...Tasks
running in group <private> are 1!			
default	16:57:16.910878 +0200	DuetHeuristic-BM	Stop network path
monitoring for '<private>'			
default	16:57:16.910944 +0200	DuetHeuristic-BM	Running activities :
<private>			
default	16:57:16.911087 +0200	nsurlsessiond	STARTING: <private>
default	16:57:16.911104 +0200	nsurlsessiond	TIC [0x7f9ac262c6f0]: activity
0x7f9ac263a270 start handler called			
default	16:57:16.911127 +0200	nsurlsessiond	TIC TCP Conn Start
[2:0x7f9ac262c6f0]			
default	16:57:16.961761 +0200	nsurlsessiond	TIC TCP Conn Event
[2:0x7f9ac262c6f0]: 1 Err(0)			
default	16:57:16.961780 +0200	nsurlsessiond	TIC TCP Conn Connected
[2:0x7f9ac262c6f0]: Err(0)			
default	16:57:16.962110 +0200	nsurlsessiond	TIC Enabling TLS
[2:0x7f9ac262c6f0]			
default	16:57:16.969172 +0200	com.apple.iCloudHelper	TIC TCP Conn
Cancel [1:0x7f9154e03d90]			
default	16:57:16.969216 +0200	com.apple.iCloudHelper	TIC TCP Conn
Cancel [3:0x7f9157205450]			
default	16:57:16.969222 +0200	com.apple.iCloudHelper	TIC TCP Conn
Destroyed [1:0x7f9154e03d90]			
default	16:57:16.969246 +0200	com.apple.iCloudHelper	TIC TCP Conn
Cancel [2:0x7f9154c2be20]			
default	16:57:16.969251 +0200	com.apple.iCloudHelper	TIC TCP Conn
Destroyed [3:0x7f9157205450]			
default	16:57:16.969285 +0200	com.apple.iCloudHelper	TIC TCP Conn
Destroyed [2:0x7f9154c2be20]			
default	16:57:16.990934 +0200	nsurlsessiond	TIC TLS Event
[2:0x7f9ac262c6f0]: 2, Pending(0)			
default	16:57:16.992709 +0200	nsurlsessiond	TIC TLS Event
[2:0x7f9ac262c6f0]: 11, Pending(0)			
default	16:57:16.997465 +0200	nsurlsessiond	TIC TLS Event
[2:0x7f9ac262c6f0]: 22, Pending(0)			
default	16:57:16.997574 +0200	nsurlsessiond	TIC TLS Event
[2:0x7f9ac262c6f0]: 12, Pending(0)			
default	16:57:16.997639 +0200	nsurlsessiond	TIC TLS Event
[2:0x7f9ac262c6f0]: 14, Pending(0)			
default	16:57:16.997838 +0200	nsurlsessiond	Task 1 for client <private>
received auth challenge with type NSURLAuthenticationMethodServerTrust			
default	16:57:17.008051 +0200	trustd	ocsp responder: (null) did not
include status of requested cert			
default	16:57:17.011932 +0200	nsurlsessiond	TIC TLS Trust Result
[2:0x7f9ac262c6f0]: 0			
default	16:57:17.038859 +0200	nsurlsessiond	TIC TLS Event
[2:0x7f9ac262c6f0]: 20, Pending(0)			
default	16:57:17.039112 +0200	nsurlsessiond	TIC TCP Conn Event
[2:0x7f9ac262c6f0]: 8 Err(0)			
default	16:57:17.039128 +0200	nsurlsessiond	TIC TLS Handshake Complete

```

[2:0x7f9ac262c6f0]
default 16:57:17.039311 +0200 nsurlsessiond TIC TCP [0x7f9ac262c6f0]
working for task <private>
default 16:57:17.039847 +0200 nsurlsessiond TIC TCP [0x7f9ac262c6f0]
working for task <private>
default 16:57:17.040018 +0200 nsurlsessiond Task 1 for client <private> has
a connection
default 16:57:17.040639 +0200 nsurlsessiond TIC TCP [0x7f9ac262c6f0]
working for task <private>
default 16:57:17.041095 +0200 nsurlsessiond TIC TCP [0x7f9ac262c6f0]
working for task <private>
default 16:57:17.068104 +0200 nsurlsessiond Task 1 for client <private>
received response, status code: 304
default 16:57:17.068404 +0200 mobileassetd metadata download received
response (status=304)
default 16:57:17.068595 +0200 nsurlsessiond Task 1 for client <private> was
cancelled
default 16:57:17.068843 +0200 mobileassetd metadata download completed,
success=0
default 16:57:17.072945 +0200 AppleSpell 0x7fdef66ba8a0 Copy
matching assets reply: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef66ba8a0>
{ count = 3, transaction: 0, voucher = 0x0, contents =
    "Assets" => <data: 0x7fdef66267b0>: { length = 34212 bytes, contents =
0x62706c6973743030d40001000200030004000500060ff90f... }
    "AssetXMLMetadata" => <data: 0x7fdef66bc4e0>: { length = 307 bytes,
contents = 0x62706c6973743030d40102030405061f2058247665727369... }
    "Result" => <int64: 0x7fdef66be8b0>: 0
}
default 16:57:17.074600 +0200 mobileassetd 0x7ffdd7a6ca0 Client
connection: XPC_TYPE_ERROR Connection invalid <error: 0x7ffdd7a6ca0> { count
= 1, transaction: 0, voucher = 0x0, contents =
    "XPCErrorDescription" => <string: 0x7ffdd7a6f18> { length = 18, contents =
"Connection invalid" }
}
default 16:57:17.074621 +0200 mobileassetd Client connection invalid
(Connection invalid); terminating connection
default 16:57:17.075347 +0200 mobileassetd 0x7f87d1007dc0 Main Listener:
XPC_TYPE_CONNECTION <connection: 0x7f87d1007dc0> { name =
com.apple.mobileassetd (peer), listener = false, pid = 406, euid = 501, egid = 20,
asid = 100008 }
default 16:57:17.075437 +0200 mobileassetd 0x7f87d1003530 Client
connection: XPC_TYPE_DICTIONARY <dictionary: 0x7f87d1003530> { count = 6,
transaction: 1, voucher = 0x7f87d10059b0, contents =
    "AssetType" => <string: 0x7f87d1007f70> { length = 36, contents =
"com.apple.MobileAsset.LinguisticData" }
    "Predicate" => <data: 0x7f87cf423420>: { length = 1952 bytes, contents =
0x62706c6973743030d4010203040506e9ea58247665727369... }
    "Local Cache Only" => <bool: 0x7ffdd7a6aa8>: true
    "Timeout" => <double: 0x7f87cf403a10>: 15.000000
    "_IPC_TYPE" => <uint64: 0x7f87cf425df0>: 13

```

```

"ClientName" => <string: 0x7f87cf41a990> { length = 10, contents =
"AppleSpell" }
}
default 16:57:17.075819 +0200 mobileassetd HANDLER - assetQuery
[com.apple.MobileAsset.LinguisticData]: (local=1) [AssetType == "Required" AND
(AssetLocale == "en" OR AssetLocale == "en_NZ" OR AssetLocale == "en_AU" OR
AssetLocale == "pt") AND _CompatibilityVersion == 2]
default 16:57:17.076090 +0200 AppleSpell 0x7fdef66c0ab0 Copy
matching assets reply: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef66c0ab0>
{ count = 3, transaction: 0, voucher = 0x0, contents =
"Assets" => <data: 0x7fdef66c2fc0>: { length = 236 bytes, contents =
0x62706c6973743030d4010203040506141558247665727369... }
"Result" => <int64: 0x7fdef66c3000>: 0
"AssetXMLMetadata" => <data: 0x7fdef66cc490>: { length = 307 bytes,
contents = 0x62706c6973743030d40102030405061f2058247665727369... }
}
default 16:57:17.076259 +0200 mobileassetd 0x7ffdd7a6ca0 Client
connection: XPC_TYPE_ERROR Connection invalid <error: 0x7ffdd7a6ca0> { count
= 1, transaction: 0, voucher = 0x0, contents =
"XPCErrorDescription" => <string: 0x7ffdd7a6f18> { length = 18, contents =
"Connection invalid" }
}
default 16:57:17.076278 +0200 mobileassetd Client connection invalid
(Connection invalid); terminating connection
default 16:57:17.076736 +0200 mobileassetd 0x7f87cf506780 Main Listener:
XPC_TYPE_CONNECTION <connection: 0x7f87cf506780> { name =
com.apple.mobileassetd (peer), listener = false, pid = 406, euid = 501, egid = 20,
asid = 100008 }
default 16:57:17.076836 +0200 mobileassetd 0x7f87d1002b50 Client
connection: XPC_TYPE_DICTIONARY <dictionary: 0x7f87d1002b50> { count = 6,
transaction: 1, voucher = 0x7f87cf6150a0, contents =
"AssetType" => <string: 0x7f87d1003280> { length = 36, contents =
"com.apple.MobileAsset.LinguisticData" }
"Predicate" => <data: 0x7f87d1006110>: { length = 1952 bytes, contents =
0x62706c6973743030d4010203040506e9ea58247665727369... }
"Local Cache Only" => <bool: 0x7ffdd7a6aa8>: true
"Timeout" => <double: 0x7f87d1003dc0>: 15.000000
"_IPC_TYPE" => <uint64: 0x7f87d1000810>: 13
"ClientName" => <string: 0x7f87d10038a0> { length = 10, contents =
"AppleSpell" }
}
default 16:57:17.077138 +0200 mobileassetd HANDLER - assetQuery
[com.apple.MobileAsset.LinguisticData]: (local=1) [AssetType == "Optional" AND
(AssetLocale == "en" OR AssetLocale == "en_NZ" OR AssetLocale == "en_AU" OR
AssetLocale == "pt") AND _CompatibilityVersion == 2]
default 16:57:17.077635 +0200 AppleSpell 0x7fdef644b7e0 Copy
matching assets reply: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef644b7e0>
{ count = 3, transaction: 0, voucher = 0x0, contents =
"Assets" => <data: 0x7fdef6465480>: { length = 3251 bytes, contents =
0x62706c6973743030d4000100020003000400050006012a01... }

```

```

"Result" => <int64: 0x7fdef641c0d0>: 0
"AssetXMLMetadata" => <data: 0x7fdef641e840>: { length = 307 bytes,
contents = 0x62706c6973743030d40102030405061f2058247665727369... }
}
default 16:57:17.077925 +0200 mobileassetd 0x7ffdd7a6ca0 Client
connection: XPC_TYPE_ERROR Connection invalid <error: 0x7ffdd7a6ca0> { count
= 1, transaction: 0, voucher = 0x0, contents =
  "XPCErrorDescription" => <string: 0x7ffdd7a6f18> { length = 18, contents =
"Connection invalid" }
}
default 16:57:17.077944 +0200 mobileassetd Client connection invalid
(Connection invalid); terminating connection
default 16:57:17.078364 +0200 mobileassetd 0x7f87d1253c10 Main Listener:
XPC_TYPE_CONNECTION <connection: 0x7f87d1253c10> { name =
com.apple.mobileassetd (peer), listener = false, pid = 406, euid = 501, egid = 20,
asid = 100008 }
default 16:57:17.078440 +0200 mobileassetd 0x7f87d1203a70 Client
connection: XPC_TYPE_DICTIONARY <dictionary: 0x7f87d1203a70> { count = 6,
transaction: 1, voucher = 0x7f87d1254780, contents =
  "AssetType" => <string: 0x7f87d1257d00> { length = 36, contents =
"com.apple.MobileAsset.LinguisticData" }
  "Predicate" => <data: 0x7f87d1203820>: { length = 1949 bytes, contents =
0x62706c6973743030d4010203040506e9ea58247665727369... }
  "Local Cache Only" => <bool: 0x7ffdd7a6aa8>: true
  "Timeout" => <double: 0x7f87cf506f60>: 15.000000
  "_IPC_TYPE" => <uint64: 0x7f87cf5083a0>: 13
  "ClientName" => <string: 0x7f87cf506fa0> { length = 10, contents =
"AppleSpell" }
}
default 16:57:17.078758 +0200 mobileassetd HANDLER - assetQuery
[com.apple.MobileAsset.LinguisticData]: (local=1) [AssetType == "Delta" AND
(AssetLocale == "en" OR AssetLocale == "en_NZ" OR AssetLocale == "en_AU" OR
AssetLocale == "pt") AND _CompatibilityVersion == 2]
default 16:57:17.079184 +0200 AppleSpell 0x7fdef9886690 Copy
matching assets reply: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef9886690>
{ count = 3, transaction: 0, voucher = 0x0, contents =
  "Assets" => <data: 0x7fdef9883c30>: { length = 3038 bytes, contents =
0x62706c6973743030d4000100020003000400050006010901... }
  "Result" => <int64: 0x7fdef9883c70>: 0
  "AssetXMLMetadata" => <data: 0x7fdef98868c0>: { length = 307 bytes,
contents = 0x62706c6973743030d40102030405061f2058247665727369... }
}
default 16:57:17.079500 +0200 mobileassetd 0x7ffdd7a6ca0 Client
connection: XPC_TYPE_ERROR Connection invalid <error: 0x7ffdd7a6ca0> { count
= 1, transaction: 0, voucher = 0x0, contents =
  "XPCErrorDescription" => <string: 0x7ffdd7a6f18> { length = 18, contents =
"Connection invalid" }
}
default 16:57:17.079534 +0200 mobileassetd Client connection invalid
(Connection invalid); terminating connection

```



```

default 16:57:17.079756 +0200 mobileassetd 0x7f87d1253c10 Main Listener:
XPC_TYPE_CONNECTION <connection: 0x7f87d1253c10> { name =
com.apple.mobileassetd (peer), listener = false, pid = 406, euid = 501, egid = 20,
asid = 100008 }
default 16:57:17.079858 +0200 mobileassetd 0x7f87d1257c50 Client
connection: XPC_TYPE_DICTIONARY <dictionary: 0x7f87d1257c50> { count = 5,
transaction: 1, voucher = 0x7f87d1254780, contents =
    "AssetType" => <string: 0x7f87d12009b0> { length = 36, contents =
"com.apple.MobileAsset.LinguisticData" }
    "AssetProperties" => <dictionary: 0x7f87d1253e70> { count = 23, transaction:
0, voucher = 0x0, contents =
        "FormatVersion" => <int64: 0x7f87d1203930>: 1
        "AssetType" => <string: 0x7f87d1255c70> { length = 5, contents =
"Delta" }
        "_DownloadSize" => <int64: 0x7f87d120fe30>: 100291
        "_MasteredVersion" => <string: 0x7f87d1203820> { length = 4, contents =
"2512" }
        "_CompressionAlgorithm" => <string: 0x7f87d1255dc0> { length = 3,
contents = "zip" }
        "__CanUseLocalCacheServer" => <bool: 0x7ffdd7a6aa8>: true
        "_MeasurementAlgorithm" => <string: 0x7f87d12018d0> { length = 5,
contents = "SHA-1" }
        "__RequiredByOS" => <int64: 0x7f87d1255bc0>: 0
        "__RelativePath" => <string: 0x7f87d1254620> { length = 81, contents =
"com_apple_Mobile<...>
default 16:57:17.080003 +0200 mobileassetd [AppleSpell] HANDLER -
copyAssetAttributes [com.apple.MobileAsset.LinguisticData]:
com_apple_MobileAsset_LinguisticData/
12124144ce3f42648e61a6a8064d2fb9b2d42605.zip
default 16:57:17.080160 +0200 AppleSpell 0x7fdef98865e0 Copy assets
attributes reply: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef98865e0> { count =
2, transaction: 0, voucher = 0x0, contents =
    "Attributes" => <data: 0x7fdef98868b0>: { length = 302 bytes, contents =
0x62706c6973743030d40102030405061a1b58247665727369... }
    "Result" => <int64: 0x7fdef9883d30>: 0
}
default 16:57:17.080280 +0200 mobileassetd 0x7ffdd7a6ca0 Client
connection: XPC_TYPE_ERROR Connection invalid <error: 0x7ffdd7a6ca0> { count
= 1, transaction: 0, voucher = 0x0, contents =
    "XPCErrorDescription" => <string: 0x7ffdd7a6f18> { length = 18, contents =
"Connection invalid" }
}
default 16:57:17.080307 +0200 mobileassetd Client connection invalid
(Connection invalid); terminating connection
default 16:57:17.080385 +0200 mobileassetd 0x7f87cf627a20 Main Listener:
XPC_TYPE_CONNECTION <connection: 0x7f87cf627a20> { name =
com.apple.mobileassetd (peer), listener = false, pid = 406, euid = 501, egid = 20,
asid = 100008 }
default 16:57:17.080507 +0200 mobileassetd 0x7f87cf625910 Client
connection: XPC_TYPE_DICTIONARY <dictionary: 0x7f87cf625910> { count = 5,

```

```

transaction: 1, voucher = 0x7f87cf548aa0, contents =
    "AssetType" => <string: 0x7f87d1255dc0> { length = 36, contents =
"com.apple.MobileAsset.LinguisticData" }
    "AssetProperties" => <dictionary: 0x7f87d1203f80> { count = 22, transaction: 0,
voucher = 0x0, contents =
        "FormatVersion" => <int64: 0x7f87d1203930>: 1
        "AssetType" => <string: 0x7f87d1200fc0> { length = 8, contents =
"Optional" }
        "_DownloadSize" => <int64: 0x7f87d120fe30>: 5540568
        "_MasteredVersion" => <string: 0x7f87d1253900> { length = 3, contents =
"752" }
        "_CompressionAlgorithm" => <string: 0x7f87d1255bc0> { length = 3,
contents = "zip" }
        "__CanUseLocalCacheServer" => <bool: 0x7ffdd7a6aa8>: true
        "_MeasurementAlgorithm" => <string: 0x7f87d1257850> { length = 5,
contents = "SHA-1" }
        "__RequiredByOS" => <int64: 0x7f87d1257830>: 0
        "__RelativePath" => <string: 0x7f87d12545c0> { length = 81, contents =
"com_apple_Mob<...>
default 16:57:17.080596 +0200 mobileassetd [AppleSpell] HANDLER -
copyAssetAttributes [com.apple.MobileAsset.LinguisticData]:
com_apple_MobileAsset_LinguisticData/
fe1bc1f2e8c52a987b179fc9cd2f3ee6bf9aca10.zip
default 16:57:17.080746 +0200 AppleSpell 0x7fdef9b12690 Copy assets
attributes reply: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef9b12690> { count =
2, transaction: 0, voucher = 0x0, contents =
    "Attributes" => <data: 0x7fdef9b17270>: { length = 302 bytes, contents =
0x62706c6973743030d40102030405061a1b58247665727369... }
    "Result" => <int64: 0x7fdef9b14670>: 0
}
default 16:57:17.080861 +0200 mobileassetd 0x7ffdd7a6ca0 Client
connection: XPC_TYPE_ERROR Connection invalid <error: 0x7ffdd7a6ca0> { count
= 1, transaction: 0, voucher = 0x0, contents =
    "XPCErrorDescription" => <string: 0x7ffdd7a6f18> { length = 18, contents =
"Connection invalid" }
}
default 16:57:17.080914 +0200 mobileassetd Client connection invalid
(Connection invalid); terminating connection
default 16:57:17.080952 +0200 mobileassetd 0x7f87d1007dc0 Main Listener:
XPC_TYPE_CONNECTION <connection: 0x7f87d1007dc0> { name =
com.apple.mobileassetd (peer), listener = false, pid = 406, euid = 501, egid = 20,
asid = 100008 }
default 16:57:17.081066 +0200 mobileassetd 0x7f87cf507420 Client
connection: XPC_TYPE_DICTIONARY <dictionary: 0x7f87cf507420> { count = 5,
transaction: 1, voucher = 0x7f87d1108380, contents =
    "AssetType" => <string: 0x7f87cf506fa0> { length = 36, contents =
"com.apple.MobileAsset.LinguisticData" }
    "AssetProperties" => <dictionary: 0x7f87cf506780> { count = 19, transaction: 0,
voucher = 0x0, contents =
        "AssetType" => <string: 0x7f87cf508cf0> { length = 5, contents = "Delta" }

```

```

        "_CompressionAlgorithm" => <string: 0x7f87cf548aa0> { length = 3,
contents = "zip" }
        "_FormatVersion" => <int64: 0x7f87cf507ac0>: 1
        "_DownloadSize" => <int64: 0x7f87cf508340>: 86109
        "_MasteredVersion" => <string: 0x7f87cf505d00> { length = 4, contents =
"2512" }
        "_MeasurementAlgorithm" => <string: 0x7f87cf54c230> { length = 5,
contents = "SHA-1" }
        "__CanUseLocalCacheServer" => <bool: 0x7ffdd7a6aa8>: true
        "__RequiredByOS" => <int64: 0x7f87cf508810>: 0
        "__RelativePath" => <string: 0x7f87cf509050> { length = 81, contents =
"com_apple_MobileA<...>
default 16:57:17.081231 +0200 mobileassetd [AppleSpell] HANDLER -
copyAssetAttributes [com.apple.MobileAsset.LinguisticData]:
com_apple_MobileAsset_LinguisticData/
fc6ae396ace7d84cd7049f6f8204511494b1c530.zip
default 16:57:17.081259 +0200 mobileassetd No matching entries found
default 16:57:17.081294 +0200 mobileassetd [AppleSpell] unable to get
asset attributes[com.apple.MobileAsset.LinguisticData]: 1
[com_apple_MobileAsset_LinguisticData/
fc6ae396ace7d84cd7049f6f8204511494b1c530.zip]
default 16:57:17.081351 +0200 AppleSpell 0x7fdef9a0afc0 Copy assets
attributes reply: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef9a0afc0> { count =
1, transaction: 0, voucher = 0x0, contents =
    "Result" => <int64: 0x7fdef9a0b2c0>: 1
}
default 16:57:17.081417 +0200 AppleSpell [MobileAssetError:1] Unable to
copy asset attributes
default 16:57:17.081497 +0200 mobileassetd 0x7ffdd7a6ca0 Client
connection: XPC_TYPE_ERROR Connection invalid <error: 0x7ffdd7a6ca0> { count
= 1, transaction: 0, voucher = 0x0, contents =
    "XPCErrorDescription" => <string: 0x7ffdd7a6f18> { length = 18, contents =
"Connection invalid" }
}
default 16:57:17.081528 +0200 mobileassetd Client connection invalid
(Connection invalid); terminating connection
default 16:57:17.081626 +0200 mobileassetd 0x7f87d1105660 Main Listener:
XPC_TYPE_CONNECTION <connection: 0x7f87d1105660> { name =
com.apple.mobileassetd (peer), listener = false, pid = 406, euid = 501, egid = 20,
asid = 100008 }
default 16:57:17.081710 +0200 mobileassetd 0x7f87d1200900 Client
connection: XPC_TYPE_DICTIONARY <dictionary: 0x7f87d1200900> { count = 5,
transaction: 1, voucher = 0x7f87d1207390, contents =
    "AssetType" => <string: 0x7f87d12009b0> { length = 36, contents =
"com.apple.MobileAsset.LinguisticData" }
    "AssetProperties" => <dictionary: 0x7f87d1203a70> { count = 18, transaction:
0, voucher = 0x0, contents =
        "AssetType" => <string: 0x7f87d1253900> { length = 8, contents =
"Optional" }
        "_CompressionAlgorithm" => <string: 0x7f87d1203600> { length = 3,

```

```

contents = "zip" }
    "FormatVersion" => <int64: 0x7f87d1203930>: 1
    "_DownloadSize" => <int64: 0x7f87d120fe30>: 2706074
    "_MasteredVersion" => <string: 0x7f87d1203b20> { length = 4, contents =
"2512" }
    "_MeasurementAlgorithm" => <string: 0x7f87d1206e50> { length = 5,
contents = "SHA-1" }
    "__CanUseLocalCacheServer" => <bool: 0x7ffdd7a6aa8>: true
    "__RequiredByOS" => <int64: 0x7f87d1256d40>: 0
    "__RelativePath" => <string: 0x7f87d12012d0> { length = 81, contents =
"com_apple_Mo<...>
default 16:57:17.081876 +0200 mobileassetd [AppleSpell] HANDLER -
copyAssetAttributes [com.apple.MobileAsset.LinguisticData]:
com_apple_MobileAsset_LinguisticData/
a76f754b2835fa56689b62d6189696ab82847901.zip
default 16:57:17.081905 +0200 mobileassetd No matching entries found
default 16:57:17.081931 +0200 mobileassetd [AppleSpell] unable to get
asset attributes[com.apple.MobileAsset.LinguisticData]: 1
[com_apple_MobileAsset_LinguisticData/
a76f754b2835fa56689b62d6189696ab82847901.zip]
default 16:57:17.081982 +0200 AppleSpell 0x7fdef9a0d020 Copy assets
attributes reply: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef9a0d020> { count =
1, transaction: 0, voucher = 0x0, contents =
    "Result" => <int64: 0x7fdef9a0d4c0>: 1
}
default 16:57:17.082048 +0200 AppleSpell [MobileAssetError:1] Unable to
copy asset attributes
default 16:57:17.082168 +0200 mobileassetd 0x7ffdd7a6ca0 Client
connection: XPC_TYPE_ERROR Connection invalid <error: 0x7ffdd7a6ca0> { count
= 1, transaction: 0, voucher = 0x0, contents =
    "XPCErrorDescription" => <string: 0x7ffdd7a6f18> { length = 18, contents =
"Connection invalid" }
}
default 16:57:17.082194 +0200 mobileassetd Client connection invalid
(Connection invalid); terminating connection
default 16:57:17.082269 +0200 mobileassetd 0x7f87cf70e6e0 Main Listener:
XPC_TYPE_CONNECTION <connection: 0x7f87cf70e6e0> { name =
com.apple.mobileassetd (peer), listener = false, pid = 406, euid = 501, egid = 20,
asid = 100008 }
default 16:57:17.082365 +0200 mobileassetd 0x7f87d1257c50 Client
connection: XPC_TYPE_DICTIONARY <dictionary: 0x7f87d1257c50> { count = 5,
transaction: 1, voucher = 0x7f87d1108380, contents =
    "AssetType" => <string: 0x7f87d1257d00> { length = 36, contents =
"com.apple.MobileAsset.LinguisticData" }
    "AssetProperties" => <dictionary: 0x7f87d1203a70> { count = 19, transaction:
0, voucher = 0x0, contents =
        "AssetType" => <string: 0x7f87d1200fc0> { length = 5, contents = "Delta" }
        "_CompressionAlgorithm" => <string: 0x7f87d1203600> { length = 3,
contents = "zip" }
        "FormatVersion" => <int64: 0x7f87d1203930>: 1

```

```

    "_DownloadSize" => <int64: 0x7f87d120fe30>: 86109
    "_MasteredVersion" => <string: 0x7f87d1203b20> { length = 4, contents =
"2512" }
    "_MeasurementAlgorithm" => <string: 0x7f87d1206e50> { length = 5,
contents = "SHA-1" }
    "__CanUseLocalCacheServer" => <bool: 0x7ffdd7a6aa8>: true
    "__RequiredByOS" => <int64: 0x7f87d120f2d0>: 0
    "__RelativePath" => <string: 0x7f87d1203320> { length = 81, contents =
"com_apple_MobileA<...>
default 16:57:17.082485 +0200 mobileassetd [AppleSpell] HANDLER -
copyAssetAttributes [com.apple.MobileAsset.LinguisticData]:
com_apple_MobileAsset_LinguisticData/
fc6ae396ace7d84cd7049f6f8204511494b1c530.zip
default 16:57:17.082511 +0200 mobileassetd No matching entries found
default 16:57:17.082543 +0200 mobileassetd [AppleSpell] unable to get
asset attributes[com.apple.MobileAsset.LinguisticData]: 1
[com_apple_MobileAsset_LinguisticData/
fc6ae396ace7d84cd7049f6f8204511494b1c530.zip]
default 16:57:17.082603 +0200 AppleSpell 0x7fdef671aea0 Copy assets
attributes reply: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef671aea0> { count =
1, transaction: 0, voucher = 0x0, contents =
    "Result" => <int64: 0x7fdef671ab70>: 1
}
default 16:57:17.082642 +0200 AppleSpell [MobileAssetError:1] Unable to
copy asset attributes
default 16:57:17.082766 +0200 mobileassetd 0x7ffdd7a6ca0 Client
connection: XPC_TYPE_ERROR Connection invalid <error: 0x7ffdd7a6ca0> { count
= 1, transaction: 0, voucher = 0x0, contents =
    "XPCErrorDescription" => <string: 0x7ffdd7a6f18> { length = 18, contents =
"Connection invalid" }
}
default 16:57:17.082784 +0200 mobileassetd Client connection invalid
(Connection invalid); terminating connection
default 16:57:17.083177 +0200 mobileassetd 0x7f87d1007dc0 Main Listener:
XPC_TYPE_CONNECTION <connection: 0x7f87d1007dc0> { name =
com.apple.mobileassetd (peer), listener = false, pid = 406, euid = 501, egid = 20,
asid = 100008 }
default 16:57:17.083266 +0200 mobileassetd 0x7f87cf507420 Client
connection: XPC_TYPE_DICTIONARY <dictionary: 0x7f87cf507420> { count = 5,
transaction: 1, voucher = 0x7f87d1008260, contents =
    "AssetType" => <string: 0x7f87cf505d00> { length = 36, contents =
"com.apple.MobileAsset.LinguisticData" }
    "AssetProperties" => <dictionary: 0x7f87cf506780> { count = 19, transaction: 0,
voucher = 0x0, contents =
        "AssetType" => <string: 0x7f87cf508cf0> { length = 5, contents = "Delta" }
        "_CompressionAlgorithm" => <string: 0x7f87cf548aa0> { length = 3,
contents = "zip" }
        "FormatVersion" => <int64: 0x7f87cf507ac0>: 1
        "_DownloadSize" => <int64: 0x7f87cf508340>: 86109
        "_MasteredVersion" => <string: 0x7f87cf506fa0> { length = 4, contents =

```

```

"2512" }
    "_MeasurementAlgorithm" => <string: 0x7f87cf54c230> { length = 5,
contents = "SHA-1" }
    "__CanUseLocalCacheServer" => <bool: 0x7ffdd7a6aa8>: true
    "__RequiredByOS" => <int64: 0x7f87cf508810>: 0
    "__RelativePath" => <string: 0x7f87cf5086a0> { length = 81, contents =
"com_apple_MobileA<...>
default 16:57:17.083389 +0200 mobileassetd [AppleSpell] HANDLER -
copyAssetAttributes [com.apple.MobileAsset.LinguisticData]:
com_apple_MobileAsset_LinguisticData/
fc6ae396ace7d84cd7049f6f8204511494b1c530.zip
default 16:57:17.083416 +0200 mobileassetd No matching entries found
default 16:57:17.083434 +0200 mobileassetd [AppleSpell] unable to get
asset attributes[com.apple.MobileAsset.LinguisticData]: 1
[com_apple_MobileAsset_LinguisticData/
fc6ae396ace7d84cd7049f6f8204511494b1c530.zip]
default 16:57:17.083472 +0200 AppleSpell 0x7fdef9b16cb0 Copy assets
attributes reply: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef9b16cb0> { count =
1, transaction: 0, voucher = 0x0, contents =
    "Result" => <int64: 0x7fdef9b13de0>: 1
}
default 16:57:17.083534 +0200 AppleSpell [MobileAssetError:1] Unable to
copy asset attributes
default 16:57:17.083635 +0200 mobileassetd 0x7ffdd7a6ca0 Client
connection: XPC_TYPE_ERROR Connection invalid <error: 0x7ffdd7a6ca0> { count
= 1, transaction: 0, voucher = 0x0, contents =
    "XPCErrorDescription" => <string: 0x7ffdd7a6f18> { length = 18, contents =
"Connection invalid" }
}
default 16:57:17.083674 +0200 mobileassetd Client connection invalid
(Connection invalid); terminating connection
default 16:57:17.083693 +0200 AppleSpell request download, asset
version : 2512, download size: 86109
default 16:57:17.083720 +0200 AppleSpell retries = 0
default 16:57:17.083877 +0200 mobileassetd 0x7f87cf506780 Main Listener:
XPC_TYPE_CONNECTION <connection: 0x7f87cf506780> { name =
com.apple.mobileassetd (peer), listener = false, pid = 406, euid = 501, egid = 20,
asid = 100008 }
default 16:57:17.083931 +0200 mobileassetd 0x7f87cf5071d0 Main Listener:
XPC_TYPE_CONNECTION <connection: 0x7f87cf5071d0> { name =
com.apple.mobileassetd (peer), listener = false, pid = 406, euid = 501, egid = 20,
asid = 100008 }
default 16:57:17.084019 +0200 mobileassetd 0x7f87d10057d0 Client
connection: XPC_TYPE_DICTIONARY <dictionary: 0x7f87d10057d0> { count = 5,
transaction: 1, voucher = 0x7f87d1008260, contents =
    "DownloadOptions" => <dictionary: 0x7f87d1004790> { count = 2, transaction:
0, voucher = 0x0, contents =
        "DownloadOptionAllowBatteryPower" => <bool: 0x7ffdd7a6aa8>: true
        "DownloadOptionPriority" => <string: 0x7f87d1003460> { length = 20,
contents = "DownloadPriorityHigh" }

```

```

    }
    "AssetType" => <string: 0x7f87d1103120> { length = 36, contents =
"com.apple.MobileAsset.LinguisticData" }
    "AssetProperties" => <dictionary: 0x7f87d11082e0> { count = 19, transaction:
0, voucher = 0x0, contents =
        "AssetType" => <string: 0x7f87d1105790> { length = 5, contents =
"Delta" }
        "_CompressionAlgorithm" => <string: 0x7f87d1105720> { length = 3,
contents = "zip" }
        "FormatVersion" => <int64: 0x7f87d1103150>: 1
        "_DownloadSize" => <int64: 0x7f87d1108120>: 86109
        "_MasteredVersion" => <string: 0x7f87d1108390> { length = 4, contents =
"2512" }
        "_Mea<...>
default 16:57:17.084023 +0200 mobileassetd 0x7f87d1003530 Client
connection: XPC_TYPE_DICTIONARY <dictionary: 0x7f87d1003530> { count = 5,
transaction: 1, voucher = 0x7f87d1008260, contents =
    "AssetType" => <string: 0x7f87d10038a0> { length = 36, contents =
"com.apple.MobileAsset.LinguisticData" }
    "AssetProperties" => <dictionary: 0x7f87d1005420> { count = 18, transaction:
0, voucher = 0x0, contents =
        "AssetType" => <string: 0x7f87d1007e70> { length = 8, contents =
"Optional" }
        "_CompressionAlgorithm" => <string: 0x7f87d1005940> { length = 3,
contents = "zip" }
        "FormatVersion" => <int64: 0x7f87d1000e00>: 1
        "_DownloadSize" => <int64: 0x7f87d1000120>: 2706074
        "_MasteredVersion" => <string: 0x7f87d1007f70> { length = 4, contents =
"2512" }
        "_MeasurementAlgorithm" => <string: 0x7f87d10054d0> { length = 5,
contents = "SHA-1" }
        "__CanUseLocalCacheServer" => <bool: 0x7ffdd7a6aa8>: true
        "__RequiredByOS" => <int64: 0x7f87d10062b0>: 0
        "__RelativePath" => <string: 0x7f87d1002f00> { length = 81, contents =
"com_apple_Mo<...>
default 16:57:17.084086 +0200 mobileassetd Handling download message
default 16:57:17.084227 +0200 mobileassetd [AppleSpell] HANDLER -
downloadAsset [com.apple.MobileAsset.LinguisticData]:
com_apple_MobileAsset_LinguisticData/
fc6ae396ace7d84cd7049f6f8204511494b1c530.zip
default 16:57:17.084303 +0200 mobileassetd Options: {
    DownloadOptionAllowBatteryPower = 1;
    DownloadOptionPriority = DownloadPriorityHigh;
}
default 16:57:17.084689 +0200 mobileassetd [AppleSpell] HANDLER -
copyAssetAttributes [com.apple.MobileAsset.LinguisticData]:
com_apple_MobileAsset_LinguisticData/
a76f754b2835fa56689b62d6189696ab82847901.zip
default 16:57:17.084730 +0200 mobileassetd No matching entries found
default 16:57:17.084753 +0200 mobileassetd [AppleSpell] unable to get

```

```

asset attributes[com.apple.MobileAsset.LinguisticData]: 1
[com_apple_MobileAsset_LinguisticData/
a76f754b2835fa56689b62d6189696ab82847901.zip]
default 16:57:17.084804 +0200 AppleSpell 0x7fdef65a12c0 Copy assets
attributes reply: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef65a12c0> { count =
1, transaction: 0, voucher = 0x0, contents =
    "Result" => <int64: 0x7fdef65a8040>: 1
}
default 16:57:17.084857 +0200 AppleSpell [MobileAssetError:1] Unable to
copy asset attributes
default 16:57:17.084961 +0200 mobileassetd 0x7ffdd7a6ca0 Client
connection: XPC_TYPE_ERROR Connection invalid <error: 0x7ffdd7a6ca0> { count
= 1, transaction: 0, voucher = 0x0, contents =
    "XPCErrorDescription" => <string: 0x7ffdd7a6f18> { length = 18, contents =
"Connection invalid" }
}
default 16:57:17.084985 +0200 mobileassetd Client connection invalid
(Connection invalid); terminating connection
default 16:57:17.085109 +0200 mobileassetd 0x7f87d12026c0 Main Listener:
XPC_TYPE_CONNECTION <connection: 0x7f87d12026c0> { name =
com.apple.mobileassetd (peer), listener = false, pid = 406, euid = 501, egid = 20,
asid = 100008 }
default 16:57:17.085151 +0200 mobileassetd Creating directory at <private>
default 16:57:17.085232 +0200 mobileassetd 0x7f87cf509910 Client
connection: XPC_TYPE_DICTIONARY <dictionary: 0x7f87cf509910> { count = 5,
transaction: 1, voucher = 0x7f87d1008260, contents =
    "AssetType" => <string: 0x7f87cf5098a0> { length = 36, contents =
"com.apple.MobileAsset.LinguisticData" }
    "AssetProperties" => <dictionary: 0x7f87cf509a70> { count = 18, transaction: 0,
voucher = 0x0, contents =
        "AssetType" => <string: 0x7f87cf508ff0> { length = 8, contents =
"Optional" }
        "_CompressionAlgorithm" => <string: 0x7f87cf506ae0> { length = 3,
contents = "zip" }
        "FormatVersion" => <int64: 0x7f87cf507280>: 1
        "_DownloadSize" => <int64: 0x7f87cf5092b0>: 2706074
        "_MasteredVersion" => <string: 0x7f87cf506fa0> { length = 4, contents =
"2512" }
        "_MeasurementAlgorithm" => <string: 0x7f87cf509bd0> { length = 5,
contents = "SHA-1" }
        "__CanUseLocalCacheServer" => <bool: 0x7ffdd7a6aa8>: true
        "__RequiredByOS" => <int64: 0x7f87cf509b20>: 0
        "__RelativePath" => <string: 0x7f87cf509d70> { length = 81, contents =
"com_apple_Mo<...>
default 16:57:17.085417 +0200 mobileassetd [AppleSpell] HANDLER -
copyAssetAttributes [com.apple.MobileAsset.LinguisticData]:
com_apple_MobileAsset_LinguisticData/
a76f754b2835fa56689b62d6189696ab82847901.zip
default 16:57:17.123223 +0200 mobileassetd No matching entries found
default 16:57:17.123254 +0200 mobileassetd [AppleSpell] unable to get

```



```

asset attributes[com.apple.MobileAsset.LinguisticData]: 1
[com_apple_MobileAsset_LinguisticData/
a76f754b2835fa56689b62d6189696ab82847901.zip]
default 16:57:17.123338 +0200 AppleSpell 0x7fdef6719600 Copy assets
attributes reply: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef6719600> { count =
1, transaction: 0, voucher = 0x0, contents =
    "Result" => <int64: 0x7fdef671af80>: 1
}
default 16:57:17.123391 +0200 AppleSpell [MobileAssetError:1] Unable to
copy asset attributes
default 16:57:17.123509 +0200 mobileassetd 0x7ffdd7a6ca0 Client
connection: XPC_TYPE_ERROR Connection invalid <error: 0x7ffdd7a6ca0> { count
= 1, transaction: 0, voucher = 0x0, contents =
    "XPCErrorDescription" => <string: 0x7ffdd7a6f18> { length = 18, contents =
"Connection invalid" }
}
default 16:57:17.123535 +0200 mobileassetd Client connection invalid
(Connection invalid); terminating connection
default 16:57:17.123618 +0200 AppleSpell request download, asset
version : 2512, download size: 2706074
default 16:57:17.123644 +0200 AppleSpell retries = 0
default 16:57:17.123802 +0200 mobileassetd 0x7f87cf608e10 Main Listener:
XPC_TYPE_CONNECTION <connection: 0x7f87cf608e10> { name =
com.apple.mobileassetd (peer), listener = false, pid = 406, euid = 501, egid = 20,
asid = 100008 }
default 16:57:17.123950 +0200 mobileassetd 0x7f87d10057d0 Client
connection: XPC_TYPE_DICTIONARY <dictionary: 0x7f87d10057d0> { count = 5,
transaction: 1, voucher = 0x7f87d1008260, contents =
    "DownloadOptions" => <dictionary: 0x7f87d10033b0> { count = 2, transaction:
0, voucher = 0x0, contents =
        "DownloadOptionAllowBatteryPower" => <bool: 0x7ffdd7a6aa8>: true
        "DownloadOptionPriority" => <string: 0x7f87d1003460> { length = 20,
contents = "DownloadPriorityHigh" }
    }
    "AssetType" => <string: 0x7f87d1000e00> { length = 36, contents =
"com.apple.MobileAsset.LinguisticData" }
    "AssetProperties" => <dictionary: 0x7f87d1004790> { count = 18, transaction:
0, voucher = 0x0, contents =
        "AssetType" => <string: 0x7f87d1007e80> { length = 8, contents =
"Optional" }
        "_CompressionAlgorithm" => <string: 0x7f87d10038a0> { length = 3,
contents = "zip" }
        "FormatVersion" => <int64: 0x7f87d1005940>: 1
        "_DownloadSize" => <int64: 0x7f87d1000120>: 2706074
        "_MasteredVersion" => <string: 0x7f87d1003280> { length = 4, contents =
"2512" }
        <...>
default 16:57:17.124006 +0200 mobileassetd Handling download message
default 16:57:17.139495 +0200 opendiroryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0

```

```

default 16:57:17.139662 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default 16:57:17.153916 +0200 mobileassetd [AppleSpell] HANDLER -
downloadAsset [com.apple.MobileAsset.LinguisticData]:
com_apple_MobileAsset_LinguisticData/
a76f754b2835fa56689b62d6189696ab82847901.zip
default 16:57:17.153970 +0200 mobileassetd Options: {
    DownloadOptionAllowBatteryPower = 1;
    DownloadOptionPriority = DownloadPriorityHigh;
}
default 16:57:17.169884 +0200 mobileassetd Creating directory at <private>
default 16:57:17.170196 +0200 mobileassetd #edcb6a0d
ACSLocateCachingServer(assetURL=http://appldnld.apple.com/
ios10.0/031-72107-2016008009-1F1D1C14-5B55-11E6-B8BB-BCDA464FE3CA/
com_apple_MobileAsset_LinguisticData/
fc6ae396ace7d84cd7049f6f8204511494b1c530.zip, locateTimeout=10.000,
options=(null), callbackQueue=0x0, callback=0x7000098dcb20)
default 16:57:17.170234 +0200 mobileassetd #edcb6a0d
runningInAgentContext=NO
default 16:57:17.174707 +0200 opendirectoryd Client: <private>, UID: 235,
EUID: 235, GID: 235, EGID: 235
default 16:57:17.175895 +0200 opendirectoryd Client: <private>, UID: 235,
EUID: 235, GID: 235, EGID: 235
default 16:57:17.182685 +0200 AssetCacheLocatorService
#00000000 [com.apple.main-thread] AssetCacheLocatorService starting for
user 235
error 16:57:17.185316 +0200 AssetCacheLocatorService error getting store
properties: (268435459) (ipc/send) invalid destination port
error 16:57:17.185355 +0200 AssetCacheLocatorService unable to get a
dev_t for store 1795162128.
error 16:57:17.185576 +0200 mds __TCCAccessRequest_block_invoke.61:
Connection invalid
default 16:57:17.185694 +0200 AssetCache XPC-C connection from pid
498 uid 235
error 16:57:17.185693 +0200 mds __TCCAccessRequest_block_invoke.61:
Connection invalid
error 16:57:17.185818 +0200 mds __TCCAccessRequest_block_invoke.61:
Connection invalid
default 16:57:17.191556 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default 16:57:17.191720 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 20, EGID: 20
default 16:57:17.191953 +0200 opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default 16:57:17.198836 +0200 opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default 16:57:17.208082 +0200 IMDMessageServicesAgent
IORegistry entry 'IODeviceTree:/efi/platform' does not contain the key 'apple-
coprocessor-version'
default 16:57:17.211162 +0200 trustd cert[2]: AnchorTrusted =(leaf)[force]>

```

0

```
default    16:57:17.212589 +0200    IMDPersistenceAgent    MacOS error:
-67050
error 16:57:17.218341 +0200    AssetCacheLocatorService    error getting store
properties: (268435459) (ipc/send) invalid destination port
error 16:57:17.218360 +0200    AssetCacheLocatorService    unable to get a
dev_t for store 1795162128.
default    16:57:17.221108 +0200    AssetCacheLocatorService
    using system preferences
default    16:57:17.222703 +0200    AssetCacheLocatorService
    0x7f9e21608080 opened /var/folders/zz/zyxvpxvq6csfxvn_n00000xc00007b/C//
mds/mdsObject.db: 4636 bytes
default    16:57:17.222957 +0200    AssetCacheLocatorService
    0x7f9e2160d1d0 opened /var/folders/zz/zyxvpxvq6csfxvn_n00000xc00007b/C//
mds/mdsDirectory.db: 50744 bytes
default    16:57:17.224283 +0200    AssetCacheLocatorService
    0x7f9e216333e0 opened /var/folders/zz/zyxvpxvq6csfxvn_n00000xc00007b/C//
mds/mdsDirectory.db: 50744 bytes
default    16:57:17.225543 +0200    AssetCacheLocatorService
    0x7f9e216112d0 opened /Library/Keychains/System.keychain: 37732 bytes
default    16:57:17.228369 +0200    AssetCacheLocatorService
    TIC TCP Conn Start [1:0x7f9e21412020]
default    16:57:17.249439 +0200    mobileassetd    #6a169984
ACSLocateCachingServer(assetURL=http://appldnld.apple.com/
ios10.0/031-72107-2016008009-1F1D1C14-5B55-11E6-B8BB-BCDA464FE3CA/
com_apple_MobileAsset_LinguisticData/
a76f754b2835fa56689b62d6189696ab82847901.zip, locateTimeout=10.000,
options=(null), callbackQueue=0x0, callback=0x7000099e2b20)
error 16:57:17.337132 +0200    sandboxd SandboxViolation:
AssetCacheLocato(498) deny mach-lookup com.apple.metadata.mds.legacy
Violation:    deny mach-lookup com.apple.metadata.mds.legacy
Process:      AssetCacheLocato [498]
Path:         /System/Library/PrivateFrameworks/AssetCacheServices.framework/
XPCServices/AssetCacheLocatorService.xpc/Contents/MacOS/
AssetCacheLocatorService
Load Address: 0x101ec7000
Identifier:   com.apple.AssetCacheLocatorService
Version:      48.3 (48.3)
Code Type:    x86_64 (Native)
Parent Process: launchd [1]
Responsible:  /System/Library/PrivateFrameworks/
AssetCacheServices.framework/XPCServices/AssetCacheLocatorService.xpc/
Contents/MacOS/AssetCacheLocatorService [498]
User ID:      235

Date/Time:    2017-05-26 16:57:17.186 GMT+2
OS Version:   Mac OS X 10.12.4 (16E195)
Report Version: 8
```

Thread 0 (id: 6734):

0	libsystem_kernel.dylib	0x00007fffd49b134a mach_msg_trap + 10
1	CoreFoundation	0x00007fffbf1284e4 __CFRunLoopServiceMachPort + 212
2	CoreFoundation	0x00007fffbf127971 __CFRunLoopRun + 1361
3	CoreFoundation	0x00007fffbf1271c4 CFRunLoopRunSpecific + 420
4	Foundation	0x00007fffc0b39572 -[NSRunLoop(NSRunLoop) runMode:beforeDate:] + 277
5	Foundation	0x00007fffc0b3944a -[NSRunLoop(NSRunLoop) run] + 76
6	AssetCacheLocatorService	0x00000000101ed506f -[AssetCacheLocatorService start] + 626
7	AssetCacheLocatorService	0x00000000101ecf844 main + 71
8	libdyld.dylib	0x00007fffd488a235 start + 1
9	AssetCacheLocatorService	0x0000000000000002

Thread 1 (id: 6735):

0	libsystem_kernel.dylib	0x00007fffd49b134a mach_msg_trap + 10
1	libxpc.dylib	0x00007fffd4ad84d7 xpc_pipe_routine + 232
2	libxpc.dylib	0x00007fffd4ad8361 _xpc_interface_routine + 164
3	libxpc.dylib	0x00007fffd4ad7f14 bootstrap_look_up3 + 193
4	libxpc.dylib	0x00007fffd4ad7e41 bootstrap_look_up2 + 45
5	Metadata	0x00007fffc044666a getPublicPort + 232
6	Metadata	0x00007fffc04461db _MDAccessCopyClientPort + 186
7	Metadata	0x00007fffc044b633 _MDAccessGetMachPort + 11
8	Metadata	0x00007fffc046df7b _DeviceForStoreToken + 238
9	Metadata	0x00007fffc046e3c5 _MDFastPath + 92
10	Metadata	0x00007fffc046e829 __newAttr + 99
11	Metadata	0x00007fffc046e663 MDItemCopyAttribute + 158
12	Metadata	0x00007fffc0458996 __MDItemUpdateData + 1067
13	Metadata	0x00007fffc046f656 __MDItemSetAttributes + 192
14	Metadata	0x00007fffc046fa78 MDItemSetAttribute + 303
15	CarbonCore	0x00007fffbfd32cc CSBackupSetItemExcluded + 568
16	CoreServicesInternal	0x00007fffc0aaac0f9 pathURLPropertyProviderSetValues(__CFURL const*, __FileCache*, __CFString const* const*, void const**, void const**, long, void const*, __CFError**) + 569
17	CoreServicesInternal	0x00007fffc0aa9e80d _FSURLSetResourcePropertyForKey + 179
18	CoreFoundation	0x00007fffbf1abd63 CFURLSetResourcePropertyForKey + 243
19	CoreFoundation	0x00007fffbf1abc2b -[NSURL setResourceValue:forKey:error:] + 187
20	AssetCacheLocatorService	0x00000000101edfddc __49-[AssetCacheLocatorService saveDiskCacheWithTag:]_block_invoke + 181
21	libdispatch.dylib	0x00007fffd485d524 _dispatch_call_block_and_release + 12
22	libdispatch.dylib	0x00007fffd48548fc _dispatch_client_callout + 8
23	libdispatch.dylib	0x00007fffd485686e _dispatch_root_queue_drain + 917
24	libdispatch.dylib	0x00007fffd485648c _dispatch_worker_thread3 + 99

25 libsystem_pthread.dylib 0x00007fffd4aa3616 _pthread_wqthread + 1299
26 libsystem_pthread.dylib 0x00007fffd4aa30f1 start_wqthread + 13

Thread 2 (id: 6736):

0 libsystem_kernel.dylib 0x00007fffd49b944e __workq_kernreturn + 10
1 libsystem_pthread.dylib 0x00007fffd4aa30f1 start_wqthread + 13
2 0x000070000a208ba0

Thread 3 (id: 6737):

0 libsystem_kernel.dylib 0x00007fffd49b944e __workq_kernreturn + 10
1 libsystem_pthread.dylib 0x00007fffd4aa30f1 start_wqthread + 13

Thread 4 (id: 6738):

0 libsystem_blocks.dylib 0x00007fffd48bec00 _Block_object_dispose + 0
1 libsystem_trace.dylib 0x00007fffd4ac7e63 _os_log_impl_stream + 546
2 libsystem_trace.dylib 0x00007fffd4ac7365
_os_log_impl_flatten_and_send + 4127
3 libsystem_trace.dylib 0x00007fffd4ac631d _os_log_impl + 175
4 AssetCacheLocatorService 0x0000000101eee60e -
[AssetCacheLocatorService
slowcateCachingServerWithTimeout:capabilities:affinityID:forceRefresh:callback:tag:
] + 321
5 AssetCacheLocatorService 0x0000000101eedb5d __143-
[AssetCacheLocatorService
locateCachingServersWithTimeout:capabilities:affinityID:autoRefresh:quickMiss:forc
eMiss:callback:callbackQueue:tag:]_block_invoke.1174 + 56
6 libdispatch.dylib 0x00007fffd485d524
_dispatch_call_block_and_release + 12
7 libdispatch.dylib 0x00007fffd48548fc _dispatch_client_callout + 8
8 libdispatch.dylib 0x00007fffd4863196
_dispatch_queue_override_invoke + 743
9 libdispatch.dylib 0x00007fffd48566b5 _dispatch_root_queue_drain +
476
10 libdispatch.dylib 0x00007fffd485648c _dispatch_worker_thread3 + 99
11 libsystem_pthread.dylib 0x00007fffd4aa3616 _pthread_wqthread + 1299
12 libsystem_pthread.dylib 0x00007fffd4aa30f1 start_wqthread + 13

Binary Images:

0x101ec7000 - 0x101f01ff3 com.apple.AssetCacheLocatorService (48.3 -
48.3) <6fd939e9-7c1d-37b8-9db8-8850f5e1d431> /System/Library/
PrivateFrameworks/AssetCacheServices.framework/XPCServices/
AssetCacheLocatorService.xpc/Contents/MacOS/AssetCacheLocatorService
0x7fffbf0a0000 - 0x7fffbf539ff7 com.apple.CoreFoundation (6.9 - 1349.65)
<f79384d1-fa3f-38ca-a847-b2625ebb790e> /System/Library/Frameworks/
CoreFoundation.framework/Versions/A/CoreFoundation
0x7fffbfb8000 - 0x7fffc0293ff7 com.apple.CoreServices.CarbonCore (1159.6 -
1159.6) <08ac074c-965b-3edf-8e45-0707c8de9ead> /System/Library/Frameworks/
CoreServices.framework/Versions/A/Frameworks/CarbonCore.framework/Versions/
A/CarbonCore
0x7fffc043e000 - 0x7fffc04eeffb com.apple.Metadata (10.7.0 - 1075.40)

<f205a001-250d-3d9a-8375-0f7a834c46e6> /System/Library/Frameworks/
CoreServices.framework/Versions/A/Frameworks/Metadata.framework/Versions/A/
Metadata
0x7ffc0b17000 - 0x7ffc0ebdff3 com.apple.Foundation (6.9 - 1349.64)
<49c8da40-9e5b-33f9-b092-f50115b59e95> /System/Library/Frameworks/
Foundation.framework/Versions/C/Foundation
0x7ffcaa8a000 - 0x7ffcaabaff3 com.apple.CoreServicesInternal (276.2 -
276.2) <05eb7d45-dd4c-3a0f-ac63-a0c2a68e6481> /System/Library/
PrivateFrameworks/CoreServicesInternal.framework/Versions/A/
CoreServicesInternal
0x7fffd4853000 - 0x7fffd4884fff libdispatch.dylib (703.50.37)
<d122e712-9593-31ca-bac4-4a54410bf4a0> /usr/lib/system/libdispatch.dylib
0x7fffd4885000 - 0x7fffd488affb libdyld.dylib (433.5) <129d3b44-
fb21-3750-9a68-48b5c3dc632b> /usr/lib/system/libdyld.dylib
0x7fffd48be000 - 0x7fffd48beff7 libsystem_blocks.dylib (67)
<10dc5404-73ab-35b3-a277-a8afecb476eb> /usr/lib/system/libsystem_blocks.dylib
0x7fffd499f000 - 0x7fffd49c1ff7 libsystem_kernel.dylib (3789.51.2)
<fc51d7b0-8292-3f6a-9231-64340b237eb7> /usr/lib/system/libsystem_kernel.dylib
0x7fffd4aa0000 - 0x7fffd4aaaff7 libsystem_pthread.dylib (218.51.1)
<62a84a68-431d-3b54-a7b6-31367ccf2884> /usr/lib/system/libsystem_pthread.dylib
0x7fffd4ab9000 - 0x7fffd4accff7 libsystem_trace.dylib (518.51.1) <e1d540d8-
cc88-3901-92ba-fc4b802fe0e8> /usr/lib/system/libsystem_trace.dylib
0x7fffd4ad3000 - 0x7fffd4afcff7 libxpc.dylib (972.50.27) <abc45890-da23-3a4a-
b50b-1384bd4cbbdf> /usr/lib/system/libxpc.dylib

MetaData: {"build": "Mac OS X 10.12.4 (16E195)", "action": "deny", "target":
["com.apple.metadata.mds.legacy"], "hardware": "Mac", "platform_binary": "yes", "profile
": "unknown", "process": "AssetCacheLocato", "op": "mach-lookup"}
default 16:57:17.370655 +0200 AssetCacheLocatorService
TIC TCP Conn Event [1:0x7f9e21412020]: 1 Err(0)
default 16:57:17.370674 +0200 AssetCacheLocatorService
TIC TCP Conn Connected [1:0x7f9e21412020]: Err(0)
default 16:57:17.370744 +0200 AssetCacheLocatorService
TIC Enabling TLS [1:0x7f9e21412020]
default 16:57:17.526349 +0200 AssetCacheLocatorService
TIC TLS Event [1:0x7f9e21412020]: 2, Pending(0)
default 16:57:17.526444 +0200 AssetCacheLocatorService
TIC TLS Event [1:0x7f9e21412020]: 11, Pending(0)
default 16:57:17.526873 +0200 AssetCacheLocatorService
TIC TLS Event [1:0x7f9e21412020]: 14, Pending(0)
default 16:57:17.527787 +0200 trustd 0x7fecedd22c50 opened /private/
var/db/mds/system/mdsObject.db: 4636 bytes
default 16:57:17.528013 +0200 trustd 0x7fecedd28830 opened /private/
var/db/mds/system/mdsDirectory.db: 50744 bytes
default 16:57:17.528161 +0200 trustd 0x7fecedd242b0 opened /Library/
Keychains/System.keychain: 37732 bytes
default 16:57:17.530338 +0200 trustd 0x7fecedd160e0 opened /System/
Library/Keychains/SystemRootCertificates.keychain: 385940 bytes
default 16:57:17.534775 +0200 trustd Stream client bypassing proxies on
TCP Conn [1:0x7fecef102330]

default 16:57:17.534800 +0200 trustd TCP Conn 0x7fecef102330 started
default 16:57:17.540558 +0200 mds directQueryOpenReply 28674
1795162144 0
default 16:57:17.540603 +0200 mds QueryOpen succeeded (0) for store
<private>
default 16:57:17.540627 +0200 mds directQueryOpenReply 28674
1795162208 0
default 16:57:17.540662 +0200 mds QueryOpen succeeded (0) for store
<private>
default 16:57:17.540687 +0200 mds directQueryOpenReply 28674
1795162112 0
default 16:57:17.540718 +0200 mds QueryOpen succeeded (0) for store
<private>
default 16:57:17.540738 +0200 mds directQueryOpenReply 28674
1795162176 0
default 16:57:17.540767 +0200 mds QueryOpen succeeded (0) for store
<private>
default 16:57:17.540789 +0200 mds directQueryFetchResultsReply 28674
1795162144 0
default 16:57:17.540842 +0200 mds directQueryFetchResultsReply 28674
1795162208 0
default 16:57:17.540907 +0200 mds directQueryFetchResultsReply 28674
1795162112 0
default 16:57:17.540958 +0200 mds directQueryFetchResultsReply 28674
1795162176 0
default 16:57:17.583893 +0200 com.apple.WebKit.WebContent
Current memory footprint: 48 MB
error 16:57:17.584252 +0200 sandboxd SandboxViolation:
AssetCacheLocato(498) deny mach-lookup com.apple.cookiec
Violation: deny mach-lookup com.apple.cookiec
Process: AssetCacheLocato [498]
Path: /System/Library/PrivateFrameworks/AssetCacheServices.framework/
XPCServices/AssetCacheLocatorService.xpc/Contents/MacOS/
AssetCacheLocatorService
Load Address: 0x101ec7000
Identifier: com.apple.AssetCacheLocatorService
Version: 48.3 (48.3)
Code Type: x86_64 (Native)
Parent Process: launchd [1]
Responsible: /System/Library/PrivateFrameworks/
AssetCacheServices.framework/XPCServices/AssetCacheLocatorService.xpc/
Contents/MacOS/AssetCacheLocatorService [498]
User ID: 235

Date/Time: 2017-05-26 16:57:17.338 GMT+2
OS Version: Mac OS X 10.12.4 (16E195)
Report Version: 8

Thread 0 (id: 6734):
0 libsystem_kernel.dylib 0x00007fffd49b134a mach_msg_trap + 10

```

1 CoreFoundation      0x00007fffbf1284e4 __CFRunLoopServiceMachPort
+ 212
2 CoreFoundation      0x00007fffbf127971 __CFRunLoopRun + 1361
3 CoreFoundation      0x00007fffbf1271c4 CFRunLoopRunSpecific + 420
4 Foundation           0x00007fffc0b39572 -[NSRunLoop(NSRunLoop)
runMode:beforeDate:] + 277
5 Foundation           0x00007fffc0b3944a -[NSRunLoop(NSRunLoop)
run] + 76
6 AssetCacheLocatorService 0x00000000101ed506f -
[AssetCacheLocatorService start] + 626
7 AssetCacheLocatorService 0x00000000101ecf844 main + 71
8 libdyld.dylib        0x00007fffd488a235 start + 1
9 AssetCacheLocatorService 0x0000000000000002

```

Thread 1 (id: 6735):

```

0 libsystem_pthread.dylib 0x00007fffd4aa30e4 start_wqthread + 0

```

Thread 2 (id: 6736):

```

0 libsystem_kernel.dylib  0x00007fffd49b134a mach_msg_trap + 10
1 libxpc.dylib             0x00007fffd4ad84d7 xpc_pipe_routine + 232
2 libxpc.dylib             0x00007fffd4ad8361 _xpc_interface_routine + 164
3 libxpc.dylib             0x00007fffd4adb9e _xpc_look_up_endpoint + 192
4 libxpc.dylib             0x00007fffd4adbbca
_xpc_connection_bootstrap_look_up_slow + 329
5 libxpc.dylib             0x00007fffd4adb88b _xpc_connection_init + 651
6 libxpc.dylib             0x00007fffd4adb5f0 _xpc_connection_resume_init + 14
7 libdispatch.dylib        0x00007fffd48548fc _dispatch_client_callout + 8
8 libdispatch.dylib        0x00007fffd486a9a0 _dispatch_queue_serial_drain
+ 896
9 libdispatch.dylib        0x00007fffd485d306 _dispatch_queue_invoke +
1046
10 libdispatch.dylib        0x00007fffd4863020
_dispatch_queue_override_invoke + 369
11 libdispatch.dylib        0x00007fffd48566b5 _dispatch_root_queue_drain +
476
12 libdispatch.dylib        0x00007fffd485648c _dispatch_worker_thread3 + 99
13 libsystem_pthread.dylib  0x00007fffd4aa3616 _pthread_wqthread + 1299
14 libsystem_pthread.dylib  0x00007fffd4aa30f1 start_wqthread + 13

```

Thread 3 (id: 6737):

```

0 CoreFoundation          0x00007fffbf0c9511 CFArrayGetCount + 1
1 CoreFoundation          0x00007fffbf28ced1 -
[_CFXPreferences(PlistSourceAdditions)
withManagedSourceForIdentifier:user:perform:] + 273
2 CoreFoundation          0x00007fffbf0d493d -[CFPrefsSearchListSource
addManagedSourceForIdentifier:user:] + 93
3 CoreFoundation          0x00007fffbf258d46 __108-
[_CFXPreferences(SearchListAdditions)
withSearchListForIdentifier:container:cloudConfigurationURL:perform:]_block_invoke
.256 + 166

```


4	CoreFoundation	0x00007fff25a10f -
	[_CFXPreferences(SearchListAdditions) withSearchLists:] + 79	
5	CoreFoundation	0x00007fff258bf3 -
	[_CFXPreferences(SearchListAdditions)	
	withSearchListForIdentifier:container:cloudConfigurationURL:perform:]_block_invoke	
	+ 259	
6	CoreFoundation	0x00007fff258a89 -
	[_CFXPreferences(SearchListAdditions)	
	withSearchListForIdentifier:container:cloudConfigurationURL:perform:] + 345	
7	CoreFoundation	0x00007fff285a16 -
	[_CFXPreferences	
	copyAppValueForKey:identifier:container:configurationURL:] + 310	
8	CoreFoundation	0x00007fff0e213f
	_CFPreferencesGetAppIntegerValueWithContainer + 63	
9	CFNetwork	0x00007fff263d76
	DiagnosticLogging::userDiagnosticLevel() + 1350	
10	CFNetwork	0x00007fff26493def
	DiagnosticLogging::newMsg(LogFormatter::LineInfo () block_pointer,	
	DiagnosticLogging::Level) + 25	
11	CFNetwork	0x00007fff2635ae
	ExternalStorage::establishConnection(void (unsigned char) block_pointer) + 320	
12	CFNetwork	0x00007fff263412
	ExternalStorage::initialize(__CFString const*, unsigned char, dispatch_queue_s*) +	
	160	
13	CFNetwork	0x00007fff26fcb5
	ExternalHSTSStorage::initialize(__CFDictionary const*) + 89	
14	CFNetwork	0x00007fff26fba2
	__CFHSTSPolicyCreateWithProperties_block_invoke + 58	
15	CFNetwork	0x00007fff26fa92
	HSTSStorage::CopyCacheOrCreate(__CFDictionary const*, HSTSStorage*	
	(__CFDictionary const*) block_pointer) + 52	
16	CFNetwork	0x00007fff26f8cd
	__CFHSTSPolicyCreateWithProperties + 129	
17	CFNetwork	0x00007fff26f820
	__ZNK14StorageSession15copyHSTSStorageEv_block_invoke + 242	
18	libdispatch.dylib	0x00007ffd48548fc
	_dispatch_client_callout + 8	
19	libdispatch.dylib	0x00007ffd48548b9
	dispatch_once_f + 38	
20	CFNetwork	0x00007fff26f72c
	StorageSession::copyHSTSStorage() const + 106	
21	CFNetwork	0x00007fff26f4b1 -
	[__NSCFURLSessionConfiguration copyHSTSPolicy] + 76	
22	CFNetwork	0x00007fff26f3d5
	HTTPProtocol::_createStrictSecurityCompliantCanonicalRequest(__CFURL const*,	
	_CFURLRequest const*, NSURLSession const*) + 117	
23	CFNetwork	0x00007fff26f065
	HTTPProtocol::_createMutableCanonicalRequest(__CFAllocator const*,	
	_CFURLRequest const*, NSURLSession const*, void const*) + 63	
24	CFNetwork	0x00007fff26f007
	HTTPProtocol::_createCanonicalRequest(__CFAllocator const*, _CFURLRequest	
	const*, NSURLSession const*, void const*) + 67	
25	CFNetwork	0x00007fff26ef6f
	+[__NSCFURLProtocol	

canonicalRequestForRequest:task:] + 94
 26 CFNetwork 0x00007fffbe26eac8 -[__NSURLSessionLocal
 _createCanonicalRequestForTask:] + 104
 27 CFNetwork 0x00007fffbe31c1d2 -[__NSURLSessionLocal
 _onqueue_canonicalizeTaskAndCreateConnection:] + 59
 28 CFNetwork 0x00007fffbe26d07e -[__NSCFLocalSessionTask
 _onqueue_completeInitialization] + 67
 29 CFNetwork 0x00007fffbe26cf35 __30-[__NSCFURLSessionTask
 resume]_block_invoke + 35
 30 libdispatch.dylib 0x00007fffd485d524
 _dispatch_call_block_and_release + 12
 31 libdispatch.dylib 0x00007fffd48548fc _dispatch_client_callout + 8
 32 libdispatch.dylib 0x00007fffd486a9a0 _dispatch_queue_serial_drain
 + 896
 33 libdispatch.dylib 0x00007fffd485d306 _dispatch_queue_invoke +
 1046
 34 libdispatch.dylib 0x00007fffd4863020
 _dispatch_queue_override_invoke + 369
 35 libdispatch.dylib 0x00007fffd48566b5 _dispatch_root_queue_drain +
 476
 36 libdispatch.dylib 0x00007fffd485648c _dispatch_worker_thread3 + 99
 37 libsystem_pthread.dylib 0x00007fffd4aa3616 _pthread_wqthread + 1299
 38 libsystem_pthread.dylib 0x00007fffd4aa30f1 start_wqthread + 13

Thread 4 (id: 6738):

0 libsystem_kernel.dylib 0x00007fffd49b944e __workq_kernreturn + 10
 1 libsystem_pthread.dylib 0x00007fffd4aa30f1 start_wqthread + 13

Thread 5 (id: 6740):

0 libsystem_kernel.dylib 0x00007fffd49b944e __workq_kernreturn + 10
 1 libsystem_pthread.dylib 0x00007fffd4aa30f1 start_wqthread + 13

Thread 6 (id: 6744):

0 libsystem_kernel.dylib 0x00007fffd49b944e __workq_kernreturn + 10
 1 libsystem_pthread.dylib 0x00007fffd4aa30f1 start_wqthread + 13

Thread 7 (id: 6745):

0 libsystem_kernel.dylib 0x00007fffd49b944e __workq_kernreturn + 10
 1 libsystem_pthread.dylib 0x00007fffd4aa30f1 start_wqthread + 13

Thread 8 (id: 6747):

0 libsystem_kernel.dylib 0x00007fffd49b944e __workq_kernreturn + 10
 1 libsystem_pthread.dylib 0x00007fffd4aa30f1 start_wqthread + 13

Thread 9 (id: 6748):

0 libsystem_kernel.dylib 0x00007fffd49b944e __workq_kernreturn + 10
 1 libsystem_pthread.dylib 0x00007fffd4aa30f1 start_wqthread + 13

Binary Images:

0x101ec7000 - 0x101f01ff3 com.apple.AssetCacheLocatorService (48.3 -

48.3) <6fd939e9-7c1d-37b8-9db8-8850f5e1d431> /System/Library/
PrivateFrameworks/AssetCacheServices.framework/XPCServices/
AssetCacheLocatorService.xpc/Contents/MacOS/AssetCacheLocatorService
0x7fffbe25f000 - 0x7fffbe639ff7 com.apple.CFNetwork (811.4.18 - 811.4.18)
<9ce329e8-6177-3474-976d-f5c63fc875cd> /System/Library/Frameworks/
CFNetwork.framework/Versions/A/CFNetwork
0x7ffbf0a0000 - 0x7ffbf539ff7 com.apple.CoreFoundation (6.9 - 1349.65)
<f79384d1-fa3f-38ca-a847-b2625ebb790e> /System/Library/Frameworks/
CoreFoundation.framework/Versions/A/CoreFoundation
0x7fffc0b17000 - 0x7fffc0ebdff3 com.apple.Foundation (6.9 - 1349.64)
<49c8da40-9e5b-33f9-b092-f50115b59e95> /System/Library/Frameworks/
Foundation.framework/Versions/C/Foundation
0x7fffd4853000 - 0x7fffd4884fff libdispatch.dylib (703.50.37)
<d122e712-9593-31ca-bac4-4a54410bf4a0> /usr/lib/system/libdispatch.dylib
0x7fffd4885000 - 0x7fffd488affb libdyld.dylib (433.5) <129d3b44-
fb21-3750-9a68-48b5c3dc632b> /usr/lib/system/libdyld.dylib
0x7fffd499f000 - 0x7fffd49c1ff7 libsystem_kernel.dylib (3789.51.2)
<fc51d7b0-8292-3f6a-9231-64340b237eb7> /usr/lib/system/libsystem_kernel.dylib
0x7fffd4aa0000 - 0x7fffd4aaaff7 libsystem_pthread.dylib (218.51.1)
<62a84a68-431d-3b54-a7b6-31367ccf2884> /usr/lib/system/libsystem_pthread.dylib
0x7fffd4ad3000 - 0x7fffd4afc7f7 libxpc.dylib (972.50.27) <abc45890-da23-3a4a-
b50b-1384bd4cbbdf> /usr/lib/system/libxpc.dylib

MetaData: {"build": "Mac OS X 10.12.4 (16E195)", "action": "deny", "target":
["com.apple.cookiecutter"], "hardware": "Mac", "platform_binary": "yes", "profile": "unknown",
process": "AssetCacheLocatorService", "op": "mach-lookup"}

default 16:57:17.587043 +0200 trustd TCP Conn 0x7fecef102330 event 1.
err: 0

default 16:57:17.587075 +0200 trustd TCP Conn 0x7fecef102330
complete. fd: 11, err: 0

default 16:57:17.626262 +0200 trustd TCP Conn 0x7fecef102330
canceled

default 16:57:17.627782 +0200 trustd SecDbBeginTransaction
kSecDbExclusiveTransactionType 0x7fecedc19150

default 16:57:17.627921 +0200 trustd SecDbEndTransaction
kSecDbTransactionWillCommit 0x7fecedc19150

default 16:57:17.628001 +0200 trustd SecDbEndTransaction
kSecDbTransactionWillCommit 0x7fecedc19150 (after notify)

default 16:57:17.628017 +0200 trustd SecDbEndTransaction
kSecDbTransactionDidCommit 0x7fecedc19150

default 16:57:17.629285 +0200 AssetCacheLocatorService
TIC TLS Trust Result [1:0x7f9e21412020]: 0

default 16:57:17.659179 +0200 com.apple.WebKit.WebContent

Current memory footprint: 21 MB

default 16:57:17.706368 +0200 identityservicesd Time since last load:
6127.261939

default 16:57:17.706390 +0200 identityservicesd Cache Time:
3600.000000

default 16:57:17.706420 +0200 identityservicesd (<private>) Bag needs
reloading

```

default    16:57:17.776287 +0200  AssetCacheLocatorService
          TIC TLS Event [1:0x7f9e21412020]: 20, Pending(0)
default    16:57:17.776507 +0200  AssetCacheLocatorService
          TIC TCP Conn Event [1:0x7f9e21412020]: 8 Err(0)
default    16:57:17.776520 +0200  AssetCacheLocatorService
          TIC TLS Handshake Complete [1:0x7f9e21412020]
default    16:57:17.921654 +0200  AssetCacheLocatorService
          TIC TCP Conn Cancel [1:0x7f9e21412020]
default    16:57:17.921703 +0200  AssetCacheLocatorService
          TIC TCP Conn Destroyed [1:0x7f9e21412020]
default    16:57:17.923343 +0200  AssetCacheLocatorService
          #edcb6a0d [AssetCacheLocatorService.queue] found no caching servers
default    16:57:17.923500 +0200  mobileassetd  #edcb6a0d
ACSLocateCachingServer -> [new] newURL (null), advice (null), error (null), elapsed
0.753/10.000
default    16:57:17.923578 +0200  mobileassetd  no local cache available for
asset
error 16:57:17.923589 +0200  AssetCacheLocatorService      error getting store
properties: (268435459) (ipc/send) invalid destination port
error 16:57:17.923608 +0200  AssetCacheLocatorService      unable to get a
dev_t for store 1795162128.
default    16:57:17.923869 +0200  AssetCacheLocatorService
          #6a169984 [AssetCacheLocatorService.queue] early hit: no caching servers
default    16:57:17.924035 +0200  mobileassetd  #6a169984
ACSLocateCachingServer -> [new] newURL (null), advice (null), error (null), elapsed
0.675/10.000
default    16:57:17.924082 +0200  mobileassetd  no local cache available for
asset
default    16:57:17.939586 +0200  mobileassetd  Started downloading URL
http://appldnld.apple.com/ios10.0/031-72107-2016008009-1F1D1C14-5B55-11E6-
B8BB-BCDA464FE3CA/com_apple_MobileAsset_LinguisticData/
fc6ae396ace7d84cd7049f6f8204511494b1c530.zip for client AppleSpell
default    16:57:17.939660 +0200  mobileassetd  start download, asset version :
2512, download size: 86109
default    16:57:17.939703 +0200  mobileassetd  starting download
default    16:57:17.955771 +0200  mobileassetd  Started downloading URL
http://appldnld.apple.com/ios10.0/031-72107-2016008009-1F1D1C14-5B55-11E6-
B8BB-BCDA464FE3CA/com_apple_MobileAsset_LinguisticData/
a76f754b2835fa56689b62d6189696ab82847901.zip for client AppleSpell
default    16:57:17.955878 +0200  mobileassetd  start download, asset version :
2512, download size: 2706074
default    16:57:17.955916 +0200  mobileassetd  starting download
default    16:57:17.955919 +0200  mobileassetd  creating session
default    16:57:17.990325 +0200  nsurlsessiond  Current discretionary status for
<private> is non-discretionary
default    16:57:17.990487 +0200  nsurlsessiond  Enqueueing Task 1 with UUID
<private> for client <private>, session <private>
default    16:57:17.990575 +0200  nsurlsessiond  Task 1 requesting URL
<private>
default    16:57:17.990722 +0200  mobileassetd  NSURLSessionDataTask

```

started, asset version : 2512, download size: 86109
 default 16:57:17.991090 +0200 nsurlsessiond Client <private> resume for task 1
 default 16:57:17.991412 +0200 nsurlsessiond Current discretionary status for <private> is non-discretionary
 default 16:57:17.991540 +0200 nsurlsessiond Enqueueing Task 2 with UUID <private> for client <private>, session <private>
 default 16:57:17.991565 +0200 nsurlsessiond Task 2 requesting URL <private>
 default 16:57:17.991691 +0200 nsurlsessiond TIC TCP [0x0] working for task <private>
 default 16:57:17.991697 +0200 mobileassetd NSURLSessionDataTask started, asset version : 2512, download size: 2706074
 default 16:57:17.991994 +0200 nsurlsessiond Client <private> resume for task 2
 default 16:57:17.992056 +0200 nsurlsessiond CCDS: requirements <private> DASActivityProperties <private>
 default 16:57:17.992132 +0200 nsurlsessiond activity [0x7f9ac4009470] <private> submitted to pool NSURLSessionBackgroundPoolName
 default 16:57:17.992157 +0200 nsurlsessiond SUBMITTING: <private>
 default 16:57:17.992311 +0200 nsurlsessiond TIC [0x7f9ac2652d60]: DAS scheduler submitted activity 0x7f9ac4009470
 default 16:57:17.992419 +0200 nsurlsessiond TIC TCP [0x0] working for task <private>
 default 16:57:17.992619 +0200 DuetHeuristic-BM Submitted Activity: <private>
 default 16:57:17.992736 +0200 DuetHeuristic-BM Start network path monitoring for '<private>'
 default 16:57:17.992737 +0200 nsurlsessiond CCDS: requirements <private> DASActivityProperties <private>
 default 16:57:17.992778 +0200 nsurlsessiond activity [0x7f9ac2410a10] <private> submitted to pool NSURLSessionBackgroundPoolName
 default 16:57:17.992827 +0200 nsurlsessiond SUBMITTING: <private>
 default 16:57:17.992984 +0200 DuetHeuristic-BM <private>:[<private>] sumScores:32.700000, denominator:34.700000, FinalDecision: Can Proceed FinalScore: 0.942363
 default 16:57:17.992991 +0200 nsurlsessiond TIC [0x7f9ac412c210]: DAS scheduler submitted activity 0x7f9ac2410a10
 default 16:57:17.993027 +0200 DuetHeuristic-BM '<private>' DecisionToRun:1 (Bypasses Predictions)
 default 16:57:17.993084 +0200 DuetHeuristic-BM With <private> ...Tasks running in group <private> are 2!
 default 16:57:17.993139 +0200 DuetHeuristic-BM Stop network path monitoring for '<private>'
 default 16:57:17.993185 +0200 DuetHeuristic-BM Running activities : <private>
 default 16:57:17.993336 +0200 nsurlsessiond STARTING: <private>
 default 16:57:17.993355 +0200 nsurlsessiond TIC [0x7f9ac2652d60]: activity 0x7f9ac4009470 start handler called
 default 16:57:17.993384 +0200 nsurlsessiond TIC TCP Conn Start

```

[3:0x7f9ac2652d60]
default 16:57:17.993659 +0200 DuetHeuristic-BM Submitted Activity:
<private>
default 16:57:17.993748 +0200 DuetHeuristic-BM Start network path
monitoring for '<private>'
default 16:57:17.993948 +0200 DuetHeuristic-BM <private>:[
<private> ] sumScores:32.700000, denominator:34.700000, FinalDecision: Can
Proceed FinalScore: 0.942363}
default 16:57:17.993971 +0200 DuetHeuristic-BM '<private>'
DecisionToRun:1 (Bypasses Predictions)
default 16:57:17.994018 +0200 DuetHeuristic-BM With <private> ...Tasks
running in group <private> are 3!
default 16:57:17.994075 +0200 DuetHeuristic-BM Stop network path
monitoring for '<private>'
default 16:57:17.994175 +0200 DuetHeuristic-BM Running activities :
<private>
default 16:57:17.994306 +0200 nsurlsessiond STARTING: <private>
default 16:57:17.994341 +0200 nsurlsessiond TIC [0x7f9ac412c210]: activity
0x7f9ac2410a10 start handler called
default 16:57:17.994366 +0200 nsurlsessiond TIC TCP Conn Start
[4:0x7f9ac412c210]
default 16:57:18.041908 +0200 nsurlsessiond TIC TCP Conn Event
[4:0x7f9ac412c210]: 1 Err(0)
default 16:57:18.041952 +0200 nsurlsessiond TIC TCP Conn Connected
[4:0x7f9ac412c210]: Err(0)
default 16:57:18.041951 +0200 nsurlsessiond TIC TCP Conn Event
[3:0x7f9ac2652d60]: 1 Err(0)
default 16:57:18.041977 +0200 nsurlsessiond TIC TCP Conn Connected
[3:0x7f9ac2652d60]: Err(0)
default 16:57:18.042463 +0200 nsurlsessiond TIC TCP [0x7f9ac2652d60]
working for task <private>
default 16:57:18.042495 +0200 nsurlsessiond TIC TCP [0x7f9ac2652d60]
working for task <private>
default 16:57:18.042587 +0200 nsurlsessiond TIC TCP [0x7f9ac412c210]
working for task <private>
default 16:57:18.042620 +0200 nsurlsessiond TIC TCP [0x7f9ac412c210]
working for task <private>
default 16:57:18.042727 +0200 nsurlsessiond Task 1 for client <private> has
a connection
default 16:57:18.042838 +0200 nsurlsessiond Task 2 for client <private> has
a connection
default 16:57:18.043062 +0200 mobileassetd will send request for
established connection (task=0x7f87cf50c7b0)
default 16:57:18.043208 +0200 mobileassetd file download consumer
0x7f87cf4286d0
default 16:57:18.043245 +0200 mobileassetd will send request for
established connection (task=0x7f87cf403080)
default 16:57:18.043313 +0200 mobileassetd file download consumer
0x7f87cf424d90
default 16:57:18.043691 +0200 nsurlsessiond TIC TCP [0x7f9ac2652d60]

```

```

working for task <private>
default 16:57:18.043726 +0200 nsurlsessiond TIC TCP [0x7f9ac2652d60]
working for task <private>
default 16:57:18.043967 +0200 nsurlsessiond TIC TCP [0x7f9ac412c210]
working for task <private>
default 16:57:18.043998 +0200 nsurlsessiond TIC TCP [0x7f9ac412c210]
working for task <private>
default 16:57:18.072582 +0200 com.apple.WebKit.Networking
TIC TCP Conn Cancel [27:0x7fa644f45de0]
default 16:57:18.072639 +0200 com.apple.WebKit.Networking
TIC TCP Conn Destroyed [27:0x7fa644f45de0]
default 16:57:18.072649 +0200 com.apple.WebKit.Networking
TIC TCP Conn Cancel [37:0x7fa644f69f80]
default 16:57:18.072691 +0200 com.apple.WebKit.Networking
TIC TCP Conn Cancel [38:0x7fa64683f020]
default 16:57:18.072699 +0200 com.apple.WebKit.Networking
TIC TCP Conn Destroyed [37:0x7fa644f69f80]
default 16:57:18.072722 +0200 com.apple.WebKit.Networking
TIC TCP Conn Cancel [39:0x7fa644d09630]
default 16:57:18.072725 +0200 com.apple.WebKit.Networking
TIC TCP Conn Destroyed [38:0x7fa64683f020]
default 16:57:18.072750 +0200 com.apple.WebKit.Networking
TIC TCP Conn Destroyed [39:0x7fa644d09630]
default 16:57:18.072752 +0200 com.apple.WebKit.Networking
TIC TCP Conn Cancel [40:0x7fa644e30f00]
default 16:57:18.072784 +0200 com.apple.WebKit.Networking
TIC TCP Conn Destroyed [40:0x7fa644e30f00]
default 16:57:18.072787 +0200 com.apple.WebKit.Networking
TIC TCP Conn Cancel [65:0x7fa644e6f840]
default 16:57:18.072815 +0200 com.apple.WebKit.Networking
TIC TCP Conn Cancel [64:0x7fa644ec7a40]
default 16:57:18.072819 +0200 com.apple.WebKit.Networking
TIC TCP Conn Destroyed [65:0x7fa644e6f840]
default 16:57:18.072840 +0200 com.apple.WebKit.Networking
TIC TCP Conn Cancel [56:0x7fa644d263f0]
default 16:57:18.072840 +0200 com.apple.WebKit.Networking
TIC TCP Conn Destroyed [64:0x7fa644ec7a40]
default 16:57:18.072870 +0200 com.apple.WebKit.Networking
TIC TCP Conn Destroyed [56:0x7fa644d263f0]
default 16:57:18.296053 +0200 nsurlsessiond Task 1 for client <private>
received response, status code: 200
default 16:57:18.296190 +0200 nsurlsessiond Task 2 for client <private>
received response, status code: 200
default 16:57:18.296439 +0200 mobileassetd receieved response
(task=0x7f87cf50c7b0 status=200)
default 16:57:18.296497 +0200 mobileassetd receieved response
(task=0x7f87cf403080 status=200)
default 16:57:18.300420 +0200 AppleSpell 0x7fdef66ba8a0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef66ba8a0> { count =
2, transaction: 1, voucher = 0x7fdef66bbc50, contents =

```

```

    "Progress" => <dictionary: 0x7fdef66be650> { count = 3, transaction: 0,
voucher = 0x0, contents =
    "OperationProgress" => <double: 0x7fdef665f470>: 0.426576
    "EstimatedTimeRemaining" => <double: 0x7fdef66bb1e0>: 0.000000
    "Operation" => <string: 0x7fdef6621090> { length = 16, contents =
"DownloadingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef66bc030>: 3
}
default 16:57:18.300494 +0200 AppleSpell 0x7fdef985df70 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef985df70> { count =
2, transaction: 1, voucher = 0x7fdef66bbc50, contents =
    "Progress" => <dictionary: 0x7fdef98719c0> { count = 3, transaction: 0,
voucher = 0x0, contents =
    "OperationProgress" => <double: 0x7fdef9884aa0>: 0.007188
    "EstimatedTimeRemaining" => <double: 0x7fdef9811d00>: 0.000000
    "Operation" => <string: 0x7fdef9871870> { length = 16, contents =
"DownloadingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef985d000>: 3
}
default 16:57:18.482046 +0200 AppleSpell 0x7fdef644b7e0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef644b7e0> { count =
2, transaction: 1, voucher = 0x7fdef9b14680, contents =
    "Progress" => <dictionary: 0x7fdef6423cb0> { count = 3, transaction: 0,
voucher = 0x0, contents =
    "OperationProgress" => <double: 0x7fdef645d540>: 0.861373
    "EstimatedTimeRemaining" => <double: 0x7fdef641ad90>: 0.000000
    "Operation" => <string: 0x7fdef642a260> { length = 16, contents =
"DownloadingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef645c980>: 3
}
default 16:57:18.482120 +0200 AppleSpell 0x7fdef67186e0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef67186e0> { count =
2, transaction: 1, voucher = 0x7fdef9b14680, contents =
    "Progress" => <dictionary: 0x7fdef6718840> { count = 3, transaction: 0,
voucher = 0x0, contents =
    "OperationProgress" => <double: 0x7fdef6716610>: 0.023684
    "EstimatedTimeRemaining" => <double: 0x7fdef67183a0>: 0.000000
    "Operation" => <string: 0x7fdef67188f0> { length = 16, contents =
"DownloadingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef6717f80>: 3
}
default 16:57:18.531775 +0200 AppleSpell 0x7fdef644b7e0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef644b7e0> { count =
2, transaction: 1, voucher = 0x7fdef641f340, contents =
    "Progress" => <dictionary: 0x7fdef6423cb0> { count = 3, transaction: 0,
voucher = 0x0, contents =

```



```

        "OperationProgress" => <double: 0x7fdef6464eb0>: 1.000000
        "EstimatedTimeRemaining" => <double: 0x7fdef6467600>: 0.000000
        "Operation" => <string: 0x7fdef641ce50> { length = 16, contents =
"DownloadingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef641ad90>: 3
}
default 16:57:18.531780 +0200 nsurlsessiond Task 1 for client <private>
completed successfully
default 16:57:18.531991 +0200 mobileassetd download completed
(task=0x7f87cf50c7b0 success=1)
default 16:57:18.532261 +0200 mobileassetd download finished, asset
version : 2512, download size: 86109
default 16:57:18.532287 +0200 mobileassetd Stopped downloading URL
http://appldnld.apple.com/ios10.0/031-72107-2016008009-1F1D1C14-5B55-11E6-
B8BB-BCDA464FE3CA/com_apple_MobileAsset_LinguisticData/
fc6ae396ace7d84cd7049f6f8204511494b1c530.zip for client AppleSpell
default 16:57:18.532322 +0200 mobileassetd task is complete
(task=0x7f87cf50c7b0)
default 16:57:18.533922 +0200 AppleSpell 0x7fdef65bf9f0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef65bf9f0> { count =
2, transaction: 1, voucher = 0x7fdef6594a70, contents =
    "Progress" => <dictionary: 0x7fdef6595110> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef6594ea0>: 0.000000
        "EstimatedTimeRemaining" => <double: 0x7fdef65955b0>: -1.000000
        "Operation" => <string: 0x7fdef65c8fe0> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef65887b0>: 3
}
default 16:57:18.534170 +0200 AppleSpell 0x7fdef98719c0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef98719c0> { count =
2, transaction: 1, voucher = 0x7fdef98717c0, contents =
    "Progress" => <dictionary: 0x7fdef98845e0> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef9876510>: 0.761082
        "EstimatedTimeRemaining" => <double: 0x7fdef986a270>: 0.000034
        "Operation" => <string: 0x7fdef98683d0> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef982ff20>: 3
}
default 16:57:18.534233 +0200 AppleSpell 0x7fdef9871910 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef9871910> { count =
2, transaction: 1, voucher = 0x7fdef98717c0, contents =
    "Progress" => <dictionary: 0x7fdef98710b0> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef985d000>: 1.000000
        "EstimatedTimeRemaining" => <double: 0x7fdef986d980>: 0.000000

```

```

        "Operation" => <string: 0x7fdef982f110> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef9884aa0>: 3
}
default 16:57:18.535480 +0200 AppleSpell 0x7fdef66ba8a0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef66ba8a0> { count =
2, transaction: 1, voucher = 0x7fdef66bbc50, contents =
    "Progress" => <dictionary: 0x7fdef66be830> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef6657ef0>: -1.000000
        "EstimatedTimeRemaining" => <double: 0x7fdef66bb1e0>: -1.000000
        "Operation" => <string: 0x7fdef6658c30> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef66bc030>: 3
}
default 16:57:18.536306 +0200 AppleSpell 0x7fdef66ba8a0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef66ba8a0> { count =
2, transaction: 1, voucher = 0x7fdef66bbc50, contents =
    "Progress" => <dictionary: 0x7fdef66be830> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef665f470>: -1.000000
        "EstimatedTimeRemaining" => <double: 0x7fdef66bb1e0>: -1.000000
        "Operation" => <string: 0x7fdef6658c30> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef66bc030>: 3
}
default 16:57:18.536978 +0200 AppleSpell 0x7fdef644b7e0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef644b7e0> { count =
2, transaction: 1, voucher = 0x7fdef641f340, contents =
    "Progress" => <dictionary: 0x7fdef6423cb0> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef641c0d0>: 0.000276
        "EstimatedTimeRemaining" => <double: 0x7fdef645c980>: 6.016047
        "Operation" => <string: 0x7fdef641ce50> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef6467600>: 3
}
default 16:57:18.538754 +0200 AppleSpell 0x7fdef66ba8a0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef66ba8a0> { count =
2, transaction: 1, voucher = 0x7fdef66bbc50, contents =
    "Progress" => <dictionary: 0x7fdef66be830> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef6657ef0>: 0.260081
        "EstimatedTimeRemaining" => <double: 0x7fdef66bb1e0>: 0.009849
        "Operation" => <string: 0x7fdef66bbaa0> { length = 16, contents =
"UnarchivingAsset" }
    }

```

```

    }
    "_IPC_TYPE" => <uint64: 0x7fdef66bc030>: 3
}
default 16:57:18.539036 +0200 AppleSpell 0x7fdef65a4510 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef65a4510> { count =
2, transaction: 1, voucher = 0x7fdef6594a70, contents =
    "Progress" => <dictionary: 0x7fdef6595110> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef6502ba0>: 0.519887
        "EstimatedTimeRemaining" => <double: 0x7fdef65a84e0>: 0.003410
        "Operation" => <string: 0x7fdef65c9030> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef65955b0>: 3
}
default 16:57:18.539182 +0200 AppleSpell 0x7fdef644b7e0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef644b7e0> { count =
2, transaction: 1, voucher = 0x7fdef641f340, contents =
    "Progress" => <dictionary: 0x7fdef6423cb0> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef6417a10>: 0.779693
        "EstimatedTimeRemaining" => <double: 0x7fdef645c980>: 0.001103
        "Operation" => <string: 0x7fdef641ce50> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef6467600>: 3
}
default 16:57:18.539473 +0200 AppleSpell 0x7fdef66ba8a0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef66ba8a0> { count =
2, transaction: 1, voucher = 0x7fdef66bbc50, contents =
    "Progress" => <dictionary: 0x7fdef66be830> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef66bc030>: 0.934833
        "EstimatedTimeRemaining" => <double: 0x7fdef665ec90>: 0.000291
        "Operation" => <string: 0x7fdef66bbaa0> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef66bb1e0>: 3
}
default 16:57:18.540362 +0200 AppleSpell 0x7fdef66ba8a0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef66ba8a0> { count =
2, transaction: 1, voucher = 0x7fdef66bbc50, contents =
    "Progress" => <dictionary: 0x7fdef66be830> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef6657ef0>: 0.998420
        "EstimatedTimeRemaining" => <double: 0x7fdef665ec90>: 0.000008
        "Operation" => <string: 0x7fdef66bf600> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef66bb1e0>: 3

```

```

}
default 16:57:18.542747 +0200 AppleSpell 0x7fdef644b7e0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef644b7e0> { count =
2, transaction: 1, voucher = 0x7fdef641f340, contents =
    "Progress" => <dictionary: 0x7fdef6423cb0> { count = 2, transaction: 0,
voucher = 0x0, contents =
    "OperationProgress" => <double: 0x7fdef641c0d0>: -1.000000
    "Operation" => <string: 0x7fdef641ce50> { length = 18, contents =
"OperationCompleted" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef6417a10>: 3
}
default 16:57:18.542879 +0200 mobileassetd 0x7ffdd7a6ca0 Client
connection: XPC_TYPE_ERROR Connection invalid <error: 0x7ffdd7a6ca0> { count
= 1, transaction: 0, voucher = 0x0, contents =
    "XPCErrorDescription" => <string: 0x7ffdd7a6f18> { length = 18, contents =
"Connection invalid" }
}
default 16:57:18.542901 +0200 mobileassetd Client connection invalid
(Connection invalid); terminating connection
error 16:57:18.543881 +0200 sandboxd SandboxViolation: mobileassetd(51) deny
file-read-data /
Violation: deny file-read-data /
Process: mobileassetd [51]
Path: /usr/libexec/mobileassetd
Load Address: 0x10187f000
Identifier: mobileassetd
Version: ??? (???)
Code Type: x86_64 (Native)
Parent Process: launchd [1]
Responsible: /usr/libexec/mobileassetd [51]
User ID: 0

```

Date/Time: 2017-05-26 16:57:18.536 GMT+2
 OS Version: Mac OS X 10.12.4 (16E195)
 Report Version: 8

Thread 0 (id: 587):

```

0 libsystem_kernel.dylib 0x00007fffd49b134a mach_msg_trap + 10
1 CoreFoundation 0x00007fffbf1284e4 __CFRunLoopServiceMachPort
+ 212
2 CoreFoundation 0x00007fffbf127971 __CFRunLoopRun + 1361
3 CoreFoundation 0x00007fffbf1271c4 CFRunLoopRunSpecific + 420
4 CoreFoundation 0x00007fffbf166c31 CFRunLoopRun + 97
5 mobileassetd 0x0000000010188fed5
6 libdyld.dylib 0x00007fffd488a235 start + 1
7 mobileassetd 0x0000000000000001

```

Thread 1 (id: 2060):

```

0 libsystem_kernel.dylib 0x00007fffd49b8a86 __open_nocancel + 10

```

1	libsystem_c.dylib	0x00007fffd48e9db5 __private_getcwd + 142
2	CoreFoundation	0x00007fffbf13190c _CFGetCurrentDirectory + 12
3	CoreFoundation	0x00007fffbf0afc7c _CFURLCreateWithFilePath + 3084
4	Foundation	0x00007fffc0b4a317 -[NSURL(NSURL) initWithURLWithPath:] + 496
5	Foundation	0x00007fffc0b4a111 +[NSURL(NSURL) fileURLWithPath:] + 45
6	mobileassetd	0x000000010188165d
7	Bom	0x00007fffc8a57d11 _copyDir + 193
8	Bom	0x00007fffc8a5aeb0 _copyFromPKZip + 1732
9	Bom	0x00007fffc8a50523 BOMCopierCopyWithOptions + 7395
10	mobileassetd	0x0000000101881229
11	mobileassetd	0x0000000101899394
12	libdispatch.dylib	0x00007fffd485d524 _dispatch_call_block_and_release + 12
13	libdispatch.dylib	0x00007fffd48548fc _dispatch_client_callout + 8
14	libdispatch.dylib	0x00007fffd485686e _dispatch_root_queue_drain + 917
15	libdispatch.dylib	0x00007fffd485648c _dispatch_worker_thread3 + 99
16	libsystem_pthread.dylib	0x00007fffd4aa3616 _pthread_wqthread + 1299
17	libsystem_pthread.dylib	0x00007fffd4aa30f1 start_wqthread + 13

Thread 2 (id: 6707):

0	libsystem_kernel.dylib	0x00007fffd49b944e __workq_kernreturn + 10
1	libsystem_pthread.dylib	0x00007fffd4aa30f1 start_wqthread + 13

Thread 3 (id: 6708):

0	libsystem_kernel.dylib	0x00007fffd49b944e __workq_kernreturn + 10
1	libsystem_pthread.dylib	0x00007fffd4aa30f1 start_wqthread + 13

Thread 4 (id: 6721):

0	libsystem_kernel.dylib	0x00007fffd49b944e __workq_kernreturn + 10
1	libsystem_pthread.dylib	0x00007fffd4aa30f1 start_wqthread + 13

Thread 5 (id: 6723):

0	libsystem_kernel.dylib	0x00007fffd49b944e __workq_kernreturn + 10
1	libsystem_pthread.dylib	0x00007fffd4aa30f1 start_wqthread + 13

Binary Images:

```

0x10187f000 - 0x1018bcff3 mobileassetd (339.51.1)
<6a3d3a42-308a-3b5f-b41c-98ac04961bfc> /usr/libexec/mobileassetd
0x7fffbf0a0000 - 0x7fffbf539ff7 com.apple.CoreFoundation (6.9 - 1349.65)
<f79384d1-fa3f-38ca-a847-b2625ebb790e> /System/Library/Frameworks/
CoreFoundation.framework/Versions/A/CoreFoundation
0x7fffc0b17000 - 0x7fffc0ebdff3 com.apple.Foundation (6.9 - 1349.64)
<49c8da40-9e5b-33f9-b092-f50115b59e95> /System/Library/Frameworks/
Foundation.framework/Versions/C/Foundation
0x7fffc8a41000 - 0x7fffc8a7eff7 com.apple.bom (14.0 - 193.8)
<bfb3ff63-6ab4-3f52-8525-87e88a5000f4> /System/Library/PrivateFrameworks/

```

Bom.framework/Versions/A/Bom

```
0x7fffd4853000 - 0x7fffd4884fff libdispatch.dylib (703.50.37)
<d122e712-9593-31ca-bac4-4a54410bf4a0> /usr/lib/system/libdispatch.dylib
0x7fffd4885000 - 0x7fffd488affb libdyld.dylib (433.5) <129d3b44-
fb21-3750-9a68-48b5c3dc632b> /usr/lib/system/libdyld.dylib
0x7fffd48bf000 - 0x7fffd494cfef libsystem_c.dylib (1158.50.2)
<b03f8915-1e9b-3c84-aed5-68e2e0031630> /usr/lib/system/libsystem_c.dylib
0x7fffd499f000 - 0x7fffd49c1ff7 libsystem_kernel.dylib (3789.51.2)
<fc51d7b0-8292-3f6a-9231-64340b237eb7> /usr/lib/system/libsystem_kernel.dylib
0x7fffd4aa0000 - 0x7fffd4aaaff7 libsystem_pthread.dylib (218.51.1)
<62a84a68-431d-3b54-a7b6-31367ccf2884> /usr/lib/system/libsystem_pthread.dylib
```

MetaData: {"build":"Mac OS X 10.12.4 (16E195)","action":"deny","target":
[""],"hardware":"Mac","platform_binary":"no","profile":"unknown","process":"mobileas
setd","op":"file-read-data"}

error 16:57:18.544005 +0200 sandboxd SandboxViolation: mobileassetd(51) deny
file-read-data / [Duplicate; no report will be generated.]

error 16:57:18.544090 +0200 sandboxd SandboxViolation: mobileassetd(51) deny
file-read-data / [Duplicate; no report will be generated.]

error 16:57:18.544187 +0200 sandboxd SandboxViolation: mobileassetd(51) deny
file-read-data / [Duplicate; no report will be generated.]

error 16:57:18.544273 +0200 sandboxd SandboxViolation: mobileassetd(51) deny
file-read-data / [Duplicate; no report will be generated.]

error 16:57:18.544349 +0200 sandboxd SandboxViolation: mobileassetd(51) deny
file-read-data / [Duplicate; no report will be generated.]

default 16:57:18.556128 +0200 mds directQueryOpenReply 53249
1795162144 0

default 16:57:18.556186 +0200 mds QueryOpen succeeded (0) for store
<private>

default 16:57:18.556299 +0200 mds directQueryOpenReply 53250
1795162144 0

default 16:57:18.556369 +0200 mds QueryOpen succeeded (0) for store
<private>

default 16:57:18.559996 +0200 mds directQueryFetchResultsReply 53249
1795162144 0

default 16:57:18.560227 +0200 mds directQueryFetchResultsReply 53250
1795162144 0

default 16:57:18.752371 +0200 CalendarAgent TIC TCP Conn Cancel
[1:0x7f940e327640]

default 16:57:18.752402 +0200 CalendarAgent TIC TCP Conn Cancel
[3:0x7f940e114050]

default 16:57:18.752437 +0200 CalendarAgent TIC TCP Conn Destroyed
[1:0x7f940e327640]

default 16:57:18.752458 +0200 CalendarAgent TIC TCP Conn Cancel
[2:0x7f940e224330]

default 16:57:18.752465 +0200 CalendarAgent TIC TCP Conn Destroyed
[3:0x7f940e114050]

default 16:57:18.752505 +0200 CalendarAgent TIC TCP Conn Destroyed
[2:0x7f940e224330]

default 16:57:18.781517 +0200 AppleSpell 0x7fdef66bac50 Download

```

listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef66bac50> { count =
2, transaction: 1, voucher = 0x7fdef66bbc50, contents =
    "Progress" => <dictionary: 0x7fdef66b5d10> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef66b82b0>: 0.053484
        "EstimatedTimeRemaining" => <double: 0x7fdef66bc030>: 0.000000
        "Operation" => <string: 0x7fdef66b5dc0> { length = 16, contents =
"DownloadingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef6657ef0>: 3
}
default 16:57:18.933165 +0200 AppleSpell 0x7fdef986d2f0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef986d2f0> { count =
2, transaction: 1, voucher = 0x7fdef98706d0, contents =
    "Progress" => <dictionary: 0x7fdef644b7e0> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef645c980>: 0.077962
        "EstimatedTimeRemaining" => <double: 0x7fdef6417a10>: 0.000000
        "Operation" => <string: 0x7fdef641cf10> { length = 16, contents =
"DownloadingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef6464eb0>: 3
}
default 16:57:19.018576 +0200 AppleSpell 0x7fdef66bac50 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef66bac50> { count =
2, transaction: 1, voucher = 0x7fdef66bbc50, contents =
    "Progress" => <dictionary: 0x7fdef66b5d10> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef665e210>: 0.104037
        "EstimatedTimeRemaining" => <double: 0x7fdef66b82b0>: 8.611993
        "Operation" => <string: 0x7fdef66b5dc0> { length = 16, contents =
"DownloadingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef6657ef0>: 3
}
default 16:57:19.075885 +0200 nsurlsessiond TIC TCP Conn Cancel
[2:0x7f9ac262c6f0]
default 16:57:19.075972 +0200 nsurlsessiond TIC TCP [0x7f9ac262c6f0]
completing activity 0x7f9ac263a270
default 16:57:19.076430 +0200 AppleSpell 0x7fdef65bf9f0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef65bf9f0> { count =
2, transaction: 1, voucher = 0x7fdef65c8f70, contents =
    "Progress" => <dictionary: 0x7fdef6549070> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef65a3760>: 0.128515
        "EstimatedTimeRemaining" => <double: 0x7fdef65a8580>: 6.781195
        "Operation" => <string: 0x7fdef65bdc20> { length = 16, contents =
"DownloadingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef6502ba0>: 3

```

```

}
default 16:57:19.076448 +0200 DuetHeuristic-BM COMPLETED <private>!
default 16:57:19.076495 +0200 DuetHeuristic-BM Stop network path
monitoring for '<private>'
default 16:57:19.076542 +0200 DuetHeuristic-BM NO LONGER RUNNING
<private> ...Tasks running in group [<private>] are 2!
default 16:57:19.128596 +0200 AppleSpell 0x7fdef641ee10 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef641ee10> { count =
2, transaction: 1, voucher = 0x7fdef6423cb0, contents =
    "Progress" => <dictionary: 0x7fdef645c780> { count = 3, transaction: 0,
voucher = 0x0, contents =
    "OperationProgress" => <double: 0x7fdef645d540>: 0.152993
    "EstimatedTimeRemaining" => <double: 0x7fdef6417a10>: 5.536237
    "Operation" => <string: 0x7fdef6419350> { length = 16, contents =
"DownloadingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef6464eb0>: 3
}
default 16:57:19.166265 +0200 AppleSpell 0x7fdef66bac50 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef66bac50> { count =
2, transaction: 1, voucher = 0x7fdef66bc000, contents =
    "Progress" => <dictionary: 0x7fdef66b5d10> { count = 3, transaction: 0,
voucher = 0x0, contents =
    "OperationProgress" => <double: 0x7fdef6657ef0>: 0.178004
    "EstimatedTimeRemaining" => <double: 0x7fdef66bb1e0>: 4.617863
    "Operation" => <string: 0x7fdef6621090> { length = 16, contents =
"DownloadingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef66b82b0>: 3
}
default 16:57:19.258610 +0200 AppleSpell 0x7fdef66bac50 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef66bac50> { count =
2, transaction: 1, voucher = 0x7fdef66bc000, contents =
    "Progress" => <dictionary: 0x7fdef66b5d10> { count = 3, transaction: 0,
voucher = 0x0, contents =
    "OperationProgress" => <double: 0x7fdef665e210>: 0.205675
    "EstimatedTimeRemaining" => <double: 0x7fdef66bb1e0>: 3.862046
    "Operation" => <string: 0x7fdef66b5dc0> { length = 16, contents =
"DownloadingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef66b82b0>: 3
}
default 16:57:19.332463 +0200 AppleSpell 0x7fdef9871cf0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef9871cf0> { count =
2, transaction: 1, voucher = 0x7fdef98706d0, contents =
    "Progress" => <dictionary: 0x7fdef9871ec0> { count = 3, transaction: 0,
voucher = 0x0, contents =
    "OperationProgress" => <double: 0x7fdef9871f70>: 0.232282
    "EstimatedTimeRemaining" => <double: 0x7fdef982ff20>: 3.305121
    "Operation" => <string: 0x7fdef9871bb0> { length = 16, contents =

```



```

"DownloadingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef9841f50>: 3
}
default 16:57:19.368679 +0200 DuettHeuristic-BM Submitted Activity:
<private>
default 16:57:19.368727 +0200 DuettHeuristic-BM Activity <private> start
beyond the 18 hour interval
default 16:57:19.422514 +0200 AppleSpell 0x7fdef66bac50 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef66bac50> { count =
2, transaction: 1, voucher = 0x7fdef66bc000, contents =
    "Progress" => <dictionary: 0x7fdef66b5d10> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef6657ef0>: 0.259953
        "EstimatedTimeRemaining" => <double: 0x7fdef66bb1e0>: 2.846855
        "Operation" => <string: 0x7fdef6658c30> { length = 16, contents =
"DownloadingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef66b82b0>: 3
}
default 16:57:19.451665 +0200 DockUSING ANON Listener
default 16:57:19.451749 +0200 Dockentitlements: <private>
default 16:57:19.451772 +0200 Dockentitlements: <private>
default 16:57:19.451790 +0200 Dockentitlements: <private>
default 16:57:19.451808 +0200 Dockentitlements: <private>
default 16:57:19.451844 +0200 Dockgot a connection for:
com.apple.cache_delete
default 16:57:19.451956 +0200 Dockgot proxy: <private> for service:
com.apple.cache_delete
default 16:57:19.452154 +0200 deleted listener: <private>
default 16:57:19.452179 +0200 deleted Skipping entitlement check...
default 16:57:19.452384 +0200 deleted Client checkin for service
com.apple.desktoppicture.cache-delete
default 16:57:19.452409 +0200 deleted Skipping entitlement check...
default 16:57:19.452467 +0200 deleted Setting up anonymous service
com.apple.desktoppicture.cache-delete
default 16:57:19.452492 +0200 deleted Establishing heartbeat to service
com.apple.desktoppicture.cache-delete
default 16:57:19.452570 +0200 deleted Pinging heartbeat connection for
service com.apple.desktoppicture.cache-delete
default 16:57:19.452686 +0200 Docklistener: <private>
default 16:57:19.452704 +0200 DockSkipping entitlement check...
default 16:57:19.452815 +0200 DockPING
default 16:57:19.452876 +0200 deleted Heartbeat established for service
com.apple.desktoppicture.cache-delete
default 16:57:19.452906 +0200 deleted Added anonymous service
com.apple.desktoppicture.cache-delete
default 16:57:19.453041 +0200 Docksetting target uid to: 501 for service:
com.apple.cache_delete
default 16:57:19.453066 +0200 DockRegistered: <private>, result: 0

```

```

default    16:57:19.453104 +0200   deleted    newConnection invalidated
default    16:57:19.453069 +0200   Dockconnection invalidated
default    16:57:19.492164 +0200   AppleSpell  0x7fdef65a4510 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef65a4510> { count =
2, transaction: 1, voucher = 0x7fdef65c8f70, contents =
    "Progress" => <dictionary: 0x7fdef654a0a0> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef654a030>: 0.286027
        "EstimatedTimeRemaining" => <double: 0x7fdef6591e20>: 2.496170
        "Operation" => <string: 0x7fdef65a44b0> { length = 16, contents =
"DownloadingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef6594ea0>: 3
}
default    16:57:19.554410 +0200   AppleSpell  0x7fdef986a770 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef986a770> { count =
2, transaction: 1, voucher = 0x7fdef98706d0, contents =
    "Progress" => <dictionary: 0x7fdef9871ec0> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef9871f70>: 0.310506
        "EstimatedTimeRemaining" => <double: 0x7fdef98190c0>: 2.220554
        "Operation" => <string: 0x7fdef986cf50> { length = 16, contents =
"DownloadingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef982f630>: 3
}
default    16:57:19.589442 +0200   AppleSpell  0x7fdef986d2f0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef986d2f0> { count =
2, transaction: 1, voucher = 0x7fdef98706d0, contents =
    "Progress" => <dictionary: 0x7fdef9871ec0> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef9871f70>: 0.335516
        "EstimatedTimeRemaining" => <double: 0x7fdef984f020>: 1.980484
        "Operation" => <string: 0x7fdef986cf50> { length = 16, contents =
"DownloadingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef986d980>: 3
}
default    16:57:19.638061 +0200   AppleSpell  0x7fdef641ee10 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef641ee10> { count =
2, transaction: 1, voucher = 0x7fdef6423cb0, contents =
    "Progress" => <dictionary: 0x7fdef645c780> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef645c980>: 0.359994
        "EstimatedTimeRemaining" => <double: 0x7fdef6417a10>: 1.777822
        "Operation" => <string: 0x7fdef6419350> { length = 16, contents =
"DownloadingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef6464eb0>: 3
}

```

```

default    16:57:19.689938 +0200  AppleSpell    0x7fdef9871cf0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef9871cf0> { count =
2, transaction: 1, voucher = 0x7fdef98706d0, contents =
    "Progress" => <dictionary: 0x7fdef9871ec0> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef9871f70>: 0.395647
        "EstimatedTimeRemaining" => <double: 0x7fdef9873f60>: 1.527503
        "Operation" => <string: 0x7fdef982f110> { length = 16, contents =
"DownloadingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef9841f50>: 3
}
default    16:57:19.743910 +0200  AppleSpell    0x7fdef66bac50 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef66bac50> { count =
2, transaction: 1, voucher = 0x7fdef66bc000, contents =
    "Progress" => <dictionary: 0x7fdef66b5d10> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef665e210>: 0.420126
        "EstimatedTimeRemaining" => <double: 0x7fdef66bb1e0>: 1.380240
        "Operation" => <string: 0x7fdef66bbaa0> { length = 16, contents =
"DownloadingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef66b82b0>: 3
}
default    16:57:19.790887 +0200  AppleSpell    0x7fdef986a770 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef986a770> { count =
2, transaction: 1, voucher = 0x7fdef9871170, contents =
    "Progress" => <dictionary: 0x7fdef9871ec0> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef9871f70>: 0.444604
        "EstimatedTimeRemaining" => <double: 0x7fdef9811d00>: 1.249193
        "Operation" => <string: 0x7fdef986cf50> { length = 16, contents =
"DownloadingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef982f630>: 3
}
default    16:57:19.829971 +0200  AppleSpell    0x7fdef986a770 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef986a770> { count =
2, transaction: 1, voucher = 0x7fdef98706d0, contents =
    "Progress" => <dictionary: 0x7fdef98763f0> { count = 3, transaction: 0, voucher
= 0x0, contents =
        "OperationProgress" => <double: 0x7fdef98764a0>: 0.469082
        "EstimatedTimeRemaining" => <double: 0x7fdef9873f60>: 1.131823
        "Operation" => <string: 0x7fdef986cf50> { length = 16, contents =
"DownloadingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef986f590>: 3
}
default    16:57:19.884206 +0200  AppleSpell    0x7fdef9871cf0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef9871cf0> { count =

```

```

2, transaction: 1, voucher = 0x7fdef98706d0, contents =
  "Progress" => <dictionary: 0x7fdef98763f0> { count = 3, transaction: 0, voucher
= 0x0, contents =
    "OperationProgress" => <double: 0x7fdef98764a0>: 0.493560
    "EstimatedTimeRemaining" => <double: 0x7fdef985d000>: 1.026094
    "Operation" => <string: 0x7fdef986cf50> { length = 16, contents =
"DownloadingAsset" }
  }
  "_IPC_TYPE" => <uint64: 0x7fdef986d980>: 3
}
default 16:57:19.918512 +0200 AppleSpell 0x7fdef641ee10 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef641ee10> { count =
2, transaction: 1, voucher = 0x7fdef6423cb0, contents =
  "Progress" => <dictionary: 0x7fdef645ba60> { count = 3, transaction: 0,
voucher = 0x0, contents =
    "OperationProgress" => <double: 0x7fdef645e500>: 0.518039
    "EstimatedTimeRemaining" => <double: 0x7fdef641ad90>: 0.930358
    "Operation" => <string: 0x7fdef645bb10> { length = 16, contents =
"DownloadingAsset" }
  }
  "_IPC_TYPE" => <uint64: 0x7fdef6417a10>: 3
}
default 16:57:19.954588 +0200 AppleSpell 0x7fdef66bac50 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef66bac50> { count =
2, transaction: 1, voucher = 0x7fdef66bc000, contents =
  "Progress" => <dictionary: 0x7fdef66aa730> { count = 3, transaction: 0,
voucher = 0x0, contents =
    "OperationProgress" => <double: 0x7fdef665e210>: 0.542517
    "EstimatedTimeRemaining" => <double: 0x7fdef6657ef0>: 0.843260
    "Operation" => <string: 0x7fdef66bbaa0> { length = 16, contents =
"DownloadingAsset" }
  }
  "_IPC_TYPE" => <uint64: 0x7fdef665ec90>: 3
}
default 16:57:19.956741 +0200 storeassetd TIC TCP Conn Cancel
[1:0x7f8410e0eef0]
default 16:57:19.981826 +0200 AppleSpell 0x7fdef66bac50 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef66bac50> { count =
2, transaction: 1, voucher = 0x7fdef66bc000, contents =
  "Progress" => <dictionary: 0x7fdef66aa730> { count = 3, transaction: 0,
voucher = 0x0, contents =
    "OperationProgress" => <double: 0x7fdef66b82b0>: 0.566995
    "EstimatedTimeRemaining" => <double: 0x7fdef6657ef0>: 0.763683
    "Operation" => <string: 0x7fdef66aa7e0> { length = 16, contents =
"DownloadingAsset" }
  }
  "_IPC_TYPE" => <uint64: 0x7fdef665ec90>: 3
}
default 16:57:20.016395 +0200 TextEdit warning: <NSRemoteView:
0x60800013ad60> determined it was necessary to configure <NSVBSavePanel:

```

```

0x7f92ed55eba0> to support remote view vibrancy
default 16:57:20.017370 +0200 AppleSpell 0x7fdef65bf9f0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef65bf9f0> { count =
2, transaction: 1, voucher = 0x7fdef6423cb0, contents =
    "Progress" => <dictionary: 0x7fdef6549070> { count = 3, transaction: 0,
voucher = 0x0, contents =
    "OperationProgress" => <double: 0x7fdef65bdcf0>: 0.591473
    "EstimatedTimeRemaining" => <double: 0x7fdef65a3760>: 1.381386
    "Operation" => <string: 0x7fdef65bdc20> { length = 16, contents =
"DownloadingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef65a8580>: 3
}
default 16:57:20.050310 +0200 nsurlsessiond TIC TCP Conn Cancel
[3:0x7f9ac2652d60]
default 16:57:20.050341 +0200 nsurlsessiond TIC TCP [0x7f9ac2652d60]
completing activity 0x7f9ac4009470
default 16:57:20.050725 +0200 AppleSpell 0x7fdef641ee10 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef641ee10> { count =
2, transaction: 1, voucher = 0x7fdef6423cb0, contents =
    "Progress" => <dictionary: 0x7fdef645c780> { count = 3, transaction: 0,
voucher = 0x0, contents =
    "OperationProgress" => <double: 0x7fdef6464eb0>: 0.615952
    "EstimatedTimeRemaining" => <double: 0x7fdef645d540>: 1.247008
    "Operation" => <string: 0x7fdef645c830> { length = 16, contents =
"DownloadingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef645e500>: 3
}
default 16:57:20.050815 +0200 DuetHeuristic-BM COMPLETED <private>!
default 16:57:20.050840 +0200 DuetHeuristic-BM Stop network path
monitoring for '<private>'
default 16:57:20.050882 +0200 DuetHeuristic-BM NO LONGER RUNNING
<private> ...Tasks running in group [<private>] are 1!
default 16:57:20.081822 +0200 AppleSpell 0x7fdef66bac50 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef66bac50> { count =
2, transaction: 1, voucher = 0x7fdef66bbc50, contents =
    "Progress" => <dictionary: 0x7fdef66aa730> { count = 3, transaction: 0,
voucher = 0x0, contents =
    "OperationProgress" => <double: 0x7fdef665ec90>: 0.640430
    "EstimatedTimeRemaining" => <double: 0x7fdef665f470>: 1.122902
    "Operation" => <string: 0x7fdef6621090> { length = 16, contents =
"DownloadingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef66b82b0>: 3
}
default 16:57:20.133864 +0200 AppleSpell 0x7fdef65a4510 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef65a4510> { count =
2, transaction: 1, voucher = 0x7fdef6594a70, contents =
    "Progress" => <dictionary: 0x7fdef654a0a0> { count = 3, transaction: 0,

```

```

voucher = 0x0, contents =
    "OperationProgress" => <double: 0x7fdef6595820>: 0.664908
    "EstimatedTimeRemaining" => <double: 0x7fdef65a3760>: 1.007934
    "Operation" => <string: 0x7fdef65bdc20> { length = 16, contents =
"DownloadingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef65a8580>: 3
}
default 16:57:20.143888 +0200 opendiroryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default 16:57:20.168607 +0200 AppleSpell 0x7fdef66bac50 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef66bac50> { count =
2, transaction: 1, voucher = 0x7fdef66bbc50, contents =
    "Progress" => <dictionary: 0x7fdef66aa730> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef66bb1e0>: 0.689387
        "EstimatedTimeRemaining" => <double: 0x7fdef665f470>: 0.901130
        "Operation" => <string: 0x7fdef66aa7e0> { length = 16, contents =
"DownloadingAsset" }
        }
        "_IPC_TYPE" => <uint64: 0x7fdef66b82b0>: 3
    }
}
default 16:57:20.195933 +0200 AppleSpell 0x7fdef9916840 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef9916840> { count =
2, transaction: 1, voucher = 0x7fdef9917720, contents =
    "Progress" => <dictionary: 0x7fdef99157f0> { count = 3, transaction: 0, voucher
= 0x0, contents =
        "OperationProgress" => <double: 0x7fdef99158a0>: 0.713865
        "EstimatedTimeRemaining" => <double: 0x7fdef9907470>: 0.801651
        "Operation" => <string: 0x7fdef9913a70> { length = 16, contents =
"DownloadingAsset" }
        }
        "_IPC_TYPE" => <uint64: 0x7fdef9905e80>: 3
    }
}
default 16:57:20.224655 +0200 AppleSpell 0x7fdef986d2f0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef986d2f0> { count =
2, transaction: 1, voucher = 0x7fdef98706d0, contents =
    "Progress" => <dictionary: 0x7fdef98763f0> { count = 3, transaction: 0, voucher
= 0x0, contents =
        "OperationProgress" => <double: 0x7fdef98764a0>: 0.738343
        "EstimatedTimeRemaining" => <double: 0x7fdef984f020>: 0.708768
        "Operation" => <string: 0x7fdef986f530> { length = 16, contents =
"DownloadingAsset" }
        }
        "_IPC_TYPE" => <uint64: 0x7fdef98190c0>: 3
    }
}
default 16:57:20.246731 +0200
com.apple.appkit.xpc.openAndSavePanelService SFBrowserCallBack (node =
<SFNode 0x6000000ead80>{domain = Network})
default 16:57:20.266524 +0200 AppleSpell 0x7fdef641ee10 Download

```

```

listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef641ee10> { count =
2, transaction: 1, voucher = 0x7fdef64242c0, contents =
    "Progress" => <dictionary: 0x7fdef986d2f0> { count = 3, transaction: 0, voucher
= 0x0, contents =
        "OperationProgress" => <double: 0x7fdef982f630>: 0.762821
        "EstimatedTimeRemaining" => <double: 0x7fdef9884aa0>: 0.621846
        "Operation" => <string: 0x7fdef986cf50> { length = 16, contents =
"DownloadingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef9873f60>: 3
}
default    16:57:20.278895 +0200
com.apple.appkit.xpc.openAndSavePanelService    Connection to sharingd
became invalid
default    16:57:20.288537 +0200    AppleSpell    0x7fdef65bf9f0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef65bf9f0> { count =
2, transaction: 1, voucher = 0x7fdef6594a70, contents =
    "Progress" => <dictionary: 0x7fdef6549070> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef65a8770>: 0.787300
        "EstimatedTimeRemaining" => <double: 0x7fdef65bdcf0>: 0.540329
        "Operation" => <string: 0x7fdef65a4680> { length = 16, contents =
"DownloadingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef65a3760>: 3
}
default    16:57:20.292321 +0200    opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default    16:57:20.292521 +0200    opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 20, EGID: 20
default    16:57:20.292771 +0200    opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default    16:57:20.299063 +0200    opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default    16:57:20.302290 +0200
com.apple.appkit.xpc.openAndSavePanelService    <NSViewServiceMarshal:
0x7fa4eb68d5d0> implicit request for resize of <NSSavePanelServicePanel:
0x7fa4eb4475f0> to {465, 213} was not granted as-is; set breakpoint on -
[NSViewServiceMarshal implicitResize:ofWindow:] to catch this
default    16:57:20.302359 +0200
com.apple.appkit.xpc.openAndSavePanelService    <NSViewServiceMarshal:
0x7fa4eb68d5d0> implicit request for resize of <NSSavePanelServicePanel:
0x7fa4eb4475f0> to {424, 213} was not granted as-is; set breakpoint on -
[NSViewServiceMarshal implicitResize:ofWindow:] to catch this
default    16:57:20.304245 +0200    opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default    16:57:20.325546 +0200    AppleSpell    0x7fdef9b167d0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef9b167d0> { count =
2, transaction: 1, voucher = 0x7fdef9b13570, contents =
    "Progress" => <dictionary: 0x7fdef9b16cb0> { count = 3, transaction: 0,

```

```

voucher = 0x0, contents =
    "OperationProgress" => <double: 0x7fdef9b0dc20>: 0.811778
    "EstimatedTimeRemaining" => <double: 0x7fdef9b0e7f0>: 0.463728
    "Operation" => <string: 0x7fdef9b0e9c0> { length = 16, contents =
"DownloadingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef9b08050>: 3
}
default    16:57:20.336542 +0200    cloudphotosd    TIC TCP Conn Cancel
[2:0x7ffb181c9fb0]
default    16:57:20.336582 +0200    cloudphotosd    TIC TCP Conn Destroyed
[2:0x7ffb181c9fb0]
default    16:57:20.338635 +0200    mds    directQueryOpenReply 53249
1795162208 0
default    16:57:20.338754 +0200    mds    QueryOpen succeeded (0) for store
<private>
default    16:57:20.338800 +0200    mds    directQueryOpenReply 53250
1795162208 0
default    16:57:20.338889 +0200    mds    QueryOpen succeeded (0) for store
<private>
default    16:57:20.339205 +0200    mds    directQueryFetchResultsReply 53249
1795162208 0
default    16:57:20.339657 +0200    mds    directQueryFetchResultsReply 53250
1795162208 0
default    16:57:20.369784 +0200    AppleSpell    0x7fdef641ee10 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef641ee10> { count =
2, transaction: 1, voucher = 0x7fdef64242c0, contents =
    "Progress" => <dictionary: 0x7fdef645c780> { count = 3, transaction: 0,
voucher = 0x0, contents =
    "OperationProgress" => <double: 0x7fdef6424310>: 0.836788
    "EstimatedTimeRemaining" => <double: 0x7fdef641c0d0>: 0.390091
    "Operation" => <string: 0x7fdef641f870> { length = 16, contents =
"DownloadingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef645d540>: 3
}
default    16:57:20.395594 +0200    AppleSpell    0x7fdef9916840 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef9916840> { count =
2, transaction: 1, voucher = 0x7fdef9917720, contents =
    "Progress" => <dictionary: 0x7fdef99157f0> { count = 3, transaction: 0, voucher
= 0x0, contents =
    "OperationProgress" => <double: 0x7fdef99158a0>: 0.861267
    "EstimatedTimeRemaining" => <double: 0x7fdef9907470>: 0.322161
    "Operation" => <string: 0x7fdef9904770> { length = 16, contents =
"DownloadingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef9902c40>: 3
}
default    16:57:20.433402 +0200    AppleSpell    0x7fdef986a770 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef986a770> { count =

```



```

2, transaction: 1, voucher = 0x7fdef9871170, contents =
  "Progress" => <dictionary: 0x7fdef98763f0> { count = 3, transaction: 0, voucher
= 0x0, contents =
    "OperationProgress" => <double: 0x7fdef986d980>: 0.887873
    "EstimatedTimeRemaining" => <double: 0x7fdef98764a0>: 0.252574
    "Operation" => <string: 0x7fdef9871bb0> { length = 16, contents =
"DownloadingAsset" }
  }
  "_IPC_TYPE" => <uint64: 0x7fdef982f630>: 3
}
default 16:57:20.465370 +0200 AppleSpell 0x7fdef9871cf0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef9871cf0> { count =
2, transaction: 1, voucher = 0x7fdef671aa90, contents =
  "Progress" => <dictionary: 0x7fdef98763f0> { count = 3, transaction: 0, voucher
= 0x0, contents =
    "OperationProgress" => <double: 0x7fdef98764a0>: 0.913948
    "EstimatedTimeRemaining" => <double: 0x7fdef982ff20>: 0.188308
    "Operation" => <string: 0x7fdef9871bb0> { length = 16, contents =
"DownloadingAsset" }
  }
  "_IPC_TYPE" => <uint64: 0x7fdef98190c0>: 3
}
default 16:57:20.473484 +0200 QuickLookSatellite Set a breakpoint at
SLSLogBreak to catch errors/faults as they are logged.
error 16:57:20.473531 +0200 QuickLookSatellite 0 is not a valid connection ID.
default 16:57:20.473546 +0200 QuickLookSatellite Invalid Connection ID 0
default 16:57:20.499617 +0200 AppleSpell 0x7fdef65a4510 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef65a4510> { count =
2, transaction: 1, voucher = 0x7fdef6594a70, contents =
  "Progress" => <dictionary: 0x7fdef654a0a0> { count = 3, transaction: 0,
voucher = 0x0, contents =
    "OperationProgress" => <double: 0x7fdef65887b0>: 0.938426
    "EstimatedTimeRemaining" => <double: 0x7fdef65a85d0>: 0.131228
    "Operation" => <string: 0x7fdef65a44b0> { length = 16, contents =
"DownloadingAsset" }
  }
  "_IPC_TYPE" => <uint64: 0x7fdef65a8580>: 3
}
error 16:57:20.520539 +0200 QuickLookSatellite 0 is not a valid connection ID.
error 16:57:20.520572 +0200 QuickLookSatellite 0 is not a valid connection ID.
error 16:57:20.520595 +0200 QuickLookSatellite 0 is not a valid connection ID.
default 16:57:20.527190 +0200 AppleSpell 0x7fdef641ee10 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef641ee10> { count =
2, transaction: 1, voucher = 0x7fdef64242c0, contents =
  "Progress" => <dictionary: 0x7fdef645ba60> { count = 3, transaction: 0,
voucher = 0x0, contents =
    "OperationProgress" => <double: 0x7fdef645e500>: 0.962905
    "EstimatedTimeRemaining" => <double: 0x7fdef6417a10>: 0.077049
    "Operation" => <string: 0x7fdef645bb10> { length = 16, contents =
"DownloadingAsset" }
  }

```

```

    }
    "_IPC_TYPE" => <uint64: 0x7fdef641c0d0>: 3
}
default 16:57:20.557763 +0200 AppleSpell 0x7fdef65bf9f0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef65bf9f0> { count =
2, transaction: 1, voucher = 0x7fdef6594a70, contents =
    "Progress" => <dictionary: 0x7fdef6549070> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef6594ea0>: 0.989511
        "EstimatedTimeRemaining" => <double: 0x7fdef65a85d0>: 0.021200
        "Operation" => <string: 0x7fdef65a44b0> { length = 16, contents =
"DownloadingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef65a8580>: 3
}
default 16:57:20.588794 +0200 AppleSpell 0x7fdef66bac50 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef66bac50> { count =
2, transaction: 1, voucher = 0x7fdef66bc000, contents =
    "Progress" => <dictionary: 0x7fdef66aa730> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef66b82b0>: 1.000000
        "EstimatedTimeRemaining" => <double: 0x7fdef665e210>: 0.000000
        "Operation" => <string: 0x7fdef66aa7e0> { length = 16, contents =
"DownloadingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef66bb1e0>: 3
}
default 16:57:20.588804 +0200 nsurlsessiond Task 2 for client <private>
completed successfully
default 16:57:20.589005 +0200 mobileassetd download completed
(task=0x7f87cf403080 success=1)
default 16:57:20.590712 +0200 mobileassetd download finished, asset
version : 2512, download size: 2706074
default 16:57:20.590766 +0200 mobileassetd Stopped downloading URL
http://appldnld.apple.com/ios10.0/031-72107-2016008009-1F1D1C14-5B55-11E6-
B8BB-BCDA464FE3CA/com_apple_MobileAsset_LinguisticData/
a76f754b2835fa56689b62d6189696ab82847901.zip for client AppleSpell
default 16:57:20.590807 +0200 mobileassetd task is complete
(task=0x7f87cf403080)
default 16:57:20.596093 +0200 AppleSpell 0x7fdef641ee10 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef641ee10> { count =
2, transaction: 1, voucher = 0x7fdef64242c0, contents =
    "Progress" => <dictionary: 0x7fdef645c780> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef645d540>: 0.000000
        "EstimatedTimeRemaining" => <double: 0x7fdef6464eb0>: -1.000000
        "Operation" => <string: 0x7fdef645c830> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef641ad90>: 3

```

```

}
default 16:57:20.596253 +0200 AppleSpell 0x7fdef986d2f0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef986d2f0> { count =
2, transaction: 1, voucher = 0x7fdef9876260, contents =
    "Progress" => <dictionary: 0x7fdef98763f0> { count = 3, transaction: 0, voucher
= 0x0, contents =
        "OperationProgress" => <double: 0x7fdef98764a0>: 0.024218
        "EstimatedTimeRemaining" => <double: 0x7fdef986f590>: 0.004029
        "Operation" => <string: 0x7fdef9863e40> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef9884aa0>: 3
}
default 16:57:20.596387 +0200 AppleSpell 0x7fdef986a770 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef986a770> { count =
2, transaction: 1, voucher = 0x7fdef9876260, contents =
    "Progress" => <dictionary: 0x7fdef98763f0> { count = 3, transaction: 0, voucher
= 0x0, contents =
        "OperationProgress" => <double: 0x7fdef98764a0>: 0.048436
        "EstimatedTimeRemaining" => <double: 0x7fdef986f590>: 0.005186
        "Operation" => <string: 0x7fdef9863e40> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef9884aa0>: 3
}
default 16:57:20.596510 +0200 AppleSpell 0x7fdef9871cf0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef9871cf0> { count =
2, transaction: 1, voucher = 0x7fdef9876260, contents =
    "Progress" => <dictionary: 0x7fdef98763f0> { count = 3, transaction: 0, voucher
= 0x0, contents =
        "OperationProgress" => <double: 0x7fdef98764a0>: 0.072654
        "EstimatedTimeRemaining" => <double: 0x7fdef9869840>: 0.005067
        "Operation" => <string: 0x7fdef986cf50> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef985d000>: 3
}
default 16:57:20.596660 +0200 AppleSpell 0x7fdef641ee10 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef641ee10> { count =
2, transaction: 1, voucher = 0x7fdef64242c0, contents =
    "Progress" => <dictionary: 0x7fdef645c780> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef6424310>: 0.096872
        "EstimatedTimeRemaining" => <double: 0x7fdef6464eb0>: 0.004764
        "Operation" => <string: 0x7fdef641ce50> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef645d540>: 3
}
default 16:57:20.596721 +0200 AppleSpell 0x7fdef644ccd0 Download

```

```

listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef644ccd0> { count =
2, transaction: 1, voucher = 0x7fdef64242c0, contents =
    "Progress" => <dictionary: 0x7fdef645c780> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef6464eb0>: 0.121091
        "EstimatedTimeRemaining" => <double: 0x7fdef6424310>: 0.004377
        "Operation" => <string: 0x7fdef645c830> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef645c980>: 3
}
default 16:57:20.596875 +0200 AppleSpell 0x7fdef644b7e0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef644b7e0> { count =
2, transaction: 1, voucher = 0x7fdef64242c0, contents =
    "Progress" => <dictionary: 0x7fdef645ba60> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef645e500>: 0.145309
        "EstimatedTimeRemaining" => <double: 0x7fdef6417a10>: 0.004341
        "Operation" => <string: 0x7fdef645bb10> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef641ad90>: 3
}
default 16:57:20.596949 +0200 AppleSpell 0x7fdef67186e0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef67186e0> { count =
2, transaction: 1, voucher = 0x7fdef671aa90, contents =
    "Progress" => <dictionary: 0x7fdef6718840> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef6714ff0>: 0.169527
        "EstimatedTimeRemaining" => <double: 0x7fdef67183a0>: 0.004071
        "Operation" => <string: 0x7fdef67097f0> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef6716610>: 3
}
default 16:57:20.597098 +0200 AppleSpell 0x7fdef66bac50 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef66bac50> { count =
2, transaction: 1, voucher = 0x7fdef66bc000, contents =
    "Progress" => <dictionary: 0x7fdef66aa730> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef6657ef0>: 0.193745
        "EstimatedTimeRemaining" => <double: 0x7fdef665e210>: 0.003982
        "Operation" => <string: 0x7fdef66bbaa0> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef66b82b0>: 3
}
default 16:57:20.597160 +0200 AppleSpell 0x7fdef66aa730 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef66aa730> { count =
2, transaction: 1, voucher = 0x7fdef66bc000, contents =

```

```

    "Progress" => <dictionary: 0x7fdef66b8570> { count = 3, transaction: 0,
voucher = 0x0, contents =
    "OperationProgress" => <double: 0x7fdef665e210>: 0.217963
    "EstimatedTimeRemaining" => <double: 0x7fdef6657ef0>: 0.003728
    "Operation" => <string: 0x7fdef66bbaa0> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef665ec90>: 3
}
default 16:57:20.597303 +0200 AppleSpell 0x7fdef66bac50 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef66bac50> { count =
2, transaction: 1, voucher = 0x7fdef66bc000, contents =
    "Progress" => <dictionary: 0x7fdef66aa730> { count = 3, transaction: 0,
voucher = 0x0, contents =
    "OperationProgress" => <double: 0x7fdef665f470>: 0.242181
    "EstimatedTimeRemaining" => <double: 0x7fdef6657ef0>: 0.003658
    "Operation" => <string: 0x7fdef66aa7e0> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef665e210>: 3
}
default 16:57:20.597393 +0200 AppleSpell 0x7fdef65a4510 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef65a4510> { count =
2, transaction: 1, voucher = 0x7fdef6594a70, contents =
    "Progress" => <dictionary: 0x7fdef654a0a0> { count = 3, transaction: 0,
voucher = 0x0, contents =
    "OperationProgress" => <double: 0x7fdef65a3760>: 0.266399
    "EstimatedTimeRemaining" => <double: 0x7fdef65a8580>: 0.003514
    "Operation" => <string: 0x7fdef65c8fe0> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef6594ea0>: 3
}
default 16:57:20.597547 +0200 AppleSpell 0x7fdef986d2f0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef986d2f0> { count =
2, transaction: 1, voucher = 0x7fdef9876260, contents =
    "Progress" => <dictionary: 0x7fdef98763f0> { count = 3, transaction: 0, voucher
= 0x0, contents =
    "OperationProgress" => <double: 0x7fdef986d980>: 0.290617
    "EstimatedTimeRemaining" => <double: 0x7fdef98764a0>: 0.003415
    "Operation" => <string: 0x7fdef9850840> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef9884aa0>: 3
}
default 16:57:20.597623 +0200 AppleSpell 0x7fdef66bac50 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef66bac50> { count =
2, transaction: 1, voucher = 0x7fdef9876260, contents =
    "Progress" => <dictionary: 0x7fdef66aa730> { count = 3, transaction: 0,
voucher = 0x0, contents =

```

```

        "OperationProgress" => <double: 0x7fdef66bb1e0>: 0.314835
        "EstimatedTimeRemaining" => <double: 0x7fdef6657ef0>: 0.003240
        "Operation" => <string: 0x7fdef66aa7e0> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef665f470>: 3
}
default    16:57:20.597737 +0200  AppleSpell    0x7fdef66bac50 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef66bac50> { count =
2, transaction: 1, voucher = 0x7fdef66bbc50, contents =
    "Progress" => <dictionary: 0x7fdef66aa730> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef66b82b0>: 0.339054
        "EstimatedTimeRemaining" => <double: 0x7fdef6657ef0>: 0.003146
        "Operation" => <string: 0x7fdef66aa7e0> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef66bb1e0>: 3
}
default    16:57:20.597892 +0200  AppleSpell    0x7fdef65bf9f0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef65bf9f0> { count =
2, transaction: 1, voucher = 0x7fdef6594a70, contents =
    "Progress" => <dictionary: 0x7fdef654a0a0> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef65a84e0>: 0.363272
        "EstimatedTimeRemaining" => <double: 0x7fdef65a8770>: 0.003050
        "Operation" => <string: 0x7fdef6594f50> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef6594a30>: 3
}
default    16:57:20.597953 +0200  AppleSpell    0x7fdef986a770 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef986a770> { count =
2, transaction: 1, voucher = 0x7fdef6594a70, contents =
    "Progress" => <dictionary: 0x7fdef98763f0> { count = 3, transaction: 0, voucher
= 0x0, contents =
        "OperationProgress" => <double: 0x7fdef98764a0>: 0.387490
        "EstimatedTimeRemaining" => <double: 0x7fdef982ff20>: 0.002888
        "Operation" => <string: 0x7fdef98725f0> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef9869840>: 3
}
default    16:57:20.598068 +0200  AppleSpell    0x7fdef644b7e0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef644b7e0> { count =
2, transaction: 1, voucher = 0x7fdef64242c0, contents =
    "Progress" => <dictionary: 0x7fdef645c780> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef6424310>: 0.411708
        "EstimatedTimeRemaining" => <double: 0x7fdef6464eb0>: 0.002782

```

```

        "Operation" => <string: 0x7fdef6440440> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef6467600>: 3
}
default    16:57:20.598178 +0200  AppleSpell    0x7fdef65a4510 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef65a4510> { count =
2, transaction: 1, voucher = 0x7fdef6594a70, contents =
    "Progress" => <dictionary: 0x7fdef654a0a0> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef65a3760>: 0.435926
        "EstimatedTimeRemaining" => <double: 0x7fdef6582a70>: 0.002664
        "Operation" => <string: 0x7fdef6591460> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef65955b0>: 3
}
default    16:57:20.598264 +0200  AppleSpell    0x7fdef66bac50 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef66bac50> { count =
2, transaction: 1, voucher = 0x7fdef66bbc50, contents =
    "Progress" => <dictionary: 0x7fdef66aa730> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef665ec90>: 0.460144
        "EstimatedTimeRemaining" => <double: 0x7fdef6657ef0>: 0.002525
        "Operation" => <string: 0x7fdef66aa7e0> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef66b82b0>: 3
}
default    16:57:20.598368 +0200  AppleSpell    0x7fdef644b7e0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef644b7e0> { count =
2, transaction: 1, voucher = 0x7fdef64242c0, contents =
    "Progress" => <dictionary: 0x7fdef645ba60> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef6424310>: 0.484362
        "EstimatedTimeRemaining" => <double: 0x7fdef645e500>: 0.002397
        "Operation" => <string: 0x7fdef641ce50> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef6417a10>: 3
}
default    16:57:20.598484 +0200  AppleSpell    0x7fdef644b7e0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef644b7e0> { count =
2, transaction: 1, voucher = 0x7fdef64242c0, contents =
    "Progress" => <dictionary: 0x7fdef645c780> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef6464eb0>: 0.508580
        "EstimatedTimeRemaining" => <double: 0x7fdef645c980>: 0.002286
        "Operation" => <string: 0x7fdef645c830> { length = 14, contents =
"VerifyingAsset" }
    }

```

```

    }
    "_IPC_TYPE" => <uint64: 0x7fdef645d540>: 3
}
default 16:57:20.598630 +0200 AppleSpell 0x7fdef65bf9f0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef65bf9f0> { count =
2, transaction: 1, voucher = 0x7fdef6594a70, contents =
    "Progress" => <dictionary: 0x7fdef654a0a0> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef65a84e0>: 0.532798
        "EstimatedTimeRemaining" => <double: 0x7fdef6502ba0>: 0.002183
        "Operation" => <string: 0x7fdef65a4680> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef65bdcf0>: 3
}
default 16:57:20.598691 +0200 AppleSpell 0x7fdef65a4510 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef65a4510> { count =
2, transaction: 1, voucher = 0x7fdef6594a70, contents =
    "Progress" => <dictionary: 0x7fdef654a0a0> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef65a3760>: 0.557017
        "EstimatedTimeRemaining" => <double: 0x7fdef6595820>: 0.002048
        "Operation" => <string: 0x7fdef6594f50> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef6591e20>: 3
}
default 16:57:20.598817 +0200 AppleSpell 0x7fdef65bf9f0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef65bf9f0> { count =
2, transaction: 1, voucher = 0x7fdef6594a70, contents =
    "Progress" => <dictionary: 0x7fdef654a0a0> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef65a84e0>: 0.581235
        "EstimatedTimeRemaining" => <double: 0x7fdef65a85d0>: 0.001939
        "Operation" => <string: 0x7fdef65c9030> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef6594ea0>: 3
}
default 16:57:20.598885 +0200 AppleSpell 0x7fdef65a4510 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef65a4510> { count =
2, transaction: 1, voucher = 0x7fdef6594a70, contents =
    "Progress" => <dictionary: 0x7fdef654a0a0> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef65a3760>: 0.605453
        "EstimatedTimeRemaining" => <double: 0x7fdef65887b0>: 0.001812
        "Operation" => <string: 0x7fdef65c9030> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef6594a30>: 3

```



```

}
default 16:57:20.599019 +0200 AppleSpell 0x7fdef66bac50 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef66bac50> { count =
2, transaction: 1, voucher = 0x7fdef66bbc50, contents =
    "Progress" => <dictionary: 0x7fdef66aa730> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef665e210>: 0.629671
        "EstimatedTimeRemaining" => <double: 0x7fdef6657ef0>: 0.001693
        "Operation" => <string: 0x7fdef6658c30> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef665ec90>: 3
}
default 16:57:20.599076 +0200 AppleSpell 0x7fdef65bf9f0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef65bf9f0> { count =
2, transaction: 1, voucher = 0x7fdef66bbc50, contents =
    "Progress" => <dictionary: 0x7fdef654a0a0> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef65a84e0>: 0.653889
        "EstimatedTimeRemaining" => <double: 0x7fdef654a030>: 0.001572
        "Operation" => <string: 0x7fdef65bdc20> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef65955b0>: 3
}
default 16:57:20.599222 +0200 AppleSpell 0x7fdef65a4510 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef65a4510> { count =
2, transaction: 1, voucher = 0x7fdef65c4b30, contents =
    "Progress" => <dictionary: 0x7fdef654a0a0> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef65a3760>: 0.678107
        "EstimatedTimeRemaining" => <double: 0x7fdef65a8580>: 0.001464
        "Operation" => <string: 0x7fdef65a4680> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef65bdcf0>: 3
}
default 16:57:20.599281 +0200 AppleSpell 0x7fdef65bf9f0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef65bf9f0> { count =
2, transaction: 1, voucher = 0x7fdef65c4b30, contents =
    "Progress" => <dictionary: 0x7fdef654a0a0> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef65a84e0>: 0.702325
        "EstimatedTimeRemaining" => <double: 0x7fdef65a8770>: 0.001343
        "Operation" => <string: 0x7fdef65a4680> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef6591e20>: 3
}
default 16:57:20.599393 +0200 AppleSpell 0x7fdef65a4510 Download

```

```

listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef65a4510> { count =
2, transaction: 1, voucher = 0x7fdef65c4b30, contents =
    "Progress" => <dictionary: 0x7fdef654a0a0> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef65a3760>: 0.726543
        "EstimatedTimeRemaining" => <double: 0x7fdef6582a70>: 0.001236
        "Operation" => <string: 0x7fdef6594f50> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef6594ea0>: 3
}
default 16:57:20.599493 +0200 AppleSpell 0x7fdef9871cf0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef9871cf0> { count =
2, transaction: 1, voucher = 0x7fdef9801dd0, contents =
    "Progress" => <dictionary: 0x7fdef98763f0> { count = 3, transaction: 0, voucher
= 0x0, contents =
        "OperationProgress" => <double: 0x7fdef98764a0>: 0.750761
        "EstimatedTimeRemaining" => <double: 0x7fdef982f630>: 0.001121
        "Operation" => <string: 0x7fdef986cf50> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef984f020>: 3
}
default 16:57:20.599581 +0200 AppleSpell 0x7fdef66bac50 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef66bac50> { count =
2, transaction: 1, voucher = 0x7fdef66bbc50, contents =
    "Progress" => <dictionary: 0x7fdef66aa730> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef665f470>: 0.774980
        "EstimatedTimeRemaining" => <double: 0x7fdef6657ef0>: 0.001009
        "Operation" => <string: 0x7fdef66aa7e0> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef665e210>: 3
}
default 16:57:20.599670 +0200 AppleSpell 0x7fdef65bf9f0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef65bf9f0> { count =
2, transaction: 1, voucher = 0x7fdef65c4b30, contents =
    "Progress" => <dictionary: 0x7fdef654a0a0> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef65a84e0>: 0.799198
        "EstimatedTimeRemaining" => <double: 0x7fdef6502ba0>: 0.000896
        "Operation" => <string: 0x7fdef6594f50> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef6594a30>: 3
}
default 16:57:20.599769 +0200 AppleSpell 0x7fdef644b7e0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef644b7e0> { count =
2, transaction: 1, voucher = 0x7fdef64242c0, contents =

```

```

    "Progress" => <dictionary: 0x7fdef645ba60> { count = 3, transaction: 0,
voucher = 0x0, contents =
    "OperationProgress" => <double: 0x7fdef6424310>: 0.823416
    "EstimatedTimeRemaining" => <double: 0x7fdef645e500>: 0.000784
    "Operation" => <string: 0x7fdef641ce50> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef641c0d0>: 3
}
default 16:57:20.599847 +0200 AppleSpell 0x7fdef644b7e0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef644b7e0> { count =
2, transaction: 1, voucher = 0x7fdef64242c0, contents =
    "Progress" => <dictionary: 0x7fdef645c780> { count = 3, transaction: 0,
voucher = 0x0, contents =
    "OperationProgress" => <double: 0x7fdef6464eb0>: 0.847634
    "EstimatedTimeRemaining" => <double: 0x7fdef645c980>: 0.000673
    "Operation" => <string: 0x7fdef645c830> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef641ad90>: 3
}
default 16:57:20.599958 +0200 AppleSpell 0x7fdef644b7e0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef644b7e0> { count =
2, transaction: 1, voucher = 0x7fdef64242c0, contents =
    "Progress" => <dictionary: 0x7fdef645ba60> { count = 3, transaction: 0,
voucher = 0x0, contents =
    "OperationProgress" => <double: 0x7fdef6424310>: 0.871852
    "EstimatedTimeRemaining" => <double: 0x7fdef645e500>: 0.000566
    "Operation" => <string: 0x7fdef645bb10> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef6467600>: 3
}
default 16:57:20.600057 +0200 AppleSpell 0x7fdef986d2f0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef986d2f0> { count =
2, transaction: 1, voucher = 0x7fdef9801dd0, contents =
    "Progress" => <dictionary: 0x7fdef98763f0> { count = 3, transaction: 0, voucher
= 0x0, contents =
    "OperationProgress" => <double: 0x7fdef98764a0>: 0.896070
    "EstimatedTimeRemaining" => <double: 0x7fdef985d000>: 0.000458
    "Operation" => <string: 0x7fdef9863e40> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef9884aa0>: 3
}
default 16:57:20.600135 +0200 AppleSpell 0x7fdef986a770 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef986a770> { count =
2, transaction: 1, voucher = 0x7fdef9801dd0, contents =
    "Progress" => <dictionary: 0x7fdef98763f0> { count = 3, transaction: 0, voucher
= 0x0, contents =

```

```

        "OperationProgress" => <double: 0x7fdef98764a0>: 0.920288
        "EstimatedTimeRemaining" => <double: 0x7fdef986f590>: 0.000349
        "Operation" => <string: 0x7fdef98725f0> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef9869840>: 3
}
default 16:57:20.600228 +0200 AppleSpell 0x7fdef644b7e0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef644b7e0> { count =
2, transaction: 1, voucher = 0x7fdef64242c0, contents =
    "Progress" => <dictionary: 0x7fdef645c780> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef6424310>: 0.944506
        "EstimatedTimeRemaining" => <double: 0x7fdef645d540>: 0.000242
        "Operation" => <string: 0x7fdef6440d30> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef6464eb0>: 3
}
default 16:57:20.600321 +0200 AppleSpell 0x7fdef65a4510 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef65a4510> { count =
2, transaction: 1, voucher = 0x7fdef65c4b30, contents =
    "Progress" => <dictionary: 0x7fdef654a0a0> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef65a3760>: 0.968724
        "EstimatedTimeRemaining" => <double: 0x7fdef6595820>: 0.000136
        "Operation" => <string: 0x7fdef65c8fe0> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef65955b0>: 3
}
default 16:57:20.600398 +0200 AppleSpell 0x7fdef65bf9f0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef65bf9f0> { count =
2, transaction: 1, voucher = 0x7fdef65c4b30, contents =
    "Progress" => <dictionary: 0x7fdef654a0a0> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef65a84e0>: 0.992943
        "EstimatedTimeRemaining" => <double: 0x7fdef65a85d0>: 0.000031
        "Operation" => <string: 0x7fdef65c9030> { length = 14, contents =
"VerifyingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef65bdcf0>: 3
}
default 16:57:20.601180 +0200 AppleSpell 0x7fdef66bac50 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef66bac50> { count =
2, transaction: 1, voucher = 0x7fdef66bbc50, contents =
    "Progress" => <dictionary: 0x7fdef66aa730> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef66bb1e0>: -1.000000
        "EstimatedTimeRemaining" => <double: 0x7fdef6657ef0>: -1.000000

```

```

        "Operation" => <string: 0x7fdef66bbaa0> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef665e210>: 3
}
default    16:57:20.601160 +0200    kernel    SandboxViolation: mobileassetd(51)
deny(1) file-read-data /
default    16:57:20.601291 +0200    kernel    SandboxViolation: mobileassetd(51)
deny(1) file-read-data /
default    16:57:20.601308 +0200    AppleSpell    0x7fdef66bac50 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef66bac50> { count =
2, transaction: 1, voucher = 0x7fdef66bbc50, contents =
    "Progress" => <dictionary: 0x7fdef66aa730> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef665f470>: -1.000000
        "EstimatedTimeRemaining" => <double: 0x7fdef6657ef0>: -1.000000
        "Operation" => <string: 0x7fdef66aa7e0> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef665e210>: 3
}
default    16:57:20.601450 +0200    AppleSpell    0x7fdef65a4510 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef65a4510> { count =
2, transaction: 1, voucher = 0x7fdef65c4b30, contents =
    "Progress" => <dictionary: 0x7fdef654a0a0> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef65a3760>: 0.000027
        "EstimatedTimeRemaining" => <double: 0x7fdef65887b0>: 12.269470
        "Operation" => <string: 0x7fdef6594f50> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef6502ba0>: 3
}
default    16:57:20.601629 +0200    kernel    SandboxViolation: mobileassetd(51)
deny(1) file-read-data /
default    16:57:20.601754 +0200    kernel    SandboxViolation: mobileassetd(51)
deny(1) file-read-data /
default    16:57:20.602424 +0200    AppleSpell    0x7fdef66bac50 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef66bac50> { count =
2, transaction: 1, voucher = 0x7fdef66bbc50, contents =
    "Progress" => <dictionary: 0x7fdef66aa730> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef66bb1e0>: 0.025542
        "EstimatedTimeRemaining" => <double: 0x7fdef6657ef0>: 0.049596
        "Operation" => <string: 0x7fdef6621090> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef665e210>: 3
}
default    16:57:20.603035 +0200    AppleSpell    0x7fdef65bf9f0 Download

```

```

listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef65bf9f0> { count =
2, transaction: 1, voucher = 0x7fdef65c4b30, contents =
    "Progress" => <dictionary: 0x7fdef6549070> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef65a8580>: 0.051057
        "EstimatedTimeRemaining" => <double: 0x7fdef65a84e0>: 0.035350
        "Operation" => <string: 0x7fdef65a44b0> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef65a85d0>: 3
}
default 16:57:20.603600 +0200 AppleSpell 0x7fdef66bac50 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef66bac50> { count =
2, transaction: 1, voucher = 0x7fdef66bbc50, contents =
    "Progress" => <dictionary: 0x7fdef66aa730> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef665f470>: 0.076572
        "EstimatedTimeRemaining" => <double: 0x7fdef6657ef0>: 0.029775
        "Operation" => <string: 0x7fdef66bbaa0> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef665e210>: 3
}
default 16:57:20.603776 +0200 AppleSpell 0x7fdef65a4510 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef65a4510> { count =
2, transaction: 1, voucher = 0x7fdef65c4b30, contents =
    "Progress" => <dictionary: 0x7fdef654a0a0> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef65a8770>: 0.102087
        "EstimatedTimeRemaining" => <double: 0x7fdef65a3760>: 0.023405
        "Operation" => <string: 0x7fdef6594f50> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef65887b0>: 3
}
default 16:57:20.604042 +0200 AppleSpell 0x7fdef644b7e0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef644b7e0> { count =
2, transaction: 1, voucher = 0x7fdef64242c0, contents =
    "Progress" => <dictionary: 0x7fdef645ba60> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef6424310>: 0.127602
        "EstimatedTimeRemaining" => <double: 0x7fdef645e500>: 0.019977
        "Operation" => <string: 0x7fdef6419350> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef645c980>: 3
}
default 16:57:20.604457 +0200 AppleSpell 0x7fdef66bac50 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef66bac50> { count =
2, transaction: 1, voucher = 0x7fdef66bbc50, contents =

```

```

    "Progress" => <dictionary: 0x7fdef66aa730> { count = 3, transaction: 0,
voucher = 0x0, contents =
    "OperationProgress" => <double: 0x7fdef66bb1e0>: 0.153117
    "EstimatedTimeRemaining" => <double: 0x7fdef6657ef0>: 0.018396
    "Operation" => <string: 0x7fdef6658c30> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef665e210>: 3
}
default 16:57:20.604848 +0200 AppleSpell 0x7fdef644b7e0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef644b7e0> { count =
2, transaction: 1, voucher = 0x7fdef64242c0, contents =
    "Progress" => <dictionary: 0x7fdef645c780> { count = 3, transaction: 0,
voucher = 0x0, contents =
    "OperationProgress" => <double: 0x7fdef6424310>: 0.178632
    "EstimatedTimeRemaining" => <double: 0x7fdef645d540>: 0.017169
    "Operation" => <string: 0x7fdef6440440> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef641c0d0>: 3
}
default 16:57:20.605234 +0200 AppleSpell 0x7fdef65bf9f0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef65bf9f0> { count =
2, transaction: 1, voucher = 0x7fdef65c4b30, contents =
    "Progress" => <dictionary: 0x7fdef6549070> { count = 3, transaction: 0,
voucher = 0x0, contents =
    "OperationProgress" => <double: 0x7fdef6594a30>: 0.204147
    "EstimatedTimeRemaining" => <double: 0x7fdef65a8580>: 0.016034
    "Operation" => <string: 0x7fdef65a44b0> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef65a84e0>: 3
}
default 16:57:20.605666 +0200 AppleSpell 0x7fdef9871cf0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef9871cf0> { count =
2, transaction: 1, voucher = 0x7fdef9801dd0, contents =
    "Progress" => <dictionary: 0x7fdef98763f0> { count = 3, transaction: 0, voucher
= 0x0, contents =
    "OperationProgress" => <double: 0x7fdef98764a0>: 0.229662
    "EstimatedTimeRemaining" => <double: 0x7fdef98190c0>: 0.015128
    "Operation" => <string: 0x7fdef9850840> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef982f630>: 3
}
default 16:57:20.605985 +0200 AppleSpell 0x7fdef65a4510 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef65a4510> { count =
2, transaction: 1, voucher = 0x7fdef65c4b30, contents =
    "Progress" => <dictionary: 0x7fdef654a0a0> { count = 3, transaction: 0,
voucher = 0x0, contents =

```

```

        "OperationProgress" => <double: 0x7fdef6594ea0>: 0.255177
        "EstimatedTimeRemaining" => <double: 0x7fdef65a8770>: 0.014194
        "Operation" => <string: 0x7fdef6594f50> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef65a3760>: 3
}
default    16:57:20.606328 +0200    kernel    SandboxViolation: mobileassetd(51)
deny(1) file-read-data /
default    16:57:20.606451 +0200    kernel    SandboxViolation: mobileassetd(51)
deny(1) file-read-data /
default    16:57:20.606654 +0200    kernel    SandboxViolation: mobileassetd(51)
deny(1) file-read-data /
default    16:57:20.607246 +0200    AppleSpell    0x7fdef65bf9f0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef65bf9f0> { count =
2, transaction: 1, voucher = 0x7fdef65c4b30, contents =
    "Progress" => <dictionary: 0x7fdef6549070> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef6595820>: 0.290669
        "EstimatedTimeRemaining" => <double: 0x7fdef6594a30>: 0.014920
        "Operation" => <string: 0x7fdef65a44b0> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef65a8580>: 3
}
default    16:57:20.607831 +0200    AppleSpell    0x7fdef986d2f0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef986d2f0> { count =
2, transaction: 1, voucher = 0x7fdef9801dd0, contents =
    "Progress" => <dictionary: 0x7fdef98763f0> { count = 3, transaction: 0, voucher
= 0x0, contents =
        "OperationProgress" => <double: 0x7fdef98764a0>: 0.316184
        "EstimatedTimeRemaining" => <double: 0x7fdef986d980>: 0.014410
        "Operation" => <string: 0x7fdef9870a10> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef982ff20>: 3
}
default    16:57:20.608432 +0200    AppleSpell    0x7fdef986a770 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef986a770> { count =
2, transaction: 1, voucher = 0x7fdef9801dd0, contents =
    "Progress" => <dictionary: 0x7fdef98763f0> { count = 3, transaction: 0, voucher
= 0x0, contents =
        "OperationProgress" => <double: 0x7fdef98764a0>: 0.341699
        "EstimatedTimeRemaining" => <double: 0x7fdef984f020>: 0.014008
        "Operation" => <string: 0x7fdef9850840> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef9869840>: 3
}
default    16:57:20.608934 +0200    AppleSpell    0x7fdef65a4510 Download

```



```

listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef65a4510> { count =
2, transaction: 1, voucher = 0x7fdef65c4b30, contents =
    "Progress" => <dictionary: 0x7fdef654a0a0> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef6591e20>: 0.367214
        "EstimatedTimeRemaining" => <double: 0x7fdef6594ea0>: 0.013463
        "Operation" => <string: 0x7fdef6594f50> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef65a8770>: 3
}
default 16:57:20.609480 +0200 AppleSpell 0x7fdef9871cf0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef9871cf0> { count =
2, transaction: 1, voucher = 0x7fdef9801dd0, contents =
    "Progress" => <dictionary: 0x7fdef98763f0> { count = 3, transaction: 0, voucher
= 0x0, contents =
        "OperationProgress" => <double: 0x7fdef98764a0>: 0.392729
        "EstimatedTimeRemaining" => <double: 0x7fdef9873f60>: 0.012847
        "Operation" => <string: 0x7fdef9870a10> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef982f630>: 3
}
default 16:57:20.610002 +0200 AppleSpell 0x7fdef644b7e0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef644b7e0> { count =
2, transaction: 1, voucher = 0x7fdef64242c0, contents =
    "Progress" => <dictionary: 0x7fdef645ba60> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef6424310>: 0.418244
        "EstimatedTimeRemaining" => <double: 0x7fdef645c980>: 0.012339
        "Operation" => <string: 0x7fdef641cf10> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef6417a10>: 3
}
default 16:57:20.610583 +0200 AppleSpell 0x7fdef986d2f0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef986d2f0> { count =
2, transaction: 1, voucher = 0x7fdef9801dd0, contents =
    "Progress" => <dictionary: 0x7fdef98763f0> { count = 3, transaction: 0, voucher
= 0x0, contents =
        "OperationProgress" => <double: 0x7fdef98764a0>: 0.443759
        "EstimatedTimeRemaining" => <double: 0x7fdef9884aa0>: 0.011804
        "Operation" => <string: 0x7fdef9850840> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef982ff20>: 3
}
default 16:57:20.611086 +0200 AppleSpell 0x7fdef644b7e0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef644b7e0> { count =
2, transaction: 1, voucher = 0x7fdef64242c0, contents =

```

```

    "Progress" => <dictionary: 0x7fdef645c780> { count = 3, transaction: 0,
voucher = 0x0, contents =
    "OperationProgress" => <double: 0x7fdef6424310>: 0.469274
    "EstimatedTimeRemaining" => <double: 0x7fdef641c0d0>: 0.011235
    "Operation" => <string: 0x7fdef642f0a0> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef641ad90>: 3
}
default 16:57:20.611632 +0200 AppleSpell 0x7fdef986a770 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef986a770> { count =
2, transaction: 1, voucher = 0x7fdef9801dd0, contents =
    "Progress" => <dictionary: 0x7fdef98763f0> { count = 3, transaction: 0, voucher
= 0x0, contents =
    "OperationProgress" => <double: 0x7fdef98764a0>: 0.494789
    "EstimatedTimeRemaining" => <double: 0x7fdef985d000>: 0.010692
    "Operation" => <string: 0x7fdef9870a10> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef9869840>: 3
}
default 16:57:20.612186 +0200 AppleSpell 0x7fdef65bf9f0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef65bf9f0> { count =
2, transaction: 1, voucher = 0x7fdef65c4b30, contents =
    "Progress" => <dictionary: 0x7fdef6549070> { count = 3, transaction: 0,
voucher = 0x0, contents =
    "OperationProgress" => <double: 0x7fdef65955b0>: 0.520304
    "EstimatedTimeRemaining" => <double: 0x7fdef6595820>: 0.010185
    "Operation" => <string: 0x7fdef65a44b0> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef6594a30>: 3
}
default 16:57:20.612722 +0200 AppleSpell 0x7fdef65a4510 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef65a4510> { count =
2, transaction: 1, voucher = 0x7fdef65c4b30, contents =
    "Progress" => <dictionary: 0x7fdef654a0a0> { count = 3, transaction: 0,
voucher = 0x0, contents =
    "OperationProgress" => <double: 0x7fdef65a46f0>: 0.545819
    "EstimatedTimeRemaining" => <double: 0x7fdef6591e20>: 0.009647
    "Operation" => <string: 0x7fdef6594f50> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef6594ea0>: 3
}
default 16:57:20.613362 +0200 AppleSpell 0x7fdef9871cf0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef9871cf0> { count =
2, transaction: 1, voucher = 0x7fdef9801dd0, contents =
    "Progress" => <dictionary: 0x7fdef98763f0> { count = 3, transaction: 0, voucher
= 0x0, contents =

```

```

        "OperationProgress" => <double: 0x7fdef98764a0>: 0.571334
        "EstimatedTimeRemaining" => <double: 0x7fdef986f590>: 0.009146
        "Operation" => <string: 0x7fdef9850840> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef982f630>: 3
}
default 16:57:20.613846 +0200 AppleSpell 0x7fdef986d2f0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef986d2f0> { count =
2, transaction: 1, voucher = 0x7fdef9801dd0, contents =
    "Progress" => <dictionary: 0x7fdef98763f0> { count = 3, transaction: 0, voucher
= 0x0, contents =
        "OperationProgress" => <double: 0x7fdef98764a0>: 0.596849
        "EstimatedTimeRemaining" => <double: 0x7fdef98190c0>: 0.008576
        "Operation" => <string: 0x7fdef9850840> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef982ff20>: 3
}
default 16:57:20.614383 +0200 AppleSpell 0x7fdef65bf9f0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef65bf9f0> { count =
2, transaction: 1, voucher = 0x7fdef65c4b30, contents =
    "Progress" => <dictionary: 0x7fdef6549070> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef654a030>: 0.622364
        "EstimatedTimeRemaining" => <double: 0x7fdef65955b0>: 0.008049
        "Operation" => <string: 0x7fdef65a44b0> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef6595820>: 3
}
default 16:57:20.614840 +0200 AppleSpell 0x7fdef65a4510 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef65a4510> { count =
2, transaction: 1, voucher = 0x7fdef65c4b30, contents =
    "Progress" => <dictionary: 0x7fdef654a0a0> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef6582a70>: 0.647879
        "EstimatedTimeRemaining" => <double: 0x7fdef65a46f0>: 0.007460
        "Operation" => <string: 0x7fdef65a44b0> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef6591e20>: 3
}
default 16:57:20.615367 +0200 AppleSpell 0x7fdef65bf9f0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef65bf9f0> { count =
2, transaction: 1, voucher = 0x7fdef65c4b30, contents =
    "Progress" => <dictionary: 0x7fdef6549070> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef65bdcf0>: 0.673394
        "EstimatedTimeRemaining" => <double: 0x7fdef654a030>: 0.006910

```

```

        "Operation" => <string: 0x7fdef65a44b0> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef65955b0>: 3
}
default 16:57:20.616002 +0200 AppleSpell 0x7fdef644b7e0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef644b7e0> { count =
2, transaction: 1, voucher = 0x7fdef64242c0, contents =
    "Progress" => <dictionary: 0x7fdef645ba60> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef6424310>: 0.698909
        "EstimatedTimeRemaining" => <double: 0x7fdef6417a10>: 0.006387
        "Operation" => <string: 0x7fdef641ce50> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef645e500>: 3
}
default 16:57:20.616544 +0200 AppleSpell 0x7fdef644b7e0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef644b7e0> { count =
2, transaction: 1, voucher = 0x7fdef64242c0, contents =
    "Progress" => <dictionary: 0x7fdef645c780> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef641ad90>: 0.724424
        "EstimatedTimeRemaining" => <double: 0x7fdef645c980>: 0.005851
        "Operation" => <string: 0x7fdef645c830> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef6417a10>: 3
}
default 16:57:20.617207 +0200 AppleSpell 0x7fdef644b7e0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef644b7e0> { count =
2, transaction: 1, voucher = 0x7fdef64242c0, contents =
    "Progress" => <dictionary: 0x7fdef645ba60> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef645e500>: 0.749939
        "EstimatedTimeRemaining" => <double: 0x7fdef641c0d0>: 0.005348
        "Operation" => <string: 0x7fdef645bb10> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef645c980>: 3
}
default 16:57:20.617834 +0200 AppleSpell 0x7fdef644b7e0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef644b7e0> { count =
2, transaction: 1, voucher = 0x7fdef64242c0, contents =
    "Progress" => <dictionary: 0x7fdef645c780> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef6417a10>: 0.775454
        "EstimatedTimeRemaining" => <double: 0x7fdef6424310>: 0.004829
        "Operation" => <string: 0x7fdef645c830> { length = 16, contents =
"UnarchivingAsset" }
    }

```

```

    }
    "_IPC_TYPE" => <uint64: 0x7fdef641c0d0>: 3
}
default 16:57:20.618520 +0200 AppleSpell 0x7fdef66bac50 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef66bac50> { count =
2, transaction: 1, voucher = 0x7fdef66bbc50, contents =
    "Progress" => <dictionary: 0x7fdef66aa730> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef665f470>: 0.800969
        "EstimatedTimeRemaining" => <double: 0x7fdef6657ef0>: 0.004312
        "Operation" => <string: 0x7fdef66aa7e0> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef665e210>: 3
}
default 16:57:20.618985 +0200 AppleSpell 0x7fdef66bac50 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef66bac50> { count =
2, transaction: 1, voucher = 0x7fdef66bbc50, contents =
    "Progress" => <dictionary: 0x7fdef66aa730> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef66bb1e0>: 0.826484
        "EstimatedTimeRemaining" => <double: 0x7fdef6657ef0>: 0.003746
        "Operation" => <string: 0x7fdef66aa7e0> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef665e210>: 3
}
default 16:57:20.619516 +0200 AppleSpell 0x7fdef66bac50 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef66bac50> { count =
2, transaction: 1, voucher = 0x7fdef66bbc50, contents =
    "Progress" => <dictionary: 0x7fdef66aa730> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef665f470>: 0.851999
        "EstimatedTimeRemaining" => <double: 0x7fdef6657ef0>: 0.003190
        "Operation" => <string: 0x7fdef66aa7e0> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef665e210>: 3
}
default 16:57:20.620038 +0200 AppleSpell 0x7fdef65a4510 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef65a4510> { count =
2, transaction: 1, voucher = 0x7fdef65c4b30, contents =
    "Progress" => <dictionary: 0x7fdef654a0a0> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef6502ba0>: 0.877514
        "EstimatedTimeRemaining" => <double: 0x7fdef6582a70>: 0.002635
        "Operation" => <string: 0x7fdef65a44b0> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef65a46f0>: 3

```

```

}
default    16:57:20.620619 +0200  AppleSpell    0x7fdef644b7e0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef644b7e0> { count =
2, transaction: 1, voucher = 0x7fdef64242c0, contents =
    "Progress" => <dictionary: 0x7fdef645ba60> { count = 3, transaction: 0,
voucher = 0x0, contents =
    "OperationProgress" => <double: 0x7fdef645c980>: 0.903029
    "EstimatedTimeRemaining" => <double: 0x7fdef641ad90>: 0.002088
    "Operation" => <string: 0x7fdef645bb10> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef6424310>: 3
}
default    16:57:20.621213 +0200  AppleSpell    0x7fdef65bf9f0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef65bf9f0> { count =
2, transaction: 1, voucher = 0x7fdef65c4b30, contents =
    "Progress" => <dictionary: 0x7fdef6549070> { count = 3, transaction: 0,
voucher = 0x0, contents =
    "OperationProgress" => <double: 0x7fdef65a85d0>: 0.928544
    "EstimatedTimeRemaining" => <double: 0x7fdef65bdcf0>: 0.001543
    "Operation" => <string: 0x7fdef65a44b0> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef654a030>: 3
}
default    16:57:20.621773 +0200  AppleSpell    0x7fdef644b7e0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef644b7e0> { count =
2, transaction: 1, voucher = 0x7fdef64242c0, contents =
    "Progress" => <dictionary: 0x7fdef645c780> { count = 3, transaction: 0,
voucher = 0x0, contents =
    "OperationProgress" => <double: 0x7fdef6424310>: 0.954059
    "EstimatedTimeRemaining" => <double: 0x7fdef641c0d0>: 0.000993
    "Operation" => <string: 0x7fdef641f870> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef645d540>: 3
}
default    16:57:20.622339 +0200  AppleSpell    0x7fdef644b7e0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef644b7e0> { count =
2, transaction: 1, voucher = 0x7fdef64242c0, contents =
    "Progress" => <dictionary: 0x7fdef645ba60> { count = 3, transaction: 0,
voucher = 0x0, contents =
    "OperationProgress" => <double: 0x7fdef645c980>: 0.979574
    "EstimatedTimeRemaining" => <double: 0x7fdef6417a10>: 0.000442
    "Operation" => <string: 0x7fdef645bb10> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef641c0d0>: 3
}
default    16:57:20.622763 +0200  AppleSpell    0x7fdef644b7e0 Download

```

```

listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef644b7e0> { count =
2, transaction: 1, voucher = 0x7fdef64242c0, contents =
    "Progress" => <dictionary: 0x7fdef645c780> { count = 3, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef645d540>: 0.999851
        "EstimatedTimeRemaining" => <double: 0x7fdef641ad90>: 0.000003
        "Operation" => <string: 0x7fdef645c830> { length = 16, contents =
"UnarchivingAsset" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef6417a10>: 3
}
default 16:57:20.625147 +0200 kernel SandboxViolation: mobileassetd(51)
deny(1) file-read-data /
default 16:57:20.630552 +0200 AppleSpell 0x7fdef644b7e0 Download
listener handler: XPC_TYPE_DICTIONARY <dictionary: 0x7fdef644b7e0> { count =
2, transaction: 1, voucher = 0x7fdef64242c0, contents =
    "Progress" => <dictionary: 0x7fdef645ba60> { count = 2, transaction: 0,
voucher = 0x0, contents =
        "OperationProgress" => <double: 0x7fdef641c0d0>: -1.000000
        "Operation" => <string: 0x7fdef645bb10> { length = 18, contents =
"OperationCompleted" }
    }
    "_IPC_TYPE" => <uint64: 0x7fdef645e500>: 3
}
default 16:57:20.630669 +0200 mobileassetd 0x7ffdd7a6ca0 Client
connection: XPC_TYPE_ERROR Connection invalid <error: 0x7ffdd7a6ca0> { count
= 1, transaction: 0, voucher = 0x0, contents =
    "XPCErrorDescription" => <string: 0x7ffdd7a6f18> { length = 18, contents =
"Connection invalid" }
}
default 16:57:20.630689 +0200 mobileassetd Client connection invalid
(Connection invalid); terminating connection
default 16:57:21.827879 +0200 nsurlsessiond TIC TCP Conn Cancel
[4:0x7f9ac412c210]
default 16:57:21.827910 +0200 nsurlsessiond TIC TCP [0x7f9ac412c210]
completing activity 0x7f9ac2410a10
default 16:57:21.828299 +0200 DuetHeuristic-BM COMPLETED <private>!
default 16:57:21.828326 +0200 DuetHeuristic-BM Stop network path
monitoring for '<private>'
default 16:57:21.828387 +0200 DuetHeuristic-BM NO LONGER RUNNING
<private> ...Tasks running in group [<private>] are 0!
default 16:57:25.050938 +0200 useractivityd -- Demoting
self.advertisingProcess to nil (was UserActivityClient(pid=291/com.apple.TextEdit
uuids={6F135D61-372B-4A67-B164-589D04F20736 41F23575-8D2B-48B0-8FCD-
C77DA62FDE2E })) and trigger pickNewAdvertisement because the previous
advertisingProcess had a current activity.
default 16:57:25.051628 +0200 gamed GKClientProxy: clientForBundleID:
default 16:57:25.051712 +0200 gamed GKClientProxy:
updateIfRecentlyInstalled
default 16:57:25.052542 +0200 gamed GKClientProxy: clientForBundleID:

```

```

default    16:57:25.052578 +0200   gamed     GKClientProxy:
updateIfRecentlyInstalled
default    16:57:25.060505 +0200
com.apple.appkit.xpc.openAndSavePanelService    errors encountered while
discovering extensions
default    16:57:25.493927 +0200   useractivityd  PICKING: E1EB6D99-
B1DD-46FE-B5C4-033FC7B9281F/<private> as the current item-to-advertise.
default    16:57:25.566698 +0200   QuickLookSatellite  In -
[NSApplication(NSQuietSafeQuit) _updateCanQuitQuietlyAndSafely],
_LSSetApplicationInformationItem(NSCanQuitQuietlyAndSafely) returned error -50
default    16:57:26.098565 +0200   parsecd      connection from <private> (387)
invalidated
default    16:57:26.098571 +0200   parsecd      connection from <private> (287)
invalidated
default    16:57:26.379464 +0200   com.apple.WebKit.Networking
TIC TCP Conn Event [50:0x7fa646a369a0]: 2 Err(0)
default    16:57:26.379511 +0200   com.apple.WebKit.Networking
TIC TCP Conn Cancel [50:0x7fa646a369a0]
default    16:57:26.379517 +0200   com.apple.WebKit.Networking
TIC TCP Conn Cancel [52:0x7fa64693c320]
default    16:57:26.379561 +0200   com.apple.WebKit.Networking
TIC TCP Conn Destroyed [52:0x7fa64693c320]
default    16:57:28.409662 +0200   gamed       TIC TCP Conn Cancel
[3:0x7ffb39c21a70]
default    16:57:28.409711 +0200   gamed       TIC TCP Conn Cancel
[1:0x7ffb39f262c0]
default    16:57:28.409737 +0200   gamed       TIC TCP Conn Destroyed
[3:0x7ffb39c21a70]
default    16:57:28.409747 +0200   gamed       TIC TCP Conn Destroyed
[1:0x7ffb39f262c0]
default    16:57:28.409788 +0200   gamed       TIC TCP Conn Cancel
[2:0x7ffb39e22790]
default    16:57:28.409851 +0200   gamed       TIC TCP Conn Destroyed
[2:0x7ffb39e22790]
default    16:57:29.181401 +0200   CommCenter   #l
CSIAppInfo.ApplicationActivationObserver: handleLSNotification_sync: Application
exited: <private>
default    16:57:29.710156 +0200   cloudd       TIC TCP Conn Cancel
[1:0x7ff28652a230]
default    16:57:29.710226 +0200   cloudd       TIC TCP Conn Destroyed
[1:0x7ff28652a230]
default    16:57:30.206130 +0200   gamed       [AVConference][INFO]
commnat_test: [000000D0] after 60.220568s (<private>)
default    16:57:30.206168 +0200   gamed       [AVConference][NOTICE]
GKNATObserver setting flags[000000D0] mask[000027FF]
old[000000D0]=>result[000000D0] (cached:0)
default    16:57:30.206237 +0200   gamed       [AVConference][INFO]
GKNATObserver: Caching NAT flags [<private>] for network "<private>"...
default    16:57:30.206290 +0200   gamed       [AVConference][WARNING]
GKNATObserver cannot report NAT Type 2 (0/2), delegate is nil!

```


default 16:57:30.206727 +0200 gamed [AVConference][INFO]
GKNATObserver: done waiting for NAT check group
default 16:57:30.206784 +0200 gamed [AVConference][WARNING]
GKNATObserver cannot report NAT Type 2 (0/2), delegate is nil!
default 16:57:30.206828 +0200 gamed [AVConference][INFO]
GKNATObserverInternal(0x7ffb3b91c610) -dealloc
default 16:57:30.206879 +0200 gamed [AVConference][INFO]
VCNAT64ResolverDeregisterFromInterface: removing context 3b91c610 from
interface <private> at index 2
default 16:57:30.209594 +0200 gamed [AVConference][INFO]
commnat_test: [000000D0] after 60.223861s (<private>)
default 16:57:30.209618 +0200 gamed [AVConference][NOTICE]
GKNATObserver setting flags[000000D0] mask[000027FF]
old[000000D0]=>result[000000D0] (cached:0)
default 16:57:30.209682 +0200 gamed [AVConference][INFO]
GKNATObserver: Caching NAT flags [<private>] for network "<private>"...
default 16:57:30.209732 +0200 gamed [AVConference][WARNING]
GKNATObserver cannot report NAT Type 2 (0/2), delegate is nil!
default 16:57:30.210077 +0200 gamed [AVConference][INFO]
GKNATObserver: done waiting for NAT check group
default 16:57:30.210137 +0200 gamed [AVConference][WARNING]
GKNATObserver cannot report NAT Type 2 (0/2), delegate is nil!
default 16:57:30.210206 +0200 gamed [AVConference][INFO]
GKNATObserverInternal(0x7ffb39f304b0) -dealloc
default 16:57:30.210247 +0200 gamed [AVConference][INFO]
VCNAT64ResolverDeregisterFromInterface: removing context 39f304b0 from
interface <private> at index 1
default 16:57:30.256100 +0200 gamed [AVConference][INFO]
commnat_test: [000000D0] after 60.269344s (<private>)
default 16:57:30.256152 +0200 gamed [AVConference][NOTICE]
GKNATObserver setting flags[000000D0] mask[000027FF]
old[000000D0]=>result[000000D0] (cached:0)
default 16:57:30.256230 +0200 gamed [AVConference][INFO]
GKNATObserver: Caching NAT flags [<private>] for network "<private>"...
default 16:57:30.256288 +0200 gamed [AVConference][INFO]
GKNATObserver _commNATFlagDictionary = <private>
default 16:57:30.256566 +0200 gamed [AVConference][INFO]
GKNATObserver: done waiting for NAT check group
default 16:57:30.256633 +0200 gamed [AVConference][INFO]
GKNATObserver _commNATFlagDictionary = <private>
default 16:57:30.646175 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default 16:57:30.646307 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default 16:57:30.646343 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 20, EGID: 20
default 16:57:30.646472 +0200 opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 89, EGID: 89
default 16:57:30.646626 +0200 opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20

```

default    16:57:30.646719 +0200    opendirectoryd Client: <private>, UID: 89,
EUID: 89, GID: 89, EGID: 89
default    16:57:30.651537 +0200    opendirectoryd Client: <private>, UID: 89,
EUID: 89, GID: 89, EGID: 89
default    16:57:30.651622 +0200    opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default    16:57:30.654114 +0200    opendirectoryd Client: <private>, UID: 501,
EUID: 501, GID: 20, EGID: 20
default    16:57:30.654131 +0200    opendirectoryd Client: <private>, UID: 89,
EUID: 89, GID: 89, EGID: 89
default    16:57:30.669460 +0200    securityd 0x7fb8ff105fa0 Session 100005
created, uid:89 sessionId:100005
default    16:57:30.669483 +0200    securityd Session 100005 created
default    16:57:30.671018 +0200    mdworker 0x7f9da2609a60 opened /var/
folders/zz/zyxvpqvq6csfxvn_n00000b400002s/C/com.apple.mdworker.bundle//mds/
mdsObject.db: 4636 bytes
default    16:57:30.671018 +0200    mdworker 0x7fa43f418580 opened /var/folders/
j8/bbhn9g892k14cv1xw2hp2fy80000gn/C/com.apple.mdworker.bundle//mds/
mdsObject.db: 4636 bytes
default    16:57:30.671326 +0200    mdworker 0x7f9da240da50 opened /var/
folders/zz/zyxvpqvq6csfxvn_n00000b400002s/C/com.apple.mdworker.bundle//mds/
mdsDirectory.db: 50744 bytes
default    16:57:30.671336 +0200    mdworker 0x7fa43f41fa30 opened /var/folders/
j8/bbhn9g892k14cv1xw2hp2fy80000gn/C/com.apple.mdworker.bundle//mds/
mdsDirectory.db: 50744 bytes
default    16:57:30.672704 +0200    mdworker 0x7fa43f6295e0 opened /var/folders/
j8/bbhn9g892k14cv1xw2hp2fy80000gn/C/com.apple.mdworker.bundle//mds/
mdsDirectory.db: 50744 bytes
default    16:57:30.672707 +0200    mdworker 0x7f9da2621c90 opened /var/
folders/zz/zyxvpqvq6csfxvn_n00000b400002s/C/com.apple.mdworker.bundle//mds/
mdsDirectory.db: 50744 bytes
default    16:57:30.675857 +0200    trustd     cert[2]: AnchorTrusted =(leaf)[force]>
0
default    16:57:30.676492 +0200    opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default    16:57:30.676822 +0200    opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 0, EGID: 0
default    16:57:30.676970 +0200    opendirectoryd Client: <private>, UID: 0, EUID:
0, GID: 89, EGID: 89
default    16:57:30.677256 +0200    opendirectoryd Client: <private>, UID: 89,
EUID: 89, GID: 89, EGID: 89
default    16:57:30.680140 +0200    opendirectoryd Client: <private>, UID: 89,
EUID: 89, GID: 89, EGID: 89
default    16:57:30.684837 +0200    trustd     cert[2]: AnchorTrusted =(leaf)[force]>
0
default    16:57:30.685099 +0200    trustd     could not create path: /var/empty/
Library/Keychains/9E0C5829-488C-534A-BB34-0962E899D086 (No such file or
directory)
default    16:57:30.685325 +0200    opendirectoryd Client: <private>, UID: 89,
EUID: 89, GID: 89, EGID: 89

```

default 0	16:57:30.685546 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
default 0, GID: 0, EGID: 0	16:57:30.688838 +0200	opendirectoryd	Client: <private>, UID: 0, EUID:
default 0	16:57:30.696986 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
default 0	16:57:31.240104 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
default 0	16:57:31.240152 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
default 0	16:57:31.254708 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
default 0	16:57:31.254712 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
default 0	16:57:31.257877 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
default 0	16:57:31.257891 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
default 0	16:57:31.263584 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
default 0	16:57:31.263588 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
default 0	16:57:31.273196 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
default 0	16:57:31.273233 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
default 0	16:57:31.277601 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
default 0	16:57:31.277615 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
default 0	16:57:31.281164 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
default 0	16:57:31.281171 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
default 0	16:57:31.286326 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
default 0	16:57:31.286333 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
default 0	16:57:31.297352 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
default 0	16:57:31.297354 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
default 0	16:57:31.309526 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
default 0	16:57:31.309531 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
default 0	16:57:31.320160 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
default 0	16:57:31.320165 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>

default	16:57:31.323671 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
0			
default	16:57:31.323720 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
0			
default	16:57:31.328694 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
0			
default	16:57:31.328706 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
0			
default	16:57:31.333071 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
0			
default	16:57:31.333081 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
0			
default	16:57:31.340384 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
0			
default	16:57:31.340417 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
0			
default	16:57:31.351598 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
0			
default	16:57:31.351599 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
0			
default	16:57:31.355917 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
0			
default	16:57:31.355930 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
0			
default	16:57:31.361613 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
0			
default	16:57:31.361613 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
0			
default	16:57:31.370771 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
0			
default	16:57:31.370772 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
0			
default	16:57:31.375032 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
0			
default	16:57:31.375033 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
0			
default	16:57:31.378776 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
0			
default	16:57:31.378820 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
0			
default	16:57:31.382398 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
0			
default	16:57:31.382431 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
0			
default	16:57:31.385800 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
0			
default	16:57:31.385852 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
0			
default	16:57:31.390523 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
0			

default 0	16:57:31.391364 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
default 0	16:57:31.396359 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
default 0	16:57:31.396385 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
default 0	16:57:31.401325 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
default 0	16:57:31.401375 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
default 0	16:57:31.405732 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
default 0	16:57:31.405744 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
default 0	16:57:31.409734 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
default 0	16:57:31.409737 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
default 0	16:57:31.413285 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
default 0	16:57:31.413290 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
default 0	16:57:31.488891 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>
default 0	16:57:31.493018 +0200	trustd	cert[2]: AnchorTrusted =(leaf)[force]>