



My Favorites

Main

Ai Tweaker

Advanced

Monitor

Boot

Tool

Exit

➤ Boot Configuration

➤ CSM (Compatibility Support Module)

➤ Secure Boot

Boot Option Priorities

Boot Option #1

UEFI: PNY USB 2.0 FD PMAP, Pai

Boot Option #2

UEFI: SMI USB DISK 1100, Partit

Boot Override

UEFI: SMI USB DISK 1100, Partition
1 (15.9GB)

UEFI: SMI USB DISK 1100, Partition 1 (15.9GB)

UEFI: PNY USB 2.0 FD PMAP, Partition 1 (61.9GB)

Sets the system boot order



Hardware Monitor

CPU/Memory

Frequency
3600 MHz

Temperature
32°C

BCLK
100.00 MHz

Core Voltage
1.039 V

Ratio
36x

DRAM Freq.
2666 MHz

DRAM Volt.
1.200 V

Capacity
32768 MB

Prediction

Cooler
186 pts

NonAVX V req
Max nonAVX
for 4900MHz

Stable

1.244 V

5277 MHz

AVX V req
Max AVX
for 4900MHz

Stable

1.293 V

4995 MHz

Cache V req
Max Cache
for 4300MHz

Stable

1.068 V

5030 MHz